
Week 1 – 2:

--Coding-C-Language Features-Optional.

ROLL NO.:240801174

Name: Lavanya.S



Q1) Write a program to input a name (as a single character) and marks of three tests as m1, m2, and m3 of a student considering all the three marks have been given in integer format. Now, you need to calculate the average of the given marks and print it along with the name as mentioned in the output format section.

All the test marks are in integers and hence calculate the average in integer as well. That is, you need to print the integer part of the average only and neglect the decimal part.

Input Format:

Line 1 : Name(Single character)

Line 2: Marks scored in the 3 tests separated by single space.

Output Format:

First line of output prints the name of the student. Second line of the output prints the average mark.

Constraints

Marks for each student lie in the range 0 to 100 (both inclusive)

Sample Input 1:

Α

346

Sample Output 1:

Α

4

Code:

```
#include<stdio.h>
int main()

int m1 ,m2 ,m3 ,avg;

char name;

scanf("%c",&name);

printf("%C\n",name);

scanf("%d %d %d", &m1 ,&m2, &m3);

avg = (m1 +m2 +m3)/3;

printf("%d",avg);

return 0;

}
```

OUTPUT:

<u> </u>	Α	A	А	~
	3 4 6	4	4	_
/	T 7 3 8	T 6	T 6	~
/	R Ø 100 99	R 66	R 66	~

Q2) Some C data types, their format specifiers, and their most common bit widths are as follows: • Int ("%d"): 32 Bit integer • Long ("%ld"): 64 bit integer • Char ("%c"): Character type • Float ("%f"): 32 bit real value • Double ("%lf"): 64 bit real value Reading To read a data type, use the following syntax: scanf("`format_specifier`", &val) For example, to read a character followed by a double: char ch; double d; scanf("%c %lf", &ch, &d); For the moment, we can ignore the spacing between format specifiers. Printing To print a data type, use the following syntax: printf("`format_specifier`", val) For example, to print a character followed by a double: char ch = 'd'; double d = 234.432; printf("%c %lf", ch, d); Note: You can also use cin and cout instead of scanf and printf; however, if you are taking a million numbers as input and printing a million lines, it is faster to use scanf and printf. Input Format Input consists of the following space-separated values: int, long, char, float, and double, respectively. **Output Format** Print each element on a new line in the same order it was received as input. Note that the floating-point value should be correct up to 3 decimal places and the double to 9 decimal

Sample Input

places.

3

12345678912345

334.23

14049.30493

Sample Output

3

12345678912345

а

334.230

14049.304930000

Code:

```
includestdio.h>
lnt main()
l
```

OUTPUT:

	Input	Expected	Got	
~	3 12345678912345 a 334.23 14049.30493	3	3	~
		12345678912345	12345678912345	
		а	a	
		334.230	334.230	
		14049.304930000	14049.304930000	

Q3) Write a program to print the ASCII value and the two adjacent characters of the given character.

Input Format: Reads the character

Output Format: First line prints the ascii value, second line prints the previous character and next character of the input character

Sample Input 1:

Ε

Sample Output 1:

69

DF

Code:

OUTPUT:

