

HandsOn-7

Create a React Application named “shoppingapp” with a class component named “OnlineShopping” and “Cart”.

Implementation

→ App.js

```
import React from 'react';

import './App.css';

import OnlineShopping from './components/OnlineShopping';

function App() {
  return (
    <div className="App">
      <OnlineShopping />
    </div>
  );
}

export default App;
```

→ Cart.js

```
import React, { Component } from 'react';

class Cart extends Component {
  render() {
    const { itemname, price } = this.props;
    return (
      <tr>
        <td>{itemname}</td>
        <td>{price}</td>
      </tr>
    );
  }
}
```

```

    }
  }
  Cart.defaultProps = {
    itemname: "Unknown Item",
    price: "0"
  };
  export default Cart;

```

→OnlineShopping.js

```

import React, { Component } from 'react';
import Cart from './Cart';
import '../style.css';
class OnlineShopping extends Component {
  render() {
    const items = [
      { itemname: 'Laptop', price: '80000' },
      { itemname: 'TV', price: '120000' },
      { itemname: 'Washing Machine', price: '50000' },
      { itemname: 'Mobile', price: '30000' },
      { itemname: 'Fridge', price: '70000' }
    ];
    return (
      <div className="container">
        <h2 className="heading">Items Ordered :</h2>
        <table>
          <thead>
            <tr>
              <th>Name</th>
              <th>Price</th>
            </tr>

```

```

        </thead>

        <tbody>

            {items.map((item, index) => (

                <Cart key={index} itemname={item.itemname} price={item.price} />

            ))}

        </tbody>

    </table>

</div>

);

}

}

export default OnlineShopping;

```

→Style.css

```

.container {

    text-align: center;

    margin-top: 40px;

}

.heading {

    color: green;

    font-weight: bold;

}

table {

    margin: 0 auto;

    border: 2px solid gray;

    border-collapse: collapse;

}

th, td {

    border: 1px solid gray;

    padding: 10px 20px;

```

```
    color: seagreen;  
  }
```

➔index.js

```
import React from 'react';  
import ReactDOM from 'react-dom/client';  
import './index.css';  
import App from './App';  
  
// ReactDOM.render() alternative using React 18  
const root = ReactDOM.createRoot(document.getElementById('root'));  
root.render(<App />);
```

output

Output

```
JS Cart.js U JS OnlineShopping.js U # style.css U JS App.js M X # index.css JS index.js M logo: ...
shoppingapp > src > JS App.js > App
1 | import React from 'react';
2 | import './App.css';
3 | import OnlineShopping from './components/OnlineShopping';
4 |
5 | function App() {
6 |   return (
7 |     <div className="App">
8 |       <OnlineShopping />
9 |     </div>
10 |   );
11 | }
12 |
13 | export default App;
14 |

Tabnine | Edit | Test | Explain | Document

(node:15188) [DEP_WEBPACK_DEV_SERVER_ON_AFTER_SETUP_MIDDLEWARE] DeprecationWarning: 'onAfterSetupMiddleware' option is deprecated. Please use the 'setupMiddlewares' option.
(node:15188) [DEP_WEBPACK_DEV_SERVER_ON_BEFORE_SETUP_MIDDLEWARE] DeprecationWarning: 'onBeforeSetupMiddleware' option is deprecated. Please use the 'setupMiddlewares' option.
Starting the development server...
compiled successfully!

You can now view shoppingapp in the browser.

Local:      http://localhost:3000
On Your Network: http://172.22.32.1:3000

Note that the development build is not optimized.
To create a production build, use npm run build.

webpack compiled successfully
```

```
JS Cart.js U JS OnlineShopping.js U # style.css U JS App.js M # index.css JS index.js M X logo: ...
shoppingapp > src > JS index.js > ...
1 | import React from 'react';
2 | import ReactDOM from 'react-dom/client';
3 | import './index.css';
4 | import App from './App';
5 |
6 | // ReactDOM.render() alternative using React 18
7 | const root = ReactDOM.createRoot(document.getElementById('root'));
8 | root.render(<App />);
9 |
```

```
JS Cart.js U JS OnlineShopping.js U # style.css U JS App.js M # index.css JS index.js M logo:
shoppingapp > src > components > JS OnlineShopping.js > OnlineShopping > render > items
import './style.css';
4
5 class OnlineShopping extends Component {
6   render() {
7     const items = [
8       { itemname: 'Laptop', price: '80000' },
9       { itemname: 'TV', price: '120000' },
10      { itemname: 'Washing Machine', price: '50000' },
11      { itemname: 'Mobile', price: '30000' },
12      { itemname: 'Fridge', price: '70000' }
13    ];
14
15    return (
16      <div className="container">
17        <h2 className="heading">Items Ordered :</h2>
18        <table>
19          <thead>
20            <tr>
21              <th>Name</th>
22              <th>Price</th>
23            </tr>
24          </thead>
25          <tbody>
26            {items.map((item, index) => (
27              <Cart key={index} itemname={item.itemname} price={item.price} />
28            ))}
```

```
JS Cart.js U X JS OnlineShopping.js U # style.css U JS App.js M # index.cs
shoppingapp > src > components > JS Cart.js > Cart > render
1 import React, { Component } from 'react';
2
3 class Cart extends Component {
4   render() {
5     const { itemname, price } = this.props;
6     return (
7       <tr>
8         <td>{itemname}</td>
9         <td>{price}</td>
10      </tr>
11    );
12  }
13 }
14
15 Cart.defaultProps = {
16   itemname: "Unknown Item",
17   price: "0"
18 };
19
20 export default Cart;
21
```

Items Ordered :

Name	Price
Laptop	80000
TV	120000
Washing Machine	50000
Mobile	30000
Fridge	70000