

HandsOn-15

Create a React App named “ticketraisingapp” which will help to raise a complaint and get it resolved.

Create a component named “ComplaintRegister” with a form containing a textbox to enter the employee name and a textarea to enter the complaint. Use “handleSubmit” event of the button to submit the complaint and generate a Reference number for further follow ups in the alert box.

.

Implementation

→App.js

```
// src/App.js

import React from 'react';
import ComplaintRegister from
'./components/ComplaintRegister';

function App() {
  return (
    <div>
      <ComplaintRegister />
    </div>
  );
}

export default App;
```

→App.css

```
.App {
  text-align: center;
}

.App-logo {
  height: 40vmin;
  pointer-events: none;
```

```
}  
@media (prefers-reduced-motion: no-preference) {  
  .App-logo {  
    animation: App-logo-spin infinite 20s linear;  
  }  
}  
.App-header {  
  background-color: #282c34;  
  min-height: 100vh;  
  display: flex;  
  flex-direction: column;  
  align-items: center;  
  justify-content: center;  
  font-size: calc(10px + 2vmin);  
  color: white;  
}  
.App-link {  
  color: #61dafb;  
}  
@keyframes App-logo-spin {  
  from {  
    transform: rotate(0deg);  
  }  
  to {  
    transform: rotate(360deg);  
  }  
}
```

→ComplaintRegister.js

```
// src/components/ComplaintRegister.js
```

```
import React, { useState } from 'react';
```

```
function ComplaintRegister() {
  const [employeeName, setEmployeeName] = useState("");
  const [complaint, setComplaint] = useState("");
  const handleSubmit = (e) => {
    e.preventDefault();
    const referenceNumber = Math.floor(Math.random() * 90000) + 10000; // 5-digit number
    alert(
      `Complaint Registered Successfully!\nEmployee: ${employeeName}\nReference No:
      ${referenceNumber}`
    );
    // Reset form
    setEmployeeName("");
    setComplaint("");
  };
  return (
    <div style={{ maxWidth: '500px', margin: '50px auto' }}>
      <h2>Complaint Registration</h2>
      <form onSubmit={handleSubmit}>
        <div style={{ marginBottom: '10px' }}>
          <label>Employee Name:</label><br />
          <input
            type="text"
            value={employeeName}
            onChange={(e) => setEmployeeName(e.target.value)}
            required
            style={{ width: '100%', padding: '8px' }}
          />
        </div>
        <div style={{ marginBottom: '10px' }}>
          <label>Complaint:</label><br />
          <textarea
            value={complaint}
            onChange={(e) => setComplaint(e.target.value)}
            required
            rows="4"
            style={{ width: '100%', padding: '8px' }}
          />
        </div>
        <button type="submit" style={{ padding: '8px 16px' }}>
          Submit Complaint
        </button>
      </form>
    </div>
  );
}
```

```
export default ComplaintRegister;
```

Output

JS ComplaintRegister.js U

JS App.js M X

ticketraisingapp > src > JS App.js > App

```
1 // src/App.js
2 import React from 'react';
3 import ComplaintRegister from './components/ComplaintRegister';
4
5 Tabnine | Edit | Test | Explain | Document
6 function App() {
7   return (
8     <div>
9       <ComplaintRegister />
10     </div>
11   );
12 }
13 export default App;
14
```

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

PORTS

node - ticketraisingapp

You can now view **ticketraisingapp** in the browser.

Local: <http://localhost:3000>
On Your Network: <http://172.22.32.1:3000>

Note that the development build is not optimized.
To create a production build, use `npm run build`.

webpack compiled **successfully**



Complaint Registration

Employee Name:

Complaint:

Please fill out this field.



Complaint Registration

Employee Name:

Complaint:

