

HandsOn-17

Create a React Application “fetchuserapp” which will retrieve the user details from <https://api.randomuser.me/> and display the title, firstname and image of a user.

Create a component named “Getuser” and in the asynchronous method “ComponentDidMount ()” invoke the URL using fetch method and the response can be displayed in the render method of the component.

.

Implementation

→App.js

```
// src/App.js

import React from 'react';
import './App.css';
import Getuser from './components/Getuser';

function App() {
  return (
    <div className="App">
      <Getuser />
    </div>
  );
}

export default App;
```

→App.css

```
.App {
  text-align: center;
}

.App-logo {
```

```
height: 40vmin;
pointer-events: none;
}
@media (prefers-reduced-motion: no-preference) {
  .App-logo {
    animation: App-logo-spin infinite 20s linear;
  }
}
.App-header {
  background-color: #282c34;
  min-height: 100vh;
  display: flex;
  flex-direction: column;
  align-items: center;
  justify-content: center;
  font-size: calc(10px + 2vmin);
  color: white;
}
.App-link {
  color: #61dafb;
}
@keyframes App-logo-spin {
  from {
    transform: rotate(0deg);
  }
  to {
    transform: rotate(360deg);
  }
}
```

→GetUser.js

```
// src/components/Getuser.js
import React, { Component } from 'react';
import './Getuser.css';
class Getuser extends Component {
  constructor() {
    super();
    this.state = {
      user: null,
    };
  }
  componentDidMount() {
    fetch('https://api.randomuser.me/')
      .then(response => response.json())
      .then(data => {
        this.setState({ user: data.results[0] });
      })
      .catch(error => {
        console.error('Error fetching user:', error);
      });
  }
  render() {
    const { user } = this.state;
    return (
      <div className="container">
        <h2>Random User Info</h2>
        {user ? (
          <div className="card">
            <img src={user.picture.large} alt="User" />
            <h3>{user.name.title}. {user.name.first}</h3>
          </div>
        ) : (
          <p>Loading user data...</p>
        )}
      </div>
    );
  }
}
export default Getuser;
```

➔GetUser.css

```
.container {  
  text-align: center;  
  padding: 30px;  
  font-family: Arial, sans-serif;  
}  
.card {  
  display: inline-block;  
  padding: 20px;  
  border: 2px solid #ddd;  
  border-radius: 8px;  
  background-color: #f9f9f9;  
  box-shadow: 0 2px 8px rgba(0,0,0,0.1);  
}  
.card img {  
  width: 120px;  
  border-radius: 50%;  
}  
.card h3 {  
  margin-top: 10px;  
  color: #333;  
}
```

Output

```
JS App.js  M  X  JS Getuser.js  U  # Getuser.css  U

fetchuserapp > src > JS App.js > App
1 // src/App.js
2 import React from 'react';
3 import './App.css';
4 import Getuser from './components/Getuser';
5
6 function App() {
7   return (
8     <div className="App">
9       <Getuser />
10     </div>
11   );
12 }
13
14 export default App;
15
```

Tabnine | Edit | Test | Explain | Document

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

node - fetchuserapp

You can now view **fetchuserapp** in the browser.

Local: http://localhost:3000
On Your Network: http://172.22.32.1:3000

Note that the development build is not optimized.
To create a production build, use `npm run build`.

webpack compiled **successfully**

Ln 11, Col 5 Spaces: 2 UTF-8 LF JavaScript Go Live



