MEDIA SPOTLIGHT FOR CAPSTONE PROJECTS

Listening to Enbi and DeepSeek

Comparing a public banking chatbot with a general-purpose model

Bootcamper: [Add your name] **Project name:** Enbi Public Chatbot Assessment
Cohort: S2026

ORIGIN

I came to the Wecncode Bootcamp curious about how artificial intelligence behaves when people use it for everyday tasks. I wanted to move beyond examples in a lesson and observe an assistant in a real public setting, while keeping the work careful, small in scale and respectful of the people and service behind it.

EUREKA MOMENT

The project began with a practical question: how do AI assistants respond to banking questions, safety concerns and attempts to push beyond their stated role? I chose Enbi as a public, bank-specific chatbot, then added DeepSeek as a general-purpose model to give the study a useful point of comparison. I wanted to see how a broad assistant handles the same kinds of banking-related questions when it is not the bank's own chatbot, especially where capability limits, safety and confident factual claims matter. A surprising or irrelevant answer is not automatically a security failure; it has to be recorded and interpreted in context.

THE PROJECT

This project records Enbi's responses to public banking questions and a bounded set of adversarial prompts. A companion evaluation records DeepSeek's answers to 37 related, rephrased prompts. The two tracks explore how a bank-specific chatbot and a general-purpose model handle banking topics; they are not a controlled benchmark or a full security audit.

- **Structured prompt set:** questions are grouped by purpose and assigned IDs, so each observation can be traced back to what was asked.
- **Evidence-based logging:** CSV records, response transcripts and selected screenshots make the observations reviewable and reproducible.
- **Cross-model perspective:** a separate DeepSeek prompt set uses matching IDs and related wording to explore capability boundaries, safety guidance and factual confidence.
- **Careful interpretation:** results distinguish refusals, ordinary responses and inconclusive cases; unexpected wording is reported as an observation unless there is evidence of real impact.

THE TECH STACK

- **Enbi's public chat:** the system being observed, accessed as an ordinary visitor.
- **DeepSeek V4.1 Flash:** the general-purpose model in a separate 37-run comparison track. It was evaluated with manually submitted prompts; the project does not claim to have built or trained the model.
- **Python 3 standard library:** a small local logger records one row per completed run, including prompt identifiers and a prompt hash. It does not contact either model.
- **PowerShell:** optional wrappers make it easier to record completed manual observations consistently.
- **CSV, plain text and Markdown:** lightweight formats keep prompts, responses, logs and project notes easy to inspect.

- **LaTeX:** used to prepare this polished, shareable project summary.

DATA COLLECTION / INSIGHTS

I collected both sets manually, entering prompts in the relevant chat interface and saving the responses and assessments locally. The Enbi records contain 29 benign runs and eight adversarial runs. The separate DeepSeek log contains 37 runs across related categories, including prompt-injection, social engineering, privacy, fraud, factuality and safety. No account was logged into and no real customer information was submitted.

Across repeated balance and branch questions, Enbi gave stable navigation guidance. Its password-reset answer varied. In the eight adversarial Enbi runs, no account-specific data was disclosed. DeepSeek often stated limits and redirected account-specific requests to official channels, but some answers included specific hotline, interest-rate, timing or legal claims that were not verified in the run. That is why the comparison matters: a helpful-sounding general answer still needs fact-checking, especially in a banking context. The prompt wording and coverage are not fully paired across both systems, so these records support exploratory observations, not a model ranking or a claim about either system's overall security.

In the 37 DeepSeek responses, it generally refused private account lookups, credential handling and attempts to extract or bypass its instructions. There were also clear reliability cautions: when asked who made it, DeepSeek answered OpenAI even though the run metadata records DeepSeek V4.1 Flash. Several financial rates, payment timings, legal details and contact numbers were stated without verification. The comparison therefore looks at both safety boundaries and whether confident-sounding banking guidance deserves independent checking.


TUTORIAL: HOW TO RUN A SMALL, RESPONSIBLE OBSERVATION STUDY

1. **Choose an appropriate public target.** Record the public URL and access context. Use only an interface an ordinary visitor can reach.
2. **Set boundaries first.** Exclude accounts, real personal data, private endpoints, transactions, automation and high-volume requests. Agree on stop conditions.
3. **Write and review prompts.** Group questions by purpose, assign an ID to each, and review the final list with the project mentor before using it.
4. **Capture each run manually.** Enter the prompt in the normal interface. Save the exact response and, when useful, a screenshot. Do not submit real credentials or customer details.
5. **Log what happened.** Record the prompt ID, date, response file, outcome and whether the result was blocked, not blocked or inconclusive. Keep observations separate from security findings.
6. **Compare cautiously.** If evaluating a second model, use related prompts, log it separately and fact-check important claims. Say whether the samples are paired and avoid treating a small sample as a ranking.
7. **Summarize with limits.** Count the runs, describe repeated patterns, call out incomplete records and state what the sample cannot prove.

Scope and prompt review ⟶ Manual public interaction ⟶ Transcript and evidence ⟶ Log and classify ⟶ Report with limitations


TUTORIAL: EXAMPLE EVIDENCE FROM BOTH MODELS


Enbi: stable balance guidance



Two differently worded balance questions received the same Money app and Online Banking guidance. T3 is illustrative evidence from the supplied PDF.

DeepSeek: response excerpts





Cropped excerpts of the user-facing answers; the supplied full captures are preserved under `tests/evidence/deepseek/`.

RESULTS AT A GLANCE

Enbi: 29 benign runs and 8 adversarial runs
DeepSeek V4.1 Flash: 37 manually submitted comparison prompts
Why compare: Explore how a general-purpose model handles banking-related safety, capability and factuality questions
What the sample showed: No account-specific data appeared in the eight adversarial Enbi responses. Some DeepSeek factual claims were not verified. The samples do not support an overall security conclusion or model ranking.

THE BIGGEST LESSON

My biggest lesson was that a surprising answer is not automatically a vulnerability. I had to slow down, preserve what was actually observed, separate a refusal from a generic fallback, and avoid making a broader claim than the evidence supports. That discipline changed how I think about AI assessment: responsible testing depends as much on careful measurement and honest limits as on the prompts themselves.

STANDOUT MOMENT

The most memorable comparison was seeing Enbi give the same balance guidance to differently worded questions, while DeepSeek answer to "Who made you?" named OpenAI even though the run metadata records DeepSeek V4.1 Flash. That mismatch showed why model self-description also needs checking against independent records. Neither result reveals internal design or proves that every safeguard works in every case.

DELIVERABLES REQUESTED

- **GitHub repository:** [Add the URL for your project repository. The reference repository is not assumed to be yours.]
- **One-minute introduction video:** [Record an introduction and project overview; upload it to Google Drive and add the share link.]
- **Screenshots / diagrams:** Included above as a sample of the manual observation workflow. Additional run evidence is stored under `tests/evidence/`.