

i386手册勘误

- 17.2.1 ModR/M and SIB Bytes中的Table 17-3:

@@ -?,2 +?,2 @@									
disp8[EDX]	010	42	4A	52	5A	62	6A	72	7A
-disp8[EPX]	011	43	4B	53	5B	63	6B	73	7B
+disp8[EBX]	011	43	4B	53	5B	63	6B	73	7B

- 17.2.1 ModR/M and SIB Bytes中的Table 17-4:

@@ -?,2 +?,2 @@									
Base =		0	1	2	3	4	5	6	7
- r32		EAX	ECX	EDX	EBX	ESP	EBP	ESI	EDI
+ r32		EAX	ECX	EDX	EBX	ESP	[*]	ESI	EDI
@@ -?,2 +?,2 @@									
[ECX*2]	001	48	49	4A	4B	4C	4D	4E	4F
-[ECX*2]	010	50	51	52	53	54	55	56	57
+ [EDX*2]	010	50	51	52	53	54	55	56	57
@@ -?,2 +?,2 @@									
[EDX*4]	010	90	91	92	93	94	95	96	97
- [EBX*4]	011	98	89	9A	9B	9C	9D	9E	9F
+ [EBX*4]	011	98	99	9A	9B	9C	9D	9E	9F
@@ -?,2 +?,2 @@									
NOTES:									
- [*]	means a disp32 with no base if MOD is 00, [ESP] otherwise. This provides the follow								
+ [*]	means a disp32 with no base if MOD is 00. Otherwise, [*] means disp8[EBP] or disp32								

- 17.2.2.11 Instruction Set Detail中的DEC -- Decrement by 1

@@ -?,2 +?,2 @@			
FF /1	DEC r/m16	2/6	Decrement r/m word by 1
-	DEC r/m32	2/6	Decrement r/m dword by 1
+FF /1	DEC r/m32	2/6	Decrement r/m dword by 1

- 17.2.2.11 Instruction Set Detail中的INC -- Increment by 1

@@ -?,2 +?,2 @@			
FF /0	INC r/m16		Increment r/m word by 1
-FF /6	INC r/m32		Increment r/m dword by 1
+FF /0	INC r/m32		Increment r/m dword by 1

- 17.2.2.11 Instruction Set Detail中的Jcc -- Jump if Condition is Met

```

@@ -?,2 +?,2 @@
72 cb      JB rel8      7+m,3      Jump short if below (CF=1)
-76 cb      JBE rel8     7+m,3      Jump short if below or (CF=1 or ZF=1)
+76 cb      JBE rel8     7+m,3      Jump short if below or equal (CF=1 or ZF=1)
@@ -?,2 +?,2 @@
7C cb      JL rel8      7+m,3      Jump short if less (SF!=0F)
-7E cb      JLE rel8     7+m,3      Jump short if less or equal (ZF=1 and SF!=0F)
+7E cb      JLE rel8     7+m,3      Jump short if less or equal (ZF=1 or SF!=0F)
@@ -?,2 +?,2 @@
0F 8C cw/cd JL rel16/32  7+m,3      Jump near if less (SF!=0F)
-0F 8E cw/cd JLE rel16/32 7+m,3      Jump near if less or equal (ZF=1 and SF!=0F)
+0F 8E cw/cd JLE rel16/32 7+m,3      Jump near if less or equal (ZF=1 or SF!=0F)

```

- 17.2.2.11 Instruction Set Detail中的MOV -- Move Data

```

@@ -?,14 +?,14 @@
8C /r      MOV r/m16,Sreg 2/2      Move segment register to r/m word
-8D /r      MOV Sreg,r/m16 2/5,pm=18/19 Move r/m word to segment register
+8E /r      MOV Sreg,r/m16 2/5,pm=18/19 Move r/m word to segment register
A0         MOV AL,moffs8   4        Move byte at (seg:offset) to AL
A1         MOV AX,moffs16  4        Move word at (seg:offset) to AX
A1         MOV EAX,moffs32 4        Move dword at (seg:offset) to EAX
A2         MOV moffs8,AL   2        Move AL to (seg:offset)
A3         MOV moffs16,AX  2        Move AX to (seg:offset)
A3         MOV moffs32,EAX 2        Move EAX to (seg:offset)
-B0 + rb    MOV reg8,imm8   2        Move immediate byte to register
-B8 + rw    MOV reg16,imm16 2        Move immediate word to register
-B8 + rd    MOV reg32,imm32 2        Move immediate dword to register
-Ciiiiii   MOV r/m8,imm8   2/2      Move immediate byte to r/m byte
-C7         MOV r/m16,imm16 2/2      Move immediate word to r/m word
-C7         MOV r/m32,imm32 2/2      Move immediate dword to r/m dword
+B0 + rb ib MOV reg8,imm8   2        Move immediate byte to register
+B8 + rw iw MOV reg16,imm16 2        Move immediate word to register
+B8 + rd id MOV reg32,imm32 2        Move immediate dword to register
+C6 ib      MOV r/m8,imm8   2/2      Move immediate byte to r/m byte
+C7 iw      MOV r/m16,imm16 2/2      Move immediate word to r/m word
+C7 id      MOV r/m32,imm32 2/2      Move immediate dword to r/m dword

```

- 17.2.2.11 Instruction Set Detail中的MUL -- Unsigned Multiplication of AL or AX

```

@@ -?,2 +?,2 @@
Flags Affected
-0F and CF as described above; SF, ZF, AF, PF, and CF are undefined
+0F and CF as described above; SF, ZF, AF, PF are undefined

```

- 17.2.2.11 Instruction Set Detail中的OR -- Logical Inclusive OR

@@ -?,6 +?,6 @@				
08	/r	OR r/m8,r8	2/6	OR byte register to r/m byte
09	/r	OR r/m16,r16	2/6	OR word register to r/m word
09	/r	OR r/m32,r32	2/6	OR dword register to r/m dword
-0A	/r	OR r8,r/m8	2/7	OR byte register to r/m byte
-0B	/r	OR r16,r/m16	2/7	OR word register to r/m word
-0B	/r	OR r32,r/m32	2/7	OR dword register to r/m dword
+0A	/r	OR r8,r/m8	2/7	OR r/m byte to byte register
+0B	/r	OR r16,r/m16	2/7	OR r/m word to word register
+0B	/r	OR r32,r/m32	2/7	OR r/m dword to dword register

- 17.2.2.11 Instruction Set Detail中的PUSH -- Push Operand onto the Stack

@@ -?,3 +?,3 @@				
FF	/6	PUSH m32	5	Push memory dword
-50	+ /r	PUSH r16	2	Push register word
-50	+ /r	PUSH r32	2	Push register dword
+50	+ rw	PUSH r16	2	Push register word
+50	+ rd	PUSH r32	2	Push register dword

- 17.2.2.11 Instruction Set Detail中的REP/REPE/REPZ/REPNE/REP NZ -- Repeat Following String Operation

```
@@ -?,13 +?,13 @@
service pending interrupts (if any);
perform primitive string instruction;
CountReg <- CountReg - 1;
IF primitive operation is CMPB, CMPW, SCAB, or SCAW
THEN
-   IF (instruction is REP/REPE/REPZ) AND (ZF=1)
+   IF (instruction is REP/REPE/REPZ) AND (ZF=0)
    THEN exit WHILE loop
    ELSE
-   IF (instruction is REP NZ or REPNE) AND (ZF=0)
+   IF (instruction is REP NZ or REPNE) AND (ZF=1)
    THEN exit WHILE loop;
    FI;
  FI;
FI;
```

- 17.2.2.11 Instruction Set Detail中的SBB -- Integer Subtraction with Borrow

@@ -?,6 +?,6 @@				
18	/r	SBB r/m8,r8	2/6	Subtract with borrow byte register from r/m byte
19	/r	SBB r/m16,r16	2/6	Subtract with borrow word register from r/m word
19	/r	SBB r/m32,r32	2/6	Subtract with borrow dword register from r/m dword
-1A	/r	SBB r8,r/m8	2/7	Subtract with borrow byte register from r/m byte
-1B	/r	SBB r16,r/m16	2/7	Subtract with borrow word register from r/m word
-1B	/r	SBB r32,r/m32	2/7	Subtract with borrow dword register from r/m dword
+1A	/r	SBB r8,r/m8	2/7	Subtract with borrow r/m byte from byte register
+1B	/r	SBB r16,r/m16	2/7	Subtract with borrow r/m word from word register
+1B	/r	SBB r32,r/m32	2/7	Subtract with borrow r/m dword from dword register

- 17.2.2.11 Instruction Set Detail中的SETcc - Byte Set on Condition

@@ -?,2 +?,2 @@				
0F	94	SETE r/m8	4/5	Set byte if equal (ZF=1)
-0F	9F	SETG r/m8	4/5	Set byte if greater (ZF=0 or SF=0F)
+0F	9F	SETG r/m8	4/5	Set byte if greater (ZF=0 and SF=0F)
@@ -?,3 +?,3 @@				
0F	9C	SETLE r/m8	4/5	Set byte if less (SF!=0F)
-0F	9E	SETLE r/m8	4/5	Set byte if less or equal (ZF=1 and SF!=0F)
-0F	96	SETNA r/m8	4/5	Set byte if not above (CF=1)
+0F	9E	SETLE r/m8	4/5	Set byte if less or equal (ZF=1 or SF!=0F)
+0F	96	SETNA r/m8	4/5	Set byte if not above (CF=1 or ZF=1)
@@ -?,2 +?,2 @@				
0F	9D	SETNL r/m8	4/5	Set byte if not less (SF=0F)
-0F	9F	SETNLE r/m8	4/5	Set byte if not less or equal (ZF=1 and SF!=0F)
+0F	9F	SETNLE r/m8	4/5	Set byte if not less or equal (ZF=0 and SF=0F)

- 17.2.2.11 Instruction Set Detail中的SHLD -- Double Precision Shift Left

@@ -?,2 +?,2 @@

Flags Affected

-OF, SF, ZF, PF, and CF as described above; AF and OF are undefined

+SF, ZF, PF, and CF as described above; AF and OF are undefined

- 17.2.2.11 Instruction Set Detail中的SHLR -- Double Precision Shift Right

@@ -?,2 +?,2 @@

Flags Affected

-OF, SF, ZF, PF, and CF as described above; AF and OF are undefined

+SF, ZF, PF, and CF as described above; AF and OF are undefined

- 17.2.2.11 Instruction Set Detail中的SUB - Integer Subtraction