

	Test No:		
	File: T1804_rad_0512	Spectrum Analyser Plots	Page: 1




## PLOT 1 Radiated Emissions

Company:	02 M8	Product:	Web Brick
Date:	08 Dec 05	Test Engineer:	Stephen Browning
Test:	EN55022	Limit:	EN (B)
Notes:			
Fully loaded, 8m cables.			
Equip: R5,R5B,CBL002,Patch1,CBL003,A12. Vertical - Black Trace, Horizontal - Blue Trace.			
Polarisation:	V + H	Orientation:	0 - 360°
Distance:	3m	Antenna:	Bilog
Height:	1m	Filename:	H5C083D9.plt
		Operating Mode:	1
		Mod. State:	0

## Frequency List (MHz)


	Test No:		
	File: T1804_rad_0512	Spectrum Analyser Plots	Page: 2




## PLOT 2 Radiated Emissions

Company:	02 M8	Product:	Web Brick
Date:	08 Dec 05	Test Engineer:	Stephen Browning
Test:	EN55022	Limit:	EN (B)
Notes:			
Fully loaded, 8m cables. Using dBTech PSU instead of customer PSU.			
Ferrites on all I/O			
Equip: R5,R5B,CBL002,Patch1,CBL003,A12. Vertical - Black Trace, Horizontal - Blue Trace.			
Polarisation:	V + H	Orientation:	0 - 360°
Distance:	3m	Antenna:	Bilog
Height:	1m	Filename:	H5C083EF.plt
		Operating Mode:	1
		Mod. State:	0

### Frequency List (MHz)


	Test No:		
	File: T1804_rad_0512	Spectrum Analyser Plots	Page: 3

h/




### PLOT 3 Radiated Emissions

Company:	02 M8	Product:	Web Brick
Date:	08 Dec 05	Test Engineer:	Stephen Browning
Test:	EN55022	Limit:	EN (B)
Notes:			
Fully loaded, 8m cables. Using dBTech PSU instead of customerPSU.			
Ferrites on all I/O, monitor PIC removed in digital ancilliary box.			
Equip: R5,R5B,CBL002,Patch1,CBL003,A12. Vertical - Black Trace, Horizontal - Blue Trace.			
Polarisation:	V + H	Orientation:	0 - 360°
Distance:	3m	Antenna:	Bilog
Height:	1m	Filename:	H5C083F9.plt
		Operating Mode:	1
		Mod. State:	0

#### Frequency List (MHz)



	Test No:		
	File: T1804_rad_0512	Spectrum Analyser Plots	Page: 4




## PLOT 4 Radiated Emissions

Company:	02 M8	Product:	Web Brick
Date:	08 Dec 05	Test Engineer:	Stephen Browning
Test:	EN55022	Limit:	EN (B)
Notes:			
Fully loaded, 8m cables. Using dBTech PSU instead of customerPSU.			
Ferrites removed, monitor PIC removed in digital ancilliary box.			
Equip: R5,R5B,CBL002,Patch1,CBL003,A12. Vertical - Black Trace, Horizontal - Blue Trace.			
Polarisation:	V + H	Orientation:	0 - 360°
Distance:	3m	Antenna:	Bilog
Height:	1m	Filename:	H5C08406.plt
		Operating Mode:	1
		Mod. State:	0

## Frequency List (MHz)



	Test No:		
	File: T1804_rad_0512	Spectrum Analyser Plots	Page: 5




## PLOT 5 Radiated Emissions

Company:	02 M8	Product:	Web Brick
Date:	08 Dec 05	Test Engineer:	Stephen Browning
Test:	EN55022	Limit:	EN (B)
Notes:			
Fully loaded, 8m cables. Using dBTech PSU instead of customer PSU.			
Ferrites removed, monitor PIC removed in digital ancilliary box.			
Second Web Brick with 10MHz clock i.e. pll disabled. No caps on I/O.			
Equip: R5,R5B,CBL002,Patch1,CBL003,A12. Vertical - Black Trace, Horizontal - Blue Trace.			
Polarisation:	V + H	Orientation:	0 - 360°
Distance:	3m	Antenna:	Bilog
Height:	1m	Filename:	H5C08411.plt
		Operating Mode:	1
		Mod. State:	0

### Frequency List (MHz)



	Test No:		
	File: T1804_rad_0512	Spectrum Analyser Plots	Page: 6




## PLOT 6 Radiated Emissions

Company:	02 M8	Product:	Web Brick
Date:	08 Dec 05	Test Engineer:	Stephen Browning
Test:	EN55022	Limit:	EN (B)
Notes:			
Fully loaded, 8m cables. Using dBTech PSU instead of customerPSU.			
Ferrites removed, monitor PIC removed in digital ancilliary box.			
Third Web Brick with 40MHz clock. Copper taped. Ethernet disconnected.			
Equip: R5,R5B,CBL002,Patch1,CBL003,A12. Vertical - Black Trace, Horizontal - Blue Trace.			
Polarisation:	V + H	Orientation:	0 - 360°
Distance:	3m	Antenna:	Bilog
Height:	1m	Filename:	H5C0841A.plt
		Operating Mode:	1
		Mod. State:	0

### Frequency List (MHz)



	Test No:		
	File: T1804_rad_0512	Spectrum Analyser Plots	Page: 7




## PLOT 7 Radiated Emissions

Company:	02 M8	Product:	Web Brick
Date:	08 Dec 05	Test Engineer:	Stephen Browning
Test:	EN55022	Limit:	EN (B)
Notes:			
Fully loaded, 8m cables. Using dBTech PSU instead of customerPSU.			
Ferrites removed, monitor PIC removed in digital ancilliary box.			
Third Web Brick with 40MHz clock. Copper taped. LV ground connected to mains ground.			
Equip: R5,R5B,CBL002,Patch1,CBL003,A12. Vertical - Black Trace, Horizontal - Blue Trace.			
Polarisation:	V + H	Orientation:	0 - 360°
Distance:	3m	Antenna:	Bilog
Height:	1m	Filename:	H5C08426.plt
		Operating Mode:	1
		Mod. State:	0

### Frequency List (MHz)


	Test No:		
	File: T1804_rad_0512	<b>Spectrum Analyser Plots</b>	Page: 8



## PLOT 8 Radiated Emissions

Company:	02 M8	Product:	Web Brick
Date:	08 Dec 05	Test Engineer:	Stephen Browning
Test:	EN55022	Limit:	EN (B)
Notes:			
Fully loaded, 8m cables. Using dBTech PSU instead of customer PSU.			
Ferrites removed, monitor PIC removed in digital ancilliary box.			
Original Web Brick with 40MHz clock. LV gnd connected to Mains Gnd.			
Equip: R5,R5B,CBL002,Patch1,CBL003,A12. Vertical - Black Trace, Horizontal - Blue Trace.			
Polarisation:	V + H	Orientation:	0 - 360°
Distance:	3m	Antenna:	Bilog
Height:	1m	Filename:	H5C08432.plt
		Operating Mode:	1
		Mod. State:	0


### Frequency List (MHz)

40.600				180.600		
50.600				220.600		
80.600						
113.800						



	Test No:		
	File: T1804_rad_0512	Spectrum Analyser Plots	Page: 9

h/p



## PLOT 9 Radiated Emissions

Company:	02 M8	Product:	Web Brick
Date:	08 Dec 05	Test Engineer:	Stephen Browning
Test:	EN55022	Limit:	EN (B)
Notes:			
Fully loaded, 8m cables. Using dBTech PSU instead of customerPSU.			
Ferrites removed, monitor PIC removed in digital ancilliary box.			
Original Web Brick with 40MHz clock. LV gnd connected to Mains Gnd.			
Equip: R5,R5B,CBL002,Patch1,CBL003,A12. Vertical - Black Trace, Horizontal - Blue Trace.			
Polarisation:	V + H	Orientation:	0 - 360°
Distance:	3m	Antenna:	Bilog
Height:	1m	Filename:	H5C08442.plt
		Operating Mode:	1
		Mod. State:	0

### Frequency List (MHz)

521.900						