

WhatsApp

Java Instanceof k

Design Parking S

Design Parking S

KotagiriAkshaya/

You are signed in

Fix Java Instance

Ask Gemini

hackerrank.com/challenges/java-instanceof-keyword/problem?isFullScreen=true

Search ☆ Bookmarks Downloads School

HackerRank

Prepare Java Object Oriented Programming Java Instanceof keyword

Exit Full Screen View

Problem

Submissions

Leaderboard

Discussions

Editorial

The Java instanceof operator is used to test if the object or instance is an instanceof the specified type.

In this problem we have given you three classes in the editor;

- Student class
- Rockstar class
- Hacker class

In the main method, we populated an ArrayList with several instances of these classes. count method calculates how many instances of each type is present in the ArrayList. The code prints three integers, the number of instance of Student class, the number of instance of Rockstar class, the number of instance of Hacker class.

But some lines of the code are missing, and you have to fix it by modifying only 3 lines! Don't add, delete or modify any extra line.

To restore the original code in the editor, click on the top left icon in the editor and create a new buffer.

Sample Input

```
5
Student
Student
Rockstar
Student
Hacker
```

Sample Output

```
3 1 1
```

28

31

32

33

34

35

36

37

38

```
for(int i=0; i<t; i++){
    String s=sc.next();
    if(s.equals("Student"))mylist.add(new Student());
    if(s.equals("Rockstar"))mylist.add(new Rockstar());
    if(s.equals("Hacker"))mylist.add(new Hacker());
}
System.out.println(count(mylist));
}
```

Upload Code as File

☐ Test against custom input

Run Code

Submit Code

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Input (stdin)

Download

1 5

2 Student

3 Student

4 Rockstar

5 Student

6 Hacker

Your Output (stdout)

1 3 1 1

Expected Output

Download

Type here to search

35°C Mostly sunny

09:43

02-09-2026

ENG

WhatsApp

Design Underground System

KotagiriAkshaya/pst-week-4

You are signed in as VTU284

Fix Java Instanceof Lines

Ask Gemini

leetcode.com/problems/design-underground-system/

Ask Google

School

Problem List

Submit

Premium

Description

Editorial

Solutions

Submissions

1396. Design Underground System

MediumTopicsCompaniesHint

An underground railway system is keeping track of customer travel times between different stations. They are using this data to calculate the average time it takes to travel from one station to another.

Implement the `UndergroundSystem` class:

- `void checkIn(int id, string stationName, int t)`
 - A customer with a card ID equal to `id`, checks in at the station `stationName` at time `t`.
 - A customer can only be checked into one place at a time.
- `void checkOut(int id, string stationName, int t)`
 - A customer with a card ID equal to `id`, checks out from the station `stationName` at time `t`.
- `double getAverageTime(string startStation, string endStation)`
 - Returns the average time it takes to travel from `startStation` to `endStation`.
 - The average time is computed from all the previous traveling times from `startStation` to `endStation` that happened **directly**, meaning a check in at `startStation` followed by a check out from `endStation`.
 - The time it takes to travel from `startStation` to `endStation` **may be different** from the time it takes to travel from `endStation` to `startStation`.

3.6K7625 Online

Code

PythonAuto

TestcaseTest Result

AcceptedRuntime: 0 ms

Case 1Case 2

Input

["UndergroundSystem","checkIn","checkOut","getAverageTime","checkIn","checkOut","getAverageTime","checkIn","checkOut","getAverageTime"]

[[{"id":10,"stationName":"Leyton","time":3}, {"id":10,"stationName":"Paradise","time":8}, {"id":5,"stationName":"Leyton","time":10}, {"id":5,"stationName":"Paradise","time":16}, {"id":2,"stationName":"Leyton","time":21}, {"id":2,"stationName":"Paradise","time":30}, {"id":10,"stationName":"Paradise","time":16}, {"id":5,"stationName":"Leyton","time":10}, {"id":2,"stationName":"Paradise","time":30}, {"id":10,"stationName":"Paradise","time":16}]]

Output

[null,null,null,5.00000,null,null,5.50000,null,null,6.66667]

Expected

[null,null,null,5.00000,null,null,5.50000,null,null,6.66667]

Type here to search

35°C Mostly sunny

ENG

10:00 02-09-2026

WhatsApp

Design Browser History - Leet

KotagiriAkshaya/pst-week-4

You are signed in as VTU284

Fix Java Instanceof Lines

Ask Gemini

leetcode.com/problems/design-browser-history/

Ask Google

School

Problem List

Submit

Premium

Description

Editorial

Solutions

Submissions

1472. Design Browser History

MediumTopicsCompaniesHint

You have a **browser** of one tab where you start on the **homepage** and you can visit another **url**, get back in the history number of **steps** or move forward in the history number of **steps**.

Implement the **BrowserHistory** class:

- BrowserHistory(string homepage)** Initializes the object with the **homepage** of the browser.
- void visit(string url)** Visits **url** from the current page. It clears up all the forward history.
- string back(int steps)** Move **steps** back in history. If you can only return **x** steps in the history and **steps > x**, you will return only **x** steps. Return the current **url** after moving back in history **at most** **steps**.
- string forward(int steps)** Move **steps** forward in history. If you can only forward **x** steps in the history and **steps > x**, you will forward only **x** steps. Return the current **url** after forwarding in history **at most** **steps**.

Example:

Input:
["BrowserHistory","visit","visit","visit","back","back","forward","visit"]

4.2K10032 Online

Code

TestcaseTest Result

AcceptedRuntime: 0 ms

Case 1

Input

["BrowserHistory","visit","visit","visit","back","back","forward","visit","forward","back","back"]

["leetcode.com"],["google.com"],["facebook.com"],["youtube.com"],[1],[1],[1],["linkedin.com"],[2],[2],[7]]

Output

[null,null,null,null,"facebook.com","google.com","facebook.com",null,"linkedin.com","google.com","leetcode.com"]

Expected

[null,null,null,null,"facebook.com","google.com","facebook.com",null,"linkedin.com","google.com","leetcode.com"]

Contribute a testcase

Type here to search

35°C Mostly sunny

ENG

10:03 02-09-2026

WhatsApp

Design HashSet - LeetCode

KotagiriAkshaya/pst-week-4

You are signed in as VTU284

Fix Java Instanceof Lines

Ask Gemini

leetcode.com/problems/design-hashset/

Problem ListSubmit

DescriptionEditorialSolutionsSubmissions

705. Design HashSet

EasyTopicsCompanies

Design a HashSet without using any built-in hash table libraries.

Implement `MyHashSet` class:

- `void add(key)` Inserts the value `key` into the HashSet.
- `bool contains(key)` Returns whether the value `key` exists in the HashSet or not.
- `void remove(key)` Removes the value `key` in the HashSet. If `key` does not exist in the HashSet, do nothing.

Example 1:

Input

```
["MyHashSet", "add", "add", "contains", "contains", "add", "contains", "remove", "contains"]
```

```
[[], [1], [2], [1], [3], [2], [2], [2]]
```

Output

```
[null, null, null, true, false, null, true, null, false]
```

Explanation

4.1K9033 Online

Code

TestcaseTest Result

AcceptedRuntime: 4 ms

Case 1

Input

```
["MyHashSet", "add", "add", "add", "remove", "contains", "add", "add", "add", "remove", "contains", "add", "add", "add", "remove", "contains"]
```

```
[[], [1], [10001], [1], [1], [1], [7], [10007], [7], [7], [7], [123], [10123], [123], [123], [123], [5000], [15000], [5000], [5000], [5000]]
```

Output

```
[null, null, null, null, null, false, null, null, null, null, false, null, null, null, null, false]
```

Expected

```
[null, null, null, null, null, false, null, null, null, null, false, null, null, null, null, false]
```

Contribute a testcase

Type here to search

35°C Mostly sunny10:0502-09-2026ENG

WhatsApp

Grading Students | HackerRank

KotagiriAkshaya/pst-week-4

You are signed in as VTU2843

Fix Java Instance of Lines

Ask Gemini

hackerrank.com/challenges/grading/problem?isFullScreen=true

HackerRank

PrepareAlgorithmsImplementationGrading Students

Exit Full Screen View

Problem

Submissions

Leaderboard

Discussions

Editorial

HackerLand University has the following grading policy:

- Every student receives a *grade* in the inclusive range from 0 to 100.
- Any *grade* less than 40 is a failing grade.

Sam is a professor at the university and likes to round each student's *grade* according to these rules:

- If the difference between the *grade* and the next multiple of 5 is less than 3, round *grade* up to the next multiple of 5.
- If the value of *grade* is less than 38, no rounding occurs as the result will still be a failing grade.

Examples

- grade* = 84 round to 85 (85 - 84 is less than 3)
- grade* = 29 do not round (result is less than 38)
- grade* = 57 do not round (60 - 57 is 3 or higher)

Given the initial value of *grade* for each of Sam's *n* students, write code to automate the rounding process.

Function Description

Complete the function `gradingStudents` with the following parameter(s):

- `int grades[n]`: the grades before rounding

Returns

- `int[n]`: the grades after rounding

Input Format

The first line contains a single integer, *n*, the number of students.

Each line *i* of the *n* subsequent lines contains a single integer, *grades[i]*.

Constraints

- $1 \leq n \leq 10$
- $0 \leq grades[i] \leq 100$

Sample Input 0

```
4
73
67
38
33
```

```
36
37
38
39
40
41
42
43
44
}

public class Solution {
    public static void main(String[] args) throws IOException {
        BufferedReader bufferedReader = new BufferedReader(new InputStreamReader(System.in));
        BufferedWriter bufferedWriter = new BufferedWriter(new FileWriter(System.getenv("OUTPUT_PATH")));

        int gradesCount = Integer.parseInt(bufferedReader.readLine().trim());

        // ... (rest of the code) ...
    }
}
```

Upload Code as File

☐ Test against custom input

Run Code

Submit Code

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Input (stdin)

Download

```
1 4
2 73
3 67
4 38
5 33
```

Your Output (stdout)

```
1 75
2 67
3 40
4 33
```

Type here to search

35°C Mostly sunny

10:09 02-09-2026

Java Inheritance I | HackerRank

Ask Gemini

hackerank.com/challenges/java-inheritance-1/problem?isFullScreen=true

HackerRank

PrepareJavaObject Oriented ProgrammingJava Inheritance I

Exit Full Screen View

Problem

Submissions

Leaderboard

Discussions

Editorial

void walk(){
 System.out.println("I am walking");
}

This class has only one method, walk. Next, we want to create a Bird class that also has a fly method. We do this using extends keyword:

class Bird extends Animal {
 void fly() {
 System.out.println("I am flying");
 }
}

Finally, we can create a Bird object that can both fly and walk:

public class Solution{
 public static void main(String[] args){

 Bird bird = new Bird();
 bird.walk();
 bird.fly();
 }
}

The above code will print:

I am walking
I am flying

This means that a Bird object has all the properties that an Animal object has, as well as some additional unique properties.

The code above is provided for you in your editor. You must add a sing method to the Bird class, then modify the main method accordingly so that the code prints the following lines:

I am walking

30
31
32
33
34

Bird bird = new Bird();
bird.walk();
bird.fly();
bird.sing();

Line: 22 Col: 44

Upload Code as File

☐ Test against custom input

Run Code

Submit Code

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Your Output (stdout)

1 I am walking
2 I am flying
3 I am singing

Expected Output

1 I am walking
2 I am flying
3 I am singing

Download

Type here to search

35°C Mostly sunny

10:13
02-09-2026

Problem

Submissions

Leaderboard

Discussions

Editorial

hackerank.com/challenges/java-inheritance-2/problem?isFullScreen=true

HackerRank

PrepareJavaObject Oriented ProgrammingJava Inheritance II

Exit Full Screen View

Write the following code in your editor below:

1. A class named Arithmetic with a method named add that takes 2 integers as parameters and returns an integer denoting their sum.

2. A class named Adder that inherits from a superclass named Arithmetic.

Your classes should not be public.

Input Format

You are not responsible for reading any input from stdin; a locked code stub will test your submission by calling the add method on an Adder object and passing it 2 integer parameters.

Output Format

You are not responsible for printing anything to stdout. Your add method must return the sum of its parameters.

Sample Output

The main method in the Solution class above should print the following:

My superclass is: Arithmetic

42 13 28

Line: 14 Col: 2

Upload Code as File

☐ Test against custom input

Run Code

Submit Code

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Your Output (stdout)

1 My superclass is: Arithmetic

2 42 13 28

Expected Output

1 My superclass is: Arithmetic

2 42 13 28

Download

Type here to search

35°C Mostly sunny

10:15 02-09-2026

Problem

Submissions

Leaderboard

Discussions

Editorial

Generic methods are a very efficient way to handle multiple datatypes using a single method. This problem will test your knowledge on Java Generic methods.

Let's say you have an integer array and a string array. You have to write a **single** method printArray that can print all the elements of both arrays. The method should be able to accept both integer arrays or string arrays.

You are given code in the editor. Complete the code so that it prints the following lines:

```
1
2
3
Hello
World
```

Do not use method overloading because your answer will not be accepted.

hackerank.com/challenges/java-generics/problem?isFullScreen=true

HackerRank

PrepareJavaData StructuresJava Generics

Exit Full Screen View

Line: 4 Col: 24

Upload Code as File

Test against custom input

Run Code

Submit Code

Sample Test case 0

Your Output (stdout)

```
1 1
2 2
3 3
4 Hello
5 World
```

Expected Output

```
1 1
2 2
3 3
4 Hello
```

Download

Type here to search

35°C

Mostly sunny

10:18

02-09-2026

2) WhatsAppThrone Inheritance - LeetCodeKotagiriAkshaya/pst-week-4You are signed in as VTU2843Fix Java Instanceof LinesAsk GeminiSchoolPremium

leetcode.com/problems/throne-inheritance/

Problem ListSubmit

DescriptionEditorialSolutionsSubmissions

1600. Throne Inheritance

MediumTopicsCompaniesHint

A kingdom consists of a king, his children, his grandchildren, and so on. Every once in a while, someone in the family dies or a child is born.

The kingdom has a well-defined order of inheritance that consists of the king as the first member. Let's define the recursive function `Successor(x, curOrder)`, which given a person `x` and the inheritance order so far, returns who should be the next person after `x` in the order of inheritance.

```
Successor(x, curOrder):
    if x has no children or all of x's children are in curOrder:
        if x is the king return null
        else return Successor(x's parent, curOrder)
    else return x's oldest child who's not in curOrder
```

For example, assume we have a kingdom that consists of the king, his children Alice and Bob (Alice is older than Bob), and finally Alice's son Jack.

1. In the beginning, `curOrder` will be `["king"]`.
2. Calling `Successor(king, curOrder)` will return Alice, so we append to `curOrder` to get `["king", "Alice"]`.
3. Calling `Successor(Alice, curOrder)` will return Jack, so we append to `curOrder` to get `["king", "Alice", "Jack"]`.

3221924 Online

Code

PythonAuto

```
1 class ThroneInheritance(object):
2
3     def __init__(self, kingName):
4         self.king = kingName
5         self.children = {}
6         self.dead = set()
7
8     def birth(self, parentName, childName):
9         if parentName not in self.children:
10             self.children[parentName] = []
11             self.children[parentName].append(childName)
```

SavedLn 28, Col 21

TestcaseTest Result

AcceptedRuntime: 0 ms

Case 1

Input

["ThroneInheritance","birth","birth","birth","birth","birth","birth","getInheritanceOrder","death","getInheritanceOrder"]

[[["king"],["king","andy"],["king","bob"],["king","catherine"],["andy","matthew"],["bob","alex"],["bob","asha"],[null],["bob"],[null]]]

Type here to search35°C Mostly sunny10:1902-09-2026ENG

Problem List

76 Online

Description

Editorial

Solutions

Submissions

```
[[1, 1, 0], [1], [2], [3], [1]]
```

Output

```
[null, true, true, false, false]
```

Explanation

```
ParkingSystem parkingSystem = new ParkingSystem(1, 1, 0);
parkingSystem.addCar(1); // return true because there is 1 available slot
for a big car
parkingSystem.addCar(2); // return true because there is 1 available slot
for a medium car
parkingSystem.addCar(3); // return false because there is no available
slot for a small car
parkingSystem.addCar(1); // return false because there is no available
slot for a big car. It is already occupied.
```

Constraints:

- $0 \leq \text{big, medium, small} \leq 1000$
- `carType` is 1, 2, or 3
- At most 1000 calls will be made to `addCar`

Code

Python

Auto

```
1 class ParkingSystem:
2
3     def __init__(self, big, medium, small):
4         self.big = big
5         self.medium = medium
6         self.small = small
7
```

Saved

Ln 25, Col 25

Testcase

Test Result

Accepted

Runtime: 0 ms

Case 1

Input

```
["ParkingSystem", "addCar", "addCar", "addCar", "addCar"]
```

```
[[1, 1, 0], [1], [2], [3], [1]]
```

Output

```
[null, true, true, false, false]
```