

chegg X Alterna X String X Alterna X Alterna X String X Long X Maxim X Subm X The M X Maxim X String X Alterna X Long X Find an X String X Search X

https://www.geeksforgeeks.org/problems/search-pattern0205/1

Search...

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

txt =
geeksforgeeks

pat =
geek

Your Output:
[0, 0]

Expected Output:
[0, 0]

Python3

Start Timer

```
1 class Solution:
2     def search(self, pat, txt):
3         result = []
4
5         # Build LPS array
6         lps = [0] * len(pat)
7         length = 0
8         i = 1
9
10        while i < len(pat):
11            if pat[i] == pat[length]:
12                length += 1
13                lps[i] = length
14                i += 1
15            elif length != 0:
16                length = lps[length - 1]
17            else:
18                lps[i] = 0
19                i += 1
20
21        # KMP search
22        i = 0 # index for txt
23        j = 0 # index for pat
24
25        while i < len(txt):
26            if txt[i] == pat[j]:
27                i += 1
28                j += 1
29
30            if j == len(pat):
31                result.append(i - j)
32                j = lps[j - 1]
33
34            elif j != 0:
35                j = lps[j - 1]
36            else:
37                i += 1
38
39        return result
40
```

Custom Input Compile & Run Submit

Type here to search

31°C Partly sunny 1000 22-06-2025

chatgpt - Search

ChatGPT

Subarray Division | HackerRank

Maximum Sum Circular Subarray - X

https://leetcode.com/problems/maximum-sum-circular-subarray/

Problem List

Submit

Chat

Description

Editorial

Solutions

Submissions

Output: -2

Explanation: Subarray [-2] has maximum sum -2.

Constraints:

- $n == \text{nums.length}$
- $1 \leq n \leq 3 \times 10^4$
- $-3 \times 10^4 \leq \text{nums}[i] \leq 3 \times 10^4$

One platform. Infinite possibilities.

Deploy to VPS

Seen this question in a real interview before? 1/5

Yes No

Accepted 4,59,313/896.0K

Acceptance Rate 51.2%

Topics

Companies

Hint 1

Hint 2

Hint 3

Discussion (135)

Copyright © 2026 LeetCode. All rights reserved.

7.5K 135 45 Online

Code

Python

Auto

```
14
15     cur_min = min(num, cur_min + num)
16     min_sum = min(min_sum, cur_min)
17
18     # If all numbers are negative, total - min_sum would be 0,
19     # which is invalid because the subarray must be non-empty.
20     if max_sum < 0:
21         return max_sum
22
23     # Circular maximum = total - minimum subarray
24     circular_sum = total - min_sum
25
26     return max(max_sum, circular_sum)
```

Saved

Ln 23, Col 42

Testcase

Test Result

Accepted

Runtime: 0 ms

Case 1

Case 2

Case 3

Input

nums = [1,-2,3,-2]

Output

-3

Expected

-3

Contribute a testcase

Type here to search

31°C Partly sunny

69:34

22-08-2025

change X Alternat X String X Alternat X Alternat X String X Long X Main X Sub X The M X Main X String X Altern X Long X Find a X String X Search X +

https://leetcode.com/problems/string-matching-in-an-array/submissions/2115671773/ Chat

Problem List < > Submit

Description Accepted X Editorial Solutions Submissions

All Submissions

Accepted 0% / 89 testcases passed
kotagiri/Akshaya77 submitted at Aug 22, 2026 09:40 Analysis Solution

7583.25ms Save only 58% Unlock the Full LeetCode Experience Company problems, Ask Leet, and expert editorials — all in one plan.

Runtime 7 ms Beats 21.97% Memory 12.28 MB Beats 92.46%



Code | Python

```
1 class Solution(object):
2     def stringMatching(self, words):
3         result = []
4
5         for i in range(len(words)):
6             for j in range(len(words)):
7                 if i != j and words[i] in words[j]:
8                     result.append(words[i])
9
10
11     return result
```

More challenges

Python Auto

```
1 class Solution(object):
2     def stringMatching(self, words):
3         result = []
4
5         for i in range(len(words)):
6             for j in range(len(words)):
7                 if i != j and words[i] in words[j]:
8                     result.append(words[i])
9                     break
10
11     return result
```

Saved Ln 11, Col 22

Testcase Test Result

Accepted Runtime: 0 ms

Case 1 Case 2 Case 3

Input

words =
["mass", "as", "hero", "superhero"]

Output

["as", "hero"]

Expected

["as", "hero"]

Contribute a testcase

Windows taskbar showing search bar, taskbar icons (File Explorer, Edge, etc.), and system tray (clock, language, volume).

changit - Search

Alternating Characters Solution

String to Integer (atoi) - LeetCode

Alternating Characters | HackerRank

Alternating Characters | HackerRank

String to Integer (atoi) - LeetCode

https://leetcode.com/problems/string-to-integer-atoi/

Problem List

Submit

0

Premium

Description

Editorial

Solutions

Submissions

8. String to Integer (atoi)

MediumTopicsCompanies

Implement the `myAtoi(string s)` function, which converts a string to a 32-bit signed integer.

The algorithm for `myAtoi(string s)` is as follows:

- Whitespace:** Ignore any leading whitespace (`" "`).
- Signedness:** Determine the sign by checking if the next character is `'-'` or `'+'`, assuming positivity if neither present.
- Conversion:** Read the integer by skipping leading zeros until a non-digit character is encountered or the end of the string is reached. If no digits were read, then the result is 0.
- Rounding:** If the integer is out of the 32-bit signed integer range $[-2^{31}, 2^{31} - 1]$, then round the integer to remain in the range. Specifically, integers less than -2^{31} should be rounded to -2^{31} , and integers greater than $2^{31} - 1$ should be rounded to $2^{31} - 1$.

Return the integer as the final result.

Example 1:

Input: `s = "42"`
Output: `42`
Explanation:
The underlined characters are what is read in and the caret is the current reader position.
Step 1: `"42"` (no characters read because there is no leading whitespace)
Step 2: `"42"` (no characters read because there is neither a `'-'` nor `'+'`)
Step 3: `"42"` (`"42"` is read in)

Example 2:

Input: `s = "-842"`

Code

Python

Auto

```
23
24
25
26
27
28
29
30
31
32
33
34
35
num *= sign

# 4. Clamp to 32-bit signed integer range
INT_MIN = -2**31
INT_MAX = 2**31 - 1

if num < INT_MIN:
    return INT_MIN
if num > INT_MAX:
    return INT_MAX

return num
```

Testcase

Test Result

Accepted

Runtime: 0 ms

Case 1

Case 2

Case 3

Case 4

Case 5

Input

s =
"42"

Output

42

Expected

42

Contribute a testcase

6.4K

992

117 Online

Type here to search

31°C Partly sunny

09:41

22-08-2025

changit - Search

Alternating Characters Solution

String to Integer (atoi) - LeetCode

Alternating Characters | HackerRank

Alternating Characters | HackerRank

String to Integer (atoi) - LeetCode

Longest Substring Without Repeating Characters

https://leetcode.com/problems/longest-substring-without-repeating-characters/

Problem List

Submit

45.6K 932 684 Online

Description

Editorial

Solutions

Submissions

3. Longest Substring Without Repeating Characters

Medium Topics Companies Hint

Given a string `s`, find the length of the **longest substring** without duplicate characters.

Example 1:

Input: `s = "abcabcbb"`
Output: `3`
Explanation: The answer is "abc", with the length of 3. Note that "bca" and "cab" are also correct answers.

Example 2:

Input: `s = "bbbbb"`
Output: `1`
Explanation: The answer is "b", with the length of 1.

Example 3:

Input: `s = "pwwkew"`
Output: `3`
Explanation: The answer is "wke", with the length of 3. Notice that the answer must be a substring, "pwe" is a subsequence and not a substring.

Constraints:

- $0 \leq s.length \leq 5 \times 10^4$
- `s` consists of English letters, digits, symbols and spaces.

Discover more Coding Bootcamp Access

</> Code

Python Auto

```
1 class Solution(object):
2     def lengthOfLongestSubstring(self, s):
3         seen = set()
4         left = 0
5         max_length = 0
6
7         for right in range(len(s)):
8             while s[right] in seen:
9                 seen.remove(s[left])
10                left += 1
11
12            seen.add(s[right])
13            max_length = max(max_length, right - left + 1)
14
15        return max_length
```

Saved

Ln 15 Col 26

Testcase Test Result

Accepted Runtime: 0 ms

Case 1 Case 2 Case 3

Input

`s = "abcabcbb"`

Output

`3`

Expected

`3`

Contribute a testcase

changer X Alternativ X String to X Alternativ X Alternativ X String to X Longest X Maximum X Subarray X The Maxi X Maximum X String to X Alternativ X Longest X Find and X

https://leetcode.com/problems/find-and-replace-pattern/

Problem List < > Submit

Description Editorial Solutions Submissions

890. Find and Replace Pattern

Medium Topics Companies

Given a list of strings `words` and a string `pattern`, return a list of `words[i]` that match `pattern`. You may return the answer in **any order**.

A word matches the pattern if there exists a permutation of letters `p` so that after replacing every letter `x` in the pattern with `p(x)`, we get the desired word.

Recall that a permutation of letters is a bijection from letters to letters: every letter maps to another letter, and no two letters map to the same letter.

Example 1:

Input: `words = ["abc","deq","mee","aqq","dkd","ccc"], pattern = "abb"`
Output: `["mee","aqq"]`
Explanation: "mee" matches the pattern because there is a permutation {a -> m, b -> e, ...}. "ccc" does not match the pattern because {a -> c, b -> c, ...} is not a permutation, since a and b map to the same letter.

Example 2:

Input: `words = ["a","b","c"], pattern = "a"`
Output: `["a","b","c"]`

Constraints:

- `1 <= pattern.length <= 28`
- `1 <= words.length <= 50`
- `words[i].length == pattern.length`
- `pattern` and `words[i]` are lowercase English letters.

4K 28 11 Online

Code

Python Auto

```
13         break
14
15         # If w in w_to_p and w_to_p[w] != p:
16         match = False
17         break
18
19         p_to_w[p] = w
20         w_to_p[w] = p
21
22         if match:
23             result.append(word)
24
25     return result
```

Saved

Ln 25, Col 22

Testcase Test Result

Accepted Runtime: 0 ms

Case 1 Case 2

Input

words =
["abc","deq","mee","aqq","dkd","ccc"]

pattern =
"abb"

Output

["mee","aqq"]

Expected

["mee","aqq"]

Type here to search

31°C Partly sunny 09:45 22-08-2025

Problems - LeetCode

ChatGPT

Maximum Subarray - LeetCode

+

https://leetcode.com/problems/maximum-subarray/

Problem List

Run

Ctrl

Submit

Chat

Premium

Description

Editorial

Solutions

Submissions

53. Maximum Subarray

Medium

Topics

Companies

Given an integer array `nums`, find the **subarray** with the largest sum, and return its sum.

Example 1:

Input: `nums = [-2,1,-3,4,-1,2,1,-5,4]`
Output: 6
Explanation: The subarray `[4,-1,2,1]` has the largest sum 6.

Example 2:

Input: `nums = [1]`
Output: 1
Explanation: The subarray `[1]` has the largest sum 1.

Example 3:

Input: `nums = [5,4,-1,7,8]`
Output: 23
Explanation: The subarray `[5,4,-1,7,8]` has the largest sum 23.

Constraints:

- $1 \leq \text{nums.length} \leq 10^5$
- $-10^4 \leq \text{nums}[i] \leq 10^4$

Follow up: If you have figured out the $O(n)$ solution, try coding another solution using the **divide and conquer** approach, which is more subtle.

Discover more

Language Resources

38.3K

580

230 Online

Solved

Code

Python

Auto

```
1 class Solution:
2     def maxSubArray(self, nums):
3         current_sum = nums[0]
4         max_sum = nums[0]
5
6         for i in range(1, len(nums)):
7             current_sum = max(nums[i], current_sum + nums[i])
8             max_sum = max(max_sum, current_sum)
9
10        return max_sum
```

Saved

Ln 10, Col 23

Testcase

Test Result

Accepted

Runtime: 0 ms

Case 1

Case 2

Case 3

Input

nums =

[-2,1,-3,4,-1,2,1,-5,4]

Output

6

Expected

6

Contribute a testcase