

Python RegEx

You are signed in

ams.veltech - Go

(11) WhatsApp

Repeated Substrin

String Similarity

Implement String

Ask Gemini

leetcode.com/problems/repeated-substring-pattern/

Problem List

Submit

0

Premium

Description

Editorial

Solutions

Submissions

459. Repeated Substring Pattern

EasyTopicsCompanies

Given a string `s`, check if it can be constructed by taking a substring of it and appending multiple copies of the substring together.

Example 1:

Input: `s = "abab"`
Output: `true`
Explanation: It is the substring "ab" twice.

Example 2:

Input: `s = "aba"`
Output: `false`

Example 3:

Input: `s = "abcabcabcabc"`
Output: `true`
Explanation: It is the substring "abc" four times or the substring "abcabc" twice.

6.9K

158

18 Online

Code

PythonAuto

```
1 class Solution(object):
2     def repeatedSubstringPattern(self, s):
3         return s in (s + s)[1:-1]
4
```

SavedLn 2, Col 43

TestcaseTest Result

AcceptedRuntime: 0 ms

Case 1

Case 2

Case 3

Input

s =
"abab"

Output

true

Type here to search

32°C Mostly cloudy

11:18
25-08-2026

Python RegEx

You are signed in as V

ams.veltech - Google S

(11) WhatsApp

Two Strings | HackerRa

Implement String Simi

Ask Gemini

hackerrank.com/challenges/two-strings/problem?isFullScreen=true

Search ☆ Copy Download K School

HackerRank

Prepare > Algorithms > Strings > Two Strings

Exit Full Screen View

Submissions

Leaderboard

Discussions

Editorial

Topics

Returns

Input Format

Constraints

Output Format

Sample Input

Sample Output

Explanation

30

31

32

33

34

35

36

37

...

q = int(input().strip())

for q_itr in range(q):

s1 = input()

s2 = input()

result = twoStrings(s1, s2)

Upload Code as File

Test against custom input

Run Code

Submit Code

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Sample Test case 1

Sample Test case 2

Input (stdin)

1 2

2 hello

3 world

4 hi

5 world

Your Output (stdout)

1 YES

2 NO

Expected Output

Download

Download

2

hello

world

hi

world

YES

NO

We have $p = 2$ pairs to check:

1. $s1 = \text{"hello"}$, $s2 = \text{"world"}$. The substrings "o" and "l" are common to both strings.

2. $a = \text{"hi"}$, $b = \text{"world"}$. $s1$ and $s2$ share no common substrings.

Type here to search

32°C Mostly cloudy

11:21 25-08-2026

Python RegEx

You are signed in as V

ams.veltech - Google S

(11) WhatsApp

Rotate String - LeetCo

Implement String Simi

Ask Gemini

leetcode.com/problems/rotate-string/

Problem List

Submit

0

Premium

Description

Editorial

Solutions

Submissions

796. Rotate String

EasyTopicsCompanies

Given two strings `s` and `goal`, return `true` if and only if `s` can become `goal` after some number of **shifts** on `s`.

A **shift** on `s` consists of moving the leftmost character of `s` to the rightmost position.

- For example, if `s = "abcde"`, then it will be `"bcdea"` after one shift.

Example 1:

Input: `s = "abcde", goal = "cdeab"`
Output: `true`

Example 2:

Input: `s = "abcde", goal = "abced"`
Output: `false`

Constraints:

5.1K

302

18 Online

Code

PythonAuto

```
1 class Solution(object):
2     def rotateString(self, s, goal):
3         if len(s) != len(goal):
4             return False
5
6         return goal in (s + s)
```

SavedLn 2, Col 37

Testcase

Test Result

AcceptedRuntime: 0 ms

Case 1

Case 2

Input

s =
"m"

goal =
"f"

Type here to search

32°C Mostly cloudy

11:26
25-08-2026

A space explorer's ship crashed on Mars! They send a series of SOS messages to Earth for help.



Letters in some of the SOS messages are altered by cosmic radiation during transmission. Given the signal received by Earth as a string, *s*, determine how many letters of the SOS message have been changed by radiation.

Example

s = 'SOSTOT'

The original message was SOS SOS. Two of the message's characters were changed in transit.

Function Description

Complete the `marsExploration` function in the editor below.

```
30 s = input()
31
32 result = marsExploration(s)
33
34 fptr.write(str(result) + '\n')
35
36 fptr.close()
37
```

Line: 25 Col: 1

Upload Code as File

☐ Test against custom input

Run Code

Submit Code

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Input (stdin)

Download

Sample Test case 1

1 SOSPPSSQSSOR

Sample Test case 2

Your Output (stdout)

1 3

Expected Output

1 3

Download

Python RegEx

LOGIN PAGE FOR INTERNET A

(11) WhatsApp

Find All Anagrams in a String

Find Anagrams Solution

Ask Gemini

K School

leetcode.com/problems/find-all-anagrams-in-a-string/

Problem List

Submit

0

Premium

Description

Editorial

Solutions

Submissions

438. Find All Anagrams in a String

MediumTopicsCompanies

Given two strings `s` and `p`, return an array of all the start indices of `p`'s **anagrams** in `s`. You may return the answer in **any order**.

Example 1:

Input: `s = "cbaebabacd", p = "abc"`

Output: `[0,6]`

Explanation:

The substring with start index = 0 is "cba", which is an anagram of "abc".

The substring with start index = 6 is "bac", which is an anagram of "abc".

Example 2:

Input: `s = "abab", p = "ab"`

Output: `[0,1,2]`

Explanation:

The substring with start index = 0 is "ab", which is an anagram of "ab".

The substring with start index = 1 is "ba", which is an anagram of "ab".

The substring with start index = 2 is "ab", which is an anagram of "ab".

13.4K

187

68 Online

Code

Python

Auto

```
19
20
21     for i in range(len(p), len(s)):
22         window_count[ord(s[i]) - ord('a')] += 1
23         window_count[ord(s[i - len(p)]) - ord('a')] -= 1
24
25         if p_count == window_count:
26             result.append(i - len(p) + 1)
27
28     return result
```

Saved

Ln 27, Col 22

Testcase

Test Result

Accepted

Runtime: 0 ms

Case 1

Case 2

Input

s =

"cbaebabacd"

p =

"abc"

Type here to search

Feels hotter

ENG

11:59

25-08-2026

Python RegEx

LOGIN PAGE FOR INTERNET A

(11) WhatsApp

Palindrome Index | HackerRank

Find Anagrams Solution

Ask Gemini

hackerrank.com/challenges/palindrome-index/problem?isFullScreen=true

HackerRank

Prepare > Algorithms > Strings > Palindrome Index

Exit Full Screen View

Submissions

Leaderboard

Discussions

Editorial

Topics

Input Format

The first line contains an integer q , the number of queries.
Each of the next q lines contains a query string s .

Constraints

- $1 \leq q \leq 20$
- $1 \leq \text{length of } s \leq 10^5 + 5$
- All characters are in the range `ascii[a-z]`.

Sample Input

STDIN	Function
3	<code>q = 3</code>
aaab	<code>s = 'aaab'</code> (first query)
baa	<code>s = 'baa'</code> (second query)
aaa	<code>s = 'aaa'</code> (third query)

Sample Output

```
3
0
-1
```

Explanation

Query 1: "aaab"
Removing 'b' at index 3 results in a palindrome, so return 3.

Query 2: "baa"
Removing 'b' at index 0 results in a palindrome, so return 0.

Query 3: "aaa"
This string is already a palindrome, so return -1. Removing any one of the characters would result in a palindrome, but this test comes first.

Note: The custom checker logic for this challenge is available [here](#).

```
45         return -1
46
47         left += 1
48         right -= 1
49
50     return -1
51
52
53
```

Upload Code as File

☐ Test against custom input

Run Code

Submit Code

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Compiler Message

Success

Input (stdin)

```
1 3
2 aaab
3 baa
4 aaa
```

Your Output (stdout)

```
1 3
2 0
```

Download

Type here to search

33°C Mostly sunny

12:04
25-08-2026

Find the Index of the First Occurrence in a String

leetcode.com/problems/find-the-index-of-the-first-occurrence-in-a-string/

Ask Gemini

Ask Google

K School

Problem List

Submit

Premium

Description

Editorial

Solutions

Submissions

28. Find the Index of the First Occurrence in a String

EasyTopicsCompanies

Given two strings `needle` and `haystack`, return the index of the first occurrence of `needle` in `haystack`, or `-1` if `needle` is not part of `haystack`.

Example 1:

Input: `haystack = "sadbutsad", needle = "sad"`
Output: `0`
Explanation: "sad" occurs at index 0 and 6. The first occurrence is at index 0, so we return 0.

Example 2:

Input: `haystack = "leetcode", needle = "leeto"`
Output: `-1`
Explanation: "leeto" did not occur in "leetcode", so we return -1.

Constraints:

- $1 \leq \text{haystack.length}, \text{needle.length} \leq 10^4$

7.8K577100 Online

Code

PythonAuto

```
1 class Solution(object):
2     def strStr(self, haystack, needle):
3         if needle in haystack:
4             return haystack.index(needle)
5         return -1
```

SavedLn 2, Col 40

Testcase

Test Result

AcceptedRuntime: 0 ms

Case 1

Case 2

Input

haystack =
"sadbutsad"

needle =
"sad"

Type here to search

33°C Mostly sunny

12:07
25-08-2026

[Description](#)
[Editorial](#)
[Solutions](#)
[Submissions](#)

Example 1:

Input: s = "babad"

Output: "bab"

Explanation: "aba" is also a valid answer.

Example 2:

Input: s = "cbbd"

Output: "bb"

Constraints:

- `1 <= s.length <= 1000`
- `s` consist of only digits and English letters.

Discover more

Seen this question in a real interview before? 1/6

Yes

No

👍 33.1K

675



?

● 340 Online

[Code](#)

Python   Auto

```
1 class Solution(object):
2     def longestPalindrome(self, s):
3         start = 0
4         end = 0
5
6         def expand(left, right):
7             while left >= 0 and right < len(s) and s[left] == s[right]:
8                 left -= 1
9                 right += 1
```

Testcase | **Test Result**

Accepted Runtime: 0 ms

✓ Case 1

✓ Case 2

Input

"babad"

Output

"aba"

Submissions

Leaderboard

Discussions

Sample Output 0

12
12
10
8
8
9
11
13
11
9

1	12
2	12
3	10
4	8
5	8
6	9
7	11

Python RegEx

You are signed in as V

ams.veltech - Google S

(11) WhatsApp

String Similarity | Hack

Implement String Simi

Ask Gemini

hackerrank.com/challenges/string-similarity/problem?isFullScreen=true

HackerRank

Prepare > Algorithms > Strings

String Similarity

Exit Full Screen View

Problem

Submissions

Leaderboard

Discussions

Editorial

For two strings A and B, we define the similarity of the strings to be the length of the longest prefix common to both strings. For example, the similarity of strings "abc" and "abd" is 2, while the similarity of strings "aaa" and "aaab" is 3.

Calculate the sum of similarities of a string S with each of its suffixes.

Input Format

The first line contains the number of test cases t.

Each of the next t lines contains a string to process, s.

Constraints

- $1 \leq t \leq 10$
- $1 \leq |s| \leq 100000$
- s is composed of characters in the range `ascii[a-z]`

Output Format

Output t lines, each containing the answer for the corresponding test case.

Sample Input

```
2
ababaa
aa
```

Sample Output

```
11
3
```

Explanation

For the first case, the suffixes of the string are "ababaa", "babaa", "abaa", "baa", "aa" and "a". The similarities of these strings with the string "ababaa" are 6,0,3,0,1, & 1 respectively. Thus, the answer is 6 + 0 + 3 + 0 + 1 + 1 = 11.

For the second case, the answer is 2 + 1 = 3.

```
34         right = i + z[i] - 1
35
36         return sum(z)
37
38     if __name__ == '__main__':
39         fptr = open(os.environ['OUTPUT_PATH'], 'w')
40
41         t = int(input().strip())
42
```

Line: 17 Col: 5

Upload Code as File

☐ Test against custom input

RunCode

Submit Code

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Sample Test case 1

Input (stdin)

1 2

2 ababaa

3 aa

Your Output (stdout)

1 11

2 3

Expected Output

1 11

2 3

Download

Download

Type here to search

32°C Mostly cloudy

11:14

25-08-2026