DJEVENTS

http://djevents.great-site.net/

Smer: Internet tehnologije

Modul: WEB programiranje

Predmet: WEB programiranje Praktikum iz PHP

Student: Filip Lazarević 134/19

Sadržaj

2 Uvod	4
2.1 Korisćene tehnologije	
2.2 Opis funkcionalnosti	
3 Sema baze podataka	
4 Template	
5 Struktura foldera	
6	
6 Mapa sajta	6
6.1 sitemap.xml	
6.2 events.php	
6.3 eventDetails.php	
6.4 Login.php	
6.5 register.php	
6.6 admin.php	
6.7 admin-insert.php	13
6.8 admin-select.php	14
6.9 admin-edit.php	15
6.10 admin-users.php	16
7 Kodovi	16
7.1 views/fixed	16
7.1.1 Head.php	16
7.2.2 nav.php	17
7.1.3 footer.php	20
7.1.4 script.php	22
7.1.5 admin/sidebar.php	22
7.2 views/pages	25
7.2.1 admin/admin.php	25
7.2.2 admin/admin-insert.php	26
7.2.3 admin/admin-edit.php	28
7.2.4 admin/admin-select.php	31
7 2 5 admin/admin-users nhn	32

	7.2.6 events/events.php	34
	7.2.7 events/eventsDetails.php	36
	7.2.8 login.php	37
	7.2.9 register.php	38
	7.2.10 author.php	39
8	Models	39
	8.1 models/event	39
	8.1.1 delete.php	39
	8.1.2 pagination.php	40
	8.1.3 /filter.php	41
	8.1.4 insert.php	42
	8.2 user	45
	8.2.1 delete.php	45
	8.3 functions.php	46
	8.4 login.php	50
	8.5 registration.php	52
	8.6 logout.php	53
9	config	54
	9.1 .env	54
	9.2 connection.php	54
	9.3 config.php	55
10	O assets	56
	10.1 main.js	56
	10.2 style.css	67
	10.3 dashboard.css	73

2 Uvod

DjEvents je web aplikacija namenjena za postavljanje eventova u gradovima Srbije.

2.1 Korisćene tehnologije

- PHP
- HTML 5
- CSS 3
- Bootstrap
- Javascript
- jQuery
- AJAX
- MySQL


2.2 Opis funkcionalnosti

Sajt je full responsive i poseduje sledeće funkcionalnosti:

- Registracija Kada se korisnik registruje, njemu se omogucava da kupi ulaznice za event. Ukoliko to ne uradi onda moze samo da razgleda eventove.
- Logovanje Nakon uspesne registracije, korisnik se redirektuje na stranicu za logovanje.
 Uspesnim logovanjem setuje se sesija u kojoj se cuvaju podaci o ulogovanom korisniku. U zavisnosti od uloge korisnika prikazuje odredjeni sadrzaj linkova u navigaciji.
- Validacija forme Sve forme koje se nalaze su validirane na klijenskoj i na serverskoj strani
- Stranicenje Realizovano je stranicenje na stranicama event.php I u admin panelu koriscenjem
 AJAX-a
- Filtriranje omoguceno je filtriranje eventova po njivovim nazivima
- Kupovine Realizovana stranica za kupovine korisnika koja sadrzi informacije o istoriji kupovina.
- Admin Panel Samo korisnik sa ulogom admina moze da pristupi ovoj stranici. Ulaskom na stranicu adminu se prikazuje procenat posecenosti stranica u procentima a podaci se citaju iz LOG fajla. Admin ime CRUD operacije nad svim eventovima I moze da brise korisnike
- Upload fajla na server putem AJAX-a,fajl(slika) se cuva u dve verzije originalna I thumbnail

- Detalji o eventovima Klikom na svaki post otvara se single page view. Stranica sa podacima vezana za taj event. Na ovoj stranici korisnik ukoliko je autorizovan moze da kupuje ulaznice
- Menu Dinamicko ispisivanje menija iz baze podataka na svim stranicama u headeru i footeru, zavisno od uloge korisnika
- Odjava Ukoliko je korisnik ulogovan, klikom na logout se brisu podaci iz sesije i korisnik se preusmerava na pocetnu stranicu

3 Sema baze podataka




4 Template

Sto se tice admin stranice koriscen je template koji je preuzet sa zvanicnog bootstrap-ovog sajta.Za sve ostale stranice sav html I css kod je pisan.

5 Struktura foldera

Sajt ima samo jednu index.php stranicu u root-u koja ucitava iz foldera views stranice.Views folder ima fixed I pages(events I admin) foldere.Pored viewsa tu su jos assets,data,models(event I user) I config folder.




6 Mapa sajta


Admin panel je stranica dostupna samo autorizovanim korisnicima koji su admini. Profilna stranica je dostupna samo autorizovanim korisnicima. Login i register stranice su dostupne samo neautorizovanim korisnicima. Stranica za kreiranje postova je dostupna samo autorizovanim korisnicima.

6.1 sitemap.xml

6.2 events.php




Ova view sadrzi najblize tj predstojece eventove(sortirano po datumu). Klikom na deteljanije korisnik se salje na view eventDetails.php koja sadrzi podatke tog eventa.Na ovoj stranici odradjeno je filtriranje po nazivu kao I paginacija putem AJAX-a.




Linkovi u footeru I header su dinamicki ispisani iz baze.

6.3 eventDetails.php




Korisnik na ovoj stranici vidi sve podatke o eventu na koji je kliknuo.

6.4 Login.php




Na ovoj stranici se nalazi forma za logovanje, validacija se vrsi na klijentskoj i serverskoj strani. Ukoliko se uneti mejl i lozinka ne poklapaju sa tim istim podacima od vec registrovanog korisnika, korisniku se ispisuje poruka da je uneo pogresne kredencijale za logovanje. Ukoliko su ispravni podaci, korisnik se redirektuje na njegove kupovine

6.5 register.php




Na ovoj stranici se nalazi forma za registraciju korisnika, korisnik mora da unese svoje ime i prezime, mejl i lozinku. Validacija se izvrsava na klijentskoj i na serverskoj strani. Ukoliko neki od podataka ne prodje proveru, korisniku se ispisuje greska ili ukoliko unese vec postojeci mejl koji se nalazi u bazi podataka. Ukoliko je sve validno, korisnik se redirektuje ka viewu login.php

6.6 admin.php



Ovim stranicama moze da pristupi samo korisnik koji je uloga admin.Inicijalno mu se iz log fajla iscitava posecenost stranicama u procentima.


6.7 admin-insert.php



Samo admin moze da doda novi event. Validacija je I na frontu I na backu. Vrsi se upload fajla putem AJAXA. File(slika) se cuva u dva foldera u jednom slika full rezolucije u drugom thumbnail slika.


DDL popunjena dinamicki iz baze.

6.8 admin-select.php




Prikaz svih eventova. Moguce je njihovo brisanje I editovanje. Paginacija putem AJAX-a

6.9 admin-edit.php



Korisnik klikom na dugme 'Edit', prikazuje mu se forma sa vec popunjenim podacima tog eventa. Korisnik moze da izmeni sav sadrzaj vec okacenog posta. Ukoliko zeli da izmeni podatke, obavezno je da ispravno unese sve podatke koji se proveravaju na klijentskoj i na serverskoj strani.

6.10 admin-users.php



Na ovom viewu je prikaz svih registrovanih korisnika. Moguce je njihovo brisanje. Paginacija putem AJAX-a

7 Kodovi

7.1 views/fixed

7.1.1 Head.php

<?php require_once "config/connection.php";</pre>

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Dj Events</title>
    <!-- meta tagovi -->
    <meta name="keywords" content="events,party,dj,karte" />
    <meta name="description" content="DjEvents je sajt na kom mozete pronaci sva</pre>
dogadjanja u gradovima sirom Srbije.Pronadji sebi omiljenu zurku i kupi ulazicu"
    <!--favicon -->
    <link rel="shorcut icon" type="image/icon" href="assets/img/favico.ico" />
    <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap@4.5.3/dis</pre>
t/css/bootstrap.min.css" integrity="sha384-
TX8t27EcRE3e/ihU7zmQxVncDAy5uIKz4rEkgIXeMed4M0jlfIDPvg6uqKI2xXr2" crossorigin="an
onymous">
    <!-- font awesome -->
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/font-</pre>
awesome/5.15.2/css/all.min.css" integrity="sha512-
HK5fgLBL+xu6dm/Ii3z4xhlSUyZgTT9tuc/hSrtw6uzJOvgRr2a9jyxxT1ely+B+xFAmJKVSTbpM/CuL7
qx08w==" crossorigin="anonymous" />
    <link rel="stylesheet" href="assets/css/style.css">
    <link rel="stylesheet" href="assets/css/dashboard.css">
:/head>
```

7.2.2 nav.php

```
<i class="fas fa-bars fa-2x"></i></i>
   </div>
   <header>
       <div class="container">
           <div class="row mt-1">
               <div class="header-content py-1 d-flex w-100 align-items-</pre>
center justify-content-between">
                   <div class="logo ">
                       <h3 class="text-uppercase"><span>DJ</span> Events</h3>
                   </div>
                   <nav class="ml-5 menu ">
                       <?php
                           for ($i = 0; $i < count($meni); $i++) {
                               if (isset($_SESSION["user"]) && $_SESSION["user"]
->naziv == "Admin" && stripos($meni[$i]->putanja, "admin-
insert") == "" && stripos($meni[$i]->putanja, "admin-
select") == "" && stripos($meni[$i]-
>putanja, "logout") == "" && stripos($meni[$i]-
>putanja, "login") == "" & stripos($meni[$i]->putanja, "users") == "") {
                                  echo ("<li class='mr-
3'><a href='index.php{$meni[$i]->putanja}'>{$meni[$i]->naziv}</a>");
                              } else if (isset($_SESSION["user"]) && $_SESSION[
"user"]->naziv == "Korisnik" && stripos($meni[$i]-
>putanja, "admin") == "" && stripos($meni[$i]-
>putanja, "logout") == "" && stripos($meni[$i]-
>putanja, "login") == "" & stripos($meni[$i]->putanja, "users") == "") {
                                  echo ("<li class='mr-
3'><a href='index.php{$meni[$i]->putanja}'>{$meni[$i]->naziv}</a>");
                           if (!isset($_SESSION["user"])) {
                               echo ("<li class='mr-
3'><a href='index.php?page=events'>Dogadjaji</a>");
                              echo ("<li class='mr-
3'><a href='index.php?page=author'>Autor</a>");
                       </nav>
                   <div class="user-action">
                     <?php
```

```
if (!isset($_SESSION["user"])) :
                             <a href="index.php?page=login" class="btn btn-</pre>
black mr-3">
                                 <i class="fas fa-sign-in-alt"></i></i>
                                 <span>Prijavi se</span>
                             </a>
                         <?php
                         else :
                             <a href="models/logout.php" class="btn btn-black mr-</pre>
3">
                                 <i class="fas fa-sign-in-alt"></i>
                                 <span>Odjavi se</span>
                             </a>
                         <?php
                         endif
                     </div>
                </div>
            </div>
        </div>
```

7.1.3 footer.php

```
<footer class="section-footer mt-5">
    <div class="container">
        <div class="row">
            <div class="col-lg-3 col-md-6">
               <h3><span>DJ</span> Events</h3>
               <a href="https://www.twitter.com/" tar</pre>
get=" blank"><i class="fab fa-twitter fa-3x"></i></a>
                <a href="https://www.facebook.com/" ta</pre>
rget="_blank"><i class="fab fa-facebook fa-
3x"></i></a>
               <a href="https://www.youtube.com/" tar</pre>
get="_blank"><i class="fab fa-youtube fa-3x"></i></a>
            </div>
            <div class="col-lg-3 col-md-6">
               <h3>Navigacija</h3>
                <l
                   <?php
                   for ($i = 0; $i < count($meni); $i
++) {
                       if (isset($_SESSION["user"]) &
& $ SESSION["user"]-
>naziv == "Admin" && stripos($meni[$i]-
>putanja, "admin-insert") == "" && stripos($meni[$i]-
>putanja, "admin-select") == "" && stripos($meni[$i]-
>putanja, "logout") == "" && stripos($meni[$i]-
>putanja, "login") == "" & stripos($meni[$i]-
>putanja, "users") == "") {
                           echo ("<li class='mr-
3'><a href='index.php{$meni[$i]->putanja}'>{$meni[$i]-
>naziv}</a>");
                        } else if (isset($_SESSION["us
>naziv == "Korisnik" && stripos($meni[$i]-
>putanja, "admin") == "" && stripos($meni[$i]-
>putanja, "logout") == "" && stripos($meni[$i]-
```

```
>putanja, "login") == "" & stripos($meni[$i]-
>putanja, "users") == "") {
                                                                                echo ("<li class='mr-
3'><a href='index.php{$meni[$i]->putanja}'>{$meni[$i]-
>naziv}</a>");
                                                         if (!isset($ SESSION["user"])) {
                                                                     echo ("<li class='mr-
3'><a href='index.php?page=events'>Dogadjaji</a>"
);
                                                                    echo ("<li class='mr-
3'><a href='index.php?page=author'>Autor</a>");
                                              </div>
                                  <div class="col-lg-3 col-md-6">
                                              <h3>Korisni Linkovi</h3>
                                                         <a href="assets/xml/sitemap.xm"> <a href="assets/xmm"> <a href="assets/xmm"> <a href="asset
1">Sitemap</a>
                                                        <a href="djevents.pdf">Documen</a>
tation</a>
                                              </div>
                                  <div class="col-lg-3 col-md-6">
                                             <h3>Subscribe</h3>
                                             Primaj obavestenja od nas.
                                              <form name=email-</pre>
form method="POST" date-netlify='true'>
                                                        <div class="email-form">
                                                                     <input type="email" name="emai</pre>
1" id="emailFooter" class="control" placeholder="Email
     size='40'>
                                                                     <button type="submit" value="S</pre>
ubmit" class="form-control submit">
                                                                               <i class="fas fa-chevron-</pre>
right"></i>
                                                                    </button>
                                                        </div>
                                              </form>
                                 </div>
```

```
</div>
</footer>
```

7.1.4 script.php

```
<script src="https://cdnjs.cloudflare.com/ajax/libs/jq</pre>
uery/3.6.0/jquery.min.js" integrity="sha512-
894YE6QWD5I59HgZOGReFYm4dnWc1Qt5NtvYSaNcOP+u1T9qYdvdih
z0PPSiiqn/+/3e7Jo4EaG7TubfWGUrMQ==" crossorigin="anony
mous" referrerpolicy="no-referrer"></script>
<script src="https://cdn.jsdelivr.net/npm/popper.js@1.</pre>
16.1/dist/umd/popper.min.js" integrity="sha384-
9/reFTGAW83EW2RDu2S0VKaIzap3H661ZH81PoY1FhbGU+6BZp6G7n
iu735Sk71N" crossorigin="anonymous"></script>
<script src="https://cdn.jsdelivr.net/npm/bootstrap@4.</pre>
5.3/dist/js/bootstrap.min.js" integrity="sha384-
w1Q4orYjBQndcko6MimVbzY0tgp4pWB41Z71r30WKz0vr/aWKhXdBN
mNb5D92v7s" crossorigin="anonymous"></script>
<script src="assets/js/main.js" type="text/javascript"</pre>
></script>
</body>
</html>
```

7.1.5 admin/sidebar.php

```
<?php
session_start();
if (isset($_SESSION["user"]) && $_SESSION["user"]-
>naziv == "Admin") {
    require_once "config/connection.php";
    include "models/functions.php";
    $meni = getAll("meni");
} else {
```

```
header("Location: err404.php");
<nav class="navbar navbar-dark sticky-top bg-</pre>
dark flex-md-nowrap p-0 shadow">
   <a class="navbar-brand col-md-3 col-lg-2 mr-0 px-</pre>
3" href="index.php"><i class="fas fa-arrow-</pre>
left"></i> DJ EVENTS Admin Panel</a>
</nav>
<div class="container">
    <div class="row">
       <nav id="sidebarMenu" class="col-md-3 col-lg-</pre>
2 d-md-block bg-dark sidebar collapse">
           <div class="mt-3 pt-3">
               <?php
                   foreach ($meni as $m) :
                       <?php
                       if (stripos($m-
>putanja, "events") == "" && stripos($m-
>putanja, "author") == "" && stripos($m-
>putanja, "tickets") == "" && stripos($m-
>putanja, "logout") == "" && stripos($m-
>putanja, "login") == "") :
                           <a class="nav-
link white-color" id="allUsers" href="index.php<?= $m-
>putanja ?>">
                                   <?= $m->naziv ?>
                               </a>
                           <?php
                       endif;
                   <?php
                   endforeach;
```

7.2 views/pages

7.2.1 admin/admin.php

```
<?php
if (isset($_SESSION["user"]) && $_SESSION["user"]->naziv == "Admin") {
   $open = fopen(LOG_FAJL, "r");
   if ($open) {
      $array = file(LOG_FAJL);
      $allUrl = [];
      foreach ($array as $arr) {
         $x = explode("\t", $arr);
          array_push($allUrl, $x[0]);
      $countUrl = array_count_values($allUrl);
      $totalNumOFLogs = 0;
      foreach ($countUrl as $x) {
          $totalNumOFLogs += $x;
   }
} else {
   header("Location: err404.php");
<section>
   <div class="container my-3">
      <div class="row mb-5">
          <thead>
                >
                    RB
                    Stranica
                    Posecenost(%)
                </thead>
             <?php
                rb = 1;
                foreach ($countUrl as $key => $value) :
```

7.2.2 admin/admin-insert.php

```
<?php
$citys = getAll("grad");
<div class="container ml-custom">
    <div class="row">
        <div class="col-md-12">
            <form>
                <div class="form-row">
                    <div class="form-group col-md-6">
                         <label for="name">Naziv Eventa</label>
                         <input type="text" class="form-control" id="name">
                         <small class="form-text text-</pre>
danger hide">Event mora poceti velikim slovom i sadrzati bar 2 karaktera.</small</pre>
                    </div>
                    <div class="form-group col-md-6">
                         <label for="artist">Izvodjaci</label>
                         <input type="text" placeholder="Izvodjac1, Izvodjac2, Iz</pre>
vodjac3..." class="form-control" id="artist">
                         <small class="form-text text-</pre>
danger hide">Nazivi izvodjaca moraju biti razdvojeni zarezom.</small>
                    </div>
                </div>
                <div class="form-row">
```

```
<div class="form-group col-md-6">
                         <label for="city">Grad</label>
                         <select id="city" class="form-control">
                             <option value="0">Izaberite</option>
                             <?php
                             foreach ($citys as $city) :
                                 <option value="<?= $city->id grad ?>"><?= $city-</pre>
>naziv ?></option>
                             <?php
                             endforeach;
                         </select>
                         <small class="form-text text-</pre>
danger hide">Morate izabrati grad.</small>
                    </div>
                    <div class="form-group col-md-6">
                         <label for="adress">Mesto</label>
                         <input type="text" class="form-control" id="adress">
                        <small class="form-text text-</pre>
danger hide">Nepostojeca adresa.</small>
                    </div>
                </div>
                <div class="form-row">
                    <div class="form-group col-md-6">
                         <label for="date">Datum</label>
                         <input type="date" class="form-control" id="date">
                        <small class="form-text text-</pre>
danger hide">Morate izabrati datum.</small>
                    </div>
                    <div class="form-group col-md-6">
                         <label for="time">Vreme</label>
                         <input type="time" class="form-control" id="time">
                        <small class="form-text text-</pre>
danger hide">Morate izabrati vreme.
                    </div>
                </div>
                <div class="form-group ">
                    <label for="taDesc">Opis</label>
                    <textarea name="" id="taDesc" class="form-
control" cols="20" rows="6"></textarea>
                    <small class="form-text text-</pre>
danger hide">Opis eventa je obavezan.
```

7.2.3 admin/admin-edit.php

```
<?php
if (isset($_GET["id"])) {
    $singleEvent = getSingleEvent($_GET["id"]);
    $preformers = getPreformers($_GET["id"]);
    $dir = "assets/img-small/";
    $preformersStr = '';
    for ($i = 0; $i < count($preformers); $i++) {</pre>
        if ($i == 0) {
            $preformersStr .= $preformers[$i]->naziv;
        } else {
            $preformersStr .= "," . $preformers[$i]->naziv;
    //var dump($preformersStr);
    $cities = getAll("grad");
    $dir = "assets/uploaded_img/";
} else {
    header("Location: index.php?page=admin-select");
<div class="container">
    <div class="row">
       <div class="col-md-12">
```

```
<form>
                <div class="form-row">
                    <div class="form-group col-md-6">
                         <label for="name">Naziv Eventa</label>
                         <input type="text" class="form-</pre>
control" id="name" value="<?= $singleEvent->ime ?>">
                        <small class="form-text text-</pre>
danger hide">Event mora poceti velikim slovom i sadrzati bar 2 karaktera.
                    </div>
                    <div class="form-group col-md-6">
                         <label for="artist">Izvodjaci</label>
                         <input type="text" placeholder="Izvodjac1, Izvodjac2, Iz</pre>
vodjac3..." value="<?= $preformersStr ?>" class="form-control" id="artist">
                        <small class="form-text text-</pre>
danger hide">Nazivi izvodjaca moraju biti razdvojeni zarezom.</small>
                    </div>
                </div>
                <div class="form-row">
                    <div class="form-group col-md-6">
                         <label for="city">Grad</label>
                         <select id="city" class="form-control">
                             <option value="0">Izaberite</option>
                             <?php
                             foreach ($cities as $city) :
                                 <?php
                                 if ($city->naziv == $singleEvent->naziv) :
                                     <option selected value=" <?= $city-</pre>
>id_grad ?>"><?= $city->naziv ?></option>
                                 <?php
                                 else :
                                     <option value=" <?= $city-</pre>
>id grad ?>"><?= $city->naziv ?></option>
                                 <?php
                                 endif;
                             <?php
                             endforeach;
                        </select>
```

```
<small class="form-text text-</pre>
danger hide">Morate izabrati grad.</small>
                    </div>
                    <div class="form-group col-md-6">
                         <label for="adress">Mesto</label>
                         <input type="text" class="form-</pre>
control" value="<?= $singleEvent->adresa ?>" id="adress">
                        <small class="form-text text-</pre>
danger hide">Nepostojeca adresa.</small>
                    </div>
                </div>
                <div class="form-row">
                    <div class="form-group col-md-6">
                        <label for="date">Datum</label>
                        <input type="date" class="form-</pre>
control" value="<?= $singleEvent->datum ?>" id="date">
                        <small class="form-text text-</pre>
danger hide">Morate izabrati datum.</small>
                    </div>
                    <div class="form-group col-md-6">
                         <label for="time">Vreme</label>
                         <input type="time" class="form-</pre>
control" value="<?= $singleEvent->vreme ?>" id="time">
                        <small class="form-text text-</pre>
danger hide">Morate izabrati vreme.
                    </div>
                </div>
                <div class="form-group ">
                    <label for="taDesc">Opis</label>
                    <textarea name="" id="taDesc" class="form-
control" cols="20" rows="6"><?= $singleEvent->opis ?></textarea>
                    <small class="form-text text-</pre>
danger hide">Opis eventa je obavezan.
                </div>
                <div class="form-group col-md-6 mb-4">
                    <label for="imgPost">Slika Eventa</label>
                    <input type="file" id="file" class="form-control-file">
                    <small class="form-text text-</pre>
danger hide">Morate izabrati sliku eventa.
                </div>
                <input type="button" id="btnInsert" class=" btn btn-purple w-</pre>
100" value="Potvrdi" />
           </form>
```

7.2.4 admin/admin-select.php

```
<?php
$events = getUpComingEvents();
$pages = countPages("countEvents");
<div class="container mt-5">
  <div class="row">
    <div class="col-md-12">
      RB
             Event
             Datum
             Grad
             Edit
             Delete
           </thead>
         <?php
           rb = 1;
           foreach ($events as $event) :
             <?= $rb ?>
               <?= $event->ime ?>
               <?= $event->datum ?>
               <?= $event->naziv ?>
```

```
<a href="index.php?page=admin-
edit&id=<?= $event->id_event ?>" class="btn btn-primary editEvent white-
color">Izmeni</a>
                         <a href="#" class="btn btn-
danger deleteEvent white-color" data-id="<?= $event-</pre>
>id_event ?>">Obrisi</a>
                     <?php
                     $rb++;
                 endforeach;
              </div>
   </div>
</div>
<section>
   <div class="container mt-2">
       <div class="row">
          <div id="res" class="my-5">
          </div>
          <nav aria-label="Page navigation example" class="mx-auto">
              <?php
                  for (\$i = 0; \$i < \$pages; \$i++):
                     <a class="page-link" data-</pre>
limit="<?= $i ?>" href="#"><?= $i + 1 ?></a>
                 <?php
                 endfor;
              </nav>
       </div>
   </div>
</section>
```

7.2.5 admin/admin-users.php

```
<?php
$users = getUsers();
```

```
$pages = countPages("countUsers");
<div class="container mt-5">
   <div class="row">
      <div class="col-md-12">
         <thead>
              RB
                  Korisnik
                  Email
                  Delete
               </thead>
            <?php
              rb = 1;
               foreach ($users as $user) :
                    <?= $rb ?>
                    <?= $user->ime . " " . $user->prezime ?>
                    <?= $user->email ?>
                    <a href="#" class="btn btn-
danger deleteUser white-color" data-id="<?= $user-</pre>
>id_korisnik ?>">Obrisi</a>
                  <?php
                  $rb++;
               endforeach;
            </div>
   </div>
</div>
<section>
  <div class="container mt-2">
     <div class="row">
        <div id="res" class="my-5">
        </div>
        <nav aria-label="Page navigation example" class="mx-auto">
```

7.2.6 events/events.php

```
<?php
$events = getUpComingEvents();
$pages = countPages("countEvents");
<div class="showcase">
    <div class="showcase-content d-flex justify-content-center align-items-</pre>
center flex-column w-100">
        <h1 class="text-uppercase">Dobrodosli na DJ events</h1>
        Pronadji svoj idealan event i pozovi ekipu!
    </div>
</div>
<div class="container">
    <div class="row d-flex justify-content-between align-items-center my-5">
        <div class="col-md-6 text-uppercase">
            <h3 class="text-white">Predstojeci Dogadjaji</h3>
        </div>
        <div class="col-md-4">
            <div class="d-flex justify-content-center align-items-center">
                <input type="text" id="search" class="form-control mr-</pre>
2" placeholder="Pretrazi po nazivu..." />
                <input type="button" id="btnSearch" value="Pretrazi" class=" btn</pre>
 btn-purple" />
            </div>
        </div>
```

```
</div>
</div>
<div class="container">
    <div class="row d-flex justify-content-between align-items" id="events">
       <?php
       foreach ($events as $event) :
           $dir = "assets/img-small/";
            <div class="col-md-12 item d-flex justify-content-between align-</pre>
items-center w-100">
               <div class="item-img w-30">
                   <img src="<?= $dir . $event-</pre>
>putanja ?>" width="200px" alt="">
               </div>
               <div class="item-info text-center">
                   <?= $event->datum . " " . $event->vreme ?>
                   <h4 class="text-white font-weight-bold"><?= $event-
>ime ?></h4>
               </div>
               <a href="index.php?page=eventDetails&id=<?= $event-</pre>
>id_event ?>" class="btn btn-purple">Detaljnije</a>
           </div>
       <?php
       endforeach;
    </div>
</div>
<section>
    <div class="container mt-2">
       <div class="row">
            <nav aria-label="Page navigation example" class="mx-auto">
               <?php
                   for (\$i = 0; \$i < \$pages; \$i++) :
                       <a class="page-link" data-</pre>
limit="<?= $i ?>" href="#"><?= $i + 1 ?></a>
                   <?php
                   endfor;
               </nav>
       </div>
```

```
</div></section>
```

7.2.7 events/eventsDetails.php

```
<?php
if (isset($_GET["id"])) {
   $singleEvent = getSingleEvent($ GET["id"]);
   $preformers = getPreformers($_GET["id"]);
   $dir = "assets/uploaded img/";
   // var_dump($preformers);
} else {
   header("Location: index.php?page=event");
?>
<div class="container py-5 ">
   <div class="row ">
      <div class="mx-auto col-md-9">
          <a href="index.php?page=events">
              <i class=" mb-4 fas fa-arrow-left fa-2x"></i>
          </a>
          Naziv Eventa:
          <h1 class="my-2 text-white"><?= $singleEvent->ime ?></h1>
          <img src=" <?= $dir . $singleEvent-</pre>
>putanja ?>" alt="<?= $singleEvent->ime ?>">
          Opis Eventa:
          <?= $singleEvent-</pre>
>opis ?>
          Izvodjaci:
          <?php foreach ($preformers as $preformer) :</pre>
              white "><?= $preformer->naziv ?>
          <?php
          endforeach
          <div class="d-flex justify-content-between align-items-center">
             <div>
                 Adresa Eventa:
```

7.2.8 login.php

```
<div class="container">
    <div class="row d-flex justify-content-center mt-5">
        <div class="col-md-7">
            <div class="login">
                <h1 class="text-white mb-2"><i class="fas fa-user mr-
3"></i>Prijavi se</h1>
                <form>
                    <div class="form-group my-4">
                        <label for="emailLog">Email adresa</label>
                        <input type="email" class="form-</pre>
control" id="emailLog" aria-describedby="emailHelp">
                        <small class="form-text text-</pre>
danger hide">Primer - marko@markovic.com</small>
                    </div>
                    <div class="form-group my-4">
                        <label for="passwordLog">Lozinka</label>
                        <input type="password" class="form-</pre>
control" id="passwordLog">
                        <small class="form-text text-</pre>
danger hide">Lozinka mora sadrzati barem 8 karaktera, po jedno veliko i malo slov
o i jedan broj.</small>
                    </div>
                    Nemas nalog? <a class="text-</pre>
primary" href="index.php?page=register">Registruj se!</a>
                    <input type="button" id="btnLog" class="w-100 btn btn-</pre>
purple" value="Login" />
```

7.2.9 register.php

```
<div class="container">
    <div class="row d-flex justify-content-center mt-5">
        <div class="col-md-8 login">
            <h1 class="text-white"><i class="fas fa-user mr-
3"></i>Registruj se</h1>
            <form>
                <div class="form-row">
                    <div class="form-group col-md-6">
                         <label for="fname">Ime</label>
                         <input type="text" class="form-control" id="fname">
                         <small class="form-text text-</pre>
danger hide">Primer - Marko</small>
                    </div>
                    <div class="form-group col-md-6">
                         <label for="lname">Prezime</label>
                         <input type="text" class="form-control" id="lname">
                         <small class="form-text text-</pre>
danger hide">Primer - Markovic</small>
                    </div>
                </div>
                <div class="form-group">
                    <label for="emailRegister">Email</label>
                    <input type="text" class="form-control" id="emailRegister">
                    <small class="form-text text-</pre>
danger hide">Primer - marko@markovic.com</small>
                </div>
                <div class="form-group">
                    <label for="password">Lozinka</label>
                    <input type="password" class="form-control" id="password">
                    <small class="form-text text-</pre>
danger hide">Lozinka mora sadrzati barem 8 karaktera,po jedno veliko i malo slov
o i jedan broj.</small>
            </div>
```

7.2.10 author.php

```
<section class="author my-5">
    <div class="container">
        <div class="row">
            <div class="col-md-6 my-5">
                <img src="assets/img/ja1.jpg" class="rounded" alt="autor">
            </div>
            <div class="col-md-6 my-5">
                My name is Filip Lazarević. I come from Pancevo. I am 21 years o
ld and I am a student of ICT collage in Belgrade that recently became academy. I
 started doing programming a little over a year ago and I really liked it. I wou
ld like to do it in the future. I spend my free time mostly with family and frien
ds.That's it from me.
            </div>
        </div>
    </div>
</section>
```

8 Models

8.1 models/event

8.1.1 delete.php

```
<?php
session_start();</pre>
```

```
if ($_SERVER["REQUEST_METHOD"] == "POST" && $_SESSION["user"]-
>naziv == "Admin" && isset($ POST["idUI"])) {
    header("Content-type: application/json");
    include_once("../../config/connection.php");
    include once("../functions.php");
    $id = $_POST["idUI"];
    try {
        $conn->beginTransaction();
        delete($id, "event_izvodjac", "id_event");
        delete($id, "events", "id_event");
        $conn->commit();
        $events = getUpComingEvents();
        $msg = ["msg" => "You have successfully deleted a post.", "events" => $e
vents];
        http response code(200);
        echo json_encode($msg);
    } catch (PDOException $ex) {
        $conn->rollback();
        $msg = ['msg' => $ex->getMessage()];
        http response code(500);
        echo json_encode($msg);
} else {
    header('Location: ../err404.php');
```

8.1.2 pagination.php

```
<?php
if ($_SERVER["REQUEST_METHOD"] == "POST") {
    header("Content-type: application/json");
    require_once("../../config/connection.php");
    include("../functions.php");

    try {
        $limit = '';
        if (isset($_POST["limitEvent"])) {
            $limit = $_POST["limitEvent"];
            $events = getUpComingEvents($limit);</pre>
```

```
echo json_encode($events);
} else {
    $limit = $_POST["limitUsers"];
    $users = getUsers($limit);
    echo json_encode($users);
}
http_response_code(200);
} catch (PDOException $ex) {
    http_response_code(500);
}
```

8.1.3 /filter.php

```
<?php
if ($_SERVER["REQUEST_METHOD"] == "POST" && isset($_POST["serachParamUI"])) {
    header("Content-type: application/json");
    require_once "../../config/connection.php";
    include "../functions.php";
    $string = trim($_POST["serachParamUI"]);
    $compereString = "%$string%";
    try {
        $filteredEvents = [];
        if (strlen($compereString) == 2) {
            $filteredEvents = getUpComingEvents();
        } else {
            $filteredEvents = filterEvents($compereString);
        http response code(200);
        echo json_encode($filteredEvents);
    } catch (PDOException $ex) {
        echo json_encode(['message' => $ex->getMessage()]);
        http_response_code(500);
} else {
    http_response_code(400);
```

8.1.4 insert.php

```
<?php
session_start();
if ($ SERVER["REQUEST METHOD"] == "POST" && $ SESSION["user"]-
>naziv == "Admin") {
    header("Content-type: application/json");
    require_once "../../config/connection.php";
    include "../functions.php";
    //promernjive
    $name = addslashes($ POST["nameUI"]);
    $adress = addslashes($ POST["adressUI"]);
    $cityID = $_POST["cityUI"];
    $artistAll = trim(addslashes($_POST["artistUI"]));
    $date = addslashes($_POST["dateUI"]);
    $time = addslashes($ POST["timeUI"]);
    $desc = addslashes($_POST["descUI"]);
    //file
    $file = $_FILES["fileUI"];
    $fileName = $file["name"];
    $tmpFIle = $file["tmp name"];
    $size = $file["size"];
    $type = $file["type"];
    $errFile = $file["error"];
    reEventName = "/^[A-Z][A-z\d]{1,20}(\s[A-Z][A-z\d]{1,20})*$/";
    $reArtist = "/^[A-z\d]{2,15}(\s[A-Za-z\d]{2,20})*(,[A-z\d]{2,15}(\s[A-Za-
z\d]{2,20})*)*$/";
    $reAdress = "/^([A-ZŠĐĆČŽ][a-zšđčćž]{2,15}|[0-9])+(\s[A-ZŠĐĆČŽ[a-zšđčćž0-
9\.\-]{2,20})+$/";
   //provera dal je idGrad u id-vima iz baze
    $allCities = getAll("grad");
    $citiesArr = [];
    foreach ($allCities as $city) {
        array_push($citiesArr, $city->id_grad);
   err = 0;
```

```
if (isset($name)) {
       if (!preg_match($reEventName, $name)) {
           $err++;
  if (isset($adress)) {
      if (!preg_match($reAdress, $adress)) {
           $err++;
  if (isset($cityID)) {
      if (!in_array($cityID, $citiesArr)) {
           $err++;
  if (isset($artist)) {
      if (!preg_match($reArtist, $artist)) {
           $err++;
  if (!isset($time)) {
      $err++;
  if (!isset($date)) {
      $err++;
  if (!isset($desc)) {
       $err++;
  $uploadErr = 0;
  $imgFormat = ["image/jpg", "image/jpeg", "image/png"];
  if (!in_array($type, $imgFormat)) {
       $uploadErr++;
       echo json_encode(['msg' => 'Format slike mora da bude .jpg, .jpeg, .png
]);
       http_response_code(401);
   }
  if ($size > 200000) {
       $uploadErr++;
       echo json_encode(['msg' => 'Slika ne sme da bude veca od 2mb']);
      http_response_code(401);
```

```
if (!$uploadErr && !$err) {
        $newFileName = time() . "-" . $fileName;
        $path = "../../assets/uploaded_img/" . $newFileName;
        $result = move uploaded file($tmpFIle, $path);
        if ($result) {
            $cords = getimagesize($path);
            $newWidth = 80;
            $newHeight = $cords[1] * $newWidth / $cords[0];
            $extension = pathinfo($path, PATHINFO_EXTENSION);
            if ($extension == "png") {
                $objImg = imagecreatetruecolor($newWidth, $newHeight);
                $resorce = imagecreatefrompng($path);
                imagecopyresampled($objImg, $resorce, 0, 0, 0, 0, $newWidth, $ne
wHeight, $cords[0], $cords[1]);
                imagepng($objImg, "../../assets/img-small/$newFileName");
            } else {
                $objImg = imagecreatetruecolor($newWidth, $newHeight);
                $resorce = imagecreatefromjpeg($path);
                imagecopyresampled($objImg, $resorce, 0, 0, 0, 0, $newWidth, $ne
wHeight, $cords[0], $cords[1]);
                imagejpeg($objImg, "../../assets/img-small/$newFileName");
        $artist = explode(",", $artistAll);
        try {
            $status = 1;
            $conn->beginTransaction();
            $insert = insertEvent($name, $adress, $cityID, $date, $time, $desc,
$status, $newFileName);
            $eventID = $conn->lastInsertId();
            $artistID = '';
            foreach ($artist as $art) {
               $a = selectArt($art);
```

```
if (count($a) == 0) {
                    insertArtist($art);
                } else {
                    $artistID = $a[0]->id_izvodjac;
                $artistID = $conn->lastInsertId();
                insertEventArtist($eventID, $artistID);
            $conn->commit();
            echo json_encode(['msg' => 'Event uspesno kreiran']);
            http_response_code(201);
        } catch (PDOException $ex) {
            $conn->rollback();
            // echo json_encode(['msg' => "Problemi sa serverom,probajte ponovo.
            echo json_encode(['msg' => $ex->getMessage()]);
            http_response_code(500);
} else {
   http_response_code(404);
```

8.2 user

8.2.1 delete.php

```
<?php
session_start();
if ($_SERVER["REQUEST_METHOD"] == "POST" && $_SESSION["user"]-
>naziv == "Admin" && isset($_POST["idUI"])) {
    header("Content-type: application/json");
    include_once("../.config/connection.php");
    include_once("../functions.php");
    $id = $_POST["idUI"];
    try {
        $delete = delete($id, "korisnici", "id_korisnik");

        if ($delete) {
            $users = getUsers();
        }
}
```

```
$msg = ["msg" => "Uspesno brisanje.", "users" => $users];
http_response_code(200);
echo json_encode($msg);
}
} catch (PDOException $ex) {
    $conn->rollback();
    $msg = ['msg' => $ex->getMessage()];
    http_response_code(500);
    echo json_encode($msg);
}
} else {
    header('Location: ../err404.php');
}
```

8.3 functions.php

```
<?php
function insertUser($fname, $lname, $email, $pass, $status, $role)
   global $conn;
   $query = "INSERT INTO korisnici (ime,prezime,email,lozinka,status,uloga) VAL
UES(?,?,?,?,?,?)";
   $insert = $conn->prepare($query);
   $result = $insert->execute([$fname, $lname, $email, $pass, $status, $role]);
    return $result;
  function insertCity($city)
       $query = "INSERT INTO grad (naziv) VALUES(:grad)";
       $insert = $conn->prepare($query);
       $insert->bindParam(":grad", $city);
       $result = $insert->execute();
       return $result;
function getAll($table)
   global $conn;
```

```
$query = "SELECT * FROM $table";
    $select = $conn->query($query);
    $result = $select->fetchAll();
    return $result;
 / function findCity($city)
       global $conn;
       $query = "SELECT * FROM grad WHERE naziv = :grad";
       $select = $conn->prepare($query);
       $select->bindParam(":grad", $city);
       $select->execute();
       $result = $select->fetch();
      return $result;
function insertArtist($art)
   global $conn;
   $query = "INSERT INTO izvodjaci (naziv) VALUES (:izvodjac)";
   $insert = $conn->prepare($query);
   $insert->bindParam(":izvodjac", $art);
   $result = $insert->execute();
    return $result;
function insertEvent($name, $adress, $cityID, $date, $time, $desc, $status, $img
    global $conn;
    $query = "INSERT INTO events (naziv,adresa,datum,vreme,opis,id_grad,status,p
utanja) VALUES (?,?,?,?,?,?,?)";
   $insert = $conn->prepare($query);
   $result = $insert-
>execute([$name, $adress, $date, $time, $desc, $cityID, $status, $img]);
    return $result;
function insertEventArtist($eventID, $artistID)
    global $conn;
   $query = "INSERT INTO event_izvodjac (id_izvodjac,id_event) VALUES (?,?)";
   $insert = $conn->prepare($query);
   $result = $insert->execute([$artistID, $eventID]);
    return $result;
```

```
function logUser($email, $pass)
    global $conn;
    $query = "SELECT * FROM korisnici k INNER JOIN uloge u ON k.uloga = u.id ulo
ge WHERE k.email=:email AND k.lozinka=:lozinka";
    $select = $conn->prepare($query);
    $select->bindParam(":email", $email);
   $select->bindParam(":lozinka", $pass);
    $select->execute();
    $result = $select-
>fetchAll(); //fetchAll,da bi mogao da pitam dal je samo 1 red vracen,jer rowCou
nt ne radi za select
    return $result;
function getUpComingEvents($limit = 0)
    global $conn;
    $query = "SELECT *,e.naziv AS ime FROM events e INNER JOIN grad g ON e.id gr
ad = g.id grad ORDER BY e.datum,e.vreme LIMIT :limit,:offset";
    $select = $conn->prepare($query);
    $limit = (int)OFFSET * (int)$limit;
    $select->bindParam(":limit", $limit, PDO::PARAM INT);
    $offset = (int)OFFSET;
    $select->bindParam(":offset", $offset, PDO::PARAM_INT);
    $select->execute();
    $result = $select->fetchAll();
    return $result;
function getUsers($limit = 0)
    global $conn;
    $query = "SELECT * FROM korisnici LIMIT :limit,:offset";
    $select = $conn->prepare($query);
    $limit = (int)OFFSET * (int)$limit;
    $select->bindParam(":limit", $limit, PDO::PARAM_INT);
    $offset = (int)OFFSET;
    $select->bindParam(":offset", $offset, PDO::PARAM_INT);
    $select->execute();
    $result = $select->fetchAll();
    return $result;
```

```
function countEvents()
    global $conn;
    $query = "SELECT COUNT(*) AS numEvents FROM events e INNER JOIN grad g ON e.
id grad = g.id grad ORDER BY e.datum,e.vreme";
    $select = $conn->query($query);
    $result = $select->fetch();
    return $result;
function countUsers()
   global $conn;
    $query = "SELECT COUNT(*) AS numEvents FROM korisnici";
   $select = $conn->query($query);
    $result = $select->fetch();
    return $result;
function countPages($fja)
    $pagesObj = $fja();
    $pages = ceil($pagesObj->numEvents / OFFSET);
    return $pages;
function getSingleEvent($id)
    global $conn;
    $query = "SELECT *,e.naziv AS ime FROM events e INNER JOIN grad g ON e.id gr
ad = g.id grad WHERE e.id event= :id";
    $select = $conn->prepare($query);
    $select->bindParam(":id", $id);
   $select->execute();
    $result = $select->fetch();
    return $result;
function filterEvents($str)
    global $conn;
    $query = "SELECT *,e.naziv AS ime FROM events e INNER JOIN grad g ON e.id_gr
ad = g.id grad WHERE e.naziv LIKE :val";
    $select = $conn->prepare($query);
    $select->bindParam(":val", $str);
   $select->execute();
   $result = $select->fetchAll();
```

```
return $result;
function getPreformers($id)
    global $conn;
    $query = "SELECT * FROM event_izvodjac AS ei INNER JOIN izvodjaci i ON ei.id
izvodjac = i.id izvodjac WHERE ei.id event=:id";
    $select = $conn->prepare($query);
    $select->bindParam(":id", $id);
    $select->execute();
    $result = $select->fetchAll();
   return $result;
function delete($id, $table, $col)
    global $conn;
    $query = "DELETE FROM $table WHERE $col = :id";
    $delete = $conn->prepare($query);
    $delete->bindParam(":id", $id);
    $result = $delete->execute();
    return $result;
function selectArt($art)
    global $conn;
    $query = "SELECT * FROM izvodjaci WHERE naziv=:art";
    $select = $conn->prepare($query);
   $select->bindParam(":art", $art);
    $select->execute();
    $result = $select->fetchAll();
    return $result;
```

8.4 login.php

```
<?php
if ($_SERVER["REQUEST_METHOD"] == "POST") {
    session_start();
    require_once "../config/connection.php";</pre>
```

```
include "functions.php";
    $email = addslashes($_POST["emailUI"]);
    $password = $_POST["passwordUI"];
    reEmail = "/^([a-zA-Z0-9_\-\.]+)@([a-zA-Z0-9_\-\.]+)\.([a-zA-Z]{2,5})$/";
    rePassword = "/^(?=.*[a-z])(?=.*[A-Z])(?=.*d)[a-zA-Zd]{8,}$/";
    err = 0;
    if (isset($_POST["emailUI"])) {
        if (!preg_match($reEmail, $email)) {
            $err++;
    if (isset($_POST["passwordUI"])) {
        if (!preg_match($rePassword, $password)) {
            $err++;
    }
    $msg = [];
    if (!$err) {
        $encryptedPass = md5($password);
        try {
            $user = logUser($email, $encryptedPass);
            if (count($user) == 1) {
                $ SESSION["user"] = $user[0];
                $msg = ["msg" => "Uspesno logovanje"];
                http_response_code(200);
                echo json_encode($msg);
            } else {
                $msg = ["msg" => "Kombinacija email/lozinka se ne poklapa"];
                http_response_code(401);
                echo json_encode($msg);
        } catch (PDOException $exception) {
            http_response_code(500);
            $msg = ["msg" => "Problemi sa serverom"];
            echo json_encode($msg);
} else {
   http_response_code(404);
```

```
header("Location: ../err404.php");
}
```

8.5 registration.php

```
<?php
if ($_SERVER["REQUEST_METHOD"] == "POST") {
   header("Content-type: application/json");
    require_once("../config/connection.php");
    include("functions.php");
    try {
        $fName = addslashes($_POST["fnameUI"]);
        $1Name = addslashes($_POST["lnameUI"]);
        $email = addslashes($_POST["emailUI"]);
        $password = $_POST["passwordUI"];
        $passwordConf = $_POST["passwordConfUI"];
        err = 0;
        reFristName = "/^([A-Z][a-z]{2,15})+$/";
        reLastName = "/^([A-Z][a-z]{2,20})+$/";
        reEmail = "/^([a-zA-Z0-9_\-\.]+)@([a-zA-Z0-9_\-\.]+)\.([a-zA-Z0-9_\-\.]+)
Z]{2,5})$/";
        rePassword = "/^(?=.*[a-z])(?=.*[A-Z])(?=.*d)[a-zA-Zd]{8,}$/";
        if (isset($fName)) {
            if (!preg_match($reFristName, $fName)) {
                $err++;
            }
        if (isset($1Name)) {
            if (!preg_match($reLastName, $1Name)) {
                $err++;
        if (isset($email)) {
            if (!preg_match($reEmail, $email)) {
                $err++;
```

```
if (isset($password)) {
            if (!preg_match($rePassword, $password)) {
                $err++;
        if (isset($passwordConf)) {
            if (!preg_match($rePassword, $passwordConf)) {
                $err++;
            }
        if ($password !== $passwordConf) {
            $err++;
        msg = [];
        if (!$err) {
            try {
                $encryptedPass = md5($password);
                $status = 1;
                $roleId = 2;
                $insert = insertUser($fName, $lName, $email, $encryptedPass, $st
atus, $roleId);
                if ($insert) {
                    $msg = ["msg" => "Uspesna registracija"];
                    http_response_code(201);
                    echo json_encode($msg);
            } catch (PDOException $exception) {
                http_response_code(401);
                $msg = ["msg" => "Email koji ste uneli je vec uzet."];
                echo json_encode($msg);
    } catch (PDOException $exception) {
        http_response_code(404);
        header("Location: ../err404.php");
```

8.6 logout.php

```
<?php
```

```
session_start();
if (isset($_SESSION['user'])) {
    unset($_SESSION['user']);
    header("Location: ../index.php?page=events");
} else {
    header("Location: ../err404.php");
}
```

9 config

9.1 .env

DBNAME=djevents SERVER=localhost USERNAME=root PASSWORD=

9.2 connection.php

```
<?php

require_once "config.php";

logAction();

try {
    $conn = new PDO("mysql:host=" . SERVER . ";dbname=" . DATABASE . ";charset=u
tf8", USERNAME, PASSWORD);
    $conn->setAttribute(PDO::ATTR_DEFAULT_FETCH_MODE, PDO::FETCH_OBJ);
    $conn->setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);
```

```
} catch (PDOException $ex) {
    echo $ex->getMessage();
}

function executeQuery($query)
{
    global $conn;
    return $conn->query($query)->fetchAll();
}

function logAction()
{
    $open = fopen(LOG_FAJL, "a");
    if ($open) {
        $date = date('d-m-Y H:iss');
        fwrite($open, "{$_SERVER['PHP_SELF']}\t{$_SERVER['REMOTE_ADDR']}\t$date\
n"); //$_SERVER['HTTP_REFERER']
        fclose($open);
    }
}
```

9.3 config.php

```
// Osnovna podesavanja
define("BASE_URL", "http://127.0.0.1/phpSajt2/");
define("ABSOLUTE_PATH", $_SERVER["DOCUMENT_ROOT"] . "/phpSajt2");

// Ostala podesavanja
define("ENV_FAJL", ABSOLUTE_PATH . "/config/.env");
define("LOG_FAJL", ABSOLUTE_PATH . "/data/log.txt");
define("OFFSET", 4);

// Podesavanja za bazu
define("SERVER", env("SERVER"));
define("DATABASE", env("DBNAME"));
```

10 assets

10.1 main.js

```
//ham meni
   let ham = document.querySelector(".menu-btn");
  ham.addEventListener("click",()=>{
       document.querySelector(".menu ul").classList.toggle("show");
   })
   //regularni izrazi
  let reEmail = /^([a-zA-Z0-9_{-}]+)@([a-zA-Z0-9_{-}]+).([a-zA-Z]{2,5})$/;
   let rePassword = /^(?=.*[a-z])(?=.*[A-Z])(?=.*d)[a-zA-Z\d]{8,}$/;
   let reFristName = /^([A-Z][a-z]{2,15})+$/;
   let reLastName = /^([A-Z][a-z]{2,20})+$/;
   let err = 0;
  var page = window.location.search;
  //ako nema paramaetra u url alternativa
  var indexPage = document.URL.split("/");
  var pageWhitoutParam = indexPage[indexPage.length-1];
   if (page == "?page=register") {
      //promenjive
      let fname = document.querySelector('#fname')
      let lname = document.querySelector('#lname');
      let email = document.querySelector('#emailRegister');
      let password = document.querySelector('#password');
      let passwordConf = document.querySelector('#passwordConf');
      //event za registraciju
      btnReg.addEventListener("click", () => {
           validRegex(fname, reFristName);
           validRegex(lname, reLastName);
           validRegex(email, reEmail);
           validRegex(password, rePassword);
           if (password.value !== passwordConf.value || passwordConf.value == "
) {
               err++;
               passwordConf.classList.add("err");
               passwordConf.classList.remove("succ");
               passwordConf.nextElementSibling.classList.remove("hide");
           } else {
               passwordConf.classList.remove("err");
               passwordConf.classList.add("succ");
               passwordConf.nextElementSibling.classList.add('hide');
           if (!err) {
               let dataUI = {
```

```
fnameUI: fname.value,
                    lnameUI: lname.value,
                    emailUI: email.value,
                    passwordUI: password.value,
                    passwordConfUI: passwordConf.value
                fetchAjax("models/registration.php", "POST", authSucc, regErr, d
ataUI);
        });
        function regErr(xhr) {
            result.innerHTML = `<p class="alert alert-danger mt-
5">${JSON.parse(xhr.responseText).msg}`;
            clearInput(fname);
            clearInput(lname);
            clearInput(email);
            clearInput(password);
            clearInput(passwordConf);
    //globalne funkcije
    function authSucc(data) {
        result.innerHTML = `<p class="alert alert-success mt-
5">${data.msg}`;
        setTimeout(() => {
            window.location.href = "index.php?page=login";
        }, 2000);
    function validRegex(obj, regex) {
        if (!regex.test(obj.value)) {
            obj.classList.add("err");
            obj.nextElementSibling.classList.remove("hide");
            err++;
        } else {
            obj.classList.remove("err");
            obj.classList.add("succ");
            obj.nextElementSibling.classList.add("hide");
    function validInput(input,compere) {
        if (input.value == compere) {
           input.classList.add("err");
```

```
input.nextElementSibling.classList.remove("hide");
          err++;
      } else {
          input.classList.remove("err");
          input.classList.add("succ");
          input.nextElementSibling.classList.add("hide");
  function clearInput(obj) {
      obj.value = "";
      obj.classList.remove("succ");
   function pagination(e){
      e.preventDefault();
      let limit = this.dataset.limit;
      let data = {
          limitEvent : limit
      fetchAjax("models/event/pagination.php", "POST", printEvents, printEmpty
data);
      $('html').animate({'scrollTop':'0'},1)
  if (page == "?page=login") {
      let email = document.querySelector('#emailLog');
      let password = document.querySelector('#passwordLog')
      btnLog.addEventListener("click", () => {
          validRegex(email, reEmail);
          validRegex(password, rePassword);
          if (!err) {
              let dataUI = {
                  emailUI: email.value,
                  passwordUI: password.value,
              fetchAjax("models/login.php", "POST", authLog, logErr, dataUI);
          function authLog(data){
```

```
result.innerHTML = `<p class="alert alert-success mt-
5">${data.msg}`;
                  setTimeout(() => {
                      window.location.href = "index.php?page=events";
                  }, 2000);
             function logErr(xhr) {
                  result.innerHTML = `<p class="alert alert-danger mt-
5">${JSON.parse(xhr.responseText).msg}```
                  clearInput(email);
                  clearInput(password);
         })
    let reEventName = /^[A-Z][A-z\d]{1,20}(\s[A-Z][A-z\d]{1,20})*$/
    let reArtist = /^[A-z\d]{2,15}(\s[A-Za-z\d]{2,20})*(,[A-z\d]{2,15}(\s[A-Za-z\d]{2,20})*(,[A-z\d]{2,15}(\s[A-Za-z\d]{2,15})(\s[A-Za-z\d]{2,15})
z\d]{2,20})*)*$/
    let reAdress = /^{(A-Z\tilde{S}D\tilde{C}\tilde{Z})[a-z\tilde{S}d\tilde{C}\tilde{Z}]\{2,15\}|[0-9])+(\sqrt{S}A-Z\tilde{S}D\tilde{C}\tilde{Z}[a-z\tilde{S}d\tilde{C}\tilde{Z}]\}
9\.\-]{2,20})+$/
    // let reCity = /^[A-ZŠDĆČŽ][a-zšđčćž]{2,15}(\s[A-ZŠDĆČŽ][a-
zšđčćž]{2,15})*$/
    if (page == "?page=admin-insert" || page.indexOf("admin-edit")!=-1) {
         btnInsert.addEventListener("click", () => {
             err = 0;
             let name = document.querySelector("#name");
             let adress = document.querySelector("#adress");
             let city = document.querySelector("#city");
             let artist = document.querySelector("#artist");
             let date = document.querySelector("#date");
             let time = document.querySelector("#time");
             let desc = document.querySelector("#taDesc");
             let file = document.querySelector("#file");
             validRegex(name, reEventName);
             validRegex(adress, reAdress);
             validRegex(artist, reArtist);
             if (file.files[0] == undefined) {
                  file.classList.add("err");
                  file.nextElementSibling.classList.remove("hide");
                  err++;
```

```
} else {
               file.classList.remove("err");
               file.classList.add("succ");
               file.nextElementSibling.classList.add("hide");
           validInput(time,"");
           validInput(date,"");
           validInput(desc,"");
           validInput(city,"0");
           if (!err) {
               let dataUI = new FormData();
               dataUI.append("nameUI", name.value);
               dataUI.append("adressUI", adress.value);
               dataUI.append("cityUI", city.value);
               dataUI.append("artistUI", artist.value);
               dataUI.append("dateUI", date.value);
               dataUI.append("timeUI", time.value);
               dataUI.append("descUI", desc.value);
               dataUI.append("fileUI", file.files[0]);
               // fetchAjax("models/event/insert.php", "POST", succInsert, err
Insert, dataUI);
               $.ajax({
                   url : "models/event/insert.php",
                   method : "POST",
                   data : dataUI,
                   contentType : false,
                   processData : false,
                   success : function(data){
                       succInsert(data);
                   },
                   error : function(xhr){
                       errInsert(xhr)
                   }
               });
           function succInsert(data){
               message.innerHTML = `
5">${data.msg}`;
               setTimeout(() => {
                   message.innerHTML = "";
               }, 2000);
```

```
clearInput(name);
               clearInput(adress);
               clearInput(artist);
               clearInput(date);
               clearInput(time);
               clearInput(desc);
               clearInput(file);
               city.classList.remove("succ");
               city.options.selectedIndex = 0;
           function errInsert(xhr){
               message.innerHTML = `
5">${JSON.parse(xhr.responseText).msg}```
       })
   if(page == "?page=events" || pageWhitoutParam == "index.php" || pageWhitoutP
aram == "index.php#"){
       $(document).on("click",".page-link",pagination);
       btnSearch.addEventListener("click",filterEvents);
   function filterEvents(){
       let serachParam = search.value;
       let data = {
           serachParamUI : serachParam
       fetchAjax("models/event/filter.php", "POST", printEvents, printEmpty, da
ta);
    function printEvents(data){
       let html = "";
       let dir = "assets/img-small/";
       if(data.length){
           for(d of data){
               html += `<div class="col-md-12 item d-flex justify-content-</pre>
between align-items-center w-100">
               <div class="item-img w-30">
                   <img src="${dir + d.putanja}" width="200px" alt="${d.ime}">
               </div>
               <div class="item-info text-center">
```

```
${d.datum} ${d.vreme}
                   <h4 class="text-white font-weight-bold">${d.ime}</h4>
               </div>
               <a href="index.php?page=eventDetails&id=${d.id event}" class="bt</pre>
n btn-purple">Detaljnije</a>
           </div>`;
       }else{
           html += `<h3 class='my-4 text-white text-</pre>
uppercase'>Trenutno nema dogadja za prikaz.</h3>`
       events.innerHTML = html;
   function printEmpty(xhr){
       events.innerHTML = "<h3 class='mt-</pre>
4'>Trenutno nema dogadja za prikaz.</h3>"
   if(page == "?page=admin-select"){
       $(document).on("click",".page-link",function(e){
           e.preventDefault();
           let limit = this.dataset.limit;
           let data = {
               limitEvent : limit
           fetchAjax("models/event/pagination.php", "POST", printEventsTable, e
rrPrint, data);
           function printEventsTable(data){
               let html = ``;
               let rb = 1;
              if(data.length){
               for(d of data){
                   html += `
                   ${rb}
                   ${d.ime}
                   ${d.datum}
                   ${d.naziv}
                   <a href="index.php?page=admin-
edit&id=${d.id event}" class="btn btn-primary white-color">Izmeni</a>
                   <a href="#" class="btn btn-danger deleteEvent white-
color" data-id="${d.id event}">Obrisi</a>
```

```
`;
              rb++;
              }else{
              html += `<h3 class='my-4 text-white text-</pre>
uppercase'>Trenutno nema dogadja za prikaz.</h3>`
           eventsTable.innerHTML = html;
           function errPrint(xhr){
              console.log(xhr);
       });
       $(document).on("click",".deleteEvent",function(e){
           e.preventDefault();
           let id = this.dataset.id;
           let data = {
              idUI : id
           fetchAjax("models/event/delete.php", "POST", printOthers, printOther
sErr, data);
       })
       function printOthers(data){
           let html = ``;
           let rb = 1;
          if(data.events.length){
           for(d of data.events){
              html += `
              ${rb}
              ${d.ime}
               ${d.datum}
               ${d.naziv}
              <a href="index.php?page=admin-
edit&id=${d.id_event}>" class="btn btn-primary white-color">Izmeni</a>
              <a href="#" class="btn btn-danger deleteEvent white-
color" data-id="${d.id event}">Obrisi</a>
           `;
           rb++;
          }else{
```

```
html += `<h3 class='my-4 text-white text-</pre>
uppercase'>Trenutno nema dogadja za prikaz.</h3>`
       eventsTable.innerHTML = html;
       res.innerHTML = `${data.msg}`
       setTimeout(()=>{
           res.innerHTML = '';
       },2000);
       function printOthersErr(xhr){
           eventsTable.innerHTML = `<h3 class='my-4 text-white text-</pre>
uppercase'>Trenutno nema dogadja za prikaz.</h3>`;
   if(page == "?page=admin-users"){
       $(document).on("click",".page-link",function(e){
           e.preventDefault();
           let limit = this.dataset.limit;
           let data = {
              limitUsers : limit
           fetchAjax("models/event/pagination.php", "POST", printUsers, errPrin
t, data);
       });
       function printUsers(data){
           let html = ``;
           let rb = 1;
          if(data.length){
           for(d of data){
              html += `
              ${rb}
              ${d.ime} ${d.prezime}
              ${d.email}
              <a href="#" class="btn btn-danger deleteUser white-
color" data-id="${d.id_korisnik}">Obrisi</a>
           rb++;
```

```
}else{
           html += `<h3 class='my-4 text-white text-</pre>
uppercase'>Trenutno nema korisnika za prikaz.</h3>`
       usersTable.innerHTML = html;
       function errPrint(xhr){
           console.log(xhr);
       $(document).on("click",".deleteUser",function(e){
           e.preventDefault();
           let id = this.dataset.id;
           let data = {
              idUI : id
           fetchAjax("models/user/delete.php", "POST", printUsersLeft, errPrint
 data);
       })
       function printUsersLeft(data){
           let html = ``;
          let rb = 1;
          if(data.users.length){
           for(d of data.users){
              html += `
              ${rb}
              ${d.ime} ${d.prezime}
              ${d.email}
              <a href="#" class="btn btn-danger deleteUser white-
color" data-id="${d.id korisnik}">Obrisi</a>
           rb++;
          }else{
          html += `<h3 class='my-4 text-white text-</pre>
uppercase'>Trenutno nema korisnika za prikaz.</h3>`
       usersTable.innerHTML = html;
       res.innerHTML = `${data.msg}`
       setTimeout(()=>{
           res.innerHTML = '';
```

```
},2000);
}
}
```

10.2 style.css

```
:root {
  --secondary-color: #a435f0;
  --primary-color: #1c1d1f;
  --font-color: #bbb7b7;
  margin: 0px;
  padding: 0px;
  scroll-behavior: smooth;
  box-sizing: border-box;
  overflow-x: hidden;
body {
  background-color: var(--primary-color);
  color: var(--font-color);
  margin-bottom: Opx !important;
h1,
h2,
h3,
h4 {
  overflow: hidden;
a {
 text-decoration: none !important;
  color: var(--font-color) !important;
ul {
 list-style: none !important;
  margin: 0;
```

```
width: 100%;
.hide {
  display: none !important;
.err {
  border: 3px solid red;
.succ {
  border: 3px solid green;
.btn {
  padding: 8px 12px;
  display: inline-block;
  border-radius: 5px;
  color: #fff !important;
.btn-black {
  background: #000;
.btn-purple {
  background: var(--secondary-color);
.btn-black:hover {
  opacity: 0.8;
.menu-btn {
 cursor: pointer;
  position: absolute;
  top: 16px;
  right: 40px;
  z-index: 99;
  display: none;
header {
  border-bottom: 1px solid #000;
nav ul li a {
  color: #fff !important;
  font-size: 20px;
nav ul li a:hover {
opacity: 0.8;
```

```
border-bottom: 2px solid var(--secondary-color);
header .logo span,
.section-footer span {
  color: var(--secondary-color);
.header-content i {
  font-size: 16px !important;
.showcase {
 width: 100%;
  height: 360px;
  background: url("../img/showcase.jpg") 50% 65% / cover no-repeat;
  position: relative;
 showcase::after {
  content: "";
  background: rgba(0, 0, 0, 0.4);
  position: absolute;
  top: 0;
  left: 0;
  width: 100%;
  height: 100%;
.w-30 {
  width: 30% !important;
.showcase-content {
  height: 100%;
  color: #fff;
  position: relative;
  z-index: 5;
.showcase-content h1 {
  text-transform: uppercase;
  font-weight: bold;
  margin-bottom: 1rem;
.showcase-content p {
 font-weight: bold;
  font-size: 1.2rem;
.login {
```

```
margin: 60px 0px;
 padding: 25px;
 box-shadow: 10px 10px 4px #000;
 border: 2px solid #000;
 border-radius: 10px;
.item {
 margin: 20px 0px;
 padding: 20px;
 box-shadow: 15px 5px 5px #000;
 border: 2px solid #000;
 border-radius: 10px;
page-link {
 padding: 10px 20px !important;
 background-color: rgba(61, 55, 55, 0.733) !important;
 border: 1px solid var(--font-color) !important;
.section-footer {
 height: 520px;
 background: #0d0d0e;
 color: #fff;
 padding: 4rem 0;
 overflow: hidden;
.section-footer i:hover {
 color: var(--secondary-color) !important;
.section-footer h2 {
 font-size: 2rem;
 margin-bottom: 1rem;
.section-footer h3 {
 margin-bottom: 0.7rem;
.section-footer a {
 line-height: 1.9;
 color: #ccc;
.section-footer a > i {
 color: #555;
```

```
margin-right: 0.5rem;
.email-form {
 width: 100%;
 display: inline-block;
 background-color: #555;
 position: relative;
 border-radius: 20px;
 line-height: 0;
 margin-top: 1rem;
email-form .control {
 display: inline-block;
 border: 0;
 outline: 0;
 font-size: 1rem;
 color: #ddd;
 background-color: transparent;
 font-family: inherit;
 margin: 0;
 padding: 0 3rem 0 1.5rem;
 width: 100%;
 height: 45px;
 border-radius: 20px;
email-form .submit {
 display: inline-block;
 position: absolute;
 top: 0;
 right: 0;
 width: 45px;
 height: 45px;
 background-color: #eee;
 font-size: 1rem;
 text-align: center;
 margin: 0;
 padding: 0;
 outline: 0;
 border: 0;
 color: #333;
 cursor: pointer;
 border-radius: 0 20px 20px 0;
```

```
@media (max-width: 800px) {
  .menu-btn {
   display: block !important;
  .menu-btn:hover {
   opacity: 0.5;
  .menu ul {
   display: block !important;
   position: absolute;
   top: 0;
    left: 0;
    background-color: #555;
   width: 50%;
   height: 100%;
    border-right: 1px solid #ccc;
   opacity: 0.9;
    z-index: 10;
   padding: 30px;
   transform: translateX(-500px);
    transition: transform 0.5s ease-in-out;
  .menu ul li {
   padding: 10px;
   border-bottom: 1px solid #ccc;
   font-size: 15px;
  .menu ul li:last-child {
   border-bottom: 0;
  .menu ul.show {
   transform: translateX(5px) !important;
  .user-action {
   margin-right: 60px;
  .showcase h1 {
   font-size: 1.5rem !important;
```

10.3 dashboard.css

```
body {
  font-size: 0.875rem;
.sidebar {
  position: fixed;
  top: 0;
  bottom: 0;
  left: 0;
  z-index: 100; /* Behind the navbar */
  padding: 48px 0 0; /* Height of navbar */
  box-shadow: inset -1px 0 0 rgba(0, 0, 0, 0.1);
@media (max-width: 767.98px) {
  .sidebar {
    top: 5rem;
.sidebar-sticky {
 position: relative;
 top: 0;
  height: calc(100vh - 48px);
  padding-top: 0.5rem;
  overflow-x: hidden;
  overflow-
y: auto; /* Scrollable contents if viewport is shorter than content. */
.sidebar .nav-link {
 font-weight: 500;
  color: #333;
```

```
.sidebar-heading {
  font-size: 0.75rem;
  text-transform: uppercase;
}
#sidebarMenu a {
  font-size: 1.2rem;
}
/*
  * Navbar
  */
.navbar-brand {
  padding-top: 0.75rem;
  padding-bottom: 0.75rem;
  font-size: 1.3rem;
  box-shadow: inset -1px 0 0 rgba(0, 0, 0, 0.25);
}
.navbar .navbar-toggler {
  top: 0.25rem;
  right: 1rem;
}
```

U assets folderu su jos folder:

Img,img-uploaded,img-small,xml.

Postoji jos data folder gde se nalazi log fajl.