

Analysing Vehicle Detection Processing Techniques: A Review

Abstract

This paper provides a review on analysing vehicle detection processing techniques. Vehicle recognition has sparked a lot of attention in the examination of the neighbourhood, moreover it has been utilised in an assortment of settings, including public wellbeing and security. One of the hardships in this field of examination is precisely perceiving vehicles out and about continuously. We separated existing vehicle identification methods into different categories based on the architecture that was employed as the backbone of these proposed approaches in our survey. We structured the full survey in chronological order to show the interrelationships between the proposed methods. We have detailed descriptions of the architectures of algorithms in this survey. In addition to providing in-depth studies of the existing approaches, we have come to the end of this study by outlining the limitations of previous research and the unexplored areas of this research issue.

Keywords- vehicle detection; computer vision; cnn; image processing

I Introduction

Vehicle recognition is one of the main advances that appoints whether there is a vehicle in a given picture and video and decides the specific area of the vehicle. Vehicle identification is the guideline and recommendation for specialists, for example, parking garage organisation, vehicle following, and vehicle tag acknowledgment. In any case, in the hour of real capacity, there are yet a portion of these hardships to be settled in vehicle recognition, like impediment, lighting, and real item shape changes. Lately, because of its cultural significance, vehicle recognition has turned into a famous exploration issue among analysts working in related areas. As per the survey, an extensive number of people kick the bucket consistently because of awful mishaps, which are principally brought about by driver flightiness or unfortunate perceivability during harsh weather conditions and so forth. On 27 November, 2021, The Business Standard (TBS) distributed "The Bangladesh Road Accident Report 2021" In the

initial eight months of 2021, 3,502 people were killed and 3,479 others were injured in 3,701 road accidents. According to police statistics, 4,138 people died in 4,147 accidents in 2019, and 2,635 people were killed and 1,920 others were injured in 2,629 street wrecks in 2018. Nonetheless, street wellbeing associations like Jatri Kalyan Samity assure that the numbers will be greater [1]. This exploration paper monocular vision-based vehicle ID draws near, with an attention on Region-based Convolutional Neural Networks (RCNN) methods. Object recognition utilises an assortment of strategies, including making highlights for sliding windows from full pictures, then ordering them to search for targets. In conventional techniques, the Deformable Parts Model creates the most striking outcomes [2]. Most contemporary best in class object identification frameworks depend on Convolution Neural Networks, with Region-based Convolutional Neural Networks (R-CNN) [3] filling in as the establishment. This exploration looks at how these strategies have advanced as of late. This paper closes profound learning calculations that are currently the best calculations for recognizing items and vehicles. At long last, this appraisal finishes up with a rundown of obscure regions for future examination in this field.

This paper is finished in the organisation: Section I incorporates the introduction, Section II surveys the sort of sensors, then, at that point, Section III examines the algorithm, after that Section IV presents the comparative result of the methods, besides Section V concludes the paper, and finally Section VI contains the references.

II Sensors

The two types of sensors are active and passive sensors. The time it takes for a sign to be delivered and reflected by an item is utilised by dynamic sensors to decide its distance. These include light identification and running [4], which makes and receives high-recurrence electromagnetic transmissions and operates in many parts of the electromagnetic spectrum, and radar, which emits radio waves into the atmosphere [5] and receives them. These sensors aren't available for vehicle discovery applications, which require gathering and characterizing the vehicle's elements. Cameras and other optical passive sensors are more effective in this regard [6].

These are viewed as detached since they gather information in a non-meddling way. These require no progressions to the street foundation, which is a critical advantage, and they are appropriate for vehicle order and location. The on-street situation is viewed as observed

utilising optical sensors, like a camera, in this examination, and afterward CNN-based approaches are analysed inside monocular vision. The CNN based vehicle discovery is given in fig.1.




Fig.1. Graph for CNN based vehicle location

III Examines the Algorithm

A. SPP net

SPP-Net is a convolutional mind plan that starts spatial pyramid pooling to dispense with the fixed-size prerequisite of the association. Especially we add a SPP layer on top of the last convolutional layer. The SPP layer pools the features and cultivates the fixed-length yields, which are then surrendered to the totally related layers (or various classifiers). With everything taken into account, we execute a few information absolute at a more significant period of the association requested movement (between convolutional layers and totally related layers) to stay away from the necessity for managing or winding around the beginning.

1. M Manana[7] (2017): SPP net is a powerful object detection technique. Spatial pyramid pooling takes out the acknowledgment precision for the pictures of an erratic size or scale. We can further develop the CNN based picture by eliminating the pictures fixed-size constraint. On top of the last convolution layer we will add the SPP layer then pool the elements and produce fixed-length yields which are added into the completely associated layers.

2. R. Girshick[8] (2014): Spatial Pyramid Pooling improves the slowness of R-CNN. SPP running the convolution layers of a picture and highlights are extricated on include maps. R-CNN and SPP-net preparation is finished with a multistage pipeline. R-CNN preparation has a high computational expense and slow on object discovery strategy. The justification for the gradualness of the item discovery is R-CNN that performs undercover forward pass without sharing calculation. SPP is multiple times quicker than the R-CNN technique.
3. M. Guo[9] (2020): Yolov3 assists the space pyramid pooling in SPP net[9]. SPP net improves the fully connected layer and receives fixed-size feature maps. Merging the feature maps provides fixed-length output. SPP expressive ability to detect the large size differentiation in images more effectively and improve the detection accuracy. The framework outline of SPP net is given in fig.2.




Fig.2. The framework outline of SPP net [8]

Limitation of SPP net: Despite the SPP layer avoiding repeatedly extracting features for different regions, the whole detection pipeline still has three stages: Region Proposal CNN Feature Extraction and SVM Classification, especially the Region Proposal method not only depends on low level image features but also is slow.

B. Fast R-CNN

The Fast R-CNN[12] identifier, similar to the R-CNN indicator, produces area proposals utilising a calculation like Edge Boxes. The Fast R-CNN locator processes the whole picture, dissimilar to the R-CNN finder, which cuts and resizes locale suggestions. Quick R-CNN pools CNN highlights relating to every area proposition, though a R-CNN finder should sort every district. Quick R-CNN is more productive than R-CNN since the calculations for covering locales are partaken in the Fast R-CNN locator.

To prepare a Fast R-CNN object identifier, use the train Fast RCNN Object detection function. The function returns a fast RCNN Object Detector that recognizes objects in a picture.

1. R. Girshick[10] (2015): This paper proposed object detection by Fast R-CNN algorithm. This paper accepts a picture as information and results. First Fast R-CNN identifier utilises a calculation like Edge Boxes. This time this algorithm extracts the image into the small pieces. Here Fast R-CNN union CNN features counter to every area and detect the object. This paper gives accuracy 70 percent.
2. Shih-Chung Hsu[11] (2018): In this paper they combine the regional proposals which are called R-CNN. This paper takes images and potential items are extricated by selective search. The Fast R-CNN process images some several pooling layers. One of the absolute affiliation layers is illustrated for fight class affirmation and the other can calibrate ROI position as a backslide system. Here the system contains a couple of convolution and max pooling layers, taken after by locale of-interest (ROI) pooling layers, and finally related to a gathering of completely associated (fc) layers which division into two fc yield layers: softmax and jumping box regressor.
3. Kaijing Shi[12] (2017): In this paper the system implementation by Fast R-CNN. This paper model is isolated into two stages - preparing, testing stage. This paper was composed by Fast R-CNN. This paper needs to alter three spots ast pooling layer is RoI pooling layer; ast completely association layer and softmax layer are supplanted by two equal layers; the organization input two arrangements of information: a bunch of pictures and the pictures of a gathering of RoIs. This paper gives accuracy 86.2 percent. This algorithm gives better results than traditional methods.
4. Kelong Wang[13] (2019): This paper system is implemented by the Fast RCNN algorithm. In this framework quick take a picture and concentrate the picture by specific inquiry technique, this strategy gets convolution consolidate guides through the multi-convolution layer and pooling layer, and thinks the feature vectors of settled length using the pooling layer and the absolute association layer of the district of interest (ROI). This system works two layers – estimating the target and foreseeing the target position, and fast training and detection. This paper fixates on the accompanying design a thorough inconvenient example extraction procedure and multilayer highlight combination. The framework outline of Fast R-CNN is given in fig.3.




Fig.3. The framework outline of Fast R-CNN [10]

Limitation of Fast R-CNN: Fast R-CNN spends the majority of its detection time on a selective search region proposition age calculation. As a result, the bottleneck of this design was architecture in Faster R-CNN.

C. Faster R-CNN

R-CNN is a calculation which is designed for profound learning object location. R-CNN has elaborated into two different networks called Fast R-CNN and Faster R-CNN. Faster R-CNN is created by merging two different networks that are named as fast R-CNN and Region Proposal Network (RPN) [14]. It's intended to lessen the amount of time it takes to make correct region proposals. By proposing RPN, it improves the system because RPN shares convolutional layers with object detection networks. It is utilised as the foundation of the profound brain models to perform vehicle identification for its capacity of diminishing time intricacy and precise district proposition.

1. H. Nguyen[15] (2019): In this paper, the author has proposed a faster R-CNN structure for speedy vehicle acknowledgment. He has embraced MobileNet Architecture to build the base organization of the faster R-CNN organization. MobileNet Architecture will improve the interface time and detection accuracy in the challenging driving environment like bad weather conditions, vehicle occlusion, large vehicle scale variation etc. When we compare the suggested method to the existing one, we can see that [15] with the original Faster R-CNN framework, it shows better outcomes in both location exactness and handling time. It shows the presentation is further developed contrasting the Faster R-CNN structure by 2.49 percent, 5.92 percent, and 3.6 percent in "easy," "moderate," and "hard" gatherings, individually.

2. S. Ren[16] (2016): In this paper, Develop a Region Proposal Network (RPN) that offers full-picture convolutional highlights with the recognition organisation, permitting district propositions to be made for basically no cash. A RPN is a completely convolutional network that predicts object cutoff points and objectness scores at each point at the same time. RPNs are prepared beginning to end to make great area propositions, which Fast R-CNN utilises in order to detect. RPN and Fast R-CNN can be prepared to share utilising a basic exchanging optimization. The trial results show that best in class object identification precision 73.2 percent.
3. Jorge E. Espinosa[17] (2017): In this method, the creators have involved Vgg16 as an element extractor in Faster R-CNN design. They performed an investigation of AlexNet and Faster R-CNN exhibition vehicle in motion identification utilising a clip of metropolitan regions. The presentation of two profound vehicle learning models acknowledgment and grouping in metropolitan clip successions was analysed in this paper. The pre-prepared Faster R-CNN model gives higher outcomes in right discoveries as indicated by the F1-score measure, regardless of whether in a particularly appointed collection of models tailored to urban circumstances, the AlexNet model is used for highlight extraction.
4. Li Yan[18] (2020): In this work, the creators have proposed an arranged vehicle identification technique for flying pictures that comprises three sections, named as oversampling, sewing information expansion strategy and a joint preparation misfortune work. Most past vehicle location calculations are beaten by this proposed system [18]. For identifying oriented cars, the strategy suggested in this research has a mAP of 8% greater than the initial Faster RCNN approach. By around 3% mAP, the organisation's intensified component map works on the organisation's capacity to recognize various kinds of cars. The system layout of Faster R-CNN is given in fig.4.




Fig.4. The framework outline of Faster R-CNN [14]

Limitation of Faster R-CNN:One impediment of Faster R-CNN is that all anchors in the little cluster of size 256 are extricated from a solitary picture when the RPN is prepared. Since all examples from a solitary picture might be connected (for example their highlights are comparative), the organisation's intermingling might consume most of the day.

D. SSD

SSD utilizes an equivalent of stage while getting ready, to arrange the particular anchor box with the bouncing boxes of each ground truth object inside an image. Fundamentally SSD works for Image request and article discovery. Image grouping is a PC vision that acknowledge a picture and gauge the item in a picture, Object recognition model remember that Possibility for object, Level of the bouncing box, Width of the jumping box, and Horizontal course of the middle characteristic of the bouncing box.

1. Qiaoqian Chen[19] (2018): The authors proposed the vehicle counting method that is actually based on an SSD. SSD is a popular algorithm in object detection. The writers of this paper performed that finding vehicle, track the absolute vehicle, and task counting which is involved via ssd. The capacity of ssd is the vehicle which is extracted, and location predicted and divided the vehicles. Going tracking vehicles are gained by balancing the vehicle and measuring the delicate distance between the

temporal of two pictures. At last, the exploratory outcomes are given to make sense of the convenience of the proposed technique on counting vehicles with over 87% accuracy.

2. Hui Li[20] (2020): The authors have proposed a gradual example of infrared vehicle recognition which is based on SSD and YOLO. In this part, I will discuss how the ssd algorithm works in this work. For infrared vehicle detection at first they know about the actual lake of detail in infrared vehicle pictures. After that they know difficulty in extracting feature data and low recognition exactness. The result show that the mpA is increased from 70.51 percent to 81.12 percent which is improved by 10.61 percent.
3. Syeda Nyma Ferdous[21] (2019): In this paper structure, the SSD (Single Shot MultiBox Detector) is utilised for vehicle recognition. Here, the SSD produces a fixed-size bounding boxes with foreseeing score for some, other item class cases in those cases. It is utilises a non-greatest concealment step to create last location. In this side an SSD detector work which trained one and just on the low-goal pictures. Finally we can see that SSD detector on super-resolved with an SSD that trained only the high resolution pictures.
4. Debojit Biswas[22] (2019): The authors proposed SSD and MobileNet-SSD to ascertain traffic density. The ability of SSD is effectively taking care of various sorts of shape, size and view point of an item. MobileNet-SSD really is a broadly educated model from SSD to MobileNet engineering, which is more adaptable and quicker than SSD. In SSD we can see that more adaptable that is the reason it shows that more huge potential in the field of traffic thickness estimation. The exploratory outcome part SSD accomplished 92.97 percent and MobileNet-SSD accomplished 79.30 percent normal location accuracy. The system framework of SSD is given in fig.5.




fig.5. The framework outline of SSD [19]

Limitations of SSD: SSD is more regrettable for more modest items than greater articles. The requirement for complex information increase additionally proposes it needs an enormous amount of information to prepare. That is the reason Shallow layers in a brain organisation may not create an adequate number of significant level highlights to do forecasts for little items.

E. Yolo

The input picture is divided into $S \times S$ squares using YOLO. Assuming that an article's GT (Ground Truth) focus coordinate falls inside a lattice, the network is responsible for recognizing the item. Just go for it's innovation is that it changes the Region Proposal location system: RCNN series should make a Region Proposal to finish arrangement as well as relapse [31]. Be that as it may, there is cross-over between Region Proposal and Region Proposal, which will bring about a great deal of rehash work. Consequences be damned, then again, gauges the BBOX (Bounding Box) of the thing remembered for all lattices, as well as the area, unwavering quality and likelihood vectors, everything being equal, at the same time, settling the issue a single shot [31]. The Detecting vehicles are given in fig.6.




Fig.6. Detecting the vehicles using YOLO algorithm

1. Yolo version1

J. Redmon[24] (2018): In this Paper, The object detection network was created by the author in order to alleviate the enormous run-time complexities of R-CNN and its proposed versions. YOLO doesn't utilise district ideas to identify and order objects; all

things considered, it partitions an image into SS matrices and finds m" number of bounding boxes inside every lattice. A class likelihood and offset values are anticipated for each bounding box. The bounding boxes that foresee class probabilities under a specific edge are handicapped. The experimental results show that their approach gets the maximum of precision 63.4 percent and FPS of 45.

2. Yolo version2

Han, X.[33] (2020): In this paper, the creators give O-YOLO-v2, another recognizable proof model in view of the notable YOLO-v2. In this mode, the model, which depends on a clever organisation configuration, outflanks YOLO-v2 concerning tiny article location. The new design further develops the organisation's component extraction abilities while likewise including leftover modules to resolve the issue of angle vanishing or scattering, which is for the most part brought about by network layer stacking. Moreover, the proposed approach [33] expanded the discovery exactness of tiny articles when multi-layered highlights disarray was presented. As the consequences of the analysis show, the O-YOLO-v2 model accomplishes more noteworthy discovery precision and basically meets the video location necessities. It very well may be used in an assortment of ways.

3. Yolo version3

B. Xu[26] (2019): In this paper, the authors have modified YOLO version 3 and used it in vehicle detection in aerial images. In the case of aerial images[25], YOLO version 3 cannot effectively detect vehicles because of the small size of vehicles, bad weather, and complex background of images. This is why the authors in[26] had to increase the number of convolutional layers to increase the depth of YOLO version 3 network. They modified the connections between up-sampling and down-sampling layers to preserve more top level features so that small vehicles can be detected accurately. The experimental results show that the YOLO version 3 mAP-50 score 57.9 percent.

4. Yolo version4

T-N. Doan [28] (2020): Using the YOLO version 4 network [29] and the DeepSORT network [30], the author devised this method for vehicle recognition and counting.

The author YOLO version 4 network is utilised in this study to predict bounding box coordinates, identified object class, and object confidence scores. The DeepSORT network is utilised to track discovered items in this study. The Kalman filter in the DeepSORT network aids in object tracking by allowing prior states to be used to forecast the closest frames of objects. Setting a threshold in the first frame also aids in avoiding duplicate vehicle monitoring. The experimental results show that their approach gets the maximum of precision 79 percent and FPS of 32. The framework outline of YOLO is given in fig.6.




Fig.7.The framework outline of YOLO [29]

Limitations of YOLO: YOLO puts serious spatial cutoff points on bounding box forecasts, on the grounds that every lattice cell can expect two boxes and just have one class. The quantity of neighbouring items our model can expect is restricted by this spatial imperative. Little things in groupings, like rushes of birds, represent a test for our model. Incorrect localizations are the most common source of error for this method [25].

IV. Comparative Result

Comparison criteria	Methods				
	SPP net	Fast R-CNN	Faster R-CNN	SSD	YOLO
Train	VOC 07	VOC 07+12	VOC 07+12	VOC 07+12	VOC 07+12
Accuracy %	63.1 [8]	70 [10]	73.2 [16]	74.3 [20]	63.4 [15]

Comparison criteria	Methods				
	SPP net	Fast R-CNN	Faster R-CNN	SSD	YOLO
Train	VOC 07	VOC 07+12	VOC 07+12	VOC 07+12	VOC 07+12
FPS	2.3 [8]	0.5 [10]	7 [15]	46 [20]	45 [15]

Table 1: Comparison of Methods

In PASCAL VOC 2007, we first contrast YOLO with various ongoing recognition methods. We examine the mistakes brought about by YOLO and Fast R-CNN, one of the most performant renditions of R-CNN, on VOC 2007 to all the more likely comprehend the differentiations among YOLO and R-CNN variations [32]. We show that YOLO might be used to rescore Fast R-CNN recognitions and decrease the mistakes from foundation bogus up-sides, bringing about a significant execution improvement, in light of the differed blunder profiles. The discoveries of VOC 2012 are likewise introduced, as well as a correlation of mAP to present status-of-the-workmanship draws near. At last, utilising two craftsmanship datasets, we show that YOLO sums up to new areas better than different locators. From table 1 we observe the normal precision of the SPP net calculation is 63.1 percent with a FPS of 2.3, the normal exactness of the Fast-RCNN calculation is 70% with a FPS of 0.5, the normal precision of the Fast-RCNN is 73.2 percent with a FPS of 7, the normal exactness of the SSD calculation is 74.3% with a FPS of 46 and the normal precision of the YOLO calculation is 63.4 percent with a FPS of 45. The Comparative result of algorithms are given in fig.8.




Fig.8. Comparative Result of Algorithms

We can observe the vertical bar with two columns that displays the accuracy and FPS for the algorithms(figure-2). It shows the same result as shown in table 1. The red bar is for the accuracy rate and the blue bar is for FPS.

In this comparison, the normal precision of the SPP net, Fast R-CNN, Faster R-CNN, SSD and YOLO calculations are contrasted with FPS. SSD and YOLO are excellent object detecting programs, with one being more exact and the other being faster. SSD (Single Shot Detector) runs a neural network on an information picture just a single time and registers a component map, whereas YOLO (You Only Look Once) is an open-source approach of object identification that can quickly distinguish objects in images and videos also YOLO V3 accomplished higher mAP then SSD that's why YOLO is much easier and simpler to use in real time than other classifier algorithms.

V. Conclusion

In this paper, we address recent developments in vehicle detection, including examples from the perspective of the other authors who have done research in this field. We gave conversation as far as the distinctions between the component extraction approach and the

apparent outcomes. We might reason that there is space for development, particularly concerning run-time intricacy, in the wake of exploring the methodologies proposed in every one of the works we have remembered for this overview. Albeit as of late vehicle location advancements are similarly adult, so experiencing the same thing it actually needs to work on in little articles, impediment and ongoing. With regards to vehicle identification innovation, how to utilise the current innovation to recognize a tad of item vehicles is as yet the focal point of exploration in different fields. Thus, future examination in this field can focus on fostering a vehicle recognizable proof strategy in light of the YOLO design. Subsequent to inspecting these papers, we can surmise that following strategies ought to be improved, as these following techniques are fundamentally manual and completely rely upon camera view. The likeness of various vehicles of many types, and the minuscule size of vehicles in satellite photographs, require calibrating of organisation boundaries to obtain results.

VI. Reference

1. The Business Standard(TBS) report2021.<https://www.tbsnews.net/bangladesh/bangladesh-106th-among-183-countries-having-most-road-accidents-report-335299>
2. Felzenszwalb, P.F., Girshick, R.B., McAllester, D. and Ramanan, D., 2009. Object detection with discriminatively trained part-based models. *IEEE transactions on pattern analysis and machine intelligence*, 32(9), pp.1627-1645.
3. Girshick, R., Donahue, J., Darrell, T. and Malik, J., 2014. Rich feature hierarchies for accurate object detection and semantic segmentation. In *Proceedings of the IEEE conference on computer vision and pattern recognition* (pp. 580-587).
4. C. Wang, C. Thorpe, and A. Suppe, "Ladar-Based Detection and Tracking of Moving Objects from a Ground Vehicle at High Speeds," Proc. IEEE Intelligent Vehicles Symp, 2003.
5. S. Park, T. Kim, S. Kang, and K. Heon, "A Novel Signal Processing Technique for Vehicle Detection Radar," 2003 IEEE MTT-S Int'l Microwave Symp. Digest, pp. 607-610, 2003.
6. M. Herbert, "Active and Passive Range Sensing for Robotics,"Proc. IEEE Int'l Conf. Robotics and Automation, vol. 1, pp. 102-110, 2000.
7. Manana, M., Tu, C. and Owolawi, P.A., 2017, December. A survey on vehicle detection based on convolution neural networks. In *2017 3rd IEEE International Conference on Computer and Communications (ICCC)* (pp. 1751-1755). IEEE.
8. R. Girshick, J. Donahue, T. Darrell, and J. Malik, "Rich Feature hierarchies for accurate object detection and semantic segmentation,"in Computer Vision and Pattern Recognition (CVPR), 2014 IEEE Conference on,pp.580-587,2014
9. Guo, M.; Xue, D.; Li, P.; Xu, H. Vehicle Pedestrian Detection Method Based on Spatial Pyramid Pooling and Attention Mechanism. *Information* 2020, 11, 583.
10. Girshick, R., 2015. Fast r-cnn. In *Proceedings of the IEEE international conference on computer vision* (pp. 1440-1448).
11. Hsu, Shih-Chung, Chung-Lin Huang, and Cheng-Hung Chuang. "Vehicle detection using simplified fast R-CNN." *2018 International Workshop on Advanced Image Technology (IWAIT)*. IEEE, 2018.
12. Shi, Kaijing, Hong Bao, and Nan Ma. "Forward vehicle detection based on incremental learning and fast r-cnn." *2017 13th International Conference on Computational Intelligence and Security (CIS)*. IEEE, 2017.
13. Wang, Kelong, and Wei Zhou. "Pedestrian and cyclist detection based on deep neural network fast R-CNN." *International Journal of Advanced Robotic Systems* 16.2 (2019): 1729881419829651.
14. Maity, Madhusri, Sriparna Banerjee, and Sheli Sinha Chaudhuri. "Faster R-CNN and YOLO based Vehicle detection: a survey." In *2021 5th International Conference on Computing Methodologies and Communication (ICCMC)*, pp. 1442-1447. IEEE, 2021.
15. Nguyen, H., 2019. Improving faster R-CNN framework for fast vehicle detection. *Mathematical Problems in Engineering*, 2019.
16. Ren, S., He, K., Girshick, R. and Sun, J., 2015. Faster r-cnn: Towards real-time object detection with region proposal networks. *Advances in neural information processing systems*, 28.

17. Espinosa, Jorge E., Sergio A. Velastin, and John W. Branch. "Vehicle detection using alex net and faster R-CNN deep learning models: a comparative study." In International visual informatics conference, pp. 3-15. Springer, Cham, 2017.
18. Mo, Nan, and Li Yan. "Improved faster RCNN based on feature amplification and oversampling data augmentation for oriented vehicle detection in aerial images." *Remote Sensing* 12, no. 16 (2020): 2558.
19. Chen, Qiaoqian, et al. "An SSD algorithm based on vehicle counting method." *2018 37th Chinese Control Conference (CCC)*. IEEE, 2018.
20. Li, Hui, et al. "Incremental learning of infrared vehicle detection method based on SSD." *2020 IEEE 20th International Conference on Communication Technology (ICCT)*. IEEE, 2020.
21. Ferdous, Syeda Nyma, Moktari Mostofa, and Nasser M. Nasrabadi. "Super resolution-assisted deep aerial vehicle detection." *Artificial Intelligence and Machine Learning for Multi-Domain Operations Applications*. Vol. 11006. International Society for Optics and Photonics, 2019.
22. Biswas, Debojit, et al. "An automatic traffic density estimation using Single Shot Detection (SSD) and MobileNet-SSD." *Physics and Chemistry of the Earth, Parts A/B/C* 110 (2019): 176-184.
23. Xiaoying, Guo, et al. "Target Detection of Forward Vehicle Based on Improved SSD." *2021 IEEE 6th International Conference on Cloud Computing and Big Data Analytics (ICCCBDA)*. IEEE, 2021.
24. Redmon, J., Divvala, S., Girshick, R. and Farhadi, A., 2016. You only look once: Unified, real-time object detection. In *Proceedings of the IEEE conference on computer vision and pattern recognition* (pp. 779-788).
25. J.Redmon and A. Farhadi, "YOLOv3: An Incremental Improvement", 2018, arXiv:1804.02767v1.
26. B. Xu, B.Wang and Y.Gu, "Vehicle Detection in Aerial Images Using Modified YOLO", IEEE Int. Conf. on Communication Technology, China, 2019.
27. Z. Rahman, A. M. Ami and M. A. Ullah, "A Real-Time Wrong-Way Vehicle Detection Based on YOLO and Centroid Tracking", IEEE Region 10 Symposium (TENSYP), June 2020
28. T-N. Doan and M-T. Truong, "Real-time vehicle detection and counting based on YOLO and DeepSORT", IEEE Int. Conf. on Knowledge and Systems Engineering, Vietnam, 2020.
29. A. Bochkovskiy, C-Y.Wang,H-Y.Mark Liao, "YOLOv4: Optimal Speed and Accuracy of Object Detection", 2020, arXiv:2004.10934v1.
30. Jocher, G., Nishimura, K., Mineeva, T. and Vilariño, R., 2020. yolov5. *Code repository* <https://github.com/ultralytics/yolov5>.
31. Lu, J., Ma, C., Li, L., Xing, X., Zhang, Y., Wang, Z. and Xu, J., 2018. A vehicle detection method for aerial image based on YOLO. *Journal of Computer and Communications*, 6(11), pp.98-107.
32. Girshick, R.B., 2015. Fast R-CNN. CoRR, abs/1504.08083.
33. Han, X., Chang, J. and Wang, K., 2021. Real-time object detection based on YOLO-v2 for tiny vehicle object. *Procedia Computer Science*, 183, pp.61-72.