Course "Automated Planning: Theory and Practice" Chapter Lab 02: Hierarchical Task Networks

Teacher: Marco Roveri - marco.roveri@unitn.it

M.S. Course: Artificial Intelligence Systems (LM)

A.A.: 2023-2024

Where: DISI, University of Trento

URL: https://bit.ly/3z0kGk8



Last updated: Wednesday 25th October, 2023

TERMS OF USE AND COPYRIGHT

USE

This material (including video recording) is intended solely for students of the University of Trento registered to the relevant course for the Academic Year 2023-2024.

SELF-STORAGE

Self-storage is permitted only for the students involved in the relevant courses of the University of Trento and only as long as they are registered students. Upon the completion of the studies or their abandonment, the material has to be deleted from all storage systems of the student.

COPYRIGHT

The copyright of all the material is held by the authors. Copying, editing, translation, storage, processing or forwarding of content in databases or other electronic media and systems without written consent of the copyright holders is forbidden. The selling of (parts) of this material is forbidden. Presentation of the material to students not involved in the course is forbidden. The unauthorised reproduction or distribution of individual content or the entire material is not permitted and is punishable by law.

The material (text, figures) in these slides is authored by Jonas Kvarnström and Marco Roveri.

THE HDDL LANGUAGE

- The *Hierarchical Domain Description Language* (HDDL) Höller et al. [10] is an extension of PDDL 2.1 Fox and Long [4].
- It is the standard language used for the International Planning Competition (IPC) 2020 on Hierarchical Planning.
 - http://ipc2020.hierarchical-task.net
 http://gki.informatik.uni-freiburg.de/competition/
- History
 - SHOP2 Nau et al. [14]
 - ANML Smith et al. [18]
 - HTN-PDDL Gonzalez-Ferrer et al. [8], González-Ferrer et al. [9]
 - HATP de Silva et al. [2], Lallement et al. [11]
 - HPDDL Alford et al. [1]
 - GTOHP Ramoul et al. [16]

HPDDL: Types and Predicates

- We use a simple transportation domain
- They are the same as in PDDL

```
(define (domain transport)
(:types
   package - locatable
   capacity_number - object
   location - object
   target - object
   vehicle - locatable
   locatable - object
 (:predicates
    (road ?arg0 - location ?arg1 - location)
    (at ?arg0 - locatable ?arg1 - location)
    (in ?arg0 - package ?arg1 - vehicle)
    (capacity ?arg0 - vehicle ?arg1 - capacity number)
    (capacity_pred ?arg0 - capacity_number ?arg1 - capacity_number)
```

HPDDL: Primitive tasks (aka actions)

• They are the same as in PDDL

```
(:action drive
 :parameters (?v - vehicle ?l1 - location ?l2 - location)
 :precondition (and (at ?v ?l1) (road ?l1 ?l2) )
 :effect (and (not (at ?v ?l1)) (at ?v ?l2) ) )
(:action noop
 :parameters (?v - vehicle ?12 - location)
 :precondition (and (at ?v ?l2) ) :effect () )
 (:action pick up
 :parameters (?v - vehicle ?l - location ?p - package
              ?s1 - capacity_number ?s2 - capacity_number)
 :precondition (and (at ?v ?l) (at ?p ?l)
                     (capacity_pred ?s1 ?s2) (capacity ?v ?s2) )
 :effect (and (not (at ?p ?l)) (in ?p ?v) (capacity ?v ?s1)
               (not (capacity ?v ?s2)) ) )
 (:action drop
 :parameters (?v - vehicle ?l - location ?p - package
              ?s1 - capacity number ?s2 - capacity number)
 :precondition (and (at ?v ?l) (in ?p ?v)
                     (capacity pred ?s1 ?s2) (capacity ?v ?s1) )
 :effect (and (not (in ?p ?v)) (at ?p ?l) (capacity ?v ?s2)
               (not (capacity ?v ?s1)) ) )
```

HPDDL: (ABSTRACT) TASKS

• In this domain: deliver, get_to, load, unload

```
(:task deliver
:parameters (?p - package ?l - location)
:precondition ()
:effect ()
(:task get to
:parameters (?v - vehicle ?l - location)
:precondition () ; No preconditions, but in principle possible
:effect () ; No effects, but in principle possible to specify them
(:task load
:parameters (?v - vehicle ?l - location ?p - package)
:precondition ()
:effect ()
(:task unload
 :parameters (?v - vehicle ?l - location ?p - package)
:precondition ()
:effect ()
```

HPDDL: METHODS

• In this domain: m_unload, m_load, m_i_am_here, m_drive_to, ...

```
(:method m unload
 :parameters (?1 - location ?p - package
              ?s1 - capacity_number ?s2 - capacity_number ?v - vehicle)
 :task (unload ?v ?l ?p)
:subtasks (and (task0 (drop ?v ?l ?p ?sl ?s2)) ) )
(:method m load
:parameters (?1 - location ?p - package
             ?s1 - capacity_number ?s2 - capacity_number ?v - vehicle)
 :task (load ?v ?l ?p)
:subtasks (and (task0 (pick up ?v ?l ?p ?s1 ?s2)) ) )
(:method m i am there
:parameters (?1 - location ?v - vehicle)
:task (get to ?v ?l)
 :subtasks (and (task0 (noop ?v ?l)) )
(:method m drive to
 :parameters (?11 - location ?12 - location ?v - vehicle)
:task (get to ?v ?12)
 :constraints (not (= ?11 ?12)) ; additional to preconditions
 :subtasks (and (task0 (drive ?v ?11 ?12)) ) )
```

HPDDL: METHODS (CONT.)

• In this domain: ... m_drive_to_via, m_deliver

```
(:method m drive to via
:parameters (?12 - location ?13 - location ?v - vehicle)
:task (get to ?v ?13)
:subtasks (and (task0 (get_to ?v ?12))
                (task1 (drive ?v ?12 ?13)) )
:ordering (and (task0 < task1) ) )</pre>
(:method m deliver
:parameters (?11 - location ?12 - location ?p - package ?v - vehicle)
:task (deliver ?p ?12)
:subtasks (and (task0 (get to ?v ?l1))
                (task1 (load ?v ?l1 ?p))
                (task2 (get_to ?v ?12))
                (task3 (unload ?v ?12 ?p)) )
:ordering (and (task0 < task1)</pre>
                (task1 < task2)
                (task2 < task3) )
```

HPDDL: Problem

Similar to PDDL

```
(define (problem pfile01)
 (:domain transport)
 (:objects
   package_0 package_1 - package
   capacity 0 capacity 1 - capacity number
   city loc 0 city loc 1 city loc 2 - location
   truck 0 - vehicle )
 (:htn
 :parameters ()
 :subtasks (and (task0 (deliver package_0 citv loc 0))
                 (task1 (deliver package_1 city_loc_2)) )
 :ordering (and (task0 < task1) ) )</pre>
 (:init
  (capacity_predecessor capacity_0 capacity_1)
  (road city_loc_0 city_loc_1) (road city_loc_1 city_loc_0)
  (road city_loc_1 city_loc_2) (road city_loc_2 city_loc_1)
  (at package 0 city loc 1) (at package 1 city loc 1)
  (at truck_0 city_loc_2) (capacity truck_0 capacity_1)
```

THE PANDA HTN PLANNER

- The PANDA planning system allows to solve different kinds of planning problems. In particular hierarchical task network (HTN) problems defined in HDDL.
 - Original web page:

```
https://www.uni-ulm.de/en/in/ki/research/software/panda/panda-planning-system/
```

• Download Java JAR file:

```
https://www.uni-ulm.de/fileadmin/website_uni_ulm/iui.inst.090/panda/PANDA.jarhttps://didatticaonline.unitn.it/dol/mod/resource/view.php?id=1011619
```

- Requirements: Java VM
 - sudo apt-get install openjdk-14-jre openjdk-14-jre-headless
- Usage: java -jar -parser hddl domain-file problem-file
 - Example:

```
java -jar ../PANDA.jar -parser hddl transport-htn.hddl transport-p01.hddl
```

• Full set of options:

```
java -jar ../PANDA.jar -help
java -jar ../PANDA.jar -help [OPTION or KEY] e.g.
java -jar ../PANDA.jar -help -parser for help on the -parser option
```

THE TRANSPORTER EXAMPLE

```
• The Domain:
    { Domains/Transporter/transport-htn.hddl }
• The first problem:
    { Domains/Transporter/p01.hddl }
• The second problem:
    { Domains/Transporter/p02.hddl }
• The third problem:
    { Domains/Transporter/p03.hddl }
```

THE ROVER EXAMPLE

THE SATELLITE EXAMPLE

- { Domains/Satellite/satellite.hddl }
 The first problem:
 { Domains/Satellite/lobs-2sat-1mod.hddl }
 The second problem:
 { Domains/Satellite/2obs-2sat-2mod.hddl }
- The third problem:

• The Domain:

{ Domains/Satellite/3obs-3sat-2mod.hddl }

13/19

THE WOOD WORKING EXAMPLE

OTHER HTN PLANNERS (FROM IPC 2020 ON HTN)

- Tools
 - Name (hyperlink to singularity image)
 - LiloTane by Schreiber [17]
 - SIADEX by Fernandez-Olivares et al. [3]
 - HyperTensioN by Magnaguagno et al. [13]
 - PDDL4J-TO and PDDL4J-PO by Pellier and Fiorino [15]
 - pyHiPOP by Lesire and Albore [12]
- Usage
 - singularity run singularityimage.sif domain.hddl problem.hddl
 - Example (For LiloTane):
 - singularity run IPC2020-competitor-1n.sif domain.hddl problem.hddl

REFERENCES I

- [1] Ron Alford, Gregor Behnke, Daniel Höller, Pascal Bercher, Susanne Biundo, and David W. Aha. Bound to plan: Exploiting classical heuristics via automatic translations of tail-recursive HTN problems. In Amanda Jane Coles, Andrew Coles, Stefan Edelkamp, Daniele Magazzeni, and Scott Sanner, editors, *Proceedings of the Twenty-Sixth International Conference on Automated Planning and Scheduling, ICAPS 2016, London, UK, June 12-17, 2016*, pages 20–28. AAAI Press, 2016. URL http://www.aaai.org/ocs/index.php/ICAPS/ICAPS/16/paper/view/13174. 3
- [2] Lavindra de Silva, Raphaël Lallement, and Rachid Alami. The HATP hierarchical planner: Formalisation and an initial study of its usability and practicality. In 2015 IEEE/RSJ International Conference on Intelligent Robots and Systems, IROS 2015, Hamburg, Germany, September 28 October 2, 2015, pages 6465–6472. IEEE, 2015. doi: 10.1109/IROS.2015.7354301. URL https://doi.org/10.1109/IROS.2015.7354301. 3
- [3] Juan Fernandez-Olivares, Ignacio Vellido, and Luis Castillo. Addressing HTN planning with blind depth first search. In *Proceedings of 10th International Planning Competition: Planner and Domain Abstracts Hierarchical Task Network (HTN) Planning Track (IPC 2020)*, pages 1–4, 2021. 15
- [4] Maria Fox and Derek Long. PDDL2.1: an extension to PDDL for expressing temporal planning domains. *J. Artif. Intell. Res.*, 20: 61–124, 2003. doi: 10.1613/jair.1129. URL https://doi.org/10.1613/jair.1129. 3
- [5] Hector Geffner and Blai Bonet. A Concise Introduction to Models and Methods for Automated Planning. Synthesis Lectures on Artificial Intelligence and Machine Learning. Morgan & Claypool Publishers, 2013. ISBN 9781608459698. doi: 10.2200/S00513ED1V01Y201306AIM022. URL https://doi.org/10.2200/S00513ED1V01Y201306AIM022.

REFERENCES II

- [6] Malik Ghallab, Dana S. Nau, and Paolo Traverso. Automated planning theory and practice. Elsevier, 2004. ISBN 978-1-55860-856-6.
- [7] Malik Ghallab, Dana S. Nau, and Paolo Traverso. Automated Planning and Acting. Cambridge University Press, 2016. ISBN 978-1-107-03727-4. URL http://www.cambridge.org/de/academic/subjects/computer-science/artificial-intelligence-and-natural-language-processing/automated-planning-and-acting?format=HB.
- [8] A. Gonzalez-Ferrer, J. Fernández-Olivares, and L. Castillo. JABBAH: A java application framework for the translation between business process models and HTN. In *International Competition on Knowledge Engineering for Planning and Scheduling (ICKEPS)*, 2009. http://kti.mff.cuni.cz/~bartak/ICKEPS2009/download/ICKEPS2009_gonzalez-ferrer_p28-37.pdf. 3
- [9] Arturo González-Ferrer, Juan Fernández-Olivares, and Luis A. Castillo. From business process models to hierarchical task network planning domains. *Knowl. Eng. Rev.*, 28(2):175–193, 2013. doi: 10.1017/S0269888912000410. URL https://doi.org/10.1017/S0269888912000410. 3
- [10] Daniel Höller, Gregor Behnke, Pascal Bercher, Susanne Biundo, Humbert Fiorino, Damien Pellier, and Ron Alford. HDDL: an extension to PDDL for expressing hierarchical planning problems. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*, pages 9883–9891. AAAI Press, 2020. URL https://aaai.org/ojs/index.php/AAAI/article/view/6542. 3

REFERENCES III

- [11] Raphaël Lallement, Lavindra de Silva, and Rachid Alami. HATP: an HTN planner for robotics. *CoRR*, abs/1405.5345, 2014. URL http://arxiv.org/abs/1405.5345. 3
- [12] Charles Lesire and Alexandre Albore. pyHiPOP Hierarchical partial-order planner. In Proceedings of 10th International Planning Competition: Planner and Domain Abstracts – Hierarchical Task Network (HTN) Planning Track (IPC 2020), pages 13–16, 2021. 15
- [13] Maurício Cecílio Magnaguagno, Felipe Meneguzzi, and Lavindra de Silva. HyperTensioN: A three-stage compiler for planning. In Proceedings of 10th International Planning Competition: Planner and Domain Abstracts – Hierarchical Task Network (HTN) Planning Track (IPC 2020), pages 5–8, 2021. 15
- [14] Dana S. Nau, Tsz-Chiu Au, Okhtay Ilghami, Ugur Kuter, J. William Murdock, Dan Wu, and Fusun Yaman. SHOP2: an HTN planning system. *J. Artif. Intell. Res.*, 20:379–404, 2003. doi: 10.1613/jair.1141. URL https://doi.org/10.1613/jair.1141. 3
- [15] Damien Pellier and Humbert Fiorino. Totally and partially ordered hierarchical planners in PDDL4J library. In Proceedings of 10th International Planning Competition: Planner and Domain Abstracts – Hierarchical Task Network (HTN) Planning Track (IPC 2020), pages 17–18, 2021. 15
- [16] Abdeldjalil Ramoul, Damien Pellier, Humbert Fiorino, and Sylvie Pesty. Grounding of HTN planning domain. Int. J. Artif. Intell. Tools, 26(5):1760021:1–1760021:24, 2017. doi: 10.1142/S0218213017600211. URL https://doi.org/10.1142/S0218213017600211. 3

REFERENCES IV

- 17] Dominik Schreiber. Lifted logic for task networks: TOHTN planner lilotane in the IPC 2020. In Proceedings of 10th International Planning Competition: Planner and Domain Abstracts – Hierarchical Task Network (HTN) Planning Track (IPC 2020), pages 9–12, 2021. 15
- [18] David E. Smith, Jeremy Frank, and William Cushing. The ANML language. In *The ICAPS-08 Workshop on Knowledge Engineering for Planning and Scheduling (KEPS)*, 2008.

https://ti.arc.nasa.gov/m/profile/de2smith/publications/ICAPS08-ANML.pdf.3