

COURSE "AUTOMATED PLANNING: THEORY AND PRACTICE"

CHAPTER 08: HEURISTICS: AN OVERVIEW

Teacher: **Marco Roveri** - `marco.roveri@unitn.it`
M.S. Course: Artificial Intelligence Systems (LM)
A.A.: 2023-2024
Where: DISI, University of Trento
URL: <https://bit.ly/3zOkGk8>



Last updated: Wednesday 18th October, 2023

TERMS OF USE AND COPYRIGHT

USE

This material (including video recording) is intended solely for students of the University of Trento registered to the relevant course for the Academic Year 2023-2024.

SELF-STORAGE

Self-storage is permitted only for the students involved in the relevant courses of the University of Trento and only as long as they are registered students. Upon the completion of the studies or their abandonment, the material has to be deleted from all storage systems of the student.

COPYRIGHT

The copyright of all the material is held by the authors. Copying, editing, translation, storage, processing or forwarding of content in databases or other electronic media and systems without written consent of the copyright holders is forbidden. The selling of (parts) of this material is forbidden. Presentation of the material to students not involved in the course is forbidden. The unauthorised reproduction or distribution of individual content or the entire material is not permitted and is punishable by law.

The material (text, figures) in these slides is authored by Jonas Kvarnström and Marco Roveri.

HEURISTIC SEARCH (REPETITION)

```
function SEARCH(problem)
  initial-node  $\leftarrow$  MAKE-INITIAL-NODE(problem)
  open  $\leftarrow$  {initial-node}
  while (open  $\neq \emptyset$ ) do
    node  $\leftarrow$  SEARCH-STRATEGY-REMOVE-FROM(open)
    if IS-SOLUTION(node) then
      return EXTRACT-PLAN-FROM(node)
    end if
    for each newnode  $\in$  SUCCESSORS(node) do
      open  $\leftarrow$  open  $\cup$  {newnode}
    end for
  end while
  return Failure
end function
```

An *heuristic strategy* bases decisions on:

\Rightarrow Heuristic value $h(n)$

\Rightarrow Often other factors e.g. $g(n)$ i.e.
the cost of reaching n

Best first search: Greedy, A*, ...

Modifications: IDA*, D*, ...

Simulated annealing, hill climbing, ...

Requires an **heuristic function**!

How do we *calculate* $h(n)$?

Landmarks,
Pattern databases,
Relaxed plan graph,
...

EXAMPLE

3 BLOCKS, ALL ON THE TABLE IN S_0




S_0

We now have
1 open node,
which is *unexpanded*

EXAMPLE (CONT.)

WE VISIT S_0 AND WE EXPAND IT!

Forward search: node \approx state
so we may write $h(n)$ or $h(s)$



We now have
3 open nodes,
which are *unexpanded*


An **heuristic function** estimates the distance from each open node to the goal:

We calculate $h(S_1)$, $h(S_2)$, $h(S_3)$

An **heuristic strategy** uses this value (and other info) to prioritize the search

EXAMPLE (CONT.)

SUPPOSE THE STRATEGY CHOOSES TO VISIT S_1 !



2 new heuristic values are calculated $h(S_{16})$, $h(S_{17})$
 The **search strategy** now has 4 nodes to prioritize

WHAT TO MEASURE?

QUESTION 1A: WHAT SHOULD AN HEURISTIC FUNCTION MEASURE?

- An **heuristic strategy** bases its decisions on:
 - Heuristic value $h(s)$
 - Other factors: e.g. $g(s)$ i.e. cost of reaching s
- A very general definition!
 - \implies **could** measure **anything** that **some** strategy might find useful!

QUESTION 1B: WHAT IS "COST"?

- **Often:** $h(s)$ *tries* to approximate the **cost** of achieving the goal from s !
 - Useful for finding **cheap plans**, and often as a **side effect**, for finding **plans cheaply**!
 - But... What is "**cost**"?

PLAN QUALITY AND ACTION COSTS

- Maybe: **long** plan = **expensive** plan
 - $c(\pi) = |\pi|$, i.e. number of actions in plan π
 - Reasonable in some domains: e.g. Tower of Hanoi
 - But: How to make sure your car is clean?

go to car wash

get supplies

wash car

go to car dealer

buy new car

shortest plan is best?

Heuristic $h(s)$ estimates:
 "How many actions are needed
 to reach the goal from s "

- Would prefer to support different **action costs**
 - Supported by most current planners
 - Each action $a \in A$ is associated with a cost $c(a)$
 - Total cost: $c(\pi) = \sum_{a \in \pi} c(a)$

Heuristic $h(s)$ estimates:
 "How **expensive** actions are needed
 to reach the goal from s "

ACTION COSTS IN PDDL

- PDDL: Specify requirements:

- `(:requirements :action-costs)`

- **Numeric state variables** for the total cost, called `(total-cost)`

- And possibly numeric variables to *calculate* action costs
- `(:functions (total-cost)`
`(travel-slow-cost ?f1 - count ?f2 - count)`
`(travel-fast-cost ?f1 - count ?f2 - count))`

- **Initial state**


- `(:init (= (total-cost) 0)`
`(= (travel-slow-cost n0 n1) 6) (= (travel-slow-cost n0 n2) 7) ...`
`(= (travel-fast-cost n0 n1) 8) (= (travel-fast-cost n0 n2) 9) ...`
`...)`

- Special **increase effects** to increase total cost


- `(:action move-up-slow`
`:parameters (?l - slow-elevator ?f1 - count ?f2 - count)`
`:precondition (and (lift-at ?l ?f1) (above ?f1 ?f2) (reachable-floor ?l ?f2))`
`:effect (and (lift-at ?l ?f2) (not (lift-at ?l ?f1))`
`(increase (total-cost) (travel-slow-cost ?f1 ?f2))))`

REMAINING COSTS


- The **remaining cost** in **any** search state s
 - The cost of a **cheapest (optimal) solution** starting in s
 - Denoted by $h^*(s)$
 - Star $*$ \implies the best, optimal, estimate: *exact* cost
- The cost of an **optimal solution** to (Σ, S_0, S_g)
 - $h^*(S_0)$



- Initially A,B,C on the table
pickup,putdown cost 1
stack,unstack cost 2




- Two reachable goal nodes
pickup,putdown cost 1
stack,unstack cost 2



TRUE REMAINING COSTS (CONT.)

- True cost of reaching a goal node from n : $h^*(n)$

Three reachable goal nodes
(there can be many)




TRUE REMAINING COSTS (CONT.)

- If we *knew* the true remaining cost $h^*(n)$ for every node:

```


function ALGORITHM SIMPLEPLAN(problem)
  initial-node  $\leftarrow$  MAKE-INITIAL-NODE(problem)
  while (not reached goal) do
    node  $\leftarrow$  A-SUCCESSOR-NODE-MINIMAL- $h^*$ (node)
  end while
end function
  
```

Trivial straight-line path
minimizing h^* values
gives an *optimal* solution!



REFLECTIONS


- What does this **mean**?
 - Calculating $h^*(n)$ is a **good idea**, because then we can **easily** find optimal plans?
- **No!!!** - because we can prove that finding optimal plans is **hard**!
 - So the hard part must be calculating $h^*(n)$...



- Must settle for an **estimate** that helps us **search less** than otherwise!

MINIMIZATION: INTRODUCTION


- Example strategy: *depth-first search*: select a child with **minimal** $h(s)$



- If I start with (pickup A), then make **optimal** choices:
 - Plan cost = 55
- If I start with (pickup C), then make **optimal** choices:
 - Plan cost = 62

MINIMIZATION: CASE 1

- Example strategy: *depth-first search*: select a child with **minimal** $h(s)$



$$h^*(s_1) = 55 \quad h^*(s_2) = 57 \quad h^*(s_3) = 62$$

$$h^A(s_1) = 50 \quad h^A(s_2) = 53 \quad h^A(s_3) = 55$$

$$h^B(s_1) = 4 \quad h^B(s_2) = 20 \quad h^B(s_3) = 21$$

- Which is best?

- The strategy only cares about **relative** values!


- h^* , h^A , and h^B all results in identical choices: s_1 first!

Close!

Far from truth...

MINIMIZATION: CASE 2

- Example strategy: *depth-first search*: select a child with **minimal** $h(s)$



$$h^*(s_1) = 55 \quad h^*(s_2) = 57 \quad h^*(s_3) = 62$$

$$h^A(s_1) = 50 \quad h^A(s_2) = 53 \quad h^A(s_3) = 55$$

$$h^B(s_1) = 107 \quad h^B(s_2) = 258 \quad h^B(s_3) = 522$$

- Which is best?


- The strategy only cares about **relative** values!
 - h^* , h^A , and h^B all results in identical choices: s_1 first!

Close!

Large overestimate!

MINIMIZATION: CASE 3

- Example strategy: *depth-first search*: select a child with **minimal** $h(s)$



$$h^*(s_1) = 55 \quad h^*(s_2) = 57 \quad h^*(s_3) = 62$$

$$h^A(s_1) = 54 \quad h^A(s_2) = 53 \quad h^A(s_3) = 47$$

$$h^B(s_1) = 4 \quad h^B(s_2) = 20 \quad h^B(s_3) = 21$$

- Which is best?


- The strategy only cares about **relative** values!
 - h^A is **worse** for **this** strategy, despite being closer to h^* : goes to s_3 first!
 - Even if we continue optimally, cost ≥ 62 !

Close!

Far from truth...

A*: CASE 1

- Example strategy: A*



$$h^*(s_1) = 55 \quad h^*(s_2) = 57 \quad h^*(s_3) = 62$$


$$h^A(s_1) = 50 \quad h^A(s_2) = 53 \quad h^A(s_3) = 55$$

$$h^B(s_1) = 4 \quad h^B(s_2) = 20 \quad h^B(s_3) = 21$$

- Which is best?
 - A* expands all nodes where $h(s) + g(s) \leq h^*(s)$
 - As long as h is admissible $[\forall s. h(s) \leq h^*(s)]$, increasing it is always better

A*: CASE 2

- Example strategy: A*



$$h^*(s_1) = 55 \quad h^*(s_2) = 57 \quad h^*(s_3) = 62$$


$$h^A(s_1) = 50 \quad h^A(s_2) = 53 \quad h^A(s_3) = 55$$

$$h^B(s_1) = 107 \quad h^B(s_2) = 258 \quad h^B(s_3) = 522$$

- Which is best?
 - A* expands all nodes where $h(s) + g(s) \leq h^*(s)$
 - Because h^B is **not** admissible, optimal solutions may be missed!

A*: CASE 3

- Example strategy: A*



$$h^*(s_1) = 55 \quad h^*(s_2) = 57 \quad h^*(s_3) = 62$$

$$h^A(s_1) = 54 \quad h^A(s_2) = 53 \quad h^A(s_3) = 47$$

$$h^B(s_1) = 4 \quad h^B(s_2) = 20 \quad h^B(s_3) = 21$$

- Which is best?
 - A* expands all nodes where $h(s) + g(s) \leq h^*(s)$
 - As long as $h(s)$ is admissible $[\forall s. h(s) \leq h^*(s)]$, increasing is **always** better: $\implies h^A$ better than h^B

TWO REQUIREMENTS FOR HEURISTIC GUIDANCE

DEFINE SEARCH STRATEGY ABLE TO TAKE GUIDANCE INTO ACCOUNT

- Example:
 - A* uses a heuristic function
 - Hill-climbing uses a heuristic ... differently!
 - ...

FIND A HEURISTIC FUNCTION SUITABLE FOR THE SELECTED STRATEGY

- Example:
 - Find an heuristic function suitable specifically for A*
 - Find an heuristic function suitable specifically for hill-climbing
 - ...
- Can be **domain specific**, given as input to the planning problem!
- Can be **domain independent**, generated automatically by the planner given the problem domain!

We will consider both – heuristics more than strategies!

SOME DESIRED PROPERTIES

- What properties do **good heuristic functions** have?
 - Shall be **Informative**: provide good guidance to the specific search strategy we use
 - Admissible?
 - Close to $h^*(n)$?
 - Correct "ordering"?
 - ...


SOME DESIRED PROPERTIES (CONT.)

- What properties do **good heuristic functions** have?
 - Shall be **efficiently computable**
 - Spend as little time as possible deciding which nodes to expand
 - Shall be **balanced...**
 - Many planners spend almost all their time calculating heuristics
 - But: Don't spend more time computing h than the time you gain by expanding few nodes!
 - Illustrative (made-up) example:

Heuristic quality	Nodes expanded	Exp. 1 node	Calc. h one node	Total time
Worst	100000	$100\mu s$	$1\mu s$	10100ms
Better	20000	$100\mu s$	$10\mu s$	2200ms
...	5000	$100\mu s$	$100\mu s$	1000ms
...	2000	$100\mu s$	$1000\mu s$	2200ms
...	500	$100\mu s$	$10000\mu s$	5050ms
Best	200	$100\mu s$	$100000\mu s$	20020ms

CHEAP PLANS, CHEAP PLANNING

- Cost can be indirectly related to plan generation time!



- If we can find a **cheap** plan "under" s_{16}
 - \implies might find a plan in **few steps**
 - \implies might not need to search so many nodes
 - \implies might find a plan **cheaply**
- Maybe!
 - Or maybe s_{16} opens up a vast number of alternatives, so finding a solution may take more time...

PRIORITIZING SPEED OR PLAN COST

- Can design strategies to prioritize speed or plan cost

FIND A SOLUTION QUICKLY

Expand nodes where you think you can **easily find a way** to a goal node

Should prefer

Open nodes

Accumulated plan cost $g(n) = 50$,
estimated "cost distance" $h(n) = 10$

FIND A GOOD SOLUTION

Expand nodes where you think you **can** find a way to a **good (high-quality) solution**, even if finding it will be difficult!

Should prefer

Accumulated plan cost $g(n) = 5$,
estimated "cost distance" $h(n) = 30$

Often one strategy+heuristic can achieve *both* reasonably well, but for optimum performance, the distinction can be important!

REFERENCES I

- [1] Hector Geffner and Blai Bonet. *A Concise Introduction to Models and Methods for Automated Planning*. Synthesis Lectures on Artificial Intelligence and Machine Learning. Morgan & Claypool Publishers, 2013. ISBN 9781608459698. doi: 10.2200/S00513ED1V01Y201306AIM022. URL <https://doi.org/10.2200/S00513ED1V01Y201306AIM022>.
- [2] Malik Ghallab, Dana S. Nau, and Paolo Traverso. *Automated planning - theory and practice*. Elsevier, 2004. ISBN 978-1-55860-856-6.
- [3] Malik Ghallab, Dana S. Nau, and Paolo Traverso. *Automated Planning and Acting*. Cambridge University Press, 2016. ISBN 978-1-107-03727-4. URL <http://www.cambridge.org/de/academic/subjects/computer-science/artificial-intelligence-and-natural-language-processing/automated-planning-and-acting?format=HB>.