GILES CHEMICAL CORPORATION						
COMPANY PROCEDURE						
Standard Operating Procedure			1 of 2	Revision	:	
Standard Operating Procedure	Page	•	1 01 2	Date	:	02/12/07
Author: Maintenance Title: Lock	Title: Lock Out Tag Out Stretch Wrap Machine					

Safety: All safety glasses and appropriate safety apparel is to be worn at all times.

Purpose or Objective: The purpose of this procedure is to define the process required to lock out the Palletizer in the main facility at 102 Commerce Street

Procedure: The proper process to lockout the Stretch Wrap Machine is as follows:

- 1. Notify all affected employees that the machine is being taken out of production.
- 2. Unplug 110 vac plug
- 3. Install cord end lock out device
- 4. *ID tag with name, date and time*
- 5. Test start switch to ensure machine is not operational

Proper procedure to return equipment to operation:

- 1. Make sure all work is complete and all tools and maintenance equipment has been removed from the machine.
- 2. Notify all affected employees that equipment is about to be put back into service
- 3. Remove ID tag with name, date and time
- 4. Remove cord end lock out device
- 5. Plug 110 vac into outlet
- 6. Ensure that stretch wrap machine is operational and available for production

GILES CHEMICAL CORPORATION						
COMPANY PROCEDURE						
Standard Operating Procedure			2 of 2	Revision	:	
Standard Operating Procedure	Page	•	2 01 2	Date	:	02/12/07
Author: Maintenance Title: Lock	Title: Lock Out Tag Out Stretch Wrap Machine					

TRAINING DOCUMENTATION

EMPLOYER	E TITLE	SIGNATURE	DATE
1			
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			
13			
14			
15			
16			
17			
18			