

GILES CHEMICAL CORPORATION		
COMPANY PROCEDURE		
Standard Operating Procedure	Page : 1 of 2	Revision : Date : 02/12/07
Author: Maintenance	Title: Lock Out Tag Out #2 Oil Pump	

Safety: *All safety glasses and appropriate safety apparel is to be worn at all times.*

Purpose or Objective: *The purpose of this procedure is to define the process required to lock out the #2 Oil Pump in the main facility at 102 Commerce Street*

Procedure: *The proper process to lockout #2 Oil Pump is as follows:*

1. *Notify all affected employees that the machine is being taken out of production.*
2. *Locate disconnect for #2 Oil Pump near the peco tank on the second floor*
3. *Turn disconnect to the off position*
4. *Install multi lockout device*
5. *ID tag with name, date and time*
6. *Test start switch to ensure that #2 Oil Pump is not operational*

Proper procedure to return equipment to operation:

1. *Make sure all work is complete and all tools and maintenance equipment has been removed from the machine.*
2. *Notify all affected employees that equipment is about to be put back into service.*
3. *Remove ID tag with name, date and time*
4. *Remove multi lockout device*
5. *Turn disconnect to the on position*
6. *Ensure that equipment is operational and available to be returned to production*

GILES CHEMICAL CORPORATION			
COMPANY PROCEDURE			
Standard Operating Procedure		Page : 2 of 2	Revision : Date : 02/12/07
	Author: Maintenance Title: Lock Out Tag Out #2 Oil Pump		

TRAINING DOCUMENTATION

	EMPLOYEE	TITLE	SIGNATURE	DATE
1				
2				
3				
4				
5				
6				
7				
8				
9				
10				
11				
12				
13				
14				
15				
16				
17				
18				