GILES CHEMICAL CORPORATION							
COMPANY PROCEDURE							
Standard Operating Procedure	Page		1 of 3	Revision	:		
Standard Operating Procedure		rage .	1015	Date	:	02/12/07	
Author: Maintenance Title: Lock	Title: Lock Out Tag Out #1 Carton Machine						

Safety: Before beginning work, notify all affected employees that the equipment is being locked out. Also all safety glasses and appropriate safety apparel is to be worn at all times.

Purpose or Objective: The purpose of this procedure is to define the process required to lock out the #1 carton machine located in our Repack facility at 396 Shelton Street.

Procedure: The proper process to lockout the carton machine is as follows:

- 1. Use padlock and multi-lockout tool and id tag to secure machine disconnect
- 2. ID tag with name and date/time machine will be locked out
- 3. Lock out hydraulic unit in same manner as item #1 above.
- 4. Turn valves on hydraulic unit off and lock out in same manner as item #1 above with valve lock device.
- 5. Test machine to see if it will start after locking out.

Proper procedure to return equipment to operation:

- 1. Make sure all work is complete and all tools and maintenance equipment has been removed from the machine.
- 2. Notify all affected employees that equipment is about to be put back into service.
- 3. Remove ID tag with name, date and time from hydraulic unit
- 4. Remove multi-lockout device with padlock from hydraulic unit
- 5. Remove multi lockout device with padlock from disconnect
- 6. Turn disconnect to the on position
- 7. Ensure that equipment is operational and available to be returned to production

GILES CHEMICAL CORPORATION							
COMPANY PROCEDURE							
Standard Operating Procedure	Page	•	2 of 3	Revision	:		
Standard Operating Procedure		•	2 01 3	Date	:	02/12/07	
Author: Maintenance Title: Lock	Title: Lock Out Tag Out #1 Carton Machine						

TRAINING DOCUMENTATION

	EMPLOYEE	TITLE	SIGNATURE	DATE
1				
2				
3				
4				
5				•
6				
7				
8				
9				
10				
11				
12				
13				
14				
15				
16				
17				

GILES CHEMICAL CORPORATION							
COMPANY PROCEDURE							
Standard Operating Procedure	Page	:	3 of 3	Revision Date	:	02/12/07	
Author: Maintenance Title: Lock Out Tag Out #1 Carton Machine							

H 1 Q		
10		
	=	