
	<b>GILES CHEMICAL ~ PREMIER MAGNESIA</b>		
	<b>Company Procedure</b>		
	Title: <b>Operating the Komline-Sanderson Filter Press</b>	Number: <b>P12-PR-200-017</b>	
	Owner: <b>Patrick Owen</b>	Revision: <b>04</b>	
	Effective Date: <b>05/13/13</b>	Page: <b>1 of 2</b>	

## 1.0 Purpose

This procedure spells out the supervising of a complete cycle of the Komline-Sanderson Filter Press, as this press is completely automated and has been pre-programmed to run one entire cycle of operation.

## 2.0 Scope

This procedure applies to all manufacturing workers.

## 3.0 Responsibility

Lead Operator, Material Handler, Assistant Operator

## 4.0 Safety Considerations

Safety glasses and steel-toed shoes.

Safety is a condition of employment. Employees are not authorized to work in an unsafe manner and are prohibited from harming the environment of the facility or community.

## 5.0 Materials/Equipment

N/A

## 6.0 Procedure



This press is computer automated. It has been pre-programmed to execute a complete cycle from start-up at the push of the start button, cycle end when the flow drops below 30 gallons per minute, through filtration to rinsing and squeezing of press cake. Dumping of press cake of press and surface washing of the filter cloths after each cycle is done manually and the press is left open for the next cycle.

### 1) ARRANGE INLET AND DISCHARGE PIPES

- a) Using a clean hose with a good gasket, attach the "Filter Press Inlet" to the "Mud to Press" line.
- b) Also using a clean hose with a good gasket, attach the "Filter Press Discharge" to the "Brine to Brine Tank #2" line.
- c) Open the associated manual valves on these four lines.

### Controlled Document

Only those quality documents viewed through the Giles Chemical electronic Documentation System are officially controlled. All other copies, whether viewed through another computer program or a printed version, are not controlled and, therefore, the Quality Unit at Giles assumes no responsibility for the accuracy of the document.

	<b>GILES CHEMICAL ~ PREMIER MAGNESIA</b>		
	<b>Company Procedure</b>		
	Title: <b>Operating the Komline-Sanderson Filter Press</b>	Number: <b>P12-PR-200-017</b>	
	Owner: <b>Patrick Owen</b>	Revision: <b>04</b>	
	Effective Date: <b>05/13/13</b>	Page: <b>2 of 2</b>	

## 2) FILTERING WITH K-S PRESS

- a) Close the press by pushing the button marked "Close Press"
- b) Push the "Start" Button on the control panel
- c) The press will begin the heat up cycle by using hot water from the wash tank.
- d) If the water is too hot for the press to start, drain some of the water from the tank and add some cool water with a hose. Then press "Start"
- e) Allow the press cycle to continue (usually several hours) until the message to open the press is displayed on the panel.
- f) Record the press run information on the Press Log

## 3) OPEN THE PRESS

- a) Press "Open Filter" to back off the press closing mechanism.
- b) Open the drip tray by pushing the square marked "Open Drip Tray"
- c) When the press is fully open, press "Start the Conveyor"
- d) Proceed to separate the press plates, thus dropping the press cakes to the conveyor. This may be done manually, one at a time, or, Press the square on the control panel labeled "Start Shifter" and allow the machine to drop all of the cakes to the conveyor.

## 4) WASH THE PLATES

- a) Press "Close Drip Tray"
- b) Using the hose provided on the cat-walk wash any cake residue adhering to the filter cloths to the drip pans and thus to waste.

**Do not close the press. Leave it open until the next cycle.**

## 7.0 Reference Documents

N/A

## 8.0 Change Information

Document review- updated format using new template and numbering system.

### Controlled Document

Only those quality documents viewed through the Giles Chemical electronic Documentation System are officially controlled. All other copies, whether viewed through another computer program or a printed version, are not controlled and, therefore, the Quality Unit at Giles assumes no responsibility for the accuracy of the document.