

GILES CHEMICAL CORPORATION		
COMPANY PROCEDURE		
Standard Operating Procedure	Page : 1 of 2	Revision : Date : 02/12/07
Author: Maintenance	Title: Lock Out Tag Out for the Air compressor for railroad acid car	

Safety: *All safety glasses and appropriate safety apparel is to be worn at all times.*

Purpose or Objective: *The purpose of this procedure is to define the process required to lock out the air compressor for the railroad acid car at the main facility at 102 Commerce Street*

Procedure: *The proper process to lockout the air compressor for the railroad acid car is as follows:*

- 1. Notify all affected employees that the machine is being taken out of production.*
- 2. Locate disconnect for air compressor for the railroad acid car*
- 3. Turn disconnect to the off position*
- 4. Attach multi lockout device with lock*
- 5. ID tag with name, date and time*
- 6. Bleed off air tank*
- 7. Compressor should not start automatically*

Proper procedure to return equipment to operation:

- 1. Make sure all work is complete and all tools and maintenance equipment has been removed from the machine.*
- 2. Notify all affected employees that equipment is about to be put back into service.*
- 3. Remove ID tag with name, date and time*
- 4. Remove multi lockout device*
- 5. Engage disconnect to the on position*
- 6. Ensure that equipment is operational and available to be returned to production*

GILES CHEMICAL CORPORATION		
COMPANY PROCEDURE		
Standard Operating Procedure	Page : 2 of 2	Revision : Date : 02/12/07
	Author: Maintenance Title: Lock Out Tag Out for the Air compressor for railroad acid car	

TRAINING DOCUMENTATION

	EMPLOYEE	TITLE	SIGNATURE	DATE
1				
2				
3				
4				
5				
6				
7				
8				
9				
10				
11				
12				
13				
14				
15				
16				
17				
18				