

GILES CHEMICAL ~ PREMIER MAGNESIA

Company Form

Title: PM Autopoucher Line #5 Number: M16-PR-200-F059

Owner: Thomas Evans Revision: 01
Effective Date: 05/1/2018 Page: 1 of 2

Items to be completed

PREMIER MAGNESIA, LLC

Not

Completed

Completed

For each of the items listed below please place a check in the *Completed* column as you complete that task. For any item that is not completed please place a check in the *Not Completed* column and give a brief explanation in the *Notes* section as to why it wasn't completed.

Auto Poucher #5 Machine	Asset Tag #:	10760
Clean Gripper jaws.		
Check springs on gripper arms for proper tension and attachment.		
Clean bushing(s) on gripper arms (both big hole and small).		
Check black nylon bushing for wear and replace if necessary.		
Check vacuum cups for wear and replace as necessary.		
Check vacuum lines for dust and blow out any trash or dust that is noticeable		
Change all vacuum filters (quantity of three)		
Grease all fittings on moving parts		
Change Teflon tape on seal bars and cooling bars		
Check bag		
Check leakage on scale (above platform toward machine)		
Convoyon		
Check helt competent with a few manner competing and manifest and/or manless if		
Check belt connector wires for proper connection and repair and/or replace if		
necessary Clean salt and trash from around end roller		
Check drive chain and grease/oil as required for proper operation		
Check drive chain and grease/on as required for proper operation		
	Asset Tag #:	
Clean salt dust and corrugate dust from inside case erector and sealer.	Asset Tag #:	
	Asset Tag #:	
Clean salt dust and corrugate dust from inside case erector and sealer.	Asset Tag #:	
Clean salt dust and corrugate dust from inside case erector and sealer. Check all filter regulators for correct labeled psi air pressure and drain water if	Asset Tag #:	
Clean salt dust and corrugate dust from inside case erector and sealer. Check all filter regulators for correct labeled psi air pressure and drain water if needed.		
Clean salt dust and corrugate dust from inside case erector and sealer. Check all filter regulators for correct labeled psi air pressure and drain water if needed. Check vacuum cups for visible wear and tears. Replace if cracked or worn. Check for loose belts on belt drives. Tighten if needed. Tensioning procedure is Combi Operating Manual if needed.	n	
Clean salt dust and corrugate dust from inside case erector and sealer. Check all filter regulators for correct labeled psi air pressure and drain water if needed. Check vacuum cups for visible wear and tears. Replace if cracked or worn. Check for loose belts on belt drives. Tighten if needed. Tensioning procedure in Combi Operating Manual if needed. Clean salt and trash from around end rollers on white plastic product conveyor be	n	
Clean salt dust and corrugate dust from inside case erector and sealer. Check all filter regulators for correct labeled psi air pressure and drain water if needed. Check vacuum cups for visible wear and tears. Replace if cracked or worn. Check for loose belts on belt drives. Tighten if needed. Tensioning procedure is Combi Operating Manual if needed. Clean salt and trash from around end rollers on white plastic product conveyor be and black packing conveyor belt.	n	
Clean salt dust and corrugate dust from inside case erector and sealer. Check all filter regulators for correct labeled psi air pressure and drain water if needed. Check vacuum cups for visible wear and tears. Replace if cracked or worn. Check for loose belts on belt drives. Tighten if needed. Tensioning procedure in Combi Operating Manual if needed. Clean salt and trash from around end rollers on white plastic product conveyor be and black packing conveyor belt. Check all air lines for cracks, leaks, or kinks. Replace if needed.	n	
Clean salt dust and corrugate dust from inside case erector and sealer. Check all filter regulators for correct labeled psi air pressure and drain water if needed. Check vacuum cups for visible wear and tears. Replace if cracked or worn. Check for loose belts on belt drives. Tighten if needed. Tensioning procedure in Combi Operating Manual if needed. Clean salt and trash from around end rollers on white plastic product conveyor beand black packing conveyor belt. Check all air lines for cracks, leaks, or kinks. Replace if needed. Clean all photo eyes and reflectors. Do not use solvent based cleaners.	n	
Clean salt dust and corrugate dust from inside case erector and sealer. Check all filter regulators for correct labeled psi air pressure and drain water if needed. Check vacuum cups for visible wear and tears. Replace if cracked or worn. Check for loose belts on belt drives. Tighten if needed. Tensioning procedure in Combi Operating Manual if needed. Clean salt and trash from around end rollers on white plastic product conveyor be and black packing conveyor belt. Check all air lines for cracks, leaks, or kinks. Replace if needed. Clean all photo eyes and reflectors. Do not use solvent based cleaners. Clean all threaded adjustment rods with mild cleaning solution.	n elt	
Clean salt dust and corrugate dust from inside case erector and sealer. Check all filter regulators for correct labeled psi air pressure and drain water if needed. Check vacuum cups for visible wear and tears. Replace if cracked or worn. Check for loose belts on belt drives. Tighten if needed. Tensioning procedure in Combi Operating Manual if needed. Clean salt and trash from around end rollers on white plastic product conveyor be and black packing conveyor belt. Check all air lines for cracks, leaks, or kinks. Replace if needed. Clean all photo eyes and reflectors. Do not use solvent based cleaners. Clean all threaded adjustment rods with mild cleaning solution. Lube all grease fittings (erector belt drives, sealer belt drives, product conveyor,	n elt	
Clean salt dust and corrugate dust from inside case erector and sealer. Check all filter regulators for correct labeled psi air pressure and drain water if needed. Check vacuum cups for visible wear and tears. Replace if cracked or worn. Check for loose belts on belt drives. Tighten if needed. Tensioning procedure in Combi Operating Manual if needed. Clean salt and trash from around end rollers on white plastic product conveyor be and black packing conveyor belt. Check all air lines for cracks, leaks, or kinks. Replace if needed. Clean all photo eyes and reflectors. Do not use solvent based cleaners. Clean all threaded adjustment rods with mild cleaning solution. Lube all grease fittings (erector belt drives, sealer belt drives, product conveyor, conveyor, carriage roller bearings)	n elt	
Clean salt dust and corrugate dust from inside case erector and sealer. Check all filter regulators for correct labeled psi air pressure and drain water if needed. Check vacuum cups for visible wear and tears. Replace if cracked or worn. Check for loose belts on belt drives. Tighten if needed. Tensioning procedure in Combi Operating Manual if needed. Clean salt and trash from around end rollers on white plastic product conveyor beand black packing conveyor belt. Check all air lines for cracks, leaks, or kinks. Replace if needed. Clean all photo eyes and reflectors. Do not use solvent based cleaners. Clean all threaded adjustment rods with mild cleaning solution. Lube all grease fittings (erector belt drives, sealer belt drives, product conveyor, conveyor, carriage roller bearings) Check all bolts and fasteners for looseness. Tighten as needed.	n elt	
Clean salt dust and corrugate dust from inside case erector and sealer. Check all filter regulators for correct labeled psi air pressure and drain water if needed. Check vacuum cups for visible wear and tears. Replace if cracked or worn. Check for loose belts on belt drives. Tighten if needed. Tensioning procedure in Combi Operating Manual if needed. Clean salt and trash from around end rollers on white plastic product conveyor be and black packing conveyor belt. Check all air lines for cracks, leaks, or kinks. Replace if needed. Clean all photo eyes and reflectors. Do not use solvent based cleaners. Clean all threaded adjustment rods with mild cleaning solution. Lube all grease fittings (erector belt drives, sealer belt drives, product conveyor, conveyor, carriage roller bearings) Check all bolts and fasteners for looseness. Tighten as needed. Clean and wipe down all doors and components.	n elt	
Clean salt dust and corrugate dust from inside case erector and sealer. Check all filter regulators for correct labeled psi air pressure and drain water if needed. Check vacuum cups for visible wear and tears. Replace if cracked or worn. Check for loose belts on belt drives. Tighten if needed. Tensioning procedure in Combi Operating Manual if needed. Clean salt and trash from around end rollers on white plastic product conveyor beand black packing conveyor belt. Check all air lines for cracks, leaks, or kinks. Replace if needed. Clean all photo eyes and reflectors. Do not use solvent based cleaners. Clean all threaded adjustment rods with mild cleaning solution. Lube all grease fittings (erector belt drives, sealer belt drives, product conveyor, conveyor, carriage roller bearings) Check all bolts and fasteners for looseness. Tighten as needed.	n elt	



GILES CHEMICAL ~ PREMIER MAGNESIA

Company Form

Title: PM Autopoucher Line #5 Number: M16-PR-200-F059

Owner: Thomas Evans Revision: 01
Effective Date: 05/1/2018 Page: 2 of 2



Oil pads that knives stop on.		
Check all springs to see if they are in proper operating condition and operating	ating	
properly.		
Notes:		
Maintenance Signature:	Date:	
Maintenance Supervisor:	Date:	