

# GILES CHEMICAL ~ PREMIER MAGNESIA

**Company Procedure** 

Title: LOTO Bag Taper #1 Number: S12-PR-200-069

Owner: Robert Willis Revision: 01
Effective Date: 05/28/13 Page: 1 of 2



## 1.0 Purpose

The purpose of this procedure is to define the process required to lock out the Box Taper #1 in repack.

## 2.0 Scope

This applies to bag taper #1 that needs to be shut down temporarily for minor repair.

## 3.0 Responsibility

Manufacturing and production

# 4.0 Safety Considerations

Safety glasses and appropriate safety apparel is to be worn at all times.

Safety is a condition of employment. Employees are not authorized to work in an unsafe manner and are prohibited from harming the environment of the facility or community.

## **5.0 Materials/Equipment**

- Lock
- Tag
- Lock out device

#### 6.0 Procedure

The proper process to lockout Box Taper #1 is as follows:

- 1. Notify all affected employees that the machine is being taken out of production.
- 2. Make sure machine is in the off position
- 3. Unplug cord and install cord end locking device
- 4. Install padlock-multi locking device
- 5. ID tag with name, date and time
- 6. Test to see if Box Taper #1 is operational

Proper procedure to return equipment to operation:

1. Make sure all work is complete and all tools and maintenance equipment has been removed from the machine.

### Controlled Document



# GILES CHEMICAL ~ PREMIER MAGNESIA

**Company Procedure** 

Title: LOTO Bag Taper #1 Number: S12-PR-200-069

Owner: Robert Willis Revision: 01
Effective Date: 05/28/13 Page: 2 of 2



- 2. Notify all affected employees that equipment is about to be put back into service.
- 3. Remove Id tag with name, date and time
- 4. Remove padlock-multi locking device
- 5. Remove cord end locking device and plug in cord
- 6. Make sure machine is in the on position and test to make sure machine is operational.

## 7.0 Reference Documents

N/A

# 8.0 Change Information

Document review- updated format using new template and numbering system.