
	GILES CHEMICAL ~ PREMIER MAGNESIA		
	Company Procedure		
	Title: PM Autopouch Line #4	Number: M15-PR-200-054	
	Owner: Brook Vaughn	Revision: 00	
	Effective Date: 03/27/2015	Page: 1 of 2	

1.0 Purpose

This procedure establishes the requirements for monthly preventive maintenance for Autopouch Line #4.

2.0 Scope

This procedure applies to Autopouch Line #4 at the Repackaging Facility. This procedure shall be performed monthly at a minimum or as necessary.

3.0 Responsibility

Maintenance will lead PM of machines with assistance of assigned production employees.

4.0 Safety Considerations

All Contractors/Service Personnel are expected to observe all safety rules and regulations while on Giles Chemical property.

Safety is a condition of employment. Employees are not authorized to work in an unsafe manner and are prohibited from harming the environment of the facility or community.

5.0 Materials/Equipment

- Tools necessary for PM of autopouchers
- Tools necessary for PM of conveyor
- Tools necessary for PM of tapers



6.0 Procedure

Auto Pouch #4 Machine

1. Clean gripper jaws.
2. Check springs on gripper arms for proper tension and attachment.
3. Clean bushings on gripper arms (both big hole and small).
4. Check black nylon bushings for wear and replace as necessary.
5. Check vacuum cups for wear and replace as necessary.
6. Check vacuum lines for dust and blow out any trash or dust that is noticeable.
7. Change all vacuum filters (quantity of three).
8. Grease all fittings on moving parts and wipe off any excess grease.
9. Change Teflon tape on seal bars and cooling bars.

Controlled Document

Only those quality documents viewed through the Giles Chemical electronic Documentation System are officially controlled. All other copies, whether viewed through another computer program or a printed version, are not controlled and, therefore, the Quality Unit at Giles assumes no responsibility for the accuracy of the document.

	GILES CHEMICAL ~ PREMIER MAGNESIA		
	Company Procedure		
	Title: PM Autopouch Line #4	Number: M15-PR-200-054	
	Owner: Brook Vaughn	Revision: 00	
	Effective Date: 03/27/2015	Page: 2 of 2	

10. Check bag.
11. Check leakage on scale (above platform toward machine).

Conveyor

1. Check belt connector wires for proper connection and repair and/or replace if necessary.
2. Clean salt and trash from around end roller.
3. Check drive chain and grease/oil as required for proper operation.

Tape Machine

1. Check knives and clean.
2. Oil pads that knives stop on.
3. Clean up and blow out all trash from machine.
4. Check all springs to see if they are in proper operating condition and operating properly.
5. Check drive belts for wear (if worn bad replace them).

7.0 Reference Documents

PM Autopouch Line #4 form (*M15-PR-200-F054*)

8.0 Change Information

New Document

Controlled Document

Only those quality documents viewed through the Giles Chemical electronic Documentation System are officially controlled. All other copies, whether viewed through another computer program or a printed version, are not controlled and, therefore, the Quality Unit at Giles assumes no responsibility for the accuracy of the document.