

GILES CHEMICAL COMPANY POLICY / PROCEDURE

55 Tons per Shift Production Rate

Page : 1 of 3

Revision

02 10/26/2009

Author: Patrick Owen

Job Specific Instruction

Personnel responsible:

1. All

Safety equipment:

Safety glasses and safety shoes, other safety equipment as needed for each situation encountered

Summary:

This document outlines the process parameters for making 110 tons of Crystal per day (55 tons per shift). It is a guideline, not an absolute since it is hard to predict every situation you may encounter. The key to running this process correctly is consistency – keep it running. Do not run hard and then shut down.

Procedure:

Raw Materials

1. Ensure a sufficient supply of MgO and Acid are in their respective storage tanks at all times.

Digesters

- 1. **Use both digesters** for making 55 tons.
- 2. Set MgO drive dials on 5.
- 3. Run about 24 gallons per minute of Mother Liquor (12 in each digester)
- 4. Aim for a Density of 1.384
- 5. Slow the Mother Liquor down if the density drops below 1.380.

Press

- 1. Kick the press off when the Mud Tanks get to 60%.
- 2. If needed set gpm shutoff to 40 gpm to get press productivity up. This shouldn't be necessary if you are turning both presses over.

Crystallizer

- 1. **Run 2 Crystallizers** when making 55 tons per shift.
- 2. Feed 10-12 gallons per minute of Mother Liquor (5 to 6 gpm in each Crystallizer)
- 3. Keep solids below 160 if possible. Use more Mother Liquor if necessary.
- 4. Density should not exceed 1.44.
- 5. The discharge pumps should run at 21 23 gallons per minute.
- 6. Adjust the brine feed if the level gets above 180 or below 150.
- 7. Run the vacuum set point at 0.85" Hg, close the automatic bleeder valve up top if you have to in warmer weather.

Dryers

- 1. Run salt temperatures at 32-35 degrees C. Do not exceed 35 C.
- 2. Dryer rotation should be set to 1350 on the dryer speed drives.



GILES CHEMICAL COMPANY POLICY / PROCEDURE

55 Tons per Shift Production Rate

Page :

2 of 3

Revision Date 02 10/26/2009

Author:

Patrick Owen

Job Specific Instruction

TRAINING DOCUMENTATION

	EMPLOYEE	TITLE	SIGNATURE	DATE
1				
2				
3				
4				
5				
6				
7				
8				
9				
10				
11				
12				0-110-11-110-11-11-11-11-11-11-11-11-11-
13				0-110-11-110-11-11-11-11-11-11-11-11-11-
14				
15				
16				
17				
18				



GILES CHEMICAL COMPANY POLICY / PROCEDURE

55 Tons per Shift Production Rate

Page :

3 of 3 Revision Date

02 10/26/2009

Author:

Patrick Owen

Job Specific Instruction

Revision Number	Revision Date	Revision Author	Revision Description
00	6/9/2006	PLO	New Procedure
01	6/5/2009	PLO	Updated for new format and level control
02	10/26/2209	PLO	Upped Mother Liquor to 5-6 gpm from 4-5