GILES CHEMICAL CORPORATION							
COMPANY PROCEDURE							
Standard Operating Procedure	Page	:	1 of 2	Revision	:	0.5 (1.5 (0.5	
1 6			Date	:	02/12/07		
Author: Maintenance Title: Lock	Title: Lock Out Tag Out #1 MGO Rotary						

Safety: All safety glasses and appropriate safety apparel is to be worn at all times.

Purpose or Objective: The purpose of this procedure is to define the process required to lock out the #1 MGO Rotary in the main facility at 102 Commerce Street

Procedure: The proper process to lockout #1 MGO Rotary is as follows:

- 1. Notify all affected employees that the machine is being taken out of production.
- 2. Locate disconnect for #1 MGO Rotary
- 3. Turn disconnect to the off position
- 4. Install multi lockout device
- 5. *ID tag with name, date and time*
- 6. Test start switch to ensure that #1 MGO Rotary is not operational

Proper procedure to return equipment to operation:

- 1. Make sure all work is complete and all tools and maintenance equipment has been removed from the machine.
- 2. Notify all affected employees that equipment is about to be put back into service.
- 3. Remove ID tag with name, date and time
- 4. Remove multi lockout device
- 5. Turn disconnect to the on position
- 6. Ensure that equipment is operational and available to be returned to production

GILES CHEMICAL CORPORATION						
COMPANY PROCEDURE						
Standard Operating Procedure	Page		2 of 2	Revision	:	
Standard Operating Procedure	1 age	•	2 01 2	Date	:	02/12/07
Author: Maintenance Title: Lock	Title: Lock Out Tag Out #1 MGO Rotary					

TRAINING DOCUMENTATION

EMPLOYEE	TITLE	SIGNATURE	DATE
1	***************************************		
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			
13			
14			
15			
16			
17			
18			