GILES CHEMICAL CORPORATION						
COMPANY PROCEDURE						
Standard Operating Procedure	Page	:	1 of 2	Revision Date	:	02/12/07
Author: Maintenance Title: Lock	Title: Lock Out Tag Out Bucket Elevator #1					

Safety: All safety glasses and appropriate safety apparel is to be worn at all times.

Purpose or Objective: The purpose of this procedure is to define the process required to lock out the Bucket Elevator #1 at the main facility at 102 Commerce Street

Procedure: The proper process to lockout Bucket Elevator #1 is as follows:

- 1. Notify all affected employees that the machine is being taken out of production.
- 2. MCC #2/Disconnect Bucket Elevator #1
- 3. Turn disconnect handle to the off position
- 4. Insert multi lockout device
- 5. Fill in ID tag with name, date and time
- 6. Test start switch to ensure that machine is not operational before beginning work

Proper procedure to return equipment to operation:

- 1. Make sure all work is complete and all tools and maintenance equipment has been removed from the machine.
- 2. Notify all affected employees that equipment is about to be put back into service.
- 3. Remove Id tag with name, date and time
- 4. Remove padlock-multi locking device from disconnect
- 5. Turn disconnect handle to the on position
- 6. Ensure that elevator is operating properly and available to be returned to production

GILES CHEMICAL CORPORATION						
COMPANY PROCEDURE						
Standard Operating Procedure	Page		2 of 2	Revision	:	
Standard Operating Procedure	1 age	•	2 01 2	Date	:	02/12/07
Author: Maintenance Title: Lock	Title: Lock Out Tag Out Bucket Elevator #1					

TRAINING DOCUMENTATION

EMPLOYEE	TITLE	SIGNATURE	DATE
1	***************************************		
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			
13			
14			
15			
16			
17			
18			