

Special Customer Requirement
(Production and Shipping requirements)

#215

Customer(s):

16.8 Kg
Regular USP Grade

Product: **U16.8Kg**

- ☐ - Tech Grade ☒ - **USP Grade** ☐ - Liquid _____
- ☐ - Screened 20/60 ☐ - Screened 60 ☐ - Other _____
(screen out dust)
- ☐ - Take Samples - _____

Production / Packaging:

- Type of Film - Giles USP 16.8Kg Film Weight per Bag 37-lbs
- Number of Bags per pallet 60 Pallet Configuration 6 layers X 10 per layer
- Type of Sacks - _____ Weight per Bag _____
- ☒ - Shrink Wrap - ☒ - Date & Lot # on each Bag ☒ - Number and Initial each pallet
- ☐ - Liners Required - ☐ - Bottom Tie Grommets ☐ - Super sack Tags
- ☒ - Placards or Tags Required - One Harris & Ford placard on the front of each pallet – Placards supplied by CSR
- ☒ - Pallets - Heat Treated Pallets
- ☒ - Other Requirements - Weight Requirements – 37-lb \pm 2.0 % or between 36.46 & 37.95 lbs
37.044 lbs \pm 0.17 bag weight =(36.46 to 37.95)
Scrap all bags out of specification ~ adjust and/or recalibrate scales

Shipping:

- ☒ - General - Load according to Giles loading chart and quantity on Bill of Lading
- ☐ - Air Bags ☐ - Double Wrap ☐ - Corner Boards ☐ - _____
- ☐ - Must have Quality Approval before loading ☐ - Must have Management Approval before loading
- ☒ - Other - Must send a corresponding Certificate of Analysis with each shipment

Revision History:

Date	Change
03/27/09	Revised weight tolerance from .5% to 2.0% MW
07/09/14	Removed Modern Ind. Placard from Placards and Tags Required section LC