

#114

Bill To:
Jim Hicks & Company
Contact - Grady Hicks
565 Mercury Lane
Brea, CA 92821

☒ - Tech Grade ☐ - USP Grade ☐ - Liquid _____

☐ - Screened 20/60 ☐ - Screened 60 ☐ - Other _____
 (screen out dust)

☐ - Take Samples - _____

Type of Film -	<u>Giles Tech 50-lb Film</u>	Weight per Bag	<u>50-lbs</u>
Number of Bags per pallet	<u>42</u>	Pallet Configuration	<u>7 per layer X 6 layers</u>
Type of Sacks -	Weight per Bag _____		
<input checked="" type="checkbox"/> - Shrink Wrap -	<input checked="" type="checkbox"/> - Date, Time & Lot # on each Bag	<input checked="" type="checkbox"/> - Number and Initial each pallet	
<input type="checkbox"/> - Liners Required -	<input type="checkbox"/> - Bottom Tie Grommets	<input type="checkbox"/> - Super sack Tags	
<input checked="" type="checkbox"/> - Placards or Tags Required -	<u>"6 X 7"</u>		
<input type="checkbox"/> - Stickers Required -	_____		
<input checked="" type="checkbox"/> - Other Requirements -	<i>* USE TREATED PALLETS ONLY *</i>		

☒ - General - Load according to Giles loading chart and quantity on Bill of Lading

☒ - Air Bags ☒ - Double Wrap ☒ - Corner Boards ☐ - _____

☐ - Must have Quality Approval before loading ☐ - Must have Management Approval before loading

Load 40' RXR containers according to chart in shipping instructions.

☒ - Other - *Must interlock first 4 pallets and use 10 Air bags down the middle.*
Each pallet gets 4 corner boards. Put one on each corner while double wrapping pallets.

Date	Change
05/30/06	Replacing SCR - 18

Special Customer Requirement

(*Production and Shipping requirements*)