

GILES CHEMICAL COMPANY POLICY / PROCEDURE

93 Tons per Shift Production Rate

Page :

1 of 3

Revision

00 1/13/2010

Author: Patrick Owen

Job Specific Instruction

Personnel responsible:

1. All

Safety equipment:

Safety glasses and safety shoes, other safety equipment as needed for each situation encountered

Summary:

This document outlines the process parameters for making 185 tons of Crystal per day (93 tons per shift). It is a guideline, not an absolute since it is hard to predict every situation you may encounter. The key to running this process correctly is consistency – keep it running. Do not run hard and then shut down.

Procedure:

Raw Materials

1. Ensure a sufficient supply of MgO and Acid are in their respective storage tanks at all times.

Digesters

- 1. **Use both digesters** for making 93 tons.
- 2. Set MgO drive dials on 8, or higher if Liquid Loads exceed 2 per day.
- 3. Run about 48 gallons per minute of Mother Liquor (24 in each digester)
- 4. Aim for a Density of 1.385
- 5. Slow the Mother Liquor down if the density drops below 1.380.

Press

- 1. Start the press when the Mud Tanks get to 60%.
- 2. If needed set gpm shutoff to 40 gpm to get press productivity up. This shouldn't be necessary if you are turning both presses over.

Crystallizer

- 1. **Run all 3 Crystallizers** when making 85 tons per shift.
- 2. Feed 18 20 gallons per minute of Mother Liquor (6 to 7 gpm in each Crystallizer)
- 3. Keep solids below 160 if possible. Use more Mother Liquor if necessary.
- 4. Density should not exceed 1.44.
- 5. The discharge pump should run at 23 25 gallons per minute.
- 6. Adjust the brine feed if the level gets above 180 or below 160.
- 7. Run the vacuum set point at 0.85" Hg, close the automatic bleeder valve up top if you have to in warmer weather.

Dryers

- 1. Run salt temperatures at 33-37 degrees C. **Do not exceed 38 C.**
- 2. Dryer rotation should be set to 1350 on the dryer speed drives.



GILES CHEMICAL COMPANY POLICY / PROCEDURE

93 Tons per Shift Production Rate

Page :

2 of 3

Revision :

00 1/13/2010

Author: Patrick Owen

Job Specific Instruction

TRAINING DOCUMENTATION

	EMPLOYEE	TITLE	SIGNATURE	DATE
1				
2				
3				
4				
5				
6				
7				
8				
9				
10				
11				
12				0-110-11-110-11-11-11-11-11-11-11-11-11-
13				0-110-11-110-11-11-11-11-11-11-11-11-11-
14				
15				
16				
17				
18				



GILES CHEMICAL COMPANY POLICY / PROCEDURE

93 Tons per Shift Production Rate

Page : 3 of 3 Revision : 00
Date : 1/13/2010

Author: Patrick Owen Job Specific Instruction

Revision Number	Revision Date	Revision Author	Revision Description
00	1/13/2010	Patrick Owen	New Document