Special Customer Requirement

(Production and Shipping requirements)

#214

Customer(s):

16.8 Kg Regular USP Grade

Harris & Ford ship to: Blois, France

| Produc | t: U16.8Kg | | | | | |
|----------|--|--------------|----------------------------|------------|------------------------|--------------------|
| Troude | - Tech Grade | ⊠ - I | JSP Grade | 🗌 - Liquio | 1 | |
| | - Screened 20/6 | 0 | creened 60 creen out dust) | Other | | |
| | Take Samples | • | | | | |
| Product | tion / Packaging | ; | | | | |
| | Type of Film - Giles USP 16.8Kg Film | | | | Weight per Bag | 37-lbs |
| | Number of Bags per pallet 60 Pallet Configuration 6 layers 2 | | | | | 10 per layer |
| | Type of Sacks - Weight per Bag | | | | | |
| | | | | | - ✓ - Number and Iı | nitial each pallet |
| | ☐ - Liners Required - ☐ - Bottom Tie Grommets ☐ - Super sack Tags | | | | | |
| | ☐ - Placards or Tags Required - One placard on the front of each pallet - Placards supplied by CSR | | | | | |
| | Stickers Required - | | | | | |
| | Weight Requirements - $37 \cdot lb \pm 2.0\%$ or between $36.46 & 37.95 \ lb = 37.044 \ lbs \pm 0.17 \ bag weight = (36.46 \ to 37.95)$ Production Scale checks need to be between 36.46 and 37.95 Scrap all bags out of specification ~ adjust and/or recalibrate scale | | | | | |
| Shippin | g: | | | | | |
| | ☐ General - Load according to Giles loading chart and quantity on Bill of Lading | | | | | |
| | ☐ - Air Bags ☐ - Double Wrap ☐ - Corner Boards ☐ - | | | | | |
| | - Must have Management Approval before loading | | | | | |
| | ✓ - Other - Must send a corresponding Certificate of Analysis with each shipment | | | | | |
| Revision | n History: | | | | | |
| | Date Change | | | | | |
| | 07/11/08 Created for BloisMW | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |