

## GILES CHEMICAL ~ PREMIER MAGNESIA

**Company Procedure** 

Title: LOTO #1 MgO Rotary Number: S12-PR-200-022

Owner: Robert Willis Revision: 01
Effective Date: 05/21/13 Page: 1 of 2

ARFMIFR MAGNESIA, LLC

### 1.0 Purpose

The purpose of this procedure is to define the process required to lock out the #1 MGO Rotary in the Manufacturing facility.

# 2.0 Scope

This procedure applies to all maintenance workers.

## 3.0 Responsibility

Manufacturing and Production

## 4.0 Safety Considerations

Safety glasses and appropriate safety apparel is to be worn at all times.

Safety is a condition of employment. Employees are not authorized to work in an unsafe manner and are prohibited from harming the environment of the facility or community.

#### 5.0 Materials/Equipment

- Lock
- Tag
- Lock out device

#### 6.0 Procedure

The proper process to lockout #1 MGO Rotary is as follows:

- 1. Notify all affected employees that the machine is being taken out of production.
- 2. Locate disconnect for #1 MGO Rotary
- 3. Turn disconnect to the off position
- 4. Install multi lockout device
- 5. ID tag with name, date and time
- 6. Test start switch to ensure that #1 MGO Rotary is not operational

Proper procedure to return equipment to operation:

- 1. Make sure all work is complete and all tools and maintenance equipment has been removed from the machine.
- 2. Notify all affected employees that equipment is about to be put back into service.

#### Controlled Document



# GILES CHEMICAL ~ PREMIER MAGNESIA

**Company Procedure** 

Title: LOTO #1 MgO Rotary Number: S12-PR-200-022

Owner: Robert Willis Revision: 01

Effective Date: 05/21/13 Page: 2 of 2



- 3. Remove ID tag with name, date and time
- 4. Remove multi lockout device
- 5. Turn disconnect to the on position
- 6. Ensure that equipment is operational and available to be returned to production

## 7.0 Reference Documents

N/A

## **8.0 Change Information**

Document review- updated format using new template and numbering system.