

#416

Customer(s):

“SCREENED” Tech grade customers

“S” means all salt is screened to assure all crystals are smaller than 16 mesh and larger than 60 mesh

MIDDLE CUT ONLY! – NO “OVERS AND NO FINES”

Product: **C10T2000SM**

- ☒ - Tech Grade ☐ - USP Grade ☐ - Liquid _____
- ☒ - **Screened 16/60** ☐ - Screened 60 ☐ - Other _____
(screen out dust)
- ☒ - Take Samples - *Use one small zip lock bag per sample*
Use time clock on each sample bag
Sample to be taken on sacks 1, 5, 10, 15, and 20 _____

Production / Packaging:

- Type of Film - _____ Weight per Bag _____
- Number of Bags per pallet 1 Pallet Configuration Must be centered on pallet
- Type of Sacks - Giles No Name sacks Weight per Bag 2,000-lbs
Stencil sacks with” 2,000” lb stencil
- ☐ - Shrink Wrap - ☐ - Date, Time & Lot # on each Bag ☐ - Number and Initial each pallet
- ☐ - Liners Required - ☐ - Heat Treated Pallets ☐ - Super sack Tags
- ☒ - Placards or Tags Required - **Placards** **Stickers On Tags**
SCREENED Arch’s
“ARCH” Letter and Number ID
- ☐ - Stickers Required - _____

Shipping:

- ☒ - General - Load according to Giles loading chart and quantity on Bill of Lading
- ☐ - Air Bags ☐ - Double Wrap ☐ - Corner Boards ☐ - _____
- ☒ - Must have Quality Approval before loading
- Operators are allowed to test ARCH and if passing*
~ release based on the Operator’s results~
Each sample is to be kept and verified by the lab
- ☒ - Other - MUST LOAD DOUBLE ON TRAILER – No Single in front or rear...

Revision History:

Date	Change
04/06/2010	Revised screen size from 20 mesh to 16 mesh. Changed sample verbiage to sample each super sack.
04/19/11	Loading doubles on trailer
06/19/12	Operators are allowed to test and release loads