

Company Procedure Title: Swab Test Auto Lines Owner: Lee Cagle Effective Date: 07/16/14 Revision: 03 Page: 1 of 1



Swab Test Auto Lines

Swab tests are to be performed any time a line is being switched from scented salt production to unscented production. When performing a swab test follow *Swabbing After Scented Salt (R12-PR-100-015)*.

- Label a zip lock bag for each of the following 24 points to be swabbed.
- Wearing latex gloves roll each end of the swab on the station being swabbed, place in the zip lock bag labeled for that station and close seal.
- Submit bags to the Quality Unit for testing and wait for results before starting production on the line being tested.

1. Bag Loader	
2. Zipper Opener	
3. Air Blast #1	
4. Bag Bottom Opening Air Blast #2	
5. Bag Top Open Air Blast	
6. Settling Table	
7. Bag Deflector	
8. Dust Remover Air Blast #4	
9. Seal Bars	
10. Cooling Bars	
11. Discharge Deflector	
12. Discharge Belt	
13. Bed of Auto	
14. Arm #1	
15. Arm #2	
16. Arm #3	
17. Arm #4	
18. Arm #5	
19. Arm #6	
20. Arm #7	
21. Arm #8	
22.Funnel	
23. Green Conveyor	
24.Packing Table	
Start Date:	End Date:
Cleaned By:	
Tested By:	
Results: Pass / Fail	
Reviewed By:	Date: