
	GILES CHEMICAL ~ PREMIER MAGNESIA		
	Company Form		
	Title: Film Specification – USP Film 16.8kg	Number: P12-PR-100-F074h	
	Owner: Lee Cagle	Revision: 01	
	Effective Date: 06/12/13	Page: 1 of 1	

GILES CHEMICAL CORPORATION
WAYNESVILLE, NC

PAGE 1 OF 1

REPLACES:

POLY FILM SPECIFICATION

16.8kg USP EPSOM SALT

Material: 6.0 mil (0.006”) ±10%
White opaque co-extruded polyethylene sheeting with UV inhibitor and differential slip. LLDPE blend with mLLDPE in the skins and HDPE in the core.

Coefficient of Friction, Film-to-Film: Inside: 0.20 to 0.35
 Outside: 0.40 to 0.60

Size Film Width = 35-1/2” ± 1/4”
 Repeat Length = 19”- 1/4 ± 1/4”

Inks: PMS 485 RED BLACK

 Use low-slip inks that are scuff and fade resistant.

Printing: 2 colors face.
 Unwind Style #2
 Do not treat 3” along each edge of the film. Skip treat
 between impressions; 5” minimum

Photo-eye: 1/2” x 2-1/2” in Black, located 12-1/4” from center of film

Perforations: 100 Micron perforations; two 5” strips, 4-1/2” to 9-1/2” from each edge.

Rolls: 23-1/2” OD Rolls (approx 500 lb, 2670 impressions)
 Wind on 3” ID cardboard cores, 35-1/2 wide.
 Roll edges to be flush with edge of core.

Packaging: 48” x 40” pallet, two rolls per pallet, laid down with cradles on top and bottom.
 Wrap each roll in plastic and use core plugs
 Band, wedge and stretchwrap

Controlled Document

Only those quality documents viewed through the Giles Chemical electronic Documentation System are officially controlled. All other copies, whether viewed through another computer program or a printed version, are not controlled and, therefore, the Quality Unit at Giles assumes no responsibility for the accuracy of the document.