Luke Colehower
Implementations of SQL
Professor Quinn, Philip
21 April 2025



```
USE information_schema;
SET sql_mode = 'ANSI';
SELECT
    CONCAT('SELECT ''', table_name, ''' AS table_name, COUNT(*) AS total_rows FROM
AS sql_line
FROM tables
WHERE table_schema = 'orta';
SELECT 'students' AS table_name, COUNT(*) AS total_rows FROM orta.students
UNION
SELECT 'courses' AS table_name, COUNT(*) AS total_rows FROM orta.courses
UNION
SELECT 'enrollments' AS table_name, COUNT(*) AS total_rows FROM orta.enrollments;
```



sql_line
SELECT 'STUDENT' AS table_name, COUNT(*) A...
SELECT 'STUDENT_GRADES' AS table_name, C...
SELECT 'cust_receivables' AS table_name, COU...
SELECT 'customers' AS table_name, COUNT(*) ...
SELECT 'employee_privileges' AS table_name, C...
SELECT 'employees' AS table_name, COUNT(*) ...
SELECT 'inventory_transaction_types' AS table...
SELECT 'inventory_view' AS table_name, COUN...
SELECT 'invoices' AS
SELECT 'latest_order_by_product_and_shipper'...
SELECT 'order_details' AS table_name, COUNT(...
SELECT 'order_details_status' AS table_name, ...
SELECT 'orders' AS table_name, COUNT(*) AS t...
SELECT 'orders_status' AS table_name, COUNT...
SELECT 'orders_tax_status' AS table_name, CO...
SELECT 'privileges' AS table_name, COUNT(*) A...
SELECT 'products' AS table_name, COUNT(*) A...
SELECT 'purchase_order_details' AS table_nam...
SELECT 'purchase_order_status' AS table_name...
SELECT 'purchase_orders' AS table_name, COU...
SELECT 'sales_reports' AS table_name, COUNT(...
SELECT 'shippers' AS table_name, COUNT(*) AS...
SELECT 'strings' AS table_name, COUNT(*) AS t...
SELECT 'suppliers' AS table_name, COUNT(*) A...

SELECT 'inventory_view' AS table_name, COUNT(*) AS total_rows FROM orta.inventory_view UNION