





CIRCUIT DIAGRAM



SMD REFLOW PATTERN (ALL TOLERANCE : ± 0.05)



SPECIFICATIONS

1. RATING : 50mA / DC12V MAX.
2. CIRCUIT : 1C-1P
3. OPERATING FORCE :
180 ± 30 gf / 250 ± 50 gf / 500 ± 80 gf
4. CONTACT RESISTANCE :
100m Ohm MAX.
5. TRAVEL : 0.25 ± 0.1 mm
6. OPERATING LIFE :
- 180gf : 50000 CYCLES MIN.
- 250gf : 30000 CYCLES MIN.
- 500gf : 10000 CYCLES MIN.
7. NON SPECIFIED DIMENSIONS
TOLERANCE : ± 0.3

NO	PARTS NAME	MATERIAL	SPECIFICATION	Q'TY	FINISH	REFERENCE
		GENERAL TOLRANCE (UNLESS SPECIFIED)	SCALE 9 / 1	UNIT METRIC	TITLE	CTT-1131
			THIRD ANGLE PROJECTION	SIZE A4	DOCUMENT NUMBER	R-T1131-AD-01A-A
		DRAWN BY C.KIM	CHECKED BY	APPROVED BY	CREATIVE ELECTRONICS CO.,LTD. www.creative-elec.com	
REV	DESCRIPTION	DATE			THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIET TO CREATIVE ELECTRONICS CO.,LTD. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.	