

Software Testing and Reliability

Lecture 6

T. Y. Chen

Department of Computer Science and Software Engineering

1

Lecture 6


Test Case Selection Strategies

2

Consider a program that accepts two integers as inputs

Input domain for a faulty program

failure-causing inputs



3

Example 1

Recognition and classification of triangles

4

Example 1 (Continued)

Given a program which

- Reads in 3 integers as the lengths of a triangle;
- Output the types of triangle – right-angled triangle, isosceles triangle, equilateral triangle, scalene triangle

5

Question?

What would be your test cases?

6

How to select test cases?

Informal yet simple approach:

- Outputs
- Inputs

7

Inputs?

3 integers

8

Outputs?

types of triangles

9

Outputs?

How many types of triangles?

10

Possible Test Cases

- Right-angled triangle – (3, 4, 5)
- Equilateral triangle – (6, 6, 6)
- Isosceles triangle – (3, 3, 5)
- Scalene triangle – (3, 4, 6)

11

Additional Test Cases

order of 3 integers not important

- Right-angled triangle – (3, 4, 5); (4, 3, 5); ..
- Equilateral triangle – 6, 6, 6
- Isosceles triangle – (3, 3, 5); (3, 5, 3); ..
- Scalene triangle – (3, 4, 6); (6, 3, 4); ..

12

test cases for a valid triangle

13

Example 1 (continued)

Given a program which

- Reads in 3 integers as the lengths of a triangle;
- Output the types of triangle – right-angled triangle, isosceles triangle, equilateral triangle, scalene triangle, *not a triangle*

14

Properties of a Triangle

- Lengths are positive integers as inputs
- Sum of the lengths of any two sides should not be less than the length of the remaining side

15

Additional Test Cases (not a triangle)

- Positive integers as inputs
 - (-3, 4, 5)
- Sum of the lengths of any two sides should not be less than the length of the remaining side
 - (4, 3, 9)

16

Commonly overlooked test cases

- Non-negative
 - $(-3, 4, 4); (4, 0, 4)$
- Sum of the lengths of any two sides should not be less than the length of the remaining side
 - $(4, 3, 9); (4, 3, 7)$

17

Valid and Invalid Test Cases

18

Example 1 (continued)

Given a program which

- Reads in 3 *positive* integers as the lengths of a triangle;
- Output the types of triangle – right-angled triangle, isosceles triangle, equilateral triangle, scalene triangle, *not a triangle*

19

- Failure-causing test case, failing test case
- Successful test case, passing test case

20

Summary

21