

L'extension `arydshln`^{*}

Hiroshi Nakashima
(Kyoto University)

28/04/2016

Résumé

Cette extension donne aux environnements `array` et `tabular` de L^AT_EX la possibilité de présenter des filets horizontaux et verticaux composés de tirets.

Table des matières

1	Introduction	3
2	Usage	3
2.1	Loading Package	3
2.2	Basic Usage	4
2.3	Style Parameters	4
2.4	Fine Tuning	4
2.5	Finer Tuning	5
2.6	Performance Tuning	6
2.7	Compatibility with Other Packages	7
3	Known Problems	8
4	Implementation	10
4.1	Problems and Solutions	10
4.2	Another Old Problem	13
4.3	Register Declaration	14
4.4	Initialization	17
4.5	Making Preamble	20
4.6	Building Columns	26
4.7	Multi-columns	29
4.8	End of Rows	30
4.9	Horizontal Lines	32
4.10	End of Environment	35

^{*}Ce fichier a pour numéro de version v1.73 et a été mis à jour le 28/04/2016. Son titre original est « *The `arydshln` package* ».

4.11	Drawing Vertical Lines	37
4.12	Drawing Dash-lines	42
4.13	Shorthand Activation	44
4.14	Compatibility with <code>colortab</code>	46
4.15	Compatibility with <code>longtable</code>	47
4.15.1	Initialization	47
4.15.2	Ending Chunks	49
4.15.3	Horizontal Lines and <code>p</code> -Boxes	51
4.15.4	First Chunk	53
4.15.5	Output Routine	54
4.16	Compatibility with <code>colortbl</code>	58
4.16.1	Initialization, Cell Coloring and Finalization	59
4.16.2	Horizontal Line Coloring	61
4.16.3	Vertical Line Coloring	63
4.16.4	Compatibility with <code>longtable</code>	65

1 Introduction

✱In January 1993, Weimin Zhang kindly posted a style `hvdashln` written by the author, which draws horizontal/vertical dash-lines in L^AT_EX's `array` and `tabular` environments, to the news group `comp.text.tex`. The style, unfortunately, has a known problem that vertical lines are broken when an array contains tall rows.

In March of the year, Monty Hayes complained of this problem encouraging the author to make a new version `arydshln` to solve the problem. The new style also has new features, such as allowing ‘:’ to specify a vertical dash-line in preamble, and `\cdashline` being a counterpart of `\cline`.

In March 1999, Sebastian Rahtz kindly invited the style, which had been improved following the bug report from Takahiro Kubota, to be included in T_EX CTAN and also in the online catalogue compiled by Graham Williams. This invitation gave the style new users including Peter Ehrbar who wished to use it with `array` style in Standard L^AT_EX Tools Bundle and had trouble because these styles were incompatible with each other. Therefore, the style became compatible with `array` and got additional new features.

In February 2000, Zsuzsanna Nagy reported that `arydshln` is not compatible with `colortab` style to let the author work on the compatibility issue again.

In February 2001, Craig Leech reported another compatibility problem with `longtable`. Although the author promised that the problem would be attacked some day, the issue had left long time¹ until three other complaints were made. Then the author attacked the problem hoping it is the last compatibility issue².

In May 2004, Klaus Dalinghaus found another incompatibility with `colortbl`. Although he was satisfied by a quick hack for cell painting, the author attacked a harder problem for line coloring to solve the problem³.

2 Usage

2.1 Loading Package

The package is usable to both L^AT_EX 2_ε and L^AT_EX-2.09 users with their standard package loading declaration. If you use L^AT_EX 2_ε, simply do the following.

```
\usepackage{arydshln}
```

If you still love L^AT_EX-2.09, the following is what you have to do.

```
\documentstyle[...arydshln,...]{<style>}
```

Only one caution given to users of `array` (v2.3m or later) and `longtable` (v4.10 or later) packages, included in Standard L^AT_EX Tools Bundle, and `colortab` and `colortbl` package is that `arydshln` has to be loaded *after* `array`, `longtable`, `colortab` and/or `colortbl` done. That is, the following is correct but reversing the order of `\usepackage` will cause some mysterious error.

-
1. Two years and a half! Sorry Craig.
 2. But his hope was dashed as described below.
 3. Without dreaming it is the last compatibility issue.

```

\usepackage{array}      % and/or
\usepackage{longtable} % and/or
\usepackage{colortab}   % or
\usepackage{colortbl}
\usepackage{arydshln}

```

2.2 Basic Usage

`array` You can simply use `array` or `tabular(*)` environments with standard preamble, such as `{r|c|l}`, and standard commands `\\`, `\hline`, `\cline` and `\multicolumn`.

`:` Drawing a vertical dash-line is quite simple. Use ‘:’ in the preamble as the separator of columns separated by the dash-line, just like using ‘|’ to draw a vertical solid-line. The *preamble* means not only that of the environment, but also the first argument of `\multicolumn`.

`\hdashline` It is also simple to draw a horizontal dash-line. Use `\hdashline` and `\cdashline` as the counterparts of `\hline` and `\cline`.

For example ;

```

\begin{tabular}{|l::c:r|}\hline
A&B&C\\ \hdashline
AAA&BBB&CCC\\ \cdashline{1-2}
\multicolumn{2}{|l:|}{AB}&C\\ \hdashline
\end{tabular}

```

will produce the following result.

A	B	C
AAA	BBB	CCC
AB		C

Note that the intersections of leftmost/rightmost vertical lines and horizontal dash-lines are little bit different from those produced by ordinary `array/tabular`. That is, with very careful examination you will find that vertical lines of ordinary ones are *broken* with small white specks at intersections, while in the example above they have no specks. In addition, the four corners of outermost rectangular also have specks in ordinary ones, while those in the example above have perfect contacts of L-shape.

`\firstdashline` If you use `array`, the dashed version of `\firsthline` and `\lasthline` named `\firstdashline` and `\lastdashline` are available.

2.3 Style Parameters

`\dashlinedash` You have two style parameters to control the shape of dash-lines : `\dashlinedash` is for the length of each dash segment in a dash line ; `\dashlinegap` controls the amount of each gap between dash segments. Both parameters have a common default value, 4pt.

2.4 Fine Tuning

Although you can control the shape of dash-lines in an `array/tabular` environment as described in §2.3, you might want to draw a dash-line of a shape different from others. To specify the shape of a vertical dash-line explicitly, you may use ;

A	A	A
B	B	B
C	C	C

(1)

A	A	A
B	B	B
C	C	C

(2)

A	A	A
B	B	B
C	C	C

(3)

FIGURE 1 – Drawing mode controlled by `\ADLdrawingmode`

`;\langle dash\rangle/\langle gap\rangle\}`

instead of ordinary ‘:’ and will have a dash-line with dash segments of $\langle dash \rangle$ long separated by spaces of $\langle gap \rangle$.

`\hdashline` As for horizontal dash-lines, explicit shape specifications may be given through optional arguments of `\hdashline` and `\cdashline` as follows.

`\cdashline` `\hdashline[\langle dash\rangle/\langle gap\rangle]`
`\cdashline{\langle col1\rangle-\langle col2\rangle}[\langle dash\rangle/\langle gap\rangle]`

For example ;

```
\begin{tabular}{|l::c;{2pt/2pt}r|}\hline
A&B&C\\hdashline[1pt/1pt]
AAA&BBB&CCC\\cdashline{1-2}[,4pt/1pt]
\multicolumn{2}{|l;{2pt/2pt}}{AB}&C\\hdashline\hdashline
\end{tabular}
```

will produce the following result.

A	B	C
AAA	BBB	CCC
AB	C	

`\ADLnullwide` The vertical solid and dashed lines are drawn as if their width is zero, as standard
`\ADLsomewide` \LaTeX ’s `array` and `tabular` do, if you don’t use `array` package. Otherwise, they have *real* width of `\arrayrulewidth` as the authors of `array` prefers. However, you may explicitly tell `arydshn` to follow your own preference by `\ADLnullwide` if you love \LaTeX standard, or `\ADLsomewide` if you second the preference of `array` authors.

2.5 Finer Tuning

To draw dash-lines, we use a powerful primitive of \TeX called `\xleaders`. It replicates a segment that consist of a dash and gap so that a dash-line has as many segments as possible and distributes *remainder* space to make the spaces between adjacent dash segments (almost) equal to each other. Therefore, you will have dash-lines with consistent steps of gaps and spaces the lines in Figure 1(1) are.

However, because of a bug (or buggy feature) of `\xleaders`, there *had been* a small possibility that a dash segment near the right/bottom end drops, until it was fixed in the version of 3.141592⁴. Though the fix ultimately made any effort to cope with the problem

4. By pointing out this problem, the author got a check of \$327.68 plus a significantly large amount of interest from DEK. Wow!!

unnecessary, the package still gives you alternative *drawing modes* which you may specify by `\ADLdrawingmode{<m>}` as follows.

- `\ADLdrawingmode` — $m = 1$
As shown in Figure 1(1), it gives most beautiful result by `\xleaders`⁵. This is default.
- $m = 2$
As shown in (2) of the figure, beautiful if dash-lines are not so sparse as right/lower lines, but dash segments near the both ends may be a little bit too long as left/upper lines, because in this mode the second first/last segments are drawn by a special mechanism.
- $m = 3$
As shown in (3) of the figure, beautiful if dash-lines are not so sparse as right/lower lines, but gaps near the both ends may be considerably too large as left/upper lines, because in this mode the lines are drawn by `\cleaders`.

It is strongly recommended to use default mode 1 unless you want to have some special effect.

2.6 Performance Tuning

Since drawing dash-lines is a hard job, you have to be patient with the fact that the performance of typesetting `array/tabular` with dash-lines is poorer than that of ordinary ones. In fact, according to author's small performance evaluation with a `tabular` having nine vertical and ten horizontal dash-lines, typesetting the `tabular` is approximately ten times as slow as its ordinary counterpart with solid lines.

However, this is not a really bad news, unfortunately. The real one is that loading `arydshln` makes typesetting `array/tabular` slower even if they only have solid lines which the package treats as special ones of dash-lines. The evaluation result shows the degradation factor is about nine. Therefore, if your document has many `array/tabular` with solid lines, \LaTeX will run slowly even with quite few (or no) `array/tabular` with dash-lines,

`\ADLinactivate` To cope with this problem, you may inactivate dash-line functions by the command `\ADLinactivate` that replaces dash-lines with solid lines drawn by a faster (i.e. ordinary) mechanism. Although the inactivation does not completely solve the performance problem, the degradation factor will become much smaller and acceptable, approximately 1.5 in the author's evaluation. For example, the draft version of your document will have the command in its preamble, which you will remove from your final version.

`\ADLactivate` Alternatively, you may do `\ADLinactivate` in the preamble, switch on by `\ADLactivate` before you really need dash-lines, and switch off again afterword. A wiser way could be surrounding `array/tabular` by `\begin{ADLactivate}` and `\end{ADLactivate}`.

`Array` If you feel it tiresome to type the long command/environment name for the activation, you may use `Array` and `Tabular(*)` environment in which dash-line functions are always active. Note that, however, since these environment names are too natural to keep them from being used by authors of other packages or yourself, name conflict could occur. If `Array` and/or `Tabular` have already been defined when `arydshln` is loaded, you will get a

5. Until the fix of `\xleaders`, the second bottom/rightmost segments of right/lower lines were dropped.

warning to show you have to define new environments, say `darray` and `dltabular`, as follows.

```
\newenvironment{darray}{\ADLactivate\begin{array}}%
{\end{array}}
\newenvironment{dltabular}{\ADLactivate\begin{tabular}}%
{\end{tabular}}
\newenvironment{dltabular*}{\ADLactivate\begin{tabular*}}%
{\end{tabular*}}
```

`\ADLnoshorthanded`

On the other hand, if they are defined after `arydshln` is loaded, their definitions are silently replaced or `LATEX` complains of multiple definitions. The error in the latter case will be avoided by putting `\ADLnoshorthanded` just after `\usepackage{arydshln}`.

2.7 Compatibility with Other Packages

Users of `array` package may use all of newly introduced preamble characters, such as ‘>’, ‘<’, ‘m’, ‘b’, and all the commands such as `\extrarowheight`, `\firsthline` and `\lasthline`. The preamble characters given by `arydshln` may be included in the second argument of `\newcolumnntype`.

Also users of `colortab` package may use `\LCC/\ECC` construct to color columns. A horizontal solid/dash line may be colored by, e.g. `\NAC\hdashline\ENAC`. The pair of `\AC` and `\EAC` may be used to color everything between them *but*, unfortunately, vertical lines are not. There are no ways to color vertical lines in a table having dash lines. You may color vertical lines of a ordinary table inactivating dash line functions by `\ADLinactivate`.

Another (and more convenient) table coloring tool `colortbl` may be also used simply by loading it before `arydshln`. Not only the painting commands `\rowcolor`, `\columncolor` and `\cellcolor` work well, but both solid and dash lines are also colored by the command `\arrayrulecolor` of `colortbl`⁶. One caution is that `\arrayrulecolor` defines the color of the dash-part of dash lines and thus gap-part has no color (i.e. color of the paper on which the line drawn). Therefore, if you have a `tabular` like;

```
\begin{tabular}{|>\columncolor{red}}l:>\columncolor{green}}r|}
...
\end{tabular}
```

you will find the vertical dash line is a sequence of black (or the color of `\arrayrulecolor`) and white segments. This problem is partly solved by declaring `\ADLnullwide`⁷ to conjunct the red and blue columns and to draw the dash line on their border.

`\ADLnullwidehline`
`\ADLsomewidehline`

Unfortunately, however, `\ADLnullwide` does not affect the real width of horizontal (dash) lines and thus you will still see white gaps in `\hdashline` and `\cdashline`. A solution is to put `\ADLnullwidehline` before you start a `array/tabular`⁸. With this command, a horizontal (dash) line is drawn adjusting its bottom edge to that of the row above. The command `\ADLsomewidehline` turns the switch to default and the top edge of a horizontal (dash) line will be adjusted to the bottom edge of the row above.

6. The `colortbl` manual says `\arrayrulecolor` and `\doublerulesepcolor` may be in `>{... }` in a preamble but they cause an error with the original implementation. This bug is fixed in `arydshln` and they are now usable to specify the color of the vertical (dash) lines whose specifications occur after the commands.

7. Since `colortbl` automatically loads `array`, the default is `\ADLsomewide`

8. This command also makes `\cline` and `\cdashline` visible even if the row below is painted.

`\dashgapcolor` Another method to avoid white gaps is to give a color to gaps by `\dashgapcolor` with arguments same as `\color`. For example;

`\arrayrulecolor{green}\dashgapcolor[rgb]{1,1,0}`

makes colorful dash lines with green dashes and yellow gaps. The command can be placed outside of `array/tabular` for dash lines in the environment, in the argument of preamble character > for vertical dash lines following them, or at the beginning of a row for horizontal dash lines following the command. The command `\nodashgapcolor` (no arguments) nullifies the effect of `\dashgapcolor`. Note that `\nodashgapcolor` is different from `\dashgapcolor{white}` because the former makes gaps *transparent* while the later whiten them.

`longtable` Usage of `longtable` with `arydshln` is quite simple. Just loading `arydshln` after `longtable` is enough to make the `longtable` environment able to draw dash-lines. A shorthand activation of dash-line functions is also available by `Longtable` environment. One caution to `longtable` users is that the temporary results before the *convergence* of the column widths may be different from those without `arydshln`. For example, the following is the first pass result of the example shown in Table 3 of the `longtable` manual.

1	2	3
wide multicolumn spanning 1-3		
multicolumn 1-2		3
wide 1	2	3

Since `LTchunksize` is one in the example, columns of each row has their own widths and thus has vertical lines drawn at the edges of the columns. On the other hand, you will have the following as the first pass result with `arydshln`.

1	2	3
wide multicolumn spanning 1-3		
multicolumn 1-2		3
wide 1	2	3

As you see, the vertical lines are drawn at the column edges of the last row⁹ because `arydshln` draws them when it see the last row. Anyway, you may ignore temporary results and will have a compatible result when the column widths are converged like the following.

1	2	3
wide multicolumn spanning 1-3		
multicolumn 1-2		3
wide 1	2	3

3 Known Problems

There are following known problems.

9. More precisely, drawn according to the column widths established by all the chunks preceding page output.

1. The new preamble specifiers ‘:’ and ‘;{*dash*}/<gap>’ cannot be followed or preceded by ‘@{<text>}’, or you will have an ugly result. More specifically, a specifier to draw a dash-line at the left edge of a column cannot be preceded by ‘@{<text>}’, while that to draw at the right edge cannot be followed by ‘@{<text>}’.
2. If you use `array` package, the restriction of ‘@’ shown above is also applied to ‘!’.
3. In order to make it sure that a dash-line always *touches* its both end, i.e. a dash-line always begins and ends with a dash segment, the amount of a gap will slightly vary depending on the dash-line length.
4. If a dash-line is too short, you will have an ugly result without overfull message. More specifically, in mode 1 or 3, a line will look to protrude beyond its column/row borders if it is shorter than a half of `\dashlinedash`. In mode 2, the minimum length to avoid the protrusion is $1.5 \times \text{\dashlinedash} + \text{\dashlinegap}$.
5. As described in §2.6, the processing speed for `array` and `tabular` environment will become slower even if dash-lines are not included.
6. As described in §2.7, `\AC` and `\EAC` pair of `colortab` such as `\AC&\EAC` cannot color the vertical line at `&`. Use `\ADLinactivate` if you want to have a ordinary table with colored vertical lines. Note that you may color vertical lines with `colortbl` package.

4 Implementation

4.1 Problems and Solutions

We have two different problems to solve; how to draw horizontal dash-lines and how to draw vertical dash-lines. The former problem is relatively easy because the technique for drawing `\cline`-s can be used. That is, if we know the number of columns, we can draw a dash-line across the `\multispan`-ed columns by `\xleaders` of dash. Modifying a preamble of `array/tabular` to count the number of columns is not hard. Since `\cdashline` is given beginning and ending columns, its implementation is also easy.

The latter problem, however, is much harder. Remember that `array/tabular` draws vertical solid lines by `\vrule`-s in each row without height/depth specification exploiting \TeX 's sophisticated mechanism of the rule extension in the surrounding box. Since \TeX does not have such a mechanism for `\xleaders` unfortunately, we at least have to know the height and depth of a row which includes vertical dash-lines. Although the height and depth are often same as those of `\@arstrutbox`, we will have an exceptionally tall and/or deep row that makes dash-lines *broken* if we assume every row has the standard height and depth.

Moreover, even if we can measure the height/depth of each row (in fact we will do as describe later), drawing dash-lines in each row will not produce a good result. Look at the following two examples closely.

A	B
A	B

In the left example, two dash-lines are individually drawn in two rows. Since the first row is not so tall and deep (8.4pt/3.6pt) as to contain enough number of default dash segments (4pt dash and 4pt gap) to keep `\xleaders` from inserting a large space, the dash-line in the first row is *sparse*. On the other hand, the second row is enough tall and deep (16.8pt/7.2pt) and thus the dash-line in the row looks better. Thus the resulting dash-line is awful because it does not have a continuous dash/gap sequence.

The right example, which we wish to produce, is much better than the left. In this example, the dash line is draw across two rows keeping continuous steps of dashes and gaps. In order to have this result, we have to draw the dash-line *after* two rows are built because it is necessary to know the total hight and depth of two rows. In general, if we know the total hight and depth of rows and whether a column has a dash-line, we can draw dash-lines by adding an extra row containing dash-lines. For example, the result shown above is obtained by the following row.

```
\omit\hss<dash-line of 36pt high>&\omit\cr
```

Note that `<dash-line of 36pt high>` have to be `\smash`-ed.

In addition to this basic scheme, we have to take the following points into account.

- A dash-line drawn by the preamble character ‘;’ will have non-default dash/gap specification.
- A column may have two or more dash-lines separated by spaces of `\doublerulesep`. Mixed sequence of solid- and dash-lines also have to be allowed.

- The first column may have dash-lines at both ends, while those of others will appear at right ends only. An exception of this rule is brought by `\multicolumn` that may have leading sequence of solid- and/or dash-line specifiers in its preamble.
- A `\multicolumn` may break or add a dash-line, or may change the dash/gap specification of a dash-line. A sequence of `\h(dash)line`-s also break dash-lines.
- If `colortbl` is in use, coloring dash/gap by `\arrayrulecolor` and `\dashgapcolor` gives another possibility of the variation of dash/gap specification.

In order to cope with them, the following data structure is constructed during rows are built.

1. The list of row information $R = \langle r_1, r_2, \dots, r_N \rangle$.
2. The i^{th} element of R , r_i , is one of the following¹⁰.
 - (a) A triple $\langle C_i^L, C_i^R, h_i \rangle$, where C_i^L and C_i^R are the lists of solid- or dash-line segments drawn at the left and right edge of columns respectively, and h_i is the height plus depth of the i^{th} row.
 - (b) `connect(h_i)` for a `\h(dash)line` of h_i wide meaning that r_i is an empty pseudo row of h_i high and dash-lines are not broken at the row.
 - (c) In `longtable` environment, `discard(h_i)` for a negative vertical space inserted by `\[- h_i]` or `\h(dash)line` meaning r_i is an empty pseudo row of h_i high and dash-lines are not broken but may be discarded by the page break at the row.
 - (d) `disconnect(h_i)` for a vertical gap generated by a sequence of `\h(dash)line` meaning that r_i is an empty pseudo row of h_i high and dash-lines are broken at the row.
3. $C_i^L = \langle e_1^i, e_2^i, \dots, e_m^i \rangle$ where e_j^i corresponds to the j^{th} (leftmost is first) solid- or dash-line segment. C_i^R is similar but its elements are ordered in reverse, i.e. the rightmost segment is the first element.
4. The j^{th} element of C_i^L or C_i^R , e_j^i , is a triple $\langle c_j^i, d_j^i, g_j^i \rangle$ where c_j^i is the column number in which the segment appears, and d_j^i and g_j^i are dash/gap specification, length and color, of the segment. For a solid line segment, the length attributes of both d_j^i and g_j^i are 0.

Then this data structure is processed to draw solid- and dash-lines at the end of the `array/tabular` as follows. Let $e_j^i = \langle c_j^i, d_j^i, g_j^i \rangle$ be the j^{th} element of C_i^L of r_i . The *position* p_j^i of e_j^i in the column c_j^i is defined as follows.

$$p_j^i = \begin{cases} 1 & \text{if } j = 1 \vee c_j^i \neq c_{j-1}^i \\ p_{j-1}^i + 1 & \text{otherwise} \end{cases}.$$

The following defines whether two elements e_j^i and $e_{j'}^{i'}$ are *connected*, or $e_j^i \sim e_{j'}^{i'}$.

$$\begin{aligned} e_j^i \sim e_{j'}^{i'} &\leftrightarrow i < i' \wedge \\ &c_j^i = c_{j'}^{i'} \wedge d_j^i = d_{j'}^{i'} \wedge g_j^i = g_{j'}^{i'} \wedge p_j^i = p_{j'}^{i'} \wedge \\ &\forall k (i < k < i' \rightarrow r_k = \text{connect}(h_k)). \end{aligned}$$

10. In the real implementation, the structure of r_i is slightly different.

With these definitions, we can classify all e_j^i into ordered sets S_1, S_2, \dots, S_n as follows.

$$\begin{aligned}
k \neq k' &\leftrightarrow S_k \cap S_{k'} = \emptyset \\
e_j^i \sim e_{j'}^{i'} &\leftrightarrow \exists k : e_j^i, e_{j'}^{i'} \in S_k \wedge S_k = \{\dots, e_j^i, e_{j'}^{i'}, \dots\} \\
k < k' &\leftrightarrow \forall e_j^i \in S_k, \forall e_{j'}^{i'} \in S_{k'} : (c_j^i < c_{j'}^{i'}) \vee \\
&\quad (c_j^i = c_{j'}^{i'} \wedge p_j^i < p_{j'}^{i'}) \vee \\
&\quad (c_j^i = c_{j'}^{i'} \wedge p_j^i = p_{j'}^{i'} \wedge i < i').
\end{aligned}$$

Now we can draw a dash-line $L_k = \langle \gamma_k, \pi_k, \delta_k, \xi_k, \tau_k, \beta_k \rangle$ corresponding to $S_k = \{e_j^i, \dots, e_{j'}^{i'}\}$ as follows.

- L_k is π_k^{th} line in the γ_k^{th} column where $\gamma_k = c_j^i = \dots = c_{j'}^{i'}$ and $\pi_k = p_j^i = \dots = p_{j'}^{i'}$.
- L_k has the dash specification (size and color) $\delta_k = d_j^i = \dots = d_{j'}^{i'}$ and gap specification $\xi_k = g_j^i = \dots = g_{j'}^{i'}$.
- The top and bottom ends of L_k are at τ_k and β_k above the bottom of the `array/tabular`, where;

$$\eta_l = \begin{cases} h_l & r_l = connect(h_l) \\ 0 & \text{otherwise} \end{cases}, \quad \tau_k = \eta_{i-1} + \sum_{l=i}^N h_l, \quad \beta_k = -\eta_{i'+1} + \sum_{l=i'+1}^N h_l.$$

Note that η_{i-1} and $\eta_{i'+1}$ are added/subtracted so that the top/bottom of L_k is at the top/bottom edge of the horizontal lines above/below the set S_k .

The row to draw L_1, \dots, L_n is;

$$\sigma_1 L_1 \sigma_2 L_2 \dots L_{n-1} \sigma_n L_n \sigma_{n+1} \backslash \text{cr}$$

where;

$$\begin{aligned}
\sigma_1 &= \backslash \text{omit}[\backslash \text{hss} \& \backslash \text{omit}]^{\gamma_1-1} \\
\sigma_{1 < k \leq n} &= \begin{cases} \backslash \text{null} & \text{if } \gamma_{k-1} = \gamma_k \wedge \pi_{k-1} = \pi_k \\ \backslash \text{hskip} \backslash \text{doublerulesep} & \text{if } \gamma_{k-1} = \gamma_k \wedge \pi_{k-1} \neq \pi_k \\ [\backslash \text{hss} \& \backslash \text{omit}]^{\gamma_k - \gamma_{k-1}} & \text{if } \gamma_{k-1} \neq \gamma_k \end{cases} \\
\sigma_{n+1} &= [\backslash \text{hss} \& \backslash \text{omit}]^{\Gamma - \gamma_n - 1} \backslash \text{hss}.
\end{aligned}$$

Note that $[x]^m$ means m -times iteration of x , and Γ is the number of columns specified in the preamble.

Dash-lines at the right edges of columns are similarly drawn by processing C_i^R with the following modifications.

$$\begin{aligned}
k < k' &\leftrightarrow \forall e_j^i \in S_k, \forall e_{j'}^{i'} \in S_{k'} : (c_j^i < c_{j'}^{i'}) \vee \\
&\quad (c_j^i = c_{j'}^{i'} \wedge p_j^i > p_{j'}^{i'}) \vee \\
&\quad (c_j^i = c_{j'}^{i'} \wedge p_j^i = p_{j'}^{i'} \wedge i < i') \\
\sigma_1 &= \backslash \text{omit} \backslash \text{hss} [\& \backslash \text{omit} \backslash \text{hss}]^{\gamma_1-1}
\end{aligned}$$

$$\sigma_{k>1} = \begin{cases} \backslash\text{null} & \text{if } \gamma_{k-1} = \gamma_k \wedge \pi_{k-1} = \pi_k \\ \backslash\text{hskip}\backslash\text{doublerulesep} & \text{if } \gamma_{k-1} = \gamma_k \wedge \pi_{k-1} \neq \pi_k \\ [\&\backslash\text{omit}\backslash\text{hss}]^{\gamma_k - \gamma_{k-1}} & \text{if } \gamma_{k-1} \neq \gamma_k \end{cases}$$

$$\sigma_{n+1} = [\&\backslash\text{omit}\backslash\text{hss}]^{\Gamma - \gamma_n - 1}$$

4.2 Another Old Problem

In the default mode 1, we draw a dash line of dash size d and gap size g as follows. Let W be the length of the line plus 10 `sp`¹¹, which is unknown for us if horizontal but known for `TeX`, and assume $W \geq d/2$ (or the line protrude to the column/row boarder.) At the both ends of the columns, dashes of $d/2$ long are drawn to make the dash-line *touched* to the ends. Then $n = \lfloor (W - d - g)/(d + g) \rfloor$ dashes are equally distributed in the remaining space. Thus we will have ;

$$D_0(d/2)G_0(g + \varepsilon')D_1(d)G_1(g + \varepsilon) \dots G_{n-1}(g + \varepsilon)D_n(d)G_n(g + \varepsilon')D_{n+1}(d/2)$$

where $D_i(l)$ and $G_i(l)$ are dash and gap of l long, $\varepsilon = (W - (n + 1)(d + g))/(n + 1)$ (rounded), and $\varepsilon' = (W - (n + 1)(d + g) - (n - 1)\varepsilon)/2$ to compensate the rounding error on the calculation of ε . For a horizontal line, this result will be obtained by `\xleaders` as follows where $G_i^m(\varepsilon)$ and $G_i^m(\varepsilon')$ are the spaces inserted by `\xleaders`.

$$\begin{aligned} & D_0(d/2)G_0^l(g/2)\backslash\text{xleaders}\backslash\text{hbox}\{G^r(g/2)D(d)G^l(g/2)\}\backslash\text{hss } G_n^r(g)D_{n+1}(d/2) \\ & = D_0(d/2)G_0^l(g/2)G_0^m(\varepsilon') (G_0^r(g/2)D_1(d)G_1^l(g/2)) G_1^m(\varepsilon) \\ & \quad (G_1^r(g/2)D_2(d)G_2^l(g/2)) G_2^m(\varepsilon) \\ & \quad \dots \\ & \quad G_{n-1}^m(\varepsilon) (G_{n-1}^r(g/2)D_n(d)G_n^l(g/2)) G_n^m(\varepsilon') G_n^r(g/2)D_{n+1}(d/2) \\ & = D_0(d/2)G_0(g + \varepsilon')D_1(d)G_1(g + \varepsilon) \dots G_{n-1}(g + \varepsilon)D_n(d)G_n(g + \varepsilon')D_{n+1}(d/2) \end{aligned}$$

The problem is that ε' could be negative and old `TeX` mistakingly ignored this possibility. That is, since the `TeX` older than 3.141592 did not put `\hbox` beyond the right edge of `\xleaders`, the rightmost `\hbox` was omitted if ε' is negative.

Since it is (almost) impossible to know the length of a horizontal line, we could not cope with this problem by adding or subtracting its length. Thus we introduced *drawing mode* to have imperfect solutions. In the mode 2, we draw a line by the following sequence.

$$\begin{aligned} & D_0(d/2)G_0^l(g/2)G_{0'}^r(g/2)D_{1'}(d)G_{1'}^l(g/2)G(-d - g) \\ & \quad \backslash\text{xleaders}\backslash\text{hbox}\{G^r(g/2)D(d)G^l(g/2)\}\backslash\text{hss} \\ & \quad G(-d - g)G_{n'}^r(g/2)D_{n'}(d)G_{n'}^l(g/2)G_n^r(g)D_{n+1}(d/2) \end{aligned}$$

That is, n^{th} `\hbox` that could be disappeared is put twice and the first one is also overlaid for symmetrization. Therefore the length of the first and n^{th} dashes is $d + |\varepsilon'|$ and thus could be a little bit longer than others.

11. This small amount is added by `\xleaders` in order to, according to the comment in `tex.web`, compensate floating point rounding error.

On the other hand, we replace `\xleaders` of mode 1 with `\cleaders` for the drawing in mode 3. The result will be ;

$$D_0(d/2)G_0(g+R)D_1(d)G_1(g)\dots G_{n-1}(g)D_n(d)G_n(g+R)D_{n+1}(d/2)$$

where $R = (W - (n + 1)(d + g))/2$ to make the first and last gaps considerably wider than others.

4.3 Register Declaration

Here registers and switches are declared.

`\dashlinedash` First of all, two `\dimen` registers `\dashlinedash` and `\dashlinegap` to control the shape of dash-lines are declared, and their default values, 4pt for both, are assigned to them.
`\dashlinegap`
`\hdashlinewidth` They have aliases, `\hdashlinewidth` and `\hdashlinegap` respectively, for the backward compatibility.
`\hdashlinegap`

```
1 %% Register Declaration
2
3 \newdimen\dashlinedash \dashlinedash4pt %
4 \newdimen\dashlinegap \dashlinegap4pt %
5 \let\hdashlinewidth\dashlinedash
6 \let\hdashlinegap\dashlinegap
7
```

Next, the following six switches are declared.

`\ifadl@leftrule` — `\ifadl@leftrule` is used in the preamble analysis macro `\@mkpream` and is true during it processes leading characters for solid- and dash-lines, i.e. ‘|’, ‘:’, and ‘;’.

`\ifadl@connected` — `\ifadl@connected` is used to indicate the *connection* $e_j^i \sim e_{j'}^{i'}$. When we process $e_{j'}^{i'}$, the switch is true iff $\exists e_j^i (e_j^i \sim e_{j'}^{i'})$.

`\ifadl@doublerule` — `\ifadl@doublerule` is used to make σ_k . When we are to make $\sigma_k L_k$, it is true iff $\gamma_{k-1} = \gamma_k \wedge \pi_{k-1} \neq \pi_k$.

`\ifadl@zwvrule` — `\ifadl@zwvrule` controls the *real* width of vertical lines. If it is true, lines are drawn as if their width is zero following L^AT_EX’s standard. Otherwise, their width `\arrayrulewidth` contribute to the width of columns as `array` does.

`\ifadl@zwhrule` — `\ifadl@zwhrule` controls the *real* width of horizontal lines. If it is true, a line is drawn as if its width is zero and its bottom edge is adjusted to that of the row above by inserting `\vskip-\arrayulewidth` before the drawing. Thus a horizontal dash line is included in the row above and its gaps look colored properly if the row is painted. If it is false, the width `\arrayrulewidth` contribute to the height of `array/tabular` as usual.

`\ifadl@usingarypkg` — `\ifadl@usingarypkg` is true iff `array` has been loaded prior to `arydshln`. This switch shows us which definitions, by L^AT_EX or `array`, we have to modify. Its value is set by examining if `\extrarowheight`, which is introduced by `array`, is defined.

`\ifadl@inactive` — `\ifadl@inactive` inactivates dash-line functions if it is true. Its default value is false.

We also use a working switch `\@tempswa`.

```

8 \newif\ifadl@leftrule
9 \newif\ifadl@connected
10 \newif\ifadl@doublerule
11 \newif\ifadl@zwvrule
12 \newif\ifadl@zwhrule
13 \newif\ifadl@usingarypkg
14 \ifx\extrarowheight\undefined \adl@usingarypkgfalse
15 \else \adl@usingarypkgtrue \fi
16 \newif\ifadl@inactive \adl@inactivefalse
17

```

`\ADLnullwide` The switch `\ifadl@hwvrule` is turned on/off by user interface macros `\ADLnullwide` and `\ADLsomewide`. Its initial value is the complement of `\adl@usingarypkg`.

`\ADLnullwidehline` The switch `\ifadl@zwvrule` is turned on/off by user interface macros `\ADLnullwidehline` and `\ADLsomewidehline`. Its initial value is false.

`\ADLactivate` The switch `\ifadl@inactive` is also turned on/off by user interface macros `\ADLactivate` and `\ADLinactivate`.

```

18 \def\ADLnullwide{\adl@zwvruletrue}
19 \def\ADLsomewide{\adl@zwvrulefalse}
20 \ifadl@usingarypkg \ADLsomewide \else \ADLnullwide \fi
21 \def\ADLnullwidehline{\adl@zwhruletrue}
22 \def\ADLsomewidehline{\adl@zwhrulefalse}
23 \ADLsomewidehline
24
25 \def\ADLactivate{\adl@inactivefalse}
26 \def\ADLinactivate{\adl@inactivetrue}
27

```

The following `\box` register and three `\dimen` registers are used to measure the height and depth of a row.

`\adl@box` — The contents of a column is packed into the `\box` register `\adl@box` to measure its height and depth.

`\adl@height` — The `\dimen` registers `\adl@height` and `\adl@depth` contain the height/depth of the tallest/deepest column in a row. When a column is processed, they are compared to the height and depth of `\adl@box` and are updated if they are less.

`\adl@heightsave` Since we have to update these registers `\global`-ly to pass their values across & and we may have a column containing `array/tabular`, they are saved into `\adl@heightsave/\adl@depthsave` at the beginning of the environment and are restored at its end.

`\adl@finaldepth` — The other `\dimen` register `\adl@finaldepth` is set to the depth of the last row, or zero if the last vertical item is a horizontal line. This value is used to shift `array/tabular` down because we add extra two `\smash`-ed rows which make the depth of `array/tabular` zero.

We also use working `\dimen` registers `\@tempdima` and `\@tempdimb`.

```

28 \newbox\adl@box

```

```

29 \newdimen\adl@height \newdimen\adl@heightsave
30 \newdimen\adl@depth \newdimen\adl@depthsave
31 \newdimen\adl@finaldepth

```

Then the following `\count` registers are declared. Note that some of them contain dimensions measured by the unit `sp`.

<code>\adl@columns</code>	— <code>\adl@columns</code> has the number of columns specified in the preamble of the environment. Because of a complicated reason related to the compatibility with <code>array</code> , we cannot count up <code>\adl@columns</code> directly but increment <code>\adl@ncol</code> when each column of preamble is built and move its value to <code>\adl@columns</code> after the preamble is constructed.
<code>\adl@ncol</code>	
<code>\adl@currentcolumn</code>	— To process <code>\multicolumn</code> , we have to know the column number where it appears. Thus we have a column counter <code>\adl@currentcolumn</code> which is <code>\global</code> -ly incremented when each column is built. Because of the <code>\global</code> assignment, the counter has to be saved/restored into/from <code>\adl@currentcolumnsave</code> .
<code>\adl@currentcolumnsave</code>	
<code>\adl@totalheight</code>	— In the real implementation, τ_k and β_k are calculated by the following equations rather than those shown in §4.1.

$$H = \sum_{l=1}^N h_l, \quad \tau_k = H - \sum_{l=1}^{i-1} h_l, \quad \beta_k = \tau_k - \sum_{l=i'}^i h_l.$$

`\adl@totalheight` contains $\sum_{l=1}^i h_l$ when the i^{th} row is built and thus its final value is H . Since the data structure R are represented by a text, we have to pay attention to the precision of its dimensional elements, such as h_i . That is, if we append h_i to R by expanding `\the\dimenn` which has the height plus depth of i^{th} row, h_i will be an approximation of `\dimenn` represented by a decimal fraction with `pt`. Although the error of the approximation is quite small and may be negligible, the error must be avoided because it is avoidable by simply using `\number\dimenn`. Therefore, h_i is an integer and thus `\adl@totalheight` is too.

<code>\adl@totalheightsave</code>	Because of the <code>\global</code> assignment to <code>\adl@totalheight</code> to pass its value across rows, it has to be saved/restored into/from <code>\adl@totalheightsave</code> .
<code>\adl@dash</code>	— In order to check $e_j^i \sim e_{j'}^{i'}$, the size attributes of d_j^i and g_j^i are kept in the registers <code>\adl@dash</code> and <code>\adl@gap</code> when we process $e_{j'}^{i'}$. As explained above, d_j^i and g_j^i are integers and thus <code>\adl@dash</code> and <code>\adl@gap</code> are <code>\count</code> registers.
<code>\adl@gap</code>	
<code>\adl@cla</code>	— The coding of <code>\cdashline</code> is similar to that of <code>\cline</code> in L ^A T _E X-2.09 which uses two global <code>\count</code> registers <code>\@cla</code> and <code>\@clb</code> . These registers are omitted from L ^A T _E X 2 _ε because its <code>\cline</code> is completely recoded. We could adopt new coding but it requires some other macro definitions that L ^A T _E X-2.09 does not have. Thus we simply introduce new global counters <code>\adl@cla</code> and <code>\adl@clb</code> for <code>\cdashline</code> in order to make <code>\cdashline</code> work in both L ^A T _E X-2.09 and L ^A T _E X 2 _ε .
<code>\adl@clb</code>	

We also use working `\count` registers `\@tempcnta` and `\@tempcntb`.

```

32 \newcount\adl@columns \newcount\adl@ncol
33 \newcount\adl@currentcolumn \newcount\adl@currentcolumnsave
34 \newcount\adl@totalheight \newcount\adl@totalheightsave
35 \newcount\adl@dash \newcount\adl@gap
36 \newcount\adl@cla \newcount\adl@clb

```


`\adl@everyvbox` The last register declaration is for a `\toks` register named `\adl@everyvbox`. In order to minimize the copy-and-modify of the codes in `LATEX` and `array`, we need to use `\everyvbox` in our own definition of `\@array`. The register is used to save the contents of `\everyvbox`.

```
37 \newtoks\adl@everyvbox
38
```

`\adl@org@arrayclassz` The other declarative stuff consists of the sequence of `\let` to capture the original definitions of macros that we will modify afterword. The main purpose of them is to nullify the modification when dash-line functions are inactive, while `\adl@org@ccline` is also referred to in its modified version.

```
\adl@org@tabclassz
\adl@org@classz
\adl@org@@startpbox
\adl@org@@endpbox
\adl@org@endpbox
\adl@org@ccline
39 \let\adl@org@arrayclassz\@arrayclassz
40 \let\adl@org@tabclassz\@tabclassz
41 \let\adl@org@classz\@classz
42 \let\adl@org@@startpbox\@@startpbox
43 \let\adl@org@@endpbox\@@endpbox
44 \let\adl@org@endpbox\@endpbox
45 \let\adl@org@ccline\ccline
46
47 %%^L
```

4.4 Initialization

`\adl@array` `LATEX`'s macro `\@array` is modified to save and initialize registers and data structures which are `\global`-ly updated in order to allow nested `array/tabular`. This saving and initializing are performed by `\adl@arrayinit` as explained below. The problem in the modification is that the code of `\@array` in `array` is completely different from that of `LATEX` original.

The main difference is that `LATEX` builds `\@preamble` locally, while `array` does globally exploiting the fact that the lifetime of `\@preamble` ends before another `array/tabular` appears in a column. The latter implementation will work well unless the building process in `\@mkpream` produces something referred to after `\@preamble` is thrown into `TEX`'s *stomach*. In our implementation, unfortunately, the number of columns has to be counted in `\@mkpream` and will be referred to by `\hdashline` and the vertical line drawing procedure.

Thus we have to change the column counting mechanism depending on whether or not `array` is in use. The simplest way could be to copy the codes of `LATEX` and `array` and modify them appropriately examining the value of `\ifadl@usingarypkg`. However this solution is vulnerable to the modification of the original version and thus we wish to refuse it as far as possible.

Therefore, we use a trick with `\everyvbox` in which `\adl@arrayinit` is temporarily included to initialize registers and locally set `\adl@columns` to the number of columns `\global`-ly counted by `\adl@ncol`. This trick works well so far because;

- the first `\vbox`, `\vtop` or `\vcenter` made by `\@array` is the vertical box surrounding `\halign`, and;
 - in `\@array` of `array` the box is opened *after* the preamble is constructed;
- and will hopefully work in future.

Next, if `\ifadl@inactive` is true, `\adl@inactivate` is invoked to inactivate dash-line functions. Otherwise, `\adl@activate` is invoked to activate them because an inactivated

`array/tabular` may have active children in it. Finally, `\adl@noalign` is made `\let`-equal to `\noalign` so that `\arrayrulecolor`, `\doublerulesepcolor` and `\dashgapcolor` are expanded with `\noalign` in the environment.

`\@@array` Another stuff for the compatibility with `array` is to `\let` a control sequence `\@@array` be equal to `\@array` because it is referred in `\@tabarray` in `array`.

```

48
49 %% Initialization
50
51 \let\adl@array\@array
52 \def\@array{\adl@everyvbox\everyvbox
53   \everyvbox{\adl@arrayinit \the\adl@everyvbox \everyvbox\adl@everyvbox}%
54   \ifadl@inactive \adl@inactivate \else \adl@activate \fi
55   \let\adl@noalign\noalign
56   \adl@array}
57 \let\@@array\@array
58

```

`\adl@arrayinit` As described in §4.3, registers updated `\global`-ly, which are `\adl@height`, `\adl@depth`, `\adl@arraysave` `\adl@currentcolumn` and `\adl@totalheight`, are saved in `\adl@arrayinit` by calling `\adl@arraysave`, and also given initial values. The macro also saves the following data structures and initializes them to empty lists.

`\adl@rowsL` — In the real implementation, the data structure R is split into two lists;
`\adl@rowsR`
`\adl@rowsLsave` $\text{\adl@rowsL} = R^L = \langle \langle C_1^L, h_1 \rangle, \dots \rangle$
`\adl@rowsRsave` $\text{\adl@rowsR} = R^R = \langle \langle C_1^R, h_1 \rangle, \dots \rangle$
`\adl@colsL`
`\adl@colsR` and they are saved into `\adl@rowsLsave` and `\adl@rowsRsave`.
`\adl@colsLsave` — When the i^{th} row is building, C_i^L and C_i^R are constructed in the macros `\adl@colsL`
`\adl@colsRsave` and `\adl@colsR`. They are saved into `\adl@colsLsave` and `\adl@colsRsave`.

`\adl@connect` In the real implementation, e_j^i is represented by a control sequence `\@elt`, and `connect(i)` by
`\adl@discard` `\adl@connect`. They are made `\let`-equal to `\relax` to keep them from expansion during R is constructed. In `longtable` environment, `connect(i)` for negative vertical space inserted by `\[\langle h \rangle]` or a horizontal line has another representation `\adl@discard` to indicate it corresponds to a discardable item of page breaking. Since this representation, however, is nonsense in usual `array/tabular` even if they are included in `\longtable`, we define `\adl@discard` as `\adl@connect` so that it transforms itself into `\adl@connect` when it is added to `\adl@rowsL/R` by `\xdef`. Note that `\adl@discard` is made `\let`-equal to `\relax` to inhibit the transformation at the beginning of `longtable` environment.

Then, we set to `\adl@columns` to the value of `\adl@ncol` *locally*. As explained above, this has an effect with `array` because `\adl@arrayinit` is called *after* the preamble is generated. Without `array`, on the other hand, this assignment has no effect but safe because it is included in a group of `\vbox` etc.

```

59 \def\adl@arrayinit{%
60     \adl@arraysave
61     \global\adl@height\z@ \global\adl@depth\z@
62     \global\adl@currentcolumn\@ne \global\adl@totalheight\z@
63     \gdef\adl@rowsL{}\gdef\adl@rowsR{}\gdef\adl@colsL{}\gdef\adl@colsR{}%
64     \let\@elt\relax \let\adl@connect\relax \def\adl@discard{\adl@connect}%
65     \adl@columns\adl@ncol}
66 \def\adl@arraysave{%
67     \adl@heightsave\adl@height
68     \adl@depthsave\adl@depth
69     \adl@currentcolumnsave\adl@currentcolumn
70     \adl@totalheightsave\adl@totalheight
71     \let\adl@rowsLsave\adl@rowsL
72     \let\adl@rowsRsave\adl@rowsR
73     \let\adl@colsLsave\adl@colsL
74     \let\adl@colsRsave\adl@colsR}
75

```

`\adl@inactivate` If `\ADLinactivate` has effect and thus `\ifadl@inactive` is true, the macro `\adl@inactivate` is called from `\@array`¹². This `\let`-s the following control sequences be equal to their counterparts in L^AT_EX and/or array package.

```

\@arrayclassz \@tabclassz \@classz \@@startpbox \@@endpbox
\@endpbox \adl@cr \adl@argcr \adl@endarray

```

Note that we have to inactivate both `\@@endpbox` for L^AT_EX and `\@endpbox` for array, while `\@startpbox` for array is not necessary because it is unmodified. Also note that `\@classz` has to be `\let`-equal to `\adl@org@classz` only if array is in use, because L^AT_EX does not define `\@classz` but refers to it which is either `\@arrayclassz` or `\@tabclassz`. Yet another remark is that we have to conceal `\cr` for `\adl@cr`/`\adl@argcr` and `\crrc` for `\adl@endarray` by bracing them from T_EX's `\halign` mechanism that searches them when an array/tabular has an nested array/tabular. This could be done by a tricky `\let`-assignment such as;

```

\iffalse{\let\adl@cr\cr \iffalse}\fi

```

but we simply use `\def` instead of `\let` because of clarity.

We also `\let` the following be *no-operation* or their inactive versions.

```

\adl@hline \adl@ihdashline \adl@cdline \adl@@vlineL \adl@@vlineR
\adl@vlineL \adl@vlineR

```

Note that we have to inactivate both `\adl@@vlineL` and `\adl@vlineL`, because the latter is referred to when array is in use while the former is done otherwise. Their R relatives are also inactivated by the same reason.

```

76 \def\adl@inactivate{%
77     \let\@arrayclassz\adl@org@arrayclassz
78     \let\@tabclassz\adl@org@tabclassz
79     \ifadl@usingarypkg \let\@classz\adl@org@classz \fi
80     \let\@@startpbox\adl@org@@startpbox

```

12. Before v1.53, `\adl@inactivate` was called from `\adl@arrayinit` and thus invoked *after* the preamble of array is built. This was incorrect of course and made inactive version of `p`, `m` and `b` produce nothing.

```

81      \let\@@endpbox\adl@org@@endpbox
82      \let\@endpbox\adl@org@endpbox
83      \def\adl@cr{\cr}%
84      \def\adl@argcr##1{\cr}%
85      \def\adl@endarray{\crr}%
86      \let\adl@hline\@gobbletwo
87      \let\adl@ihdashline\adl@inactivehdl
88      \let\adl@cdline\adl@inactivecdl
89      \let\adl@@vlineL\adl@inactivevl
90      \let\adl@@vlineR\adl@inactivevl
91      \let\adl@vlineL\adl@inactivevl
92      \let\adl@vlineR\adl@inactivevl}

```

`\adl@activate` On the other hand, if `\ifadl@inactive` is false, the macro `\adl@activate` is called from `\@array` to make inactivated macros active again in order to cope with the case in which an inactive `array/tabular` has active children in it¹³. To do that, `\adl@activate` makes `\@arrayclassz` etc. `\let-equal` to their active version `\adl@act@arrayclassz` etc. which will be defined (`\let-equal` to) as our own `\@arrayclassz` etc. in §4.13.

```

93 \def\adl@activate{%
94     \let\@arrayclassz\adl@act@arrayclassz
95     \let\@tabclassz\adl@act@tabclassz
96     \ifadl@usingarypkg \let\@classz\adl@act@classz \fi
97     \let\@@startpbox\adl@act@@startpbox
98     \let\@@endpbox\adl@act@@endpbox
99     \let\@endpbox\adl@act@endpbox
100    \let\adl@cr\adl@act@cr
101    \let\adl@argcr\adl@act@argcr
102    \let\adl@endarray\adl@act@endarray
103    \let\adl@hline\adl@act@hline
104    \let\adl@ihdashline\adl@act@ihdashline
105    \let\adl@cdline\adl@act@cdline
106    \let\adl@@vlineL\adl@act@@vlineL
107    \let\adl@@vlineR\adl@act@@vlineR
108    \let\adl@vlineL\adl@act@vlineL
109    \let\adl@vlineR\adl@act@vlineR}
110
111 %%~L

```

The summary of the activation and inactivation is shown in Table 1.

4.5 Making Preamble

Each preamble character is converted to a part of `\halign`'s preamble as follows.

`\adl@colhtdp` — ‘l’, ‘r’ and ‘c’ are converted to the following `\lrc`.

$$\langle lrc \rangle ::= [\backslash\mathrm{hfil}]\langle put\text{-}lrc \rangle[\backslash\mathrm{hfil}]$$

$$\langle put\text{-}lrc \rangle ::= \backslash\mathrm{setbox}\backslash\mathrm{adl@box}\backslash\mathrm{hbox}\{\langle lrc\text{-}contents \rangle\}$$

13. Before v1.54, an active `array/tabular` in an inactive parent was not activated.

TABLE 1 – Active and Inactive Operations

command	active	inactive
<code>l c r</code> with array without array	<code>\adl@act@classz</code> <code>\adl@act@tabclassz</code> <code>\adl@act@arrayclassz</code>	<code>\adl@org@classz</code> <code>\adl@org@tabclassz</code> <code>\adl@org@arrayclassz</code>
<code>p m b</code> (open) with array without array	<code>\adl@act@classz</code> <code>\adl@act@@startpbox</code>	<code>\adl@org@classz</code> <code>\adl@org@@startpbox</code>
<code>p m b</code> (close)	<code>\adl@act@@endpbox</code>	<code>\adl@org@@endpbox</code>
<code> /:/;</code>	<code>\adl@act@@vlineL/R</code>	<code>\adl@inactivev1</code>
<code>\\</code>	<code>→\adl@act@(arg)cr</code>	<code>→\cr</code>
<code>\hline</code>	<code>→\adl@act@hline</code>	<code>→\@gobbletwo</code>
<code>\hdashline</code>	<code>→\adl@act@ihdashline</code>	<code>→\adl@inactivehdl</code>
<code>\cdashline</code>	<code>→\adl@act@cdline</code>	<code>→\adl@inactivecdl</code>

```

\adl@colhtdp \unhbox\adl@box
⟨lrc-contents⟩ ::= $\relax#$ |
                #\unskip

```

That is, the content of a column is at first packed into the `\box` register `\adl@box`, then its height and depth are compared to `\adl@height` and `\adl@depth` by the macro `\adl@colhtdp`, and finally the box is put with leading and/or trailing `\hfil`. — ‘|’, ‘:’ and `;\{⟨dash⟩/⟨gap⟩\}` are converted to the following `⟨vline⟩`.

`\adl@vlineL`
`\adl@vlineR`

```

⟨vline⟩ ::= [\hskip\doublerulesep]⟨vline-LR⟩
⟨vline-LR⟩ ::= \adl@vlineL{⟨Γd⟩}{⟨Γg⟩}{⟨c⟩}{⟨d⟩/⟨g⟩} |
               \adl@vlineR{⟨Γd⟩}{⟨Γg⟩}{⟨c⟩}{⟨d⟩/⟨g⟩}
⟨d⟩ ::= 0 | ... for ‘|’
        \dashlinedash | ... for ‘:’
        ⟨dash⟩ ... for ‘;’
⟨g⟩ ::= 0 | ... for ‘|’
        \dashlinegap | ... for ‘:’
        ⟨gap⟩ ... for ‘;’

```

Note that `⟨c⟩` is the column number (leftmost is 1) where the character appears, and `⟨Γd⟩` and `⟨Γg⟩` is the color of dashes and gaps specified in `\CT@arc@` and `\adl@dashgapcolor`.

Additionally, each column except for the last one has ;

```
\global\advance\adl@currentcolumn\@ne
```

just before `&` to increment `\adl@currentcolumn`. Other features, such as inserting spaces of `\arraycolsep/\tabcolsep`, are as same as original scheme. This means that `@{<text>}` and `!{<text>}` of `array` are *not* handled specially although it could interfere with drawing vertical lines. Therefore, we have the problem 1 shown in §3, which is very hard to solve. Note that the measurement of the column of ‘p’ of L^AT_EX original is done by (modified) `\@@startpbox` and `\@@endpbox` and thus the preamble for ‘p’ is not modified. In the case with `array`, however, the preambles for ‘p’ and its relatives ‘m’ and ‘b’ are modified to set `\adl@box` to the box for them.

`\adl@mkpream` To make the preamble shown above, `\@mkpream` is modified to `\let` control sequences `\adl@colhtpd`, `\adl@vlineL` and `\adl@vlineR` be `\relax` in order to keep them from being expanded by `\edef/\xdef` for the preamble construction. The control sequences `\adl@startmbox` and `\adl@endmbox` for m-columns of `array` are also made `\let`-equal to `\relax`.

`\@mkpream`

Giving them their own definition is done by `\adl@preamininit` that is called using `\afterassignment` after `\@preamble` is made by `\adl@mkpream`, the original version of `\@mkpream`. If `array` is not in use, `\@mkpream` is followed by an `\edef` of `\@preamble` to add `\ialign` etc. and thus `\adl@preamininit` is properly called *after* this final *assignment* to make `\@preamble`.

With `array`, on the other hand, calling `\adl@preamininit` is safe because `\@mkpream` is followed by `\xdef` for `\@preamble` too, but has no effect because it is in the group for `\@mkpream`. This grouping, however, gives us an easier way to give those control sequences their own definition. That is, we simply initiate them with the definitions that will be regained when the group is closed.

The modified `\@mkpream` also initializes `\adl@ncol` and `\ifadl@leftrule`, and set `\adl@columns` to the value of `\adl@ncol` locally after the preamble is made. This has an effect in the case without `array` because the body of `array/tabular` is in the same grouping context of `\@mkpream`. With `array`, on the other hand, this assignment has no effect but safe because it is included in a group of `\@mkpream`’s own.

```

112
113 %% Making Preamble
114
115 \let\adl@mkpream\@mkpream
116 \def\@mkpream#1{\let\adl@colhtpd\relax
117     \let\adl@vlineL\relax \let\adl@vlineR\relax
118     \let\adl@startmbox\relax \let\adl@endmbox\relax
119     \global\adl@ncol\@ne \adl@leftruletrue
120     \adl@mkpream{#1}\adl@columns\adl@ncol \afterassignment\adl@preamininit}
121

```

`\@addamp` The macro `\@addamp` is also modified to add the code for incrementing the counter `\adl@currentcolumn` to `\@preamble` with `&`. The counter `\adl@ncol` is also incremented by `\@addamp` so that we can refer to its value as `<c>` of `\adl@vlineL/R`. This increment is done `\global`-ly in order that we locally set `\adl@columns` to the counting result outside of the group for `\@mkpream` of `array`. Therefore, whether or not `array` is in use, `\adl@columns` will have a correct value and will be correctly referred to by `\hdashline` to know how many columns are specified in the preamble. Note that this `\global` assignment is safe because the life time of `\adl@ncol` is same as that of `\@preamble`.

```

122 \def\@addamp{\if@firstamp\@firstampfalse \else
123         \@addtopreamble{\global\advance\adl@currentcolumn\@ne &}%
124         \global\advance\adl@ncol\@ne \fi}
125

```

Since the implementation of `\@testpach` and macros for class-0 characters (i.e. l, r and c) is completely different between L^AT_EX and array, we have to have two versions switched by `\adl@usingarypkg`.

With array

`\@testpach` Although we introduced two preamble characters ‘:’ and ‘;’, we did not introduce new character *class* because we want to minimize the modification of original codes. Therefore, ‘:’ and ‘;’ is classified into class-1 together with ‘|’. Since these characters obviously have their own appropriate operations, `\@testpach` is modified so that `\@arrayrule`, which is invoked from `\@mkpream` in the case of class-1 character, is `\let`-equal to the macro corresponding to each character.

```

126 \ifadl@usingarypkg
127 \def\@testpach{\@chclass
128 \ifnum \@lastchclass=6 \@ne \@chnum \@ne \else
129 \ifnum \@lastchclass=7 5 \else
130 \ifnum \@lastchclass=8 \tw@ \else
131 \ifnum \@lastchclass=9 \thr@@
132 \else \z@
133 \ifnum \@lastchclass = 10 \else
134 \edef\@nextchar{\expandafter\string\@nextchar}%
135 \@chnum
136 \if \@nextchar c\z@ \else
137 \if \@nextchar l\@ne \else
138 \if \@nextchar r\tw@ \else
139 \z@ \@chclass
140 \if \@nextchar |\@ne \let\@arrayrule\adl@arrayrule \else
141 \if \@nextchar : \@ne \let\@arrayrule\adl@arraydashrule \else
142 \if \@nextchar ; \@ne \let\@arrayrule\adl@argarraydashrule \else
143 \if \@nextchar !6 \else
144 \if \@nextchar @7 \else
145 \if \@nextchar <8 \else
146 \if \@nextchar >9 \else
147 10
148 \@chnum
149 \if \@nextchar m\thr@@\else
150 \if \@nextchar p4 \else
151 \if \@nextchar b5 \else
152 \z@ \@chclass \z@ \@preamerr \z@ \fi \fi \fi \fi \fi \fi
153 \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi
154

```

`\@classz` In array, array and tabular share common macro for class-0 named `\@classz`, which also generates the preamble for ‘p’, ‘m’ and ‘b’. Thus we modify it to measure the height and

depth of the class-0 column by the macro `\adl@putlrc`, and to set `\adl@box` to the box for ‘p’ and its relatives. Note that a m-type preamble (`@chnum = 3`) has to be generated to have `\adl@startmbox` and `\adl@endmbox` in it because a `\vcenter` construct cannot be assigned to `\adl@box` by `\setbox` directly.

```

155 \def\@classz{\@classx
156   \@tempcnta \count@
157   \prepnext@tok
158   \@addtopreamble{\ifcase \@chnum
159     \hfil
160     \adl@putlrc{\d@llarbegin \insert@column \d@llarend}\hfil \or
161     \hskip1sp\adl@putlrc{\d@llarbegin \insert@column \d@llarend}\hfil \or
162     \hfil\hskip1sp\adl@putlrc{\d@llarbegin \insert@column \d@llarend}\or
163     \setbox\adl@box\hbox \adl@startmbox{\@nextchar}\insert@column
164     \adl@endmbox\or
165     \setbox\adl@box\vtop \@startpbox{\@nextchar}\insert@column \@endpbox \or
166     \setbox\adl@box\ vbox \@startpbox{\@nextchar}\insert@column \@endpbox
167   \fi}\prepnext@tok}

```

`\adl@class@start` Another stuff for compatibility is to refer to the class number for the beginning of preamble which is different between L^AT_EX and array, and that for ‘p’ or ‘@’ to get the argument of ‘;’ as explained later. In the case with array, the former is class-4 and we use ‘@’ (class-7) for the latter.

```

168 \def\adl@class@start{4}
169 \def\adl@class@iiiorvii{7}
170

```

Without array

`\@testpach` The reason why and how we modify `\@testpach` of L^AT_EX is same as those of array.

```

171 \else
172 \def\@testpach#1{\@chclass \ifnum \@lastchclass=\tw@ 4\relax \else
173   \ifnum \@lastchclass=\thr@@ 5\relax \else
174     \z@ \if #1c\@chnum \z@ \else
175       \if #1l\@chnum \@ne \else
176       \if #1r\@chnum \tw@ \else
177       \@chclass
178       \if #1|\@ne \let\@arrayrule\adl@arrayrule \else
179       \if #1:\@ne \let\@arrayrule\adl@arraydashrule \else
180       \if #1;\@ne \let\@arrayrule\adl@argarraydashrule \else
181       \if #1@\tw@ \else
182       \if #1p\thr@@ \else \z@ \@preamerr 0\fi
183     \fi \fi \fi \fi \fi \fi \fi \fi \fi}
184

```

`\@arrayclassz` Since L^AT_EX has two macros for class-0, one for array and the other for tabular, we have to modify both. Since the box for ‘p’ is opened by `\@startpbox`, however, we may not worry about it.


```

185 \def\@arrayclassz{\ifcase \@lastchclass \@acolampacol \or \@ampacol \or
186         \or \or \@addamp \or
187         \@acolampacol \or \@firstampfalse \@acol \fi
188 \edef\@preamble{\@preamble
189         \ifcase \@chnum
190         \hfil\adl@putlrc{\$ \relax \@sharp$}\hfil
191         \or \adl@putlrc{\$ \relax \@sharp$}\hfil
192         \or \hfil\adl@putlrc{\$ \relax \@sharp$}\fi}}
193 \def\@tabclassz{\ifcase \@lastchclass \@acolampacol \or \@ampacol \or
194         \or \or \@addamp \or
195         \@acolampacol \or \@firstampfalse \@acol \fi
196 \edef\@preamble{\@preamble
197 \ifcase \@chnum
198         \hfil\adl@putlrc{\@sharp\unskip}\hfil
199         \or \adl@putlrc{\@sharp\unskip}\hfil
200         \or \hfil\hskip\z@ \adl@putlrc{\@sharp\unskip}\fi}}

```

`\adl@class@start` In L^AT_EX, the beginning of preamble is class-6 and we use ‘p’ (class-3) to get the argument of ‘;’.

```

201 \def\adl@class@start{6}
202 \def\adl@class@iiiorvii{3}
203 \fi
204

```

Hereafter, codes for L^AT_EX and array are common again.

`\adl@putlrc` The macro `\adl@putlrc` is for class-0 preamble characters to set `\adl@box` to the contents of a column, measure its height/depth by `\adl@colhtdp` and put the box by `\unhbox` (not by `\box`) in order to make the glues in the contents effective.

```

205 \def\adl@putlrc#1{\setbox\adl@box\hbox{#1}\adl@colhtdp \unhbox\adl@box}
206

```

`\adl@arrayrule` The preamble parts for vertical solid- and dash-lines are constructed by the macros `\adl@arrayrule` for ‘|’, `\adl@arraydashrule` for ‘:’, and `\adl@argarraydashrule` for ‘;’. The macro;

```

\adl@xarraydashrule{\langle c^L \rangle}{\langle c^R \rangle}{\langle d \rangle}{\langle g \rangle}

```

is invoked by them to perform common operations. It at first checks the preamble character is the first element of the preamble (`\@lastchclass = \adl@class@start`) or it follows another character for vertical line (`\@lastchclass = 1`). If this is not satisfied, the vertical line is put at the right edge of a column and thus `\ifadl@leftrule` is set to false. Then it adds `\adl@vlineL{\langle \Gamma_d \rangle}{\langle \Gamma_g \rangle}{\langle c^L \rangle}{\langle d \rangle}{\langle g \rangle}` if `\ifadl@leftrule` is true indicating the vertical line will appear at the left edge of the column $\langle c^L \rangle$, or `\adl@vlineR{\langle \Gamma_d \rangle}{\langle \Gamma_g \rangle}{\langle c^R \rangle}{\langle d \rangle}{\langle g \rangle}` otherwise. Note that $\langle c^L \rangle$ is always 1 for *main* preamble while $\langle c^R \rangle$ is the column number given by `\adl@ncol`, but $\langle c^L \rangle$ may not be 1 for the preamble of `\multicolumn` as described in §4.7. Also note that Γ_d and Γ_g are `\CT@arc@` and `\adl@dashgapcolor` respectively whose bodies are `\color` for dashes and gaps specified by `\arrayrulecolor` and `\dashgapcolor`, or `\relax` if they are not colored.

In addition, an invisible `\vrule` of `\arrayrulewidth` wide is added if both `\ADLsome` wide and `\ADLactivate` are in effect, i.e. both `\ifadl@zwrule` and `\ifadl@inactive` are false, to keep a space for the vertical line having *real* width.

`\adl@classv` The argument of ‘;’ is not provided by `\adl@argarraydashrule` but is directly passed from
`\adl@classvfordash` the preamble text through `\@nextchar`. This direct passing is implemented by the following trick. The macro `\adl@argarraydashrule` set `\@chclass` to `\adl@class@iiiorvii` to pretend it is for ‘p’ if array is not in use, or ‘@’ otherwise. Then it temporally changes the definition of `\@classv`, which is incidentally for the argument of ‘p’ and ‘@’ in the case without/with array respectively, to `\adl@classvfordash` to process the argument of ‘;’ rather than that of ‘p’ or ‘@’. Then `\adl@classvfordash` is invoked by `\@mkpream` and it adds the argument to `\@preamble`. Finally, it restores the definition of `\@classv` and sets `\@chclass` to 1 to indicate that the last item is a vertical line specification.

```

207 \def\adl@arrayrule{%
208     \adl@xarraydashrule
209     {\@ne}{\adl@ncol}{\z@/\z@}}
210 \def\adl@arraydashrule{%
211     \adl@xarraydashrule
212     {\@ne}{\adl@ncol}%
213     {\dashlinedash/\dashlinegap}}
214 \def\adl@argarraydashrule{%
215     \adl@xarraydashrule
216     {\@ne}{\adl@ncol}{}}%
217     \@chclass\adl@class@iiiorvii \let\@classv\adl@classvfordash}
218 \def\adl@xarraydashrule#1#2#3{%
219     \ifnum\@lastchclass=\adl@class@start\else
220     \ifnum\@lastchclass=\@ne\else
221         \adl@leftrulefalse \fi\fi
222     \ifadl@zwvrule\else \ifadl@inactive\else
223         \@addtopreamble{\vrule\@width\arrayrulewidth
224             \@height\z@ \@depth\z@}\fi \fi
225     \ifadl@leftrule
226         \@addtopreamble{\adl@vlineL{\CT@arc@}{\adl@dashgapcolor}%
227             {\number#1}#3}%
228     \else \@addtopreamble{\adl@vlineR{\CT@arc@}{\adl@dashgapcolor}%
229             {\number#2}#3}\fi}
230 \let\adl@classv\@classv
231 \def\adl@classvfordash{\@addtopreamble{\@nextchar}}\let\@classv\adl@classv
232     \@chclass\@ne}
233
234 %%~L

```

4.6 Building Columns

`\adl@preamininit` If array is not in use, after the `\@preamble` is completed, the control sequences for macros in
`\adl@colhtdp` it should regain their own definition. The macro `\adl@preamininit` performs this operation
`\adl@vlineL` for macros we introduced, `\adl@colhtdp`, `\adl@vlineL` and `\adl@vlineR`. For the case
`\adl@vlineR`

with array, we will call `\adl@preaminit` in `arydshln` to initiate them with the definitions as described later.

```

235
236 %% Building Columns
237
238 \def\adl@preaminit{\let\adl@colhtdp\adl@@colhtdp
239     \let\adl@vlineL\adl@@vlineL \let\adl@vlineR\adl@@vlineR}
240
\adl@@colhtdp For the measurement of the height and depth of a row, \adl@@colhtdp compares \adl@
height and \adl@depth to the height and depth of \adl@box which contains the main part
of the column to be built, and \global-ly updates the registers if they are less.

241 \def\adl@@colhtdp{%
242     \ifdim\adl@height<\ht\adl@box \global\adl@height\ht\adl@box \fi
243     \ifdim\adl@depth<\dp\adl@box \global\adl@depth\dp\adl@box\fi}
244

\adl@@vlineL The macro \adl@@vlineL $\langle\Gamma_d\rangle\langle\Gamma_g\rangle\langle c\rangle\{\langle d\rangle/\langle g\rangle\}$  adds the element  $e = \langle c, d, g \rangle = \@elt\{\langle c \rangle\}$ 
\adl@@vlineR  $\{\langle d \rangle\}\{\langle g \rangle\}\{\langle \gamma_d \rangle\}\{\langle \gamma_g \rangle\}$  to the tail of the list \adl@colsL to construct  $C_i^L$ , where  $\gamma_d$  and
\adl@@ivline  $\gamma_g$  are the color specifications given by \color macros in  $\Gamma_d$  and  $\Gamma_g$ . The macro \add@@
\adl@setcolor vlineR performs similar operation but the element is added to the head of \adl@colsR for
\adl@nocolor  $C_i^R$  because it is processed right-to-left manner. The argument  $\langle d \rangle$  and  $\langle g \rangle$  are extracted
\adl@dashcolor by the macro \adl@ivline which converts given dimensional values of them to integers. It
\adl@gapcolor also sets  $\langle d \rangle$  and  $\langle g \rangle$  to 0 (i.e. solid-line) if one of given values are not positive, in order to
make it sure that one dash segment has positive length. Then it invokes \adl@setcolor
to define \adl@dashcolor and \adl@gapcolor with the color specification of  $\Gamma_d$  and  $\Gamma_g$ .
Since \adl@setcolor locally expands \color macro in  $\Gamma_d$  and  $\Gamma_g$  to define \currnet@color
that becomes the body of \adl@dashcolor ( $\gamma_d$ ) and \adl@gapcolor ( $\gamma_g$ ) with expansion,
different \color specifications of a color, such as \color{red} and \color[rgb]{1,0,0},
will produce a unified result such as {rgb 1 0 0}. If  $\Gamma_d$  or  $\Gamma_g$  is \relax which is the body
of \adl@nocolor,  $\gamma_d$  or  $\gamma_g$  is also \relax to indicate dashes are colored (or not colored) as
done in outer world and gaps are transparent.

245 \def\adl@@vlineL#1#2#3#4{\adl@ivline#4\@nil{#1}{#2}%
246     \xdef\adl@colsL{\adl@colsL
247         \@elt{#3}{\number\@tempcnta}{\number\@tempcntb}%
248         {\adl@dashcolor}{\adl@gapcolor}}}
249 \def\adl@@vlineR#1#2#3#4{\adl@ivline#4\@nil{#1}{#2}%
250     \xdef\adl@colsR{%
251         \@elt{#3}{\number\@tempcnta}{\number\@tempcntb}%
252         {\adl@dashcolor}{\adl@gapcolor}%
253         \adl@colsR}}
254 \def\adl@ivline#1/#2\@nil#3#4{%
255     \@tempdima#1\relax \@tempcnta\@tempdima
256     \@tempdima#2\relax \@tempcntb\@tempdima
257     \ifnum\@tempcnta>\z@ \else \@tempcnta\z@ \@tempcntb\z@ \fi
258     \ifnum\@tempcntb>\z@ \else \@tempcnta\z@ \@tempcntb\z@ \fi

```

```

259         \adl@setcolor\adl@dashcolor{#3}\adl@setcolor\adl@gapcolor{#4}}
260 \def\adl@setcolor#1#2{\def\@tempa{#2}\ifx\@tempa\adl@nocolor \def#1{\relax}%
261         \else{#2\xdef#1{\currentcolor}}\fi}
262 \def\adl@nocolor{\relax}

\adl@colhtdp After \adl@@colhtdp, \adl@@vlineL and \adl@@vlineR are defined, we call \adl@
\adl@vlineL preaminit to \let their single @ counterparts be equal to them. Therefore, in the case
\adl@vlineR with array, \adl@colhtdp etc. are temporarily \relax when \@preamble is being genera-
ted in the group of \@mkpream, and regain their own definitions outside the group where
the completed \@preamble is referred to.

263 \adl@preaminit
264

\adl@inactivevl If \ADLinactivate is in effect, \adl@vlineL/R and \adl@@vlineL/R are \let-equal to
\adl@inactivevl. This macro simply puts a \vrule by \vline with \color (or \relax)
in its first argument and with/without negative \hskip of a half of \arrayrulewidth wide
depending on \ifadl@zwvrule, discarding other arguments.

265 \def\adl@inactivevl#1#2#3#4{\ifadl@zwvrule \hskip-.5\arrayrulewidth \fi
266         {#1\vline}\ifadl@zwvrule \hskip-.5\arrayrulewidth \fi}
267

\@@startpbox The macros to make \parbox for ‘p’ (and ‘b’ of array), \@@startpbox and \@@endpbox,
\@@endpbox are modified for height/depth measurement. The code for \@@endpbox is based on that
of LATEX 2ε to fix the bug of \strut-ing in LATEX-2.09, but \@finalstrut is manually
\adl@startmbox expanded because it is not available in LATEX-2.09.
\adl@endmbox In array, \@@endpbox is not used but \@endpbox is. Therefore, we \let them be equal. As
for \@startpbox, however, we may not worry about it because we have modified \@classz
in §4.5 for the measurement. However, we have to take care of m-type columns specially
because its body \vcenter cannot be assigned directly to \adl@box by \setbox14. Thus
we enclose a $\vcenter{...}$ construct in a \hbox and assign it to \adl@box. The macro
\adl@startmbox opens the construct with array’s \@startpbox, while \adl@endmbox closes
it calling \adl@org@endpbox which is the unmodified \@endpbox of array and measures the
height and depth of the \hbox by \adl@colhtdp.

268 \def\@@startpbox#1{\setbox\adl@box\top\bggroup \hsize#1\@arrayparboxrestore}
269 \def\@@endpbox{\unskip \ifhmode \nobreak
270         \vrule\@width\z@\@height\z@\@depth\dp\@arstrutbox \fi
271         \par \egroup \adl@colhtdp \box\adl@box \hfil}
272 \let\@endpbox\@@endpbox
273 \def\adl@startmbox{\bggroup $\vcenter\@startpbox}
274 \def\adl@endmbox{\adl@org@endpbox $\egroup \adl@colhtdp \box\adl@box \hfil}
275
276 %%~L

```

14. The author had forgotten this fact until Morten Høgholm pointed out it. Thanks Morten.

4.7 Multi-columns

- `\multicolumn` The macro `\multicolumn` is modified for the followings.
- `\adl@preamble` — The macros to construct the parts of `\@preamble` for vertical lines, `\adl@arrayrule`, `\adl@arraydashrule` and `\adl@argarraydashrule`, have to perform operations slightly different from those for main preamble. Thus they are `\def`-ined to multicolumn version `\adl@mcarrayrule`, etc. These `\def`-initions are enclosed in a group so that they are not affected to `array` or `tabular` which may occur in the third argument of `\multicolumn`. In order to make `\@preamble` work well outside of the group containing `\@makepream`, `\adl@preamble` is `\global`-ly `\let`-equal to `\@preamble` just after `\@makepream` in the group and then reverse `\let`-assignment is performed just after the group is closed. These global assignment is unnecessary with `array` because `\@preamble` is constructed `\global`-ly, but safe. Since this grouping nullifies the effect of `\adl@preamininit` called in `\@mkpream`, we call `\adl@preamininit` again after the group closing.
 - `\adl@mcaddamp` — In `array`, `\@addamp` to make `\@preamble` for `\multicolumn` has a different definition from that for main one. Thus it is `\let`-equal to `\adl@mcaddamp` whose definition is switched by `\ifadl@usingarypkg`.
 - `\adl@activatepbox` — If `array` is in use, `\@preamble` has to be `\xdef`-ed once again by `\@addpreamble` with an `\@empty` argument after `\@mkpreamble` to expand the contents of `\toks` registers. This is performed whether or not with `array` because it is safe.
 - As done in `\@array`, `\set@typeset@protect` is replaced with direct `\let`.
 - If without `array`, `\@startpbox` and `\@endpbox` should be `\let`-equal to their `@` counterparts, while should not with `array`. Thus we define `\adl@activatepbox` to do or not to do so depending on `\ifadl@usingarypkg`.
 - The counter `\adl@currentcolumn` is `\global`-ly incremented by the first argument of `\multicolumn` (number of columns to be `\span`-ned).

Note that `\adl@columns` is modified by `\@mkpream`, but it is not referred to by `\adl@mcarrayrule` etc., and its value is restored before referred to by `\hdashline`, etc.

```

277
278 %% Multi-Columns
279
280 \def\multicolumn#1#2#3{\multispan{#1}\begingroup \begingroup
281     \def\adl@arrayrule{\adl@mcarrayrule{#1}}%
282     \def\adl@arraydashrule{\adl@mcarraydashrule{#1}}%
283     \def\adl@argarraydashrule{\adl@mcargarraydashrule{#1}}%
284     \let\@addamp\adl@mcaddamp
285     \@mkpream{#2}\@addtopreamble\@empty
286     \global\let\adl@preamble\@preamble \endgroup
287     \let\@preamble\adl@preamble
288     \def\@sharp{#3}\let\protect\relax
289     \adl@activatepbox
290     \adl@preamininit
291     \@arstrut \@preamble\hbox{}\endgroup
292     \global\advance\adl@currentcolumn#1\ignorespaces}
293 \ifadl@usingarypkg
294     \def\adl@mcaddamp{\if@firstamp\@firstampfalse \else\@preamerror5\fi}

```

```

295      \let\adl@activatepbox\relax
296 \else
297      \let\adl@mcaddamp\@addamp
298      \def\adl@activatepbox{\let\@startpbox\@@startpbox
299          \let\@endpbox\@@endpbox}
300 \fi
301

```

`\adl@mcarrayrule` The preamble parts for vertical lines are constructed by the macros `\adl@mcarrayrule`,
`\adl@mcarraydashrule` `\adl@mcarraydashrule` and `\adl@mcargarraydashrule` to which the first argument $\langle n \rangle$
`\adl@mcargarraydashrule` of `\multicolumn` is passed to know the number of columns to be `\span`-ned. They are
similar to their relatives for main preamble, `\adl@arrayrule`, etc., but the arguments $\langle c^L \rangle$
and $\langle c^R \rangle$ passed to `\adl@xarraydashrule` are;

$$c^L = c, \quad c^R = c + n - 1$$

where $c = \text{\adl@currentcolumn}$. This makes leading vertical lines drawn at the left edge of
the leftmost `\span`-ned column and trailing ones at the right edge of the rightmost column.

```

302 \def\adl@mcarrayrule#1{\@tempcnta#1\advance\@tempcnta\adl@currentcolumn
303     \advance\@tempcnta\m@ne
304     \adl@xarraydashrule
305         {\adl@currentcolumn}\@tempcnta}{\z@/\z@}}
306 \def\adl@mcarraydashrule#1{\@tempcnta#1\advance\@tempcnta\adl@currentcolumn
307     \advance\@tempcnta\m@ne
308     \adl@xarraydashrule
309         {\adl@currentcolumn}\@tempcnta}%
310         {\dashlinedash/\dashlinegap}}
311 \def\adl@mcargarraydashrule#1{\@tempcnta#1\advance\@tempcnta\adl@currentcolumn
312     \advance\@tempcnta\m@ne
313     \adl@xarraydashrule
314         {\adl@currentcolumn}\@tempcnta}{\}%
315     \@chclass\adl@class@iiiorvii \let\@classv\adl@classvfordash}
316
317 %%~L

```

4.8 End of Rows

`\@xarraycr` At the end of the i^{th} row, we have to calculate h_i which is the height plus depth of the row,
`\@xtabularcr` and add elements $\langle C_i^L, h_i \rangle$ and $\langle C_i^R, h_i \rangle$ to R^L and R^R . To do this, `\cr`-s in the macros
`\@xargarraycr` `\@xarraycr`, `\@xtabularcr`, `\@xargarraycr` are replaced with our own `\adl@cr`. The ma-
`\@yargarraycr` cro `\@yargarraycr(dimen)` is also modified but its `\cr` is replaced with `\adl@argcr(dimen)`
to add (negative) `\dimen` to h_i . Note that `\@xargarraycr(dimen)` uses ordinary `\adl@cr`
because the extra vertical space of $\langle dimen \rangle$ is inserted to the last column.

Note that the implementation of `\@xarraycr` is slightly different between L^AT_EX and
array, we have to have two versions and choose one.

```

318
319 %% End of row

```

```

320
321 \ifadl@usingarypkg
322 \def\@xarraycr{\@ifnextchar[\@argarraycr]{\ifnum0='{ }\fi\adl@cr}}
323 \else
324 \def\@xarraycr{\@ifnextchar[\@argarraycr]{\ifnum0='{ \fi}$\fi}\adl@cr}}
325 \fi
326 \def\@xtabularcr{\@ifnextchar[\@argtabularcr]{\ifnum0='{ \fi}\adl@cr}}
327 \def\@xargarraycr#1{\@tempdima#1\advance\@tempdima\dp\@arstrutbox
328     \vrule\@height\z@\@depth\@tempdima\@width\z@
329     \adl@cr}
330 \def\@yargarraycr#1{\adl@argcr{#1}\noalign{\vskip #1}}
331

```

`\adl@cr` The macro `\adl@cr` and `\adl@argcr` perform `\cr` and then invoke the common macro `\adl@@cr⟨x⟩`. The argument `⟨x⟩` is the extra (negative) vertical space for `\adl@argcr`, while it is 0 for `\adl@cr`.

`\adl@@cr` The macro `\adl@@cr⟨x⟩` at first calculate h_i as follows. The registers `\adl@height` = η and `\adl@depth` = δ have the maximum height and depth of the columns in the row. However, they could be smaller than the height and/or depth of `\@arstrutbox`, η_s and δ_s . If so, the height and/or depth of the row are η_s and δ_s . Therefore, h_i is calculated by;

$$h_i = \max(\eta, \eta_s) + \max(\delta, \delta_s).$$

Additionally, if the extra space `⟨x⟩` is negative, a vertical space of x is inserted below the row¹⁵. Thus the integer value of $h_i + x$ is `\global`-ly added to `\adl@totalheight`, and the elements $\langle C_i^L = \text{\adl@colsL}, h_i \rangle$ and $\langle C_i^R = \text{\adl@colsR}, h_i \rangle$ are added to the tail of $R^L = \text{\adl@rowsL}$ and $R^C = \text{\adl@rowsR}$. If x is not 0 (negative), `discard(x)` or `connect(x)` is also added after $\langle C_i^{L/R}, h_i \rangle$ according to the current environment (`longtable` or not). In the real implementation, R^L and R^C has the following format of `⟨rows⟩`.

$$\begin{aligned}
\langle rows \rangle &::= [\langle row \rangle ;]^* \\
\langle row \rangle &::= (\langle cols \rangle / \langle h_i \rangle) \\
\langle cols \rangle &::= [\text{\relt}\{ \langle c \rangle \} \{ \langle d \rangle \} \{ \langle g \rangle \}]^* \mid \dots C^L \text{ or } C^R \\
&\quad \text{\adl@connect} \mid \dots \text{for } connect(h_i) \\
&\quad \text{\adl@discard} \mid \dots \text{for } discard(h_i) \\
&\quad \text{\relax} \mid \dots \text{for } disconnect(h_i)
\end{aligned}$$

Since `\adl@discard` is `\def`-ined as `\adl@connect` by `\adl@arrayinit`, added `\adl@discard` transforms itself into `\adl@connect` if current environment is not `longtable`. Otherwise, as we make `\adl@discard` `\let`-equal to `\relax` when a `longtable` environment starts, it keeps its own form.

Then, `\adl@finaldepth` is set to `\adl@depth` if x is zero, or to zero otherwise (negative), in order to make the depth of `array/tabular` equal to that of the last row. Finally, `\adl@`

15. Before v1.54, negative `⟨x⟩` shrinks the height of the row by $|x|$. Although the former result may be more appropriate if the row has vertical lines than the current because lines extrude to the next row now, new feature is considered compatible with original `array/tabular`.

`colsL`, `\adl@colsR`, `\adl@currentcolumn`, `\adl@height` and `\adl@depth` are reinitialized to process the next row.

```

332 \def\adl@cr{\cr\noalign{\adl@cr\z@}}
333 \def\adl@argcr#1{\cr\noalign{\adl@cr{#1}}}
334 \def\adl@cr#1{
335     \ifdim\adl@height<\ht\@arstrutbox \adl@height\ht\@arstrutbox\fi
336     \ifdim\adl@depth<\dp\@arstrutbox \adl@depth\dp\@arstrutbox\fi
337     \advance\adl@height\adl@depth
338     \global\advance\adl@totalheight\adl@height
339     \@tempdima#1\relax \global\advance\adl@totalheight\@tempdima
340     \xdef\adl@rowsL{\adl@rowsL
341         (\adl@colsL/\number\adl@height);%
342         \ifdim#1=\z@\else (\adl@discard/\number\@tempdima);\fi}%
343     \xdef\adl@rowsR{\adl@rowsR
344         (\adl@colsR/\number\adl@height);%
345         \ifdim#1=\z@\else (\adl@discard/\number\@tempdima);\fi}%
346     \gdef\adl@colsL{}\gdef\adl@colsR{}
347     \global\adl@currentcolumn\@ne
348     \ifdim#1=\z@ \global\adl@finaldepth\adl@depth
349     \else \global\adl@finaldepth\z@\fi
350     \global\adl@height\z@ \global\adl@depth\z@}
351
352 %%~L

```

4.9 Horizontal Lines

`\hline` The macro `\hline` is modified to insert `\vskip-\arrayrulewidth` before drawing if `\ADLnullwidehline` is in effect, or to add the element $connect(w) = (\adl@connect/\number\arrayrulewidth)$ to the end of R^L and R^R by `\adl@hline` otherwise. The other modifications are to set `\adl@finaldepth` to zero for the case that the last vertical item is `\hline`, and to check if it is followed by not only `\hline` but also `\hdashline` by `\adl@xhline`.

The macro `\cline` is also modified to set `\adl@finaldepth` to zero. As for the feature of `\ADLnullwidehline`, it inserts `\vskip-\arrayrulewidth` to shift the line up before drawing, and `\vskip\arrayrulewidth` after drawing to cancel the negative skip inserted by `\adl@org@cline`.

```

353
354 %% Horizontal Lines
355
356 \def\hline{\noalign{\ifnum0='}\fi
357     \ifadl@zwhrule \vskip-\arrayrulewidth
358     \else \adl@hline\adl@connect\arrayrulewidth \fi
359     \hrule\@height\arrayrulewidth
360     \global\adl@finaldepth\z@
361     \futurelet\@tempa\adl@xhline}
362 \def\cline#1{\noalign{\global\adl@finaldepth\z@
363     \ifadl@zwhrule \vskip-\arrayrulewidth\fi}

```



```

364      \adl@org@ccline{#1}%
365      \noalign{\ifadl@zwhrule \vskip\arrayrulewidth\fi}}
366
\hdashline The macro \hdashline calls \adl@hdashline to open the \noalign construct by the
\adl@hdashline well-known trick {\ifnum0='}\fi and then to invoke \adl@ihdashline checking the
\adl@ihdashline existence of its optional argument [dash]/[gap]. Before the invocation, it inserts
\vskip-\arrayrulewidth if \ADLnullwidehline is in effect, or adds connect(w) to the
end of  $R^L$  and  $R^R$ . Then \adl@ihdashline closes the \noalign by \ifnum0='{ \fi} to
start the pseudo row for the horizontal dash-line. Before the dash-line is drawn by \adl@
hcline which is also used for \cdashline, all the columns are \span-ned by giving \adl@
columns to \multispan. Finally, the \noalign is opened again and \adl@xhline is invoked
to check whether \h(dash)line is followed.

\adl@inactivehdl If \ADLinactivate is in effect, \adl@ihdashline is \let-equal to \adl@inactivehdl.
This macro simply puts a \hrule discarding its arguments after inserting \vskip
-\arrayrulewidth if \ADLnullwidehline is in effect.

367 \def\hdashline{\adl@hdashline\adl@ihdashline}
368 \def\adl@hdashline#1{\noalign{\ifnum0='}\fi
369      \ifadl@zwhrule \vskip-\arrayrulewidth
370      \else \adl@hline\adl@connect\arrayrulewidth \fi
371      \@ifnextchar[%]
372          {#1}%
373          {#1[\dashlinedash/\dashlinegap]}}
374 \def\adl@ihdashline[#1/#2]{\ifnum0='{ \fi}%
375      \multispan{\adl@columns}\unskip \adl@hcline\z@[#1/#2]%
376      \noalign{\ifnum0='}\fi
377      \futurelet\@tempa\adl@xhline}
378 \def\adl@inactivehdl[#1/#2]{\ifadl@zwhrule \vskip-\arrayrulewidth \fi
379      \hrule\@height\arrayrulewidth
380      \futurelet\@tempa\adl@xhline}
381

\adl@xhline The macro \adl@xhline is the counterpart of the original \xhline. This is introdu-
ced to check the mixed sequence of \hline and \hdashline, and to add the element
disconnect(s) = (\relax/\doublerulesep) to the end of  $R^L$  and  $R^R$  by \adl@hline
if a pair of \h(dash)line is found.

382 \def\adl@xhline{\ifx\@tempa\hline \adl@ixhline\fi
383      \ifx\@tempa\hdashline \adl@ixhline\fi
384      \ifnum0='{ \fi}}
385 \def\adl@ixhline{\vskip\doublerulesep \adl@hline\relax\doublerulesep}
386

\adl@hline The macro \adl@hline<cs><dimen> \global-ly adds the integer value of <dimen> to
\adl@totalheight and adds the element (<cs>/\number<dimen>) to the tail of  $R^L$  and
 $R^R$ . The arguments <cs><dimen> are \adl@connect\arrayrulewidth for connect(w) or
\relax\doublerulesep for disconnect(s).

```

```

387 \def\adl@hline#1#2{\@tempcnta#2
388     \global\advance\adl@totalheight\@tempcnta
389     \xdef\adl@rowsL{\adl@rowsL
390         (#1/\number\@tempcnta);}
391     \xdef\adl@rowsR{\adl@rowsR
392         (#1/\number\@tempcnta);}
393

```

`\cdashline` The macro `\cdashline` at first opens `\noalign` and then invokes `\adl@cdline` checking the existence of its optional argument [*dash*]/[*gap*]. The macro `\adl@cdline` first inserts `\vskip-\arrayrulewidth` if `\ADLnullwidehline` is in effect. Then it performs column `\span`-ing by the code based on that of `\@cline` in L^AT_EX-2.09 because L^AT_EX 2_ε's version will not work with L^AT_EX-2.09. The main job is done by `\adl@hcline` after the target columns are `\span`-ned by `\adl@cdlinea` or `\adl@cdlineb`.

`\adl@inactivecdl` If `\ADLinactivate` is in effect, `\adl@cdline` is `\let`-equal to `\adl@inactivecdl`. This macro simply calls our own `\cline`, after closing the `\noalign` opened by `\cdashline`.

```

394 \def\cdashline#1{\noalign{\ifnum0='}\fi
395     \@ifnextchar[%]
396         {\adl@cdline[#1]}%
397         {\adl@cdline[#1][\dashlinedash/\dashlinegap]}}
398 \def\adl@cdline[#1-#2]{\ifadl@zwhrule \vskip-\arrayrulewidth \fi
399     \global\adl@cla#1\relax
400     \global\advance\adl@cla\m@ne
401     \ifnum\adl@cla>\z@ \global\let\@gtempa\adl@cdlinea
402     \else \global\let\@gtempa\adl@cdlineb\fi
403     \global\adl@clb#2\relax
404     \global\advance\adl@clb-\adl@cla \ifnum0='{\fi}
405     \@gtempa{-\arrayrulewidth}}
406 \def\adl@cdlinea{\multispan\adl@cla &\multispan\adl@clb \unskip \adl@hcline}
407 \def\adl@cdlineb{\multispan\adl@clb \unskip \adl@hcline}
408
409 \def\adl@inactivecdl[#1-#2][#3]{\ifnum0='{\fi}\cline{#1-#2}}
410

```

`\adl@hcline` The macro `\adl@hcline`*w*[[*d*]/[*g*]] draws a horizontal dash-line of dash size *d* and gap size *g* for `\hdashline` and `\cdashline` in the `\span`-ned columns by `\adl@draw`. As we will discuss in §4.12, the macro requires *d* and *g* are passed through `\@tempdima` and `\@tempdimb`, and control sequences *rule*, *skip* and *box* are passed through its arguments to make it usable for both horizontal and vertical lines. Then the vertical space of *w*, `-\arrayrulewidth` for `\cdashline`, is inserted if it is not 0 (for `\hdashline`) and `\ADLnullwidehline` is not in effect.

```

411 \def\adl@hcline#1[#2/#3]{\@tempdima#2\relax \@tempdimb#3\relax
412     \adl@draw\adl@vrule\hskip\hbox \cr
413     \noalign{\global\adl@finaldepth\z@ \ifdim#1=\z@\else
414         \ifadl@zwhrule\else \vskip#1\fi\fi}}
415

```

`\firsthdashline` If array is in use, we wish to have dashed counterparts of `\first/lasthline` named `\first/lasthdashline`, which simply call `\adl@hdashline` with an argument to call `\adl@first/lasthdashline` after closing `\noalign` opened by `\adl@hdashline`.

`\adl@defflhd1` The macros `\adl@first/lasthdashline`, however, are defined in a tricky manner to replace
`\adl@idefflhd1` `\hline` in `\first/lasthline` with;

`\adl@firsthdashline` `\adl@hdashline\adl@ihdashline[$\langle dash \rangle$ / $\langle gap \rangle$]`
`\adl@lasthdashline` in order to avoid copy-and-replace. To do that, we define `\adl@defflhd1` and `\adl@idefflhd1` in which the body of `\first/lasthline` is expanded by `\expandafter` and the parts preceding and following `\hline` are extracted. Then the preceding part $\langle p \rangle$, the calling sequence of `\adl@hdashline`, and the following part $\langle f \rangle$ are connected to be the body of `\adl@first/lasthdashline`. Thus we define `\adl@firsthdashline` as follows.

```

\def\adl@firsthdashline[#1/#2]{%
    \mathrel{\mathop{\kern.25em\hbox{\scriptsize p}}\kern.25em}
    \adl@hdashline\adl@ihdashline[#1/#2]
    \mathrel{\mathop{\kern.25em\hbox{\scriptsize f}}\kern.25em}}
416 \ifadl@usingarypkg
417 \def\firsthdashline{\adl@hdashline{\ifnum0='{fi}\adl@firsthdashline}}
418 \def\lasthdashline{\adl@hdashline{\ifnum0='{fi}\adl@lasthdashline}}
419
420 \def\adl@defflhd1#1{\def\@tempa{#1}
421     \expandafter\adl@idefflhd1}
422 \def\adl@idefflhd1#1\hline#2\@nil{%
423     \@namedef\@tempa[##1/##2]{#1\adl@hdashline\adl@ihdashline[##1/##2]#2}}
424 \adl@defflhd1{\adl@firsthdashline}\firsthline\@nil
425 \adl@defflhd1{\adl@lasthdashline}\lasthline\@nil
426 \fi
427
428 %%~L

```

4.10 End of Environment

`\endarray` The macros to close the `array/tabular` environment, `\endarray` and `\endtabular(*)`,
`\endtabular` are modified so that they invoke `\adl@endarray` to draw vertical lines just before closing `\halign`, and `\adl@arrayrestore` to restore registers and data structures `\global`-ly
`\endtabular*` modified in the environment.

```

429
430 %% End of Environment
431
432 \def\endarray{\adl@endarray \egroup \adl@arrayrestore \egroup}
433 \def\endtabular{\endarray $\egroup}
434 \expandafter\let\csname endtabular*\endcsname\endtabular
435

```

`\adl@endarray` The macro `\adl@endarray` at first closes the last row by `\crcr`. If this `\crcr` has real effect, we have to invoke `\adl@@cr` to perform our own end-of-row operations. We assume that the `\crcr` is effective if either `\adl@height` or `\adl@depth` has a non-zero value¹⁶.
`\adl@rows`
`\adl@addv1` Then the rows to draw vertical lines L_1, \dots, L_n ;
`\adl@vlrowL`
`\adl@vlrowR`
`\adl@vlrow`

$$\sigma_1 L_1 \sigma_2 L_2 \dots L_{n-1} \sigma_n L_n \sigma_{n+1}$$

are created in `\adl@vlrowL` and `\adl@vlrowR` by `\adl@makev1rL` and `\adl@makev1rR`. In the real implementation, $L_k = \langle \gamma_k, \pi_k, \delta_k, \xi_k, \tau_k, \beta_k \rangle$ is represented as;

`\adl@v1{\beta_k}{\tau_k - \beta_k}{\delta_k}{\xi_k}`.

Thus `\adl@v1` is made `\let`-equal to `\relax` when the rows are constructed and to `\adl@@v1` when the rows are put.

Since `\adl@makev1rL` and `\adl@makev1rR` shares common macros, they conceptually have the following interface.

`\adl@vlrow = \adl@makev1rL/R(\adl@rows : $\langle R^L$ or $R^R \rangle$,
\adl@currentcolumn : $\langle start column \rangle$,
\adl@addv1 : $\langle macro to add an element \rangle$)`

Thus they are invoked as;

`\adl@vlrowL = \adl@makev1rL(\adl@rowsL, 1, \adl@addv1L)`
`\adl@vlrowR = \adl@makev1rR(\adl@rowsR, \adl@columns, \adl@addv1R)`

Finally, after constructed rows for vertical lines are put by `\adl@drawv1`, a vertical skip of `-\adl@finaldepth` is inserted to move back to the last baseline, and then an invisible `\vrule` of `\adl@finaldepth` deep is put to make `array/tabular` has the depth of the last real row or zero if it ends with a horizontal line.

```

436 \def\adl@endarray{\crcr \noalign{
437     \ifdim\adl@height=\z@
438     \ifdim\adl@depth=\z@ \else \adl@@cr\z@ \fi
439     \else \adl@@cr\z@ \fi
440     \let\adl@v1\relax
441     \def\adl@vlrow{}\adl@currentcolumn\@ne
442     \let\adl@rows\adl@rowsL
443     \let\adl@addv1\adl@addv1L
444     \adl@makev1rL \global\let\adl@vlrowL\adl@vlrow
445     \def\adl@vlrow{}\adl@currentcolumn\adl@columns
446     \let\adl@rows\adl@rowsR
447     \let\adl@addv1\adl@addv1R
448     \adl@makev1rR \global\let\adl@vlrowR\adl@vlrow
449     \global\let\adl@v1\adl@@v1}%
450     \adl@drawv1
451     \noalign{\vskip-\adl@finaldepth}%
452     \omit\vrule\@width\z@\@height\z@\@depth\adl@finaldepth\cr}
453

```

16. The author confesses that this rule is not strict and the introduction of a switch could improve the strictness.

`\adl@arrayrestore` The macro `\adl@arrayrestore` restores the values of registers and data structures, `\adl@height`, `\adl@depth`, `\adl@currentcolumn`, `\adl@totalheight`, `\adl@rowsL`, `\adl@rowsR`, `\adl@colsL` and `\adl@colsR`, saved by `\adl@arrayinit`.

```

454 \def\adl@arrayrestore{%
455     \global\adl@height\adl@heightsave
456     \global\adl@depth\adl@depthsave
457     \global\adl@currentcolumn\adl@currentcolumnsave
458     \global\adl@totalheight\adl@totalheightsave
459     \global\let\adl@rowsL\adl@rowsLsave
460     \global\let\adl@rowsR\adl@rowsRsave
461     \global\let\adl@colsL\adl@colsLsave
462     \global\let\adl@colsR\adl@colsRsave}
463
464 %%~L

```

4.11 Drawing Vertical Lines

Figure 2 shows the conceptual code of `\adl@makev1rL`. The correspondance of variables in the code and control sequences in the real implementation is as follows.

R^L	: <code>\adl@rowsL</code>	R	: <code>\adl@rows</code>	R'	: <code>\@tempb</code>	A	: <code>\adl@vlrowL</code>
Γ	: <code>\adl@columns</code>	γ	: <code>\adl@currentcolumn</code>				
τ	: <code>\@tempcnta</code>	β	: <code>\@tempcntb</code>	η	: <code>\adl@lastconn</code>		
δ	: <code>\adl@dash/\adl@dashcolor</code>			ξ	: <code>\adl@gap/\adl@gapcolor</code>		
H	: <code>\adl@totalheight</code>						
$conn$: <code>\ifadl@connected</code>			$double$: <code>\ifadl@doublerule</code>		

`\adl@makev1rL` The macro `\adl@makev1rL` corresponds to the line (2) and (31)–(36). Its right-edge counterpart `\adl@makev1rR` has the same correspondance but the lines (1)–(2) are;

```

(1)  $A \leftarrow \langle \rangle$ ;  $R \leftarrow R^R$ ;  $\gamma \leftarrow \Gamma$ ;
(2) while  $\gamma > 0$  do begin

```

and (31)–(36) are;

```

(31) if  $double$  then  $A \leftarrow \langle \hspace{\adl@doublerulesep}, A \rangle$ ;
(32) else begin
(33)      $\gamma \leftarrow \gamma - 1$ ;
(34)     if  $\gamma = 0$  then  $A \leftarrow \langle \hss, A \rangle$ ;
(35)     else  $A \leftarrow \langle \&\omit\hss, A \rangle$ ;
(36) end;

```

```

465
466 %% Drawing Vertical Lines
467
468 \def\adl@makev1rL{\adl@makev1r
469     \ifadl@doublerule
470         \edef\adl@vlrow{\adl@vlrow \hspace{\adl@doublerulesep}}%
471         \let\next\adl@makev1rL

```

```

(1)  $\Lambda \leftarrow \langle \rangle$ ;  $R \leftarrow R^L$ ;  $\gamma \leftarrow 1$ ;
(2) while  $\gamma \leq \Gamma$  do begin
(3)    $\tau \leftarrow H$ ;  $\beta \leftarrow H$ ;  $\eta \leftarrow 0$ ;  $\delta \leftarrow \langle -1, \perp \rangle$ ;  $\xi \leftarrow \langle -1, \perp \rangle$ ;
(4)    $conn \leftarrow \mathbf{false}$ ;  $double \leftarrow \mathbf{false}$ ;  $R' \leftarrow \langle \rangle$ 
(5)   while  $R \neq \langle \rangle$  do begin
(6)      $\langle r, R \rangle \leftarrow R$ ;
(7)      $\langle C, h \rangle \leftarrow r$ ;
(8)     if  $C = \langle \rangle$  then begin  $add(\tau, \beta, \delta, \xi)$ ;  $\eta \leftarrow 0$ ; end;
(9)     elseif  $C = \langle connect \rangle$  then  $\eta \leftarrow h$ ;
(10)    else begin
(11)       $\langle e, C' \rangle = C$ ;  $\langle c, d, g \rangle = e$ ;
(12)      if  $c = \gamma$  then begin
(13)        if  $d = \delta \wedge g = \xi$  then begin
(14)          if  $\neg conn$  then begin
(15)             $\tau \leftarrow \beta + \eta$ ;  $conn \leftarrow \mathbf{true}$ ;
(16)          end;
(17)        end;
(18)        else begin
(19)           $add(\tau, \beta, \delta, \xi)$ ;
(20)           $\delta \leftarrow d$ ;  $\xi \leftarrow g$ ;  $\tau \leftarrow \beta + \eta$ ;  $conn \leftarrow \mathbf{true}$ ;
(21)        end;
(22)        if  $C' = \langle \langle \gamma, ?, ? \rangle, ? \rangle$  then  $double \leftarrow \mathbf{true}$ ;
(23)         $C \leftarrow C'$ ;
(24)      end;
(25)      else  $add(\tau, \beta, \delta, \xi)$ ;
(26)       $\eta \leftarrow 0$ ;
(27)    end;
(28)     $\beta \leftarrow \beta - h$ ;  $R' \leftarrow \langle R', \langle C, h \rangle \rangle$ 
(29)  end;
(30)   $add(\tau, \beta, \delta, \xi)$ ;  $R \leftarrow R'$ ;
(31)  if  $double$  then  $\Lambda \leftarrow \langle \Lambda, \backslash \text{skip} \backslash \text{doublerulesep} \rangle$ ;
(32)  else begin
(33)     $\gamma \leftarrow \gamma + 1$ ;
(34)    if  $\gamma > \Gamma$  then  $\Lambda \leftarrow \langle \Lambda, \backslash \text{fil} \rangle$ ;
(35)    else  $\Lambda \leftarrow \langle \Lambda, \backslash \text{fil} \& \backslash \text{omit} \rangle$ ;
(36)  end;
(37) end;
(38)
(39) procedure  $add(\tau, \beta, \delta, \xi)$  begin
(40)   if  $conn$  then begin
(41)      $\Lambda \leftarrow \langle \Lambda, \langle \beta, \tau - \beta, \delta, \xi \rangle \rangle$ ;  $conn \leftarrow \mathbf{false}$ ;
(42)   end;
(43) end;

```

FIGURE 2 – Conceptual Code of `\adl@makev1rL`

```

472         \else
473             \advance\adl@currentcolumn\@ne
474             \ifnum\adl@currentcolumn>\adl@columns \let\next\relax
475                 \edef\adl@vrow{\adl@vrow \hss}%
476             \else \let\next\adl@makevrl
477                 \edef\adl@vrow{\adl@vrow \hss &\omit}%
478         \fi\fi\next}
479 \def\adl@makevrlR{\adl@makevrl
480     \ifadl@doublerule
481         \edef\adl@vrow{\hskip\doublerulesep \adl@vrow}%
482         \let\next\adl@makevrlR
483     \else
484         \advance\adl@currentcolumn\m@ne
485         \ifnum\adl@currentcolumn=\z@ \let\next\relax
486             \edef\adl@vrow{\hss \adl@vrow}%
487         \else \let\next\adl@makevrlR
488             \edef\adl@vrow{&\omit \hss \adl@vrow}%
489     \fi\fi\next}
490

```

`\adl@makevrl` The macro `\adl@makevrl` corresponds to the lines (3)–(4) and (30).

```

491 \def\adl@makevrl{\@tempcnta\adl@totalheight \@tempcntb\adl@totalheight
492     \let\adl@lastconn\z@ \adl@dash\m@ne \adl@gap\m@ne
493     \let\adl@dashcolor\relax \let\adl@gapcolor\relax
494     \adl@connectedfalse \adl@doublerulefalse \def\@tempb{}%
495     \expandafter\adl@imakevrl\adl@rows\@nil;%
496     \adl@addv1
497     \edef\adl@rows{\@tempb}}
498

```

`\adl@imakevrl` The macro `\adl@imakevrl $\langle r \rangle$` ; corresponds to the lines (5)–(6), and the macro `\adl@iimakevrl` `iimakevrl $\langle\langle C \rangle\rangle/\langle h \rangle$` to (7) and (28).
`\adl@endmakevrl`

```

499 \def\adl@imakevrl#1{\def\@tempa{#1}\ifx\@tempa\@nnil \let\next\relax
500     \else \adl@iimakevrl#1\let\next\adl@imakevrl \fi \next}
501 \def\adl@iimakevrl(#1/#2){\let\@elt\adl@iiimakevrl
502     \def\adl@connect{\adl@@connect#2}%
503     \let\adl@endmakevrl\adl@endmakevrlcut
504     #1\adl@endmakevrl
505     \let\@elt\relax \let\adl@connect\relax
506     \advance\@tempcntb-#2\edef\@tempb{\@tempb(\@tempc/#2);}}
507

```

`\adl@iiimakevrl` The correspondance of the lines (8)–(30) is a little bit complicated. As shown above, `\adl@iimakevrl` expands C attaching the sentinel `\adl@endmakevrl`.
`\adl@vmakevrl` 1. If $C \neq \langle \rangle$ and $C \neq \langle connect \rangle$, C has at least one `\@elt $\langle c \rangle\langle d \rangle\langle g \rangle$` which is made
`\adl@endmakevrlcut` `\let`-equal to `\adl@iiimakevrl` by `\adl@iimakevrl`. Thus the lines (10)–(21) and
`\adl@endmakevrlrconn` (25)–(26) are performed by `\adl@iiimakevrl`.
`\adl@@connect` Then;

- (a) if $c = \gamma$, `\@elt` becomes `\let-equal` to `\adl@ivmakevlr` which corresponds to (22) in the case of $C' \neq \langle \rangle$. Then `\adl@vmakevlr` is invoked for (23) and to eat the sentinel `\adl@endmakevlr`. If $C' = \langle \rangle$, `\adl@endmakevlrconn` is invoked, because the sentinel `\adl@endmakevlr` is made `\let-equal` to it by `\adl@iiimakevlr`, for (23) (i.e. $C \leftarrow \langle \rangle$).
 - (b) if $c \neq \gamma$, `\adl@vmakevlr` is invoked to perform implicit $C \leftarrow C$ operation and to eat the sentinel.
2. If $C = \langle connect \rangle$, i.e. it has only one element `\adl@connect`, the macro `\adl@@connect` is invoked with h because it is `\define-dl` to be `\adl@@connect\langle h \rangle`. The macro performs (9) and implicit $C \leftarrow C (= \langle connect \rangle)$ eating the sentinel.
 3. If $C = \langle \rangle$, `\adl@endmakevlr` cut that is `\let-equal` to the sentinel `\adl@endmakevlr` is invoked to perform (8) and implicit $C \leftarrow C (= \langle \rangle)$.

```

508 \def\adl@iiimakevlr#1#2#3#4#5{\let\@elt\adl@ivmakevlr \let\next\relax
509     \ifnum#1=\adl@currentcolumn\relax
510         \let\adl@endmakevlr\adl@endmakevlrconn
511         \@tempswafalse
512         \ifnum#2=\adl@dash\relax
513         \ifnum#3=\adl@gap\relax
514         \def\@tempa{#4}\ifx\@tempa\adl@dashcolor
515         \def\@tempa{#5}\ifx\@tempa\adl@gapcolor
516             \@tempwatrue
517         \fi\fi\fi\fi
518         \if@tempswa
519             \ifadl@connected\else
520                 \@tempcnta\@tempcntb
521                 \advance\@tempcnta\adl@lastconn\relax
522                 \adl@connectedtrue
523             \fi
524         \else
525             \adl@addv1
526             \adl@dash#2\relax \adl@gap#3\relax
527             \def\adl@dashcolor{#4}\def\adl@gapcolor{#5}%
528             \@tempcnta\@tempcntb
529             \advance\@tempcnta\adl@lastconn\relax
530             \adl@connectedtrue
531         \fi
532     \else
533         \adl@addv1
534         \def\next{\adl@vmakevlr\@elt{#1}{#2}{#3}{#4}{#5}}%
535     \fi
536     \let\adl@lastconn\z@ \next}
537 \def\adl@ivmakevlr#1{%
538     \ifnum#1=\adl@currentcolumn \adl@doubleruletrue \fi
539     \adl@vmakevlr\@elt{#1}}
540 \def\adl@vmakevlr#1\adl@endmakevlr{\def\@tempc{#1}}
541 \def\adl@endmakevlr\cut{\adl@addv1 \let\adl@lastconn\z@ \def\@tempc{}}
542 \def\adl@endmakevlrconn{\def\@tempc{}}

```



```

543 \def\adl@connect#1\adl@endmakev1r{\def\adl@lastconn{#1}%
544     \def\@tempc{\adl@connect}}
545

```

\adl@addv1L The macro \adl@addv1L corresponds to the lines (38)–(42), i.e. the procedure *add*. The
\adl@addv1R macro \adl@addv1R performs similar operations, but its conceptual code is the following.

```

(38) procedure add( $\tau, \beta, \delta, \xi$ ) begin
(39)     if conn then begin
(40)          $\Lambda \leftarrow \langle \langle \beta, \tau - \beta, \delta, \xi \rangle, \Lambda \rangle$ ; conn  $\leftarrow$  false;
(41)     end;
(42) end;

```

```

546 \def\adl@addv1L{\ifadl@connected
547     \advance\@tempcnta-\@tempcntb
548     \edef\adl@v1row{\adl@v1row
549         \adl@v1{\number\@tempcntb}{\number\@tempcnta}%
550         {\number\adl@dash}{\number\adl@gap}%
551         {\adl@dashcolor}{\adl@gapcolor}}%
552     \adl@connectedfalse \fi}
553 \def\adl@addv1R{\ifadl@connected
554     \advance\@tempcnta-\@tempcntb
555     \edef\adl@v1row{\adl@v1{\number\@tempcntb}{\number\@tempcnta}%
556         {\number\adl@dash}{\number\adl@gap}%
557         {\adl@dashcolor}{\adl@gapcolor}\adl@v1row}%
558     \adl@connectedfalse \fi}
559

```

\adl@drawv1 After the the macros \adl@v1rowL and \adl@v1rowR are constructed, they are expanded to
\adl@v1 draw vertical lines by \adl@drawv1. Prior to the expansion, the macro \adl@drawv1 globally
\adl@v1@leftskip defines \adl@v1@leftskip and \adl@v1@rightskip, which are the amount of negative
\adl@v1@rightskip spaces inserted to the left/right of a vertical line, as follows.

$$\begin{aligned}
 \text{\adl@v1@leftskip} &= \begin{cases} \arrayrulewidth/2 & \text{if \text{\ifadl@zwrule}} \\ 0 & \text{else if leftside} \\ \arrayrulewidth & \text{otherwise} \end{cases} \\
 \text{\adl@v1@rightskip} &= \begin{cases} \arrayrulewidth/2 & \text{if \text{\ifadl@zwrule}} \\ 0 & \text{else if rightside} \\ \arrayrulewidth & \text{otherwise} \end{cases}
 \end{aligned}$$

That is, if \ADLnulwide is in effect, a vertical line is surrounded by horizontal spaces of $-\arrayrulewidth/2$ to adjust the center of the line to the left or right edge of its column. Otherwise, a horizontal space $-\arrayrulewidth$ is inserted after (before) the line is drawn to adjust its left (right) edge to the left (right) edge of the column¹⁷.

Then the macros \adl@v1rowL and \adl@v1rowR are expanded. These macros will have \adl@v1, which is made \let-equal to \adl@v1 prior to the expansion, to draw a vertical

17. Before v1.54, the horizontal spaces was not inserted if \ADLsomewide and thus disconnected lines were not aligned vertically.

line. The macro `\adl@v1< β >< λ >< δ_l >< γ_l >< δ_c >< γ_c >` (x_l and x_c are length and color) draws a solid line if $\gamma_l = 0$ or a dash-line otherwise in a `\vbox` of $\lambda = \tau - \beta$ high and `\raise`-s it by β . The method to draw a dash line in the `\vbox` is analogous to that for horizontal line shown in §4.9, except that a line is surrounded by horizontal spaces of `\adl@v1@leftskip` and `\adl@v1@rightskip`. Coloring gaps is done by drawing a vertical rule setting γ_c by `\set@color` prior to dash line drawing if γ_c is not `\relax`. To color dashes or solid line, `\set@color` with δ_c is done if it is not `\relax` before line drawing.

```

560 \def\adl@drawv1{%
561     \omit \relax \ifadl@zwvrule
562         \gdef\adl@v1@leftskip{.5\arrayrulewidth}%
563         \global\let\adl@v1@rightskip\adl@v1@leftskip
564     \else \global\let\adl@v1@leftskip\z@
565         \global\let\adl@v1@rightskip\arrayrulewidth
566     \fi \adl@v1rowL \cr
567 \omit \relax \ifadl@zwvrule
568     \gdef\adl@v1@leftskip{.5\arrayrulewidth}%
569     \global\let\adl@v1@rightskip\adl@v1@leftskip
570 \else \global\let\adl@v1@leftskip\arrayrulewidth
571     \global\let\adl@v1@rightskip\z@
572 \fi \adl@v1rowR \cr}
573
574 \def\adl@v1#1#2#3#4#5#6{\vbox to\z@{\vss\hbox{%
575     \hskip-\adl@v1@leftskip
576     \ifnum#3=\z@\else \def\@tempa{#6}\ifx\@tempa\adl@nocolor\else
577         \raise#1sp\hbox{\let\current@color\@tempa \set@color
578             \vrule height#2sp width\arrayrulewidth}%
579     \hskip-\arrayrulewidth \fi \fi
580     \raise#1sp\vbox to#2sp{
581         \def\@tempa{#5}\ifx\@tempa\adl@nocolor\else
582             \let\current@color\@tempa \set@color \fi
583         \ifnum#3=\z@
584             \hrule height#2sp depth\z@ width\arrayrulewidth
585         \else \@tempdima#3sp \@tempdimb#4sp
586             \adl@draw\adl@hrule\vskip\vbox
587         \fi}%
588     \hskip-\adl@v1@rightskip}}
589
590 %%~L

```

4.12 Drawing Dash-lines

`\adl@vrule` As explained later, horizontal and vertical lines are drawn by a common macro `\adl@draw` to which the length of a dash segment, d , is passed through `\@tempdima`. The macro also has an argument that is either `\adl@vrule` to draw a dash for *horizontal* lines or `\adl@hrule` for *vertical*. These two macros commonly have one argument $\langle f \rangle$ to draw a dash of $f \times d$ long and of `\arrayrulewidth` wide.

591

```

592 %% Draw Dash Lines (\adl@vrule/\adl@hrule, \hskip/\vskip, \hbox/\vbox)
593
594 \def\adl@vrule#1{\vrule\@width#1\@tempdima\@height\arrayrulewidth\relax}
595 \def\adl@hrule#1{\hrule\@height#1\@tempdima\@width\arrayrulewidth\relax}

```

`\adl@drawi` The macro `\adl@draw` is to draw a horizontal or vertical line. It is `\let`-equal to one of `\adl@drawi`, `\adl@drawii` and `\adl@drawiii` according to the drawing mode specified by `\ADLdrawingmode`. These three macros have common interface, `\@tempdima` and `\@tempdimb` for the length of dash and gap, d and g , and three arguments $\langle rule \rangle$, $\langle skip \rangle$ and $\langle box \rangle$ with which `\adl@draw` is called in the following manner.

```

\adl@draw\adl@vrule\hskip\hbox ... horizontal
\adl@draw\adl@hrule\vskip\vbox ... vertical

```

The drawing methods in three modes have been explained in §4.2. More specifically, `\adl@drawi` for mode 1, to which `\adl@draw` is `\let`-equal by default, conceptually performs the following operations.

```

\rule{1/2} \skip{g/2}
\leaders\box{1}\skip{g/2} \rule{1} \skip{g/2}
\skip{0 plus 1fil minus 1fil}
\skip{g/2} \rule{1/2}

```

The conceptual operations of `\adl@drawii` for mode 2 are as follows.

```

\rule{1/2} \skip{g/2}
\box{1}\skip{g/2} \rule{1} \skip{g/2} \skip{-d-g}
\leaders\box{1}\skip{g/2} \rule{1} \skip{g/2}
\skip{0 plus 1fil minus 1fil}
\skip{-d-g} \box{1}\skip{g/2} \rule{1} \skip{g/2}
\skip{g/2} \rule{1/2}

```

The macro `\adl@drawiii` for mode 3 is quite similar to `\adl@drawi` except that `\xleaders` is replaced by `\cleaders`. This replacement is done by temporarily `\let`-ing `\xleaders` be equal to `\cleaders`.

```

596 \def\adl@drawi#1#2#3{%
597     #1{.5}#2.5\@tempdimb
598     \xleaders#3{#2.5\@tempdimb #1{1}#2.5\@tempdimb}%
599     #2\z@ plus1fil minus1fil\relax
600     #2.5\@tempdimb #1{.5}}
601 \def\adl@drawii#1#2#3{%
602     \setbox\adl@box#3{#2.5\@tempdimb #1{1}#2.5\@tempdimb}%
603     #1{.5}#2.5\@tempdimb
604     \copy\adl@box #2-\@tempdima #2-\@tempdimb
605     \xleaders\copy\adl@box#2\z@ plus1fil minus1fil\relax
606     #2-\@tempdima #2-\@tempdimb \copy\adl@box
607     #2.5\@tempdimb #1{.5}}
608 \def\adl@drawiii#1#2#3{{\let\xleaders\cleaders \adl@drawi#1#2#3}}
609 \let\adl@draw\adl@drawi
610

```

`\ADLdrawingmode` The macro `\ADLdrawingmode{⟨m⟩}` defines the drawing mode by `\let`-ing `\adl@draw` be equal to `\adl@drawi` if $m = 1$, and so on. If $\langle m \rangle$ is neither 1, 2 nor 3, it is assumed as 1.

```
611 \def\ADLdrawingmode#1{\ifcase #1%
612     \let\adl@draw\adl@drawi \or
613     \let\adl@draw\adl@drawi \or
614     \let\adl@draw\adl@drawii \or
615     \let\adl@draw\adl@drawiii \else
616     \let\adl@draw\adl@drawi \fi}
617
618 %%~L
```

4.13 Shorthand Activation

`\adl@Array` The macros `\adl@Array`, `\adl@Tabular`, `\adl@Tabular*` and `\adl@Longtable` start environments `array`, `tabular`, `tabular*` and `longtable` respectively, turning `\ifadl@`
`\adl@Tabular` `inactive` false to activate dash-line functions. We will `\let` macros `\Array` etc. be equal
`\adl@Tabularstar` to them for shorthand activation.
`\adl@Longtable`

```
619
620 %% Shorthand Activation
621
622 \def\adl@Array{\adl@inactivefalse \array}
623 \def\adl@Tabular{\adl@inactivefalse \tabular}
624 \def\adl@Tabularstar{\adl@inactivefalse \@nameuse{tabular*}}
625 \def\adl@Longtable{\adl@inactivefalse \longtable}
626
```

`\@notdefinable` Before making `\Array` etc. `\let`-equal to `\adl@Array` etc., we have to check if these macros
`\adl@notdefinable` having too natural names have already used. This check is done by `\@ifdefinable` that will call `\@notdefinable` for the complaint if undefinable. Since we want to complain with our own warning message, `\@notdefinable` is temporarily `\def`-ined so that it simply `\def`-ines a macro `\adl@notdefinable` as empty. Therefore, `\adl@notdefinebale` will have some definition if one of `\Array`, `\Tabular`, `\Tabular*` and `\Longtable` (if `longtable` is loaded) cannot be defined, while it will stay undefined otherwise.

```
627 \begingroup
628 \def\@notdefinable{\gdef\adl@notdefinable{}}
629 \@ifdefinable\Array\relax
630 \@ifdefinable\Tabular\relax
631 \expandafter\@ifdefinable\csname Tabular*\endcsname\relax
632 \ifx\longtable\undefined\else \@ifdefinable\Longtable\relax \fi
633 \endgroup
634
```

`\Array` If `\adl@notdefinable` is `\undefined` indicating that all `\Array` etc. are definable, we `\let`
`\Tabular` them be equal to `\adl@Array` etc. We also `\let` ending macros `\endArray` etc. be equal to
`\Tabular*` `\endarray` etc. Note that `\Longtable` and `\endLongtable` are defined only when `longtable`
`\Longtable` is loaded, and `\endLongtable` is `\def`-ined as (not being `\let`-equal to) `\endlongtable`
`\endArray` because its definition of our own is not given yet.
`\endTabular`
`\endTabular*`
`\endLongtable`

Otherwise, we complain with a warning message put by `\PackageWarning` if it is defined (i.e. $\text{\LaTeX 2}_\varepsilon$) or `\@warning` otherwise (i.e. \LaTeX-2.09).

```

635 \ifx\adl@notdefinable\undefined
636     \let\Array\adl@Array
637     \let\Tabular\adl@Tabular
638     \expandafter\let\csname Tabular*\endcsname\adl@Tabularstar
639     \let\endArray\endarray
640     \let\endTabular\endtabular
641     \expandafter\let\csname endTabular*\endcsname\endtabular
642     \ifx\longtable\undefined\else
643         \let\Longtable\adl@Longtable
644         \def\endLongtable{\endlongtable}
645     \fi
646 \else
647 \begingroup
648 \ifx\longtable\undefined
649 \def\@tempa{Array and Tabular are not defined because one of them\MessageBreak
650     has been defined}
651 \else
652 \def\@tempa{Array/Tabular/Longtable are not defined because \MessageBreak
653     one of them has been defined}
654 \fi
655 \ifx\PackageWarning\undefined
656     \def\MessageBreak{^^J}
657     \@warning\@tempa
658 \else
659     \let\on@line\empty
660     \PackageWarning{arydshln}\@tempa
661 \fi
662 \endgroup
663 \fi
664

```

`\ADLnoshorthanded` If a user wishes to define an environment named `Array` or `Tabular(*)` (or `Longtable` if `longtable` is in use) by him/herself or by loading other packages *after* `arydshln` is loaded, `\newenvironment` for `Array` etc. will fail because they have already been undefinable. The macro `\ADLnoshorthanded` makes them definable again by `\let`-ing them and their ending counterparts be equal to `\relax`.

```

665 \def\ADLnoshorthanded{%
666     \let\Array\relax
667     \let\Tabular\relax
668     \expandafter\let\csname Tabular*\endcsname\relax
669     \let\endArray\relax
670     \let\endTabular\relax
671     \expandafter\let\csname endTabular*\endcsname\relax
672     \ifx\longtable\undefined\else
673         \let\Longtable\relax
674         \let\endLongtable\relax \fi}

```

```

\adl@act@arrayclassz  Finally here we define active version of \@arrayclassz named \adl@act@arrayclassz
\adl@act@tabclassz    etc. for \adl@activate (see §4.4). The definitions are simply done by \let-ing \adl@act@
\adl@act@classz       arrayclassz equal to \@arrayclassz etc18.
\adl@act@@startpbox
\adl@act@@endpbox     676 \let\adl@act@arrayclassz\@arrayclassz
\adl@act@@endpbox     677 \let\adl@act@tabclassz\@tabclassz
\adl@act@@endpbox     678 \ifadl@usingarypkg \let\adl@act@classz\@classz \fi
\adl@act@cr           679 \let\adl@act@@startpbox\@@startpbox
\adl@act@argcr        680 \let\adl@act@@endpbox\@@endpbox
\adl@act@ccline       681 \let\adl@act@endpbox\@endpbox
\adl@act@endarray     682 \let\adl@act@cr\adl@cr
\adl@act@hline        683 \let\adl@act@argcr\adl@argcr
\adl@act@ihdashline   684 \let\adl@act@endarray\adl@endarray
\adl@act@cdline       685 \let\adl@act@hline\adl@hline
\adl@act@@vlineL      686 \let\adl@act@ihdashline\adl@ihdashline
\adl@act@@vlineR      687 \let\adl@act@cdline\adl@cdline
                     688 \let\adl@act@@vlineL\adl@@vlineL
                     689 \let\adl@act@@vlineR\adl@@vlineR
                     690
                     691 %%~L

```

4.14 Compatibility with colortab

```

\adl@CC@  The package colortab has a macro ;
\CC@      \LCC{colorspec}\{<rows>\ECC

```

to color $\langle rows \rangle$ referring $\langle colorspec \rangle$. The macro $\backslash CC@$, the heart of the coloring function, first makes a box with $\langle rows \rangle$ using $\backslash @preamble$ to measure the height of $\langle rows \rangle$, then makes a row putting a heavy rule of the height in each column with a color command for the column specified by $\langle colorspec \rangle$, and finally puts $\langle rows \rangle$ overlaying them on the colored rule. Therefore $\langle rows \rangle$ is processed twice by $\backslash CC@$ to update $\backslash global$ registers/structures incorrectly.

Thus we modify $\backslash CC@$, if the package `colortab` is provided, to save $\backslash global$ stuff by $\backslash adl@arraysave$ before the height measurement and restore them by $\backslash adl@arrayrestore$ after that.

```

692
693 %% Compatibility with colortab
694
695 \def\adl@CC@#1#2#3{%
696   \ifcolortab
697     \noalign{%
698       \adl@arraysave
699       \setbox\CT@box=\vbox{#1#3\crrc\egroup}%

```

18. Alternatively, we may define $\backslash adl@act@arrayclassz$ in place of $\backslash @arrayclassz$ but the author chose this way to minimize the possibility of *enbug*.

```

700      \adl@arrayrestore
701      \CT@dim=\ht\CT@box
702      \global\advance\CT@dim by \dp\CT@box
703      \def\CT@next{ }%
704      \futurelet\next\CT@columncolor#2&\@nil}%
705      \CT@next\cr
706      \noalign{\vskip-\CT@dim}%
707      \fi
708      #3}
709 \ifx\ColortabLoaded\undefined\else
710 \let\CC@\adl@CC@
711 \fi
712
713 %%^L

```

4.15 Compatibility with longtable

Making `arydshln` compatible with `longtable` is a hard job because a `longtable` consists of multiple *chunks* and each chunk is a distinct `\halign`. We could draw vertical lines in each chunk as we do with ordinary `array/table`. However this straightforward solution should *break* dash-lines at invisible borders of chunks and produce awful results.

Therefore, this implementation draws dash-lines in `\output` routine in which we have all the rows to be put in a page. The hard part is to know which rows are being put in `\output`. This problem is solved by extracting the leading part of R^L (`\adl@rowsL`) and R^R (`\adl@rowsR`) by the height/depth of the table fraction to be put and removing the part from $R^{L/R}$.

4.15.1 Initialization

First of all, the following switch and `\dimen` register are declared.

- `\ifadl@LTfirstpage` — `\ifadl@LTfirstpage` is tested in `\output` routine to examine if the page being put has the first fraction of a `longtable`.
- `\adl@LTpagetotal` — `\adl@LTpagetotal` is set to `\pagetotal` just before the first portion of a `longtable` is added to the main vertical list. Since the `\box255` has items preceding the `\longtable` and its first fraction, we can obtain the height of the first fraction by subtracting `\adl@LTpagetotal` from the height plus depth of `\box255`.

```

714
715 %% Compatibility with longtable: initialization
716
717 \newif\ifadl@LTfirstpage
718 \newdimen\adl@LTpagetotal
719

```

Next, we skip everything if `longtable` is not in use, or we have undefined-error when we refer to the definitions in it. Note that since `\newif` cannot be in the `\ifx/\fi` construct, the declarations above are excluded.

```

720 \ifx\longtable\undefined\else
721

```

`\adl@LT@array` Then we redefine the macro `\LT@array`, which is the heart of `\longtable`, saving its original definition in `\adl@LT@array`. The modified `\LT@array` first calls `\adl@arrayinit` to initialize the global data structures, and sets `\ifadl@LTfirstpage` to true. Then `\adl@dashline`, `\adl@idashline` and `\adl@discard` are made `\let`-equal to the `longtable` versions `\adl@LTdashline` and `\adl@LTidashline`, and `\relax` (to inhibit expansion) respectively. Then the macro calls `\adl@LTinactivate` if `\adl@inactive` is true, and finally calls its original version `\adl@LT@array`. Note that since `longtable` cannot be nested;

- `\adl@arraysave` in `\adl@arrayinit` is unnecessary but safe, and thus its invocation timing is not so sensitive; and
- activator is not required.

Also note that the assignment `\adl@ncol` to `\adl@columns` in `\adl@arrayinit` is void and thus we will do it afterward.

`\adl@LTinactivate` The macro `\adl@LTinactivate` first calls `\adl@inactivate` to do basic inactivation and then `\let`-s the following control sequences be equal to their counterparts in `longtable`.

```
\endlongtable \LT@make@row \LT@echunk \LT@end@hd@ft \LT@kill
\LT@output
```

It also make `\adl@idashline` `\let`-equal to its inactive version because we need the macro to find mixed `\hline` and `\hdasline` sequence.

```
722 \let\adl@LT@array\LT@array
723 \def\LT@array{\adl@arrayinit \adl@LTfirstpagetrue
724     \let\adl@discard\relax \let\adl@hdashline\adl@LTdashline
725     \let\adl@ihdashline\adl@LTidashline
726     \ifadl@inactive \adl@LTinactivate \fi
727     \adl@LT@array}
728 \def\adl@LTinactivate{\adl@inactivate
729     \let\endlongtable\adl@org@endlongtable
730     \let\LT@make@row\adl@org@LT@make@row
731     \let\LT@echunk\adl@org@LT@echunk
732     \let\LT@end@hd@ft\adl@org@LT@end@hd@ft
733     \let\LT@kill\adl@org@LT@kill
734     \let\LT@output\adl@org@LT@output
735     \let\adl@ihdashline\adl@LTinactivehdl}
736
```

`\adl@org@LT@make@row` The macro `\LT@make@row` is redefined for additional initialization which must be done after the original `\LT@array` performs its own initialization. First, `\LT@make@row` itself is reset to its original version `\adl@org@LT@make@row` to initialize stuff only once, since `\LT@make@row` is called repeatedly at each chunk. Next `\adl@ncol` is assigned to `\adl@columns` to give its value calculated in `\@mkpream`. Then macros to begin/end p-boxes are made `\let`-equal to our own version because the original `\LT@array` has done it with its own version. Note that `\@startpbox` and `\@statpbox` are `\let`-equal to our own `\adl@LTstartpbox` if array is not in use because with array opening a p-box is not done by `\@startpbox` but is embedded in `\@preamble`. Also note that we need `\adl@LTendmbox` to close m-boxes through our own closing macro `\adl@endmbox`, whose definition is kept in `\adl@endmbox`, for `longtable`-specific operations for footnotes. Finally, the original version `\adl@org@LT@make@row` is called.

TABLE 2 – Active and Inactive longtable Operations

command	active	inactive
p b (open) with array	<code>\adl@act@classz</code> \rightarrow <code>\LT@startpbox</code>	<code>\adl@org@classz</code> \rightarrow <code>\LT@startpbox</code>
without array	<code>\adl@LT@startpbox</code>	<code>\LT@startpbox</code>
m (open)	<code>\adl@act@classz</code> \rightarrow <code>\adl@startmbox</code> \rightarrow <code>\LT@startpbox</code>	<code>\adl@org@classz</code> \rightarrow <code>\LT@startpbox</code>
p b (close)	<code>\adl@LT@endpbox</code>	<code>\LT@endpbox</code>
m (close)	<code>\adl@LT@endmbox</code>	<code>\LT@endpbox</code>
<code>\hline</code>	\rightarrow <code>\adl@act@hline</code>	\rightarrow <code>\@gobbletwo</code>
<code>\hdashline</code>	\rightarrow <code>\adl@LT@hdashline</code> \rightarrow <code>\adl@act@hline</code>	\rightarrow <code>\adl@LT@inactivehdl</code> \rightarrow <code>\@gobbletwo</code>
<code>\endlongtable</code> <code>\LT@make@row</code> <code>\LT@echunk</code> <code>\LT@end@hd@ft</code> <code>\LT@kill</code> <code>\LT@output</code>	modified version	<code>\adl@org@endlongtable</code> <code>\adl@org@LT@make@row</code> <code>\adl@org@LT@echunk</code> <code>\adl@org@LT@end@hd@ft</code> <code>\adl@org@LT@kill</code> <code>\adl@org@LT@output</code>

```

737 \let\adl@org@LT@make@row\LT@make@row
738 \def\LT@make@row{\let\LT@make@row\adl@org@LT@make@row
739     \adl@columns\adl@ncol
740     \ifadl@usingarypkg\else
741         \let\@startpbox\adl@LT@startpbox
742         \let\@startpbox\adl@LT@startpbox \fi
743     \let\@endpbox\adl@LT@endpbox
744     \let\@endpbox\adl@LT@endpbox
745     \let\adl@LT@endmbox\adl@endmbox
746     \let\adl@endmbox\adl@LT@endmbox
747     \adl@org@LT@make@row}
748
749 %%~L

```

The summary of the activation and inactivation specific to `longtable` is shown in Table 2.

4.15.2 Ending Chunks

`\adl@org@endlongtable` When a chunk is closed with `\crrc`, we have to add the information of the last row to $R^{L/R} = \text{\adl@rowsL/R}$ if the row is not finished by an explicit `\\`. This is done by `\adl@org@LT@echunk` `\adl@LT@lastrow` as we did at the first job of `\adl@endarray`. Two chunk closing macros, `\endlongtable` and `\LT@echunk`, are modified to call `\adl@LT@lastrow` before its original job done by `\adl@org@endlongtable` and `\adl@org@LT@echunk` respectively. Note that `\adl@LT@lastrow` only has `\crrc` and `\noalign` and thus another `\crrc` in original

`\endlongtable` and `\LT@echunk` is no-operation as desired. Also note that `\adl@LTlastrow` is called twice from `\endlongtable`, once from `\LT@echunk` in the original version, but it is safe because the first call makes `\adl@height` and `\adl@depth` zero and thus the second become no-operation.

```

750
751 %% Compatibility with longtable: end chunk
752
753 \let\adl@org@endlongtable\endlongtable
754 \def\endlongtable{\adl@LTlastrow \adl@org@endlongtable}
755
756 \let\adl@org@LT@echunk\LT@echunk
757 \def\LT@echunk{\adl@LTlastrow \adl@org@LT@echunk}
758
759 \def\adl@LTlastrow{\crrc \noalign{
760     \ifdim\adl@height=\z@
761     \ifdim\adl@depth=\z@ \else \adl@cr\z@ \fi
762     \else \adl@cr\z@ \fi}}
763

```

<pre> \adl@org@LT@end@hd@ft \LT@end@hd@ft \adl@LTthsave \adl@LTth \\adl@LTth\LT@firsthead \\adl@LTth\LT@head \\adl@LTth\LT@lastfoot \\adl@LTth\LT@foot \\adl@rowsL\LT@firsthead \\adl@rowsL\LT@head \\adl@rowsL\LT@lastfoot \\adl@rowsL\LT@foot \\adl@rowsR\LT@firsthead \\adl@rowsR\LT@head \\adl@rowsR\LT@lastfoot \\adl@rowsR\LT@foot </pre>	<p>Another chunk ending macro is <code>\LT@end@hd@ft<box></code> to close a header/footer called by <code>\endfirsthead</code>, <code>\endhead</code>, <code>\endlastfoot</code> and <code>\endfoot</code> with an argument <code><box></code> being <code>\LT@firsthead</code>, <code>\LT@head</code>, <code>\LT@lastfoot</code> and <code>\LT@foot</code> respectively. In order to maintain the information of rows $R^{L/R} = \text{\adl@rowsL/R}$ of headers/footers separately from the main one, the modified <code>\LT@end@hd@ft</code> saves them together with <code>\adl@totalheight</code> to weirdly named macros;</p> <pre> \\adl@LTth<box> \\adl@rowsL<box> \\adl@rowsR<box> </pre> <p>after closing the last row by <code>\adl@LTlastrow</code>. The <code>\string</code> representation of the macros looks like;</p> <pre> \\adl@LTth\LT@firsthead </pre> <p>and so on. The saving operation is done by the macro <code>\adl@LTthsave<box><info></code> and is equivalent to;</p> <pre> \global\let\<info><box>=<info> </pre>
---	--

After the saving, three global variables are reinitialized. Calling `\adl@LTlastrow` twice, once from the original version through `\LT@echunk` is safe as described above.

```

764 \let\adl@org@LT@end@hd@ft\LT@end@hd@ft
765 \def\LT@end@hd@ft#1{\adl@LTlastrow
766     \noalign{\edef\adl@LTth{\number\adl@totalheight}%
767         \adl@LTthsave#1\adl@LTth \global\adl@totalheight\z@
768         \adl@LTthsave#1\adl@rowsL\gdef\adl@rowsL{}}%
769         \adl@LTthsave#1\adl@rowsR\gdef\adl@rowsR{}}
770     \adl@org@LT@end@hd@ft#1}
771 \def\adl@LTthsave#1#2{\expandafter\global\expandafter\let
772     \csname\string#2\string#1\endcsname#2}
773

```

`\adl@org@LT@kill` The additional job for yet another chunk closer `\LT@kill` to kill a template row is a little bit harder. Since the row information might have been added by an explicit `\\` preceding `\LT@kill`, we have to remove it from the tail of `\adl@rowsL/R`, and subtract its h_i from `\adl@totalheight` because `\kill`-ed row may be in header/footer definition. To do that, modified `\LT@kill` first ensures the information addition by `\adl@LTlastrow`, then traverses `\adl@rowsL/R` adding its non-last elements to `\@tempb` by the loop of `\adl@LTkill`, and assigns `\@tempb` to `\adl@rowsL/R` globally by `\adl@LTkillend` when `\adl@LTkill` finds the tail. The macro `\adl@LTkillend` also sets the h_i of the last element to `\@tempcnta`, which is subtracted from `\adl@totalheight` globally. Finally, the original version `\adl@org@LT@kill` is called.

```

774 \let\adl@org@LT@kill\LT@kill
775 \def\LT@kill{\adl@LTlastrow \noalign{
776     \def\@tempb{}\expandafter\adl@LTkill\adl@rowsL\@nil\adl@rowsL
777     \def\@tempb{}\expandafter\adl@LTkill\adl@rowsR\@nil\adl@rowsR
778     \global\advance\adl@totalheight-\@tempcnta}%
779     \adl@org@LT@kill}
780 \def\adl@LTkill#1;#2{\def\@tempa{#2}%
781     \ifx\@tempa\@nnil\def\next{\adl@LTkillend#1}%
782     \else\edef\@tempb{\@tempb#1;}\def\next{\adl@LTkill#2}\fi
783     \next}
784 \def\adl@LTkillend(#1/#2)#3{\global\let#3\@tempb \@tempcnta#2\relax}
785
786 %%~L

```

4.15.3 Horizontal Lines and p-Boxes

`\LT@hline` The macro `\LT@hline`, longtable version of `\hline`, is redefined to add pseudo row information to $R^{L/R}$ and to check mixed sequence of `\hline` and `\hdashline`¹⁹. We also define the macro `\adl@LTihdashline`[*dash*]/[*gap*] and its inactive counterpart `\adl@LTinactivehdl` as the longtable version of `\adl@ihdashline` and `\adl@inactivehdl`. These two macros, the main part of `\hdashline`, are redefined to make it possible that `\hdashline` can be broken into two part by TeX's page breaker.

These three macros call a common routine `\adl@LTthdline` after defining `\adl@LThdlrow` which makes a row of horizontal (dash) line drawn by `\multispan` and `\leaders\hrule` or `\adl@hcline`[*dash*]/[*gap*].

Note that we define `\adl@LTthdline` to make `\adl@hdashline` `\let`-equal to it in longtable environments because its version without longtable performs a part of the job done by `\adl@LTthdline` as shown soon.

```

787
788 %% Compatibility with longtable: horizontal lines and p-boxes
789
790 \def\LT@hline{\noalign{\ifnum0='}\fi
791     \gdef\adl@LThdlrow{\multispan{\LT@cols}\unskip
792     \leaders\hrule\@height\arrayrulewidth\hfill\cr}%

```

¹⁹. In the original longtable, a sequence of three `\hline`-s are not recognized. This buggy feature is fixed in this implementation.

```

793      \adl@LThdline}
794 \def\adl@LThdashline#1{\noalign{\ifnum0='}\fi
795      \@ifnextchar[%]
796          {#1}%
797          {#1[\dashlinedash/\dashlinegap]}}
798 \def\adl@LTihdashline[#1/#2]{%
799      \gdef\adl@LThdlrow{\multispan{\LT@cols}\unskip
800          \adl@hcline\z@[#1/#2]}%
801      \adl@LThdline}
802 \def\adl@LTinactivehdl[#1/#2]{%
803      \gdef\adl@LThdlrow{\multispan{\LT@cols}\unskip
804          \leaders\hrule\@height\arrayrulewidth\hfill\cr}%
805      \adl@LThdline}
806

```

`\adl@LThdline` The macro `\adl@LThdline` called by above three macros first inserts a vertical penalty 10000 to inhibit page break between the horizontal line and preceding row. Then it inserts `\adl@LTxhline` `\vskip-\arrayrulewidth` with another break inhibitor if `\ADLnullwidehline` is in effect, or adds the pseudo row information `connect(\arrayrulewidth)` to $R^{L/R}$ by `\adl@hline`²⁰. Next, it draw a horizontal (dash) line by `\adl@LThdlrow` and checks if the following control sequence is `\hline` or `\hdashline` by `\futurelet` and `\adl@LTxhline`. If `\hline` or `\hdashline` is the next token, `\adl@LTixhline` is called to insert a vertical penalty of `-\@medpenalty` and a vertical space of `\doublerulesep`. The macro `\adl@LTixhline` also adds `disconnect(\doublerulesep)` to $R^{L/R}$ and makes `\adl@LThdlrow` void. Otherwise, `\adl@LThdline` inserts a vertical penalty of `-\@lowpanalty` and a vertical space of `-\arrayrulewidth` and draws the horizontal (dash) line again by `\adl@LThdlrow`. Thus a page can be broken between two overlaid horizontal (dash) lines²¹. Two pseudo row information, `discard(-\arrayrulewidth)` for the negative vertical space which may be discarded and `connect(\arrayrulewidth)` for the second horizontal line, are also added to $R^{L/R}$.

```

807 \def\adl@LThdline{\penalty\@M
808      \ifadl@zwhrule \vskip-\arrayrulewidth \penalty\@M
809      \else          \adl@hline\adl@connect\arrayrulewidth \fi
810      \ifnum0='{ \fi}%
811      \adl@LThdlrow
812      \noalign{\ifnum0='}\fi
813      \futurelet\@tempa\adl@LTxhline}
814 \def\adl@LTxhline{\ifx\@tempa\hline \adl@LTixhline
815      \else\ifx\@tempa\hdashline \adl@LTixhline
816      \else \penalty-\@lowpanalty \vskip-\arrayrulewidth
817          \adl@hline\adl@discard{-\arrayrulewidth}%
818          \adl@hline\adl@connect\arrayrulewidth
819      \fi\fi \ifnum0='{ \fi}%
820      \adl@LThdlrow \noalign{\penalty\@M}}
821 \def\adl@LTixhline{\penalty-\@medpenalty \vskip\doublerulesep
822      \adl@hline\relax\doublerulesep \global\let\adl@LThdlrow\@empty}

```

20. Or do noting if inactive and thus it is `\let-equal` to `\gobbletwo`.

21. If the page is broken, the horizontal line at the beginning of the succeeding page has a width even if `\ADLnullwidehline` is in effect.

`\adl@LTstartpbox` Macros for opening/closing p-boxes are fairly simple. The macro `\adl@LTstartpbox{⟨w⟩}` is `\let`-assigned to `\@@startpbox` by `\LT@make@row` to open a p-box of w wide by our own `\adl@act@@startpbox` and performs a footnote related operation introduced by `longtable`, when `array` is not in use. Note that if `array` is in use, a p-box is opened by codes embedded in `\@preamble` and its initialization is done by `\@startpbox = \LT@startpbox`, unnecessitating our own version of opening macros.

On the other hand, the closing macro `\adl@LTendpbox` for p(or d)-boxes is `\let`-equal to `\@endpbox` and `\@@endpbox` for the cases with/without `array`, and performs the footnote operations after doing our own ones by `\adl@act@@endpbox`. Similarly, `\adl@LTendmbox` for m-boxes is `\let`-equal to `\adl@endmbox` and performs our own operations by `\adl@endmbox` in which the original definition of `\adl@enmbox` is kept.

```

824 \def\adl@LTstartpbox#1{%
825     \adl@act@@startpbox{#1}\let\@footnotetext\LT@p@ftntext}
826 \def\adl@LTendpbox{\adl@act@@endpbox \the\LT@p@ftn \global\LT@p@ftn{}}
827 \def\adl@LTendmbox{\adl@endmbox \the\LT@p@ftn \global\LT@p@ftn{}}
828
829 %%~L

```

4.15.4 First Chunk

`\LT@start` The macro `\LT@start` which puts (first) head and controls the page break of the first page is modified for the followings.

- After it inserts a vertical skip `\LTpre`, `\endgraf` is performed so that the skip contributes to `\pagetotal`²².
- When the `\box2` is `\vsplit` to get first item of the first chunk, `\vbadness` is saved into `\@tempcnta`, set to 10000 to avoid unnecessary `underfull` message²³, and restored from `\@tempcnta`.
- The `\dimen` register `\adl@LTpagetotal` is set to `\pagetotal` to know the total height of the items preceding `longtable`. Since the assignment is performed after the inserted `\endgraf` and the intentional page break, it should have real total height.
- The box `\LT@firsthead` is put by `\copy` rather than `\box` because it is referred to in the `\output` routine.

This macro does not have inactive counterpart because the modification shown above is desirable (first two) or not-harmful²⁴ (last two) to the original version.

```

830
831 %% Compatibility with longtable: first chunk
832
833 \def\LT@start{%
834     \let\LT@start\endgraf
835     \endgraf \penalty\z@ \vskip\LTpre \endgraf

```

22. This modification is necessary for the original `longtable`, or it underestimates the room of the first page and leaves head and foot only.

23. This is also necessary for the original version.

24. Logically, at least.

```

836      \dimen@ \pagetotal
837      \advance \dimen@ \ht \ifvoid \LT@firsthead \LT@head \else \LT@firsthead \fi
838      \advance \dimen@ \dp \ifvoid \LT@firsthead \LT@head \else \LT@firsthead \fi
839      \advance \dimen@ \ht \LT@foot
840      \dimen@ii \vfuzz \@tempcnta \vbadness
841      \vfuzz \maxdimen \vbadness \@M
842      \setbox \tw@ \copy \z@
843      \setbox \tw@ \vsplit \tw@ to \ht \@arstrutbox
844      \setbox \tw@ \vbox {\unvbox \tw@}%
845      \vfuzz \dimen@ii \vbadness \@tempcnta
846      \advance \dimen@ \ht
847      \ifdim \ht \@arstrutbox > \ht \tw@ \@arstrutbox \else \tw@ \fi
848      \advance \dimen@ \dp
849      \ifdim \dp \@arstrutbox > \dp \tw@ \@arstrutbox \else \tw@ \fi
850      \advance \dimen@ - \pagegoal
851      \ifdim \dimen@ > \z@ \vfil \break \fi
852      \global \adl@LT@pagetotal \pagetotal
853      \global \@colroom \@colht
854      \ifvoid \LT@foot \else
855          \advance \vsize - \ht \LT@foot
856          \global \advance \@colroom - \ht \LT@foot
857          \dimen@ \pagegoal \advance \dimen@ - \ht \LT@foot \pagegoal \dimen@
858          \maxdepth \z@
859      \fi
860      \copy \ifvoid \LT@firsthead \LT@head \else \LT@firsthead \fi
861      \output {\LT@output}}
862
863 %%~L

```

4.15.5 Output Routine

`\adl@org@LT@output` The output routine is the heart of the longtable compatible implementation. The macro `\LT@output` which is set to `\output` by `\LT@start` is modified from its original (and thus inactive) version `\adl@org@LT@output` as follows.

- Three fractions of the original version to compile the final output image of the table portion into `\box255` or the main vertical list are modified to set the image into `\box255` unconditionally and to call `\adl@LTdraw<foot><tail>` which is the real heart of the compatible implementation. The argument `<foot>` is `\LT@foot` or `\LT@lastfoot` according to the portion of the longtable to be output. The argument `<tail>` is `\vss` if the last item is it which is not included in `\box255` yet, or `\@empty` otherwise. Since `\adl@LTdraw` builds final output image drawing vertical (dash) lines in `\box255`, it is put to the main vertical list if the longtable portion is the last one.
- Since the boxes `\LT@head`, `\LT@foot` and `\LT@lastfoot` are referred to in `\adl@LTdraw`, they are put by `\copy` rather than `\box`.

```

864
865 %% Compatibility with longtable: output routine
866

```

```

867 \let\adl@org@LT@output\LT@output
868 \def\LT@output{%
869     \ifnum\outputpenalty <-\@Mi
870     \ifnum\outputpenalty > -\LT@end@pen
871         \LT@err{floats and marginpars not allowed in a longtable}\@ehc
872     \else
873         \setbox\z@\vbox{\unvbox\@cclv}%
874         \ifdim \ht\LT@lastfoot>\ht\LT@foot
875             \dimen@ \pagegoal
876             \advance\dimen@-\ht\LT@lastfoot
877             \ifdim\dimen@<\ht\z@
878                 \setbox\@cclv\vbox{\unvbox\z@\copy\LT@foot}%
879                 \adl@LTdraw\LT@foot\vss
880                 \@makecol
881                 \@outputpage
882                 \setbox\z@\vbox{\copy\LT@head}%
883             \fi
884         \fi
885         \global\@colroom\@colht
886         \global\vsizel\@colht
887         \setbox\@cclv\vbox{\unvbox\z@
888             \copy\ifvoid\LT@lastfoot\LT@foot\else\LT@lastfoot\fi}%
889         \adl@LTdraw\LT@lastfoot\@empty \box\@cclv
890     \fi
891 \else
892     \setbox\@cclv\vbox{\unvbox\@cclv\copy\LT@foot}%
893     \adl@LTdraw\LT@foot\vss
894     \@makecol
895     \@outputpage
896     \global\vsizel\@colroom
897     \copy\LT@head
898 \fi}
899

```

\adl@LTdraw The macro \adl@LTdraw{foot}{tail} draws vertical (dash) lines onto the image in \box255.

\adl@LTinit First it measures the total height H (\adl@totalheight) of longtable rows in \box255

\adl@LTheadL and the total height H_b (\@tempdima) of its *body* which consists of the rows without the

\adl@LTheadR header and footer, as follows where H_{255} , H_h and H_t are the height plus depth of \box255

\adl@LTfootL and the effective header and footer of the page respectively.

\adl@LTfootR

$$\begin{aligned}
 T &= \begin{cases} \adl@LTpagetotal & \text{if } \ifadl@LTfirstpage \\ 0 & \text{otherwise} \end{cases} \\
 t &= \begin{cases} \topskip \text{ glue} & \text{if longtable is the first item of the page} \\ 0 & (\neg(\ifadl@firstpage \wedge T > 0)) \\ & \text{otherwise} \end{cases} \\
 H &= H_{255} - t - T \\
 H_b &= H - H_h - H_t
 \end{aligned}$$

The hard part is to measure t because it is not \topskip but that minus the first box of \box255. Thus we do not measure t but remove it from the box by the following tricky

way. First we copy `\box255` items into `\box0` adding a `\hrule` of 1sp high as its first item. Then `\box0` is `\vsplit` to 1sp setting `\splittopskip` to 0. Since the `\topskip` glue is the first item of `\box255` and the `\vsplit` discards it at the breakpoint, `\box0` must have all the items in `\box255` lead by 0 (`\splittopskip`) glue rather than `\topskip` glue. Thus the height of `\box0` is $H_{255} - t$.

Subtraction of H_h and H_t is done by the macro `\adl@LTinit{<hf>}<box>`, where `<hf>` is `head` or `foot` and `<box>` is one of `\LT@firsthead`, `\LT@head` and `<foot>` (`\LT@lastfoot` or `\LT@foot`). This macro also copies the contents of weirdly named structure such as `\adl@rowsL\LT@head` into `\adl@LtheadL` and so on²⁵ if `<box>` is not void. Otherwise, `\adl@LtheadL` etc. is kept to their initial value, `\@empty`.

Next, we make rows for vertical lines by `\adl@makevL/R` after extracting the leading part of $R^{L/R}$ corresponding to the *body* by the macro `\adl@LTsplit<RL/R><RL/Rh><RL/Rf>`, where $R_h^{L/R}$ and $R_f^{L/R}$ are `\adl@LtheadL` and so on. Since the macro defines `\adl@rows` given to `\adl@makevL/R` to the sequence of $R_h^{L/R}$, the extracted part of $R^{L/R}$ and $R_f^{L/R}$, the rows for vertical lines for all the rows including header and footer are build in `\adl@vrowL` and `\adl@vrowR` as in the ordinary case without `longtable`.

Then the rows are put into `\box0` by calling `\LT@bchunk` with `\adl@drawv1` (line drawing) and `\LT@save@row` (column widths adjustment), saving/restoring counters `\LT@rows` and `\c@LT@chunks` which `\LT@bchunk` globally updates. Since we refer to potentially immature `\LT@save@row` here, some weird looking vertical lines could be drawn but the result after convergence should be correct. Finally, the contents of `\box255` followed by the vertical lines in `\box0` are put back into `\box255` keeping its original depth and adding `<tail>` (`\vss` or nothing) to its end.

```

900 \def\adl@LTdraw#1#2{%
901     \@tempswatrue
902     \ifadl@LTfirstpage\ifdim\adl@LTpagetotal>\z@\@tempswafalse \fi\fi
903     \if@tempswa
904         \setbox\z@\vbox{\hrule height1sp\unvcopy\@cclv}
905         \splittopskip\z@
906         \setbox\@ne\vsplit\z@ to1sp\relax
907         \@tempdima\ht\z@
908     \else \@tempdima\ht\@cclv \fi
909     \advance\@tempdima\dp\@cclv
910     \adl@totalheight\@tempdima
911     \let\adl@LtheadL\@empty \let\adl@LtheadR\@empty
912     \let\adl@LTfootL\@empty \let\adl@LTfootR\@empty
913     \ifadl@LTfirstpage
914         \global\adl@LTfirstpagefalse
915         \advance\@tempdima-\adl@LTpagetotal
916         \adl@totalheight\@tempdima
917         \ifvoid\LT@firsthead
918             \adl@LTinit{head}\LT@head
919         \else \adl@LTinit{head}\LT@firsthead
920         \fi
921     \else \adl@LTinit{head}\LT@head \fi

```

25. Copying by `\edef` can be replaced by `\let` with many `\expandafter` but it is not comprehensible.


```

922      \ifvoid#1%
923          \adl@LTinit{foot}\LT@foot
924      \else    \adl@LTinit{foot}#1\fi
925      \let\adl@vl\relax \def\adl@discard{\adl@connect}%
926      \def\adl@vrow{\adl@currentcolumn\@ne
927          \adl@LTsplit\adl@rowsL\adl@LtheadL\adl@LTfootL
928          \let\adl@addv1\adl@addv1L
929          \adl@makev1rL \let\adl@v1rowL\adl@v1row
930      \def\adl@v1row{\adl@currentcolumn\adl@columns
931          \adl@LTsplit\adl@rowsR\adl@LtheadR\adl@LTfootR
932          \let\adl@addv1\adl@addv1R
933          \adl@makev1rR \let\adl@v1rowR\adl@v1row
934      \let\adl@v1\adl@v1
935      \@tempcnta\LT@rows
936      \LT@bchunk \adl@drawv1
937      \LT@save@row\cr \egroup \setbox\@ne\lastbox \unskip \egroup
938      \global\advance\c@LT@chunks\m@ne
939      \global\LT@rows\@tempcnta
940      \@tempdima\dp\@cclv
941      \setbox\@cclv\vbox{\unvbox\@cclv \box\z@ \vskip-\@tempdima
942          \hrule\@width\z@\@height\z@\@depth\@tempdima#2}}
943 \def\adl@LTinit#1#2{\ifvoid#2\else
944     \advance\@tempdima-\csname\string\adl@LTth\string#2\endcsname sp%
945     \expandafter\edef\csname adl@LT#1L\endcsname{%
946         \csname\string\adl@rowsL\string#2\endcsname}%
947     \expandafter\edef\csname adl@LT#1R\endcsname{%
948         \csname\string\adl@rowsR\string#2\endcsname}\fi}
949

```

`\adl@LTsplit` The macro `\adl@LTsplit` $\langle R^{L/R} \rangle \langle R_h^{L/R} \rangle \langle R_f^{L/R} \rangle$ moves leading elements in $R^{L/R}$ into R'
`\adl@LTxsplit` (`\adl@rows`) until total heights of the elements summed in h (`\@tempdimb`) reaches to H_b
`\adl@LTrowrelax` (`\@tempdima`)²⁶ by a straightforward loop with the macros `\adl@LTisplit` to fetch the
`\adl@LTrowdiscard` i -th element and `\adl@LTisplit` to get h_i . Before moving, however, we have to remove
`\adl@LTysplit` discardable item(s)²⁷ from the top of $R^{L/R}$. Since an element for a discardable item is
`\adl@LTisplit` *disconnect* (`\relax`) or *discard* (`\adl@discard`), we check the first part of the element by
`\adl@LTisplit` `\ifx`-comparison with `\adl@LTrowrelax` and `\adl@LTrowdiscard` whose bodies are `\relax`
`\adl@LTsplitend` and `\adl@discard` if the *longtable* portion does not have a header ($R_h^{L/R}$ is `\@empty`).
Otherwise, the discardable item was not discarded because the first item of the page is not
it but the header.

Note that since moving from $R^{L/R}$ to R' is done by `\edef` and `\adl@discard` is `\def`-
ined as `\adl@connect` in `\adl@LTdraw`, non-discarded *discard* transforms into *connect* in
 R' . Also note that since the remaining part of $R^{L/R}$ is `\def`-ined as the body of `\@tempb`
which is globally `\let`-assigned to $R^{L/R}$ again, `\adl@discard` survives in the new $R^{L/R}$.

```

950 \def\adl@LTsplit#1#2#3{\def\adl@rows{\@tempdimb\z@
951     \expandafter\adl@LTxsplit#1\@nil;%

```

²⁶. Although h must become H_b exactly in usual case, we stop the loop when $h \geq H_b$ to avoid accidental
overrun in unusual cases.

²⁷. Must be only one but the implementation allows two or more.

```

952         \edef\adl@rows{#2\adl@rows#3}%
953         \global\let#1\@tempb}
954 \def\adl@LTxsplitlet#1;{\def\@tempa{#1}%
955     \ifx\@tempa\@nnil \def\@tempb{}\let\next\relax
956     \else\ifx\adl@LTheadL\@empty \def\next{\adl@LTysplitlet#1}%
957     \else \def\next{\adl@LTisplitlet#1;}\fi \fi
958     \next}
959 \def\adl@LTrowrelax{\relax}
960 \def\adl@LTrowdiscard{\adl@discard}
961 \def\adl@LTysplitlet(#1/#2){\def\@tempa{#1}%
962     \ifx\@tempa\adl@LTrowrelax \let\next\adl@LTxsplitlet
963     \else\ifx\@tempa\adl@LTrowdiscard \let\next\adl@LTxsplitlet
964     \else \def\next{\adl@LTisplitlet(#1/#2);}\fi \fi
965     \next}
966 \def\adl@LTisplitlet#1;{\def\@tempa{#1}%
967     \ifx\@tempa\@nnil \def\@tempb{}\let\next\relax
968     \else\ifdim\@tempdimb<\@tempdima
969         \adl@LTisplitlet#1\let\next\adl@LTisplitlet
970     \else \def\next{\adl@LTsplitend#1;}\fi \fi
971     \next}
972 \def\adl@LTisplitlet(#1/#2){\edef\adl@rows{\adl@rows(#1/#2);}%
973     \advance\@tempdimb#2sp}
974 \def\adl@LTsplitend#1;\@nil;{\def\@tempb{#1;}}
975 \fi
976
977 %%~L

```

4.16 Compatibility with colortbl

The implementation to make `arydshln` compatible with `colortbl` consists of the following three (almost independent) issues.

Cell coloring is the easiest part because it does not affect dash line drawing. Another reason of the easiness is that `colortbl` packs each cell in a box to measure its height for painting in the modified version of `\@classz`. Thus we do not need to code `\@classz` for both of `colortbl` and `arydshln`, but may sneak our own height/depth measurement into `\@classz` of `colortbl`. Almost everything we have to pay attention to is the compatibility of the initialization and finalization of `colortbl` and `arydshln`.

Horizontal line coloring is relatively easy because it is almost enough to insert coloring macro `\CT@arc@` before the line drawing. A little bit complicated part is the gap coloring which is done by drawing a solid line of gap color before dash line is drawn.

Vertical line coloring is the hardest part but almost everything is done in previous sections to attach dash/gap color to each vertical line segment e_j^i in the list C_i^L and C_i^R of the i -th row information r_i . What we do here is to fix the bugs of `\arrayrulecolor` and `\doublerulesepcolor` in `colortbl` implementation and to add `\dashgapcolor`. If you put `\arrayrulecolor` in $\>\{\dots\}$ construct to specify the color of the vertical lines following the construct as the manual of `colortbl` says, you

will have an error message “Misplaced `\noalign`” because the macro is expanded with `\noalign` in a column body. Even if you somehow remove `\noalign` to avoid the error, you will have a mysterious line coloring as follows :

- If you have `\arrayrulecolor` before the `\array/\tabular` starts, `\arrayrulecolor` in the preamble has no effect to vertical lines but decides the color of horizontal lines except for those at the top of the environment. Additional `\arrayrulecolor` at the beginning of a row has no effect to vertical lines (as expected) but decides horizontal lines following it (also as expected). The effect of `\doublerulesepcolor` is same as `\arrayrulecolor`.
- Otherwise, i.e. without `\arrayrulecolor` outside the environment, `\arrayrulecolor` in the preamble decides the color of vertical and horizontal lines except for verticals preceding columns in the first row and horizontal at the top of the environment. Additional `\arrayrulecolor` at the beginning of a row decides all the vertical and horizontal lines following it. On the other hand, `\doublerulesepcolor` acts as if `\doublerulesepcolor{white}` is done outside the environment.

The reason of the mysterious behavior is as follows. An `\arrayrulecolor`, which globally `\def`-ines a macro `\CT@arc@` with a body containing `\color`, in the preamble is not expanded nor evaluated in the preamble construction phase but done when the first (and succeeding) row is build. On the other hand, `\CT@arc@` attached to vertical line drawing is expanded in the preamble construction phase. Thus if `\CT@arc@` has been defined before the environment starts, vertical lines are colored following the outside definition. Otherwise, since `\CT@arc@` is `\let`-equal to `\relax`, it remains unchanged in the preamble construction phase and expanded when each row is build referring to its definition that `\arrayrulecolor` modifies in the row building phase. Since the macro `\CT@drsc@` defined by `\doublerulesepcolor` is examined if it is `\relax` or not in the preamble construction phase, `\doublerulesepcolor` in the preamble has no effect regardless the existence of the outside definition.

Thus we have to expand and evaluate `\arrayrulecolor` and `\doublerulecolor` in the preamble construction phase to define `\CT@arc@` and `\CT@drsc@`. We also have to initialize `\CT@arc@` as an expandable but non-operative token (e.g. a macro with a body of `\relax` as we do) to make it is expanded in the preamble construction phase rather than the row building.

4.16.1 Initialization, Cell Coloring and Finalization

`\CT@arc@` First of all, we initialize the macro `\CT@arc@`, which will be `\def`-ined as `\color` to specify the color of solid lines and dash segments by `\arrayrulecolor`, with a body of `\relax` because it will be referred to by the vertical line drawing process even if `colortbl` is not in use. We also initialize the macro `\adl@dashgapcolor` for the color of gaps of dash lines similarly. Note that these macros are not `\let`-equal to `\relax` but have bodies of `\relax` so that they are replaced with `\relax` in the preamble construction phase rather than surviving with their own name.

978

979 %% Compatibility with colortbl

```

980
981 \def\CT@arc@{\relax}
982 \def\adl@dashgapcolor{\relax}

Next we examine if colortbl is in use by \@ifpackageloaded, and skip everything if not, or
we have some errors especially when array is not in use.

983 \@ifpackageloaded{colortbl}{\@tempswattrue\@tempswafalse}
984 \if@tempswa

\adl@org@inactivate Then we redefine \adl@inactivate and \adl@activate referring their original version
\adl@org@activate \adl@org@inactivate and \adl@org@activate so that they make \CT@setup \let-equal
\adl@inactivate to its original version \adl@CT@setup if \ADLinactivate is in effect, or to our own ver-
\adl@activate sion \adl@act@CT@setup which will be defined soon. New \adl@activate also inactivates
\CT@setup \CT@setup because our own one for column height/depth measuremnt is inappropriate with
\endpbox colortbl as explained soon.

985 \let\adl@org@inactivate\adl@inactivate
986 \let\adl@org@activate\adl@activate
987 \def\adl@inactivate{\adl@org@inactivate \let\CT@setup\adl@CT@setup}
988 \def\adl@activate{\adl@org@activate \let\CT@setup\adl@act@CT@setup
989 \let\CT@setup\adl@act@CT@setup}
990

\adl@CT@setup Cell coloring is done by \@classz preamble of colortbl in which a column is packed in
\CT@setup \box0. On the other hand, our own \@classz one with array packs the column in \adl@box
\adl@act@CT@setup so that we measure its height and depth. Thus we have choices; to insert height/depth
measurement into colortbl's version; or to insert coloring into our own version. Since the
code of height/depth measurement is much simpler than the coloring, we choose the first
way. Thus the macro \adl@act@CT@setup, which is \let-equal to \CT@setup and is invoked
from \@classz preamble after the column is packed into \box0, measures the height and
depth of \box0 and sets \adl@height and/or \adl@depth to them if they break the records
as \adl@colhtdp does with \adl@box, after it invokes its original version \adl@CT@setup.
Note that we compare \adl@height with the height of \box0 plus \minrowclearance
because it is the real height. Also note that we could insert the measurement code into
the modified version of colortbl's \@classz placing it just before the \box0 is put where
\ht0 plus \minrowclearance is calculated, but did not because the author wished to
make it clear that \@classz is modified only for the bug fix of \arrayrulecolor and
\doublerulesepcolor (and to introduce \dashgapcolor).

991 \let\adl@CT@setup\CT@setup
992 \def\CT@setup{\adl@CT@setup
993 \let\adl@height\ht\z@ \advance\@tempdima\minrowclearance
994 \ifdim\adl@height<\@tempdima \global\adl@height\@tempdima \fi
995 \ifdim\adl@depth<\dp\z@ \global\adl@depth\dp\z@\fi}
996 \let\adl@act@CT@setup\CT@setup
997

\adl@activatepbox Another job for cell coloring is to make \CT@x@color ( $x \in \{\text{cell}, \text{column}, \text{do}\}$ ) \let-equal
to \relax before the body of \multicolumn is put so that the \columncolor in the envi-
ronment preamble does not affect the \spanned column. Note that resetting \CT@cell@

```

color will be unnecessary (but safe) because it is always reset after its invocation. Also note that resetting `\CT@row@color` in `colortbl`'s `\multicolumn` is a buggy feature because it should be effective, and thus we remove it. Although we have our own `\multicolumn` for dash lines, we keep it unchanged. Instead we redefine `\adl@activatepbox`, which is usually `\relax` with `array`, to do the color resetting to minimize recoding.

```

998 \def\adl@activatepbox{\let\CT@cell@color\relax
999         \let\CT@column@color\relax
1000         \let\CT@do@color\relax}
1001

```

<pre> \adl@CT@start \CT@start \adl@dashgapcolor@save \adl@CT@end \CT@end \endarray \endArray </pre>	<p>Yet another job is the save/restore of color information at the beginning and end of the environment. Since this is done by <code>\CT@start</code> and <code>\CT@end</code>, we modify them to save/restore <code>\adl@dashgapcolor</code> to/from <code>\adl@dashgapcolor@save</code> referring their original version <code>\adl@CT@start</code> and <code>\adl@CT@end</code>. We also modify our own <code>\endarray</code> and its shorthand active version <code>\endArray</code> so that <code>\CT@end</code> is invoked at the end of environment. Note that we may not modify <code>\endtabular</code> because it refers <code>\endarray</code>. Also note that <code>\endArray</code> <code>\CT@start</code> is invoked from <code>\@tabarray</code> which we keep unchanged.</p>
---	---

```

1002 \let\adl@CT@start\CT@start
1003 \def\CT@start{\adl@CT@start \let\adl@dashgapcolor@save\adl@dashgapcolor}
1004 \let\adl@CT@end\CT@end
1005 \def\CT@end{\adl@CT@end \global\let\adl@dashgapcolor\adl@dashgapcolor@save}
1006 \def\endarray{\adl@endarray \egroup \adl@arrayrestore \CT@end \egroup}
1007 \ifx\adl@notdefinable\undefined \let\endArray\endarray \fi
1008

```

4.16.2 Horizontal Line Coloring

<pre> \hline \adl@inactivehdl \adl@ixhline </pre>	<p>To color <code>\hline</code> and inactivated <code>\hdashline</code>, we modify our own <code>\hline</code> and <code>\adl@inactivehdl</code> inserting the line coloring macro <code>\CT@arc@</code> before drawing by <code>\hrule</code> and pushing the coloring/drawing into a group. We also modify <code>\adl@ixhline</code> to draw a colored horizontal rule of <code>\doublerulesep</code> wide with the color defined in <code>\CT@drsc@</code> if it is not <code>\relax</code>, rather than to insert a vertical skip. Note that the <code>\cline</code> coloring is done by <code>colortbl</code>'s <code>\cline</code> renamed as <code>\adl@org@cline</code> and invoked from our own one.</p>
---	---

```

1009 \def\hline{\noalign{\ifnum0='}\fi
1010         \ifadl@zwhrule \vskip-\arrayrulewidth
1011         \else \adl@hline\adl@connect\arrayrulewidth \fi
1012         {\CT@arc@ \hrule\@height\arrayrulewidth}%
1013         \global\adl@finaldepth\z@
1014         \futurelet\@tempa\adl@xhline}
1015 \def\adl@inactivehdl[#1/#2]{\ifadl@zwhrule \vskip-\arrayrulewidth \fi
1016         {\CT@arc@ \hrule\@height\arrayrulewidth}%
1017         \futurelet\@tempa\adl@xhline}
1018 \def\adl@ixhline{\ifx\CT@drsc@\relax \vskip \else
1019         \CT@drsc@\hrule\@height \fi \doublerulesep}%
1020         \adl@hline\relax\doublerulesep}

```

`\adl@ihdashline` To draw a horizontal dash line with colored dashes and also colored gaps, we drastically modified `\adl@ihdashline` for `\hdashline` and `\adl@cdline` for `\cdashline`. First, they invoke `\adl@hclinesetup` that makes the prefix of a `\multispan`-ned row from the first to last columns for `\hdashline` or given columns for `\cdashline`. Then the line is drawn by the modified version of `\adl@hcline`. We have to declare these macros are active ones again.

```

1021 \def\adl@ihdashline[#1/#2]{\adl@hclinesetup\@ne\adl@columns
1022     \adl@hcline\z@[#1/#2]%
1023     \noalign{\ifnum0='}\fi
1024     \futurelet\@tempa\adl@xhline}
1025 \let\adl@act@ihdashline\adl@ihdashline
1026 \def\adl@cdline[#1-#2]{\ifadl@zwhrule \vskip-\arrayrulewidth \fi
1027     \adl@hclinesetup{#1}{#2}%
1028     \adl@hcline{-\arrayrulewidth}}
1029 \let\adl@act@cdline\adl@cdline

```

`\adl@hclinesetup` The macro `\adl@hclinesetup{f}{t}` makes the prefix of a `\multispan`-ned row from the column f to t and `\global`-ly defines it as `\@gtempa`. This is done by a code very similar to original `\adl@cdline` (and thus L^AT_EX-2.09's `\cline`) but the invocation of `\adl@hcline` is removed from `\adl@cdliena` and `\adl@cdlineb`, one of which is `\@gtempa`.

```

1030 \def\adl@hclinesetup#1#2{\global\adl@cla#1\relax
1031     \global\advance\adl@cla\m@ne
1032     \ifnum\adl@cla>\z@ \global\let\@gtempa\adl@cdliena
1033     \else \global\let\@gtempa\adl@cdlineb\fi
1034     \global\adl@clb#2\relax
1035     \global\advance\adl@clb-\adl@cla \ifnum0='}\fi}}
1036 \def\adl@cdliena{\multispan\adl@cla &\multispan\adl@clb \unskip}
1037 \def\adl@cdlineb{\multispan\adl@clb \unskip}

```

`\adl@hcline` The modified version of `\adl@hcline{w}[\langle d \rangle/\langle g \rangle]` draws a colored horizontal dash line of dash size d and gap size g and insert vertical skip of w . First it `\span`-s columns by `\@gtempa` and checks if the body of `\adl@dashgapcolor` is something other than `\relax`. If so, i.e. it has `\color`, `\adl@paintdashgap` is invoked to draw a horizontal rule of `\color` by `\leaders` as the background of the dash line, to insert `\nobreak` (for longtable) and a negative space for canceling the width of the rule, and to `\span` the columns again. Then `\adl@hcline` draws the colored dash line, over the background if the gaps are colored, by inserting `\CT@arc@` before the invocation of `\adl@draw`.

```

1038 \def\adl@hcline#1[#2/#3]{\@gtempa
1039     \ifx\adl@dashgapcolor\adl@nocolor \else \adl@paintdashgap \fi
1040     {\@tempdima#2\relax \@tempdimb#3\relax
1041         \CT@arc@ \adl@draw\adl@vrule\hskip\hbox}\cr
1042     \noalign{\global\adl@finaldepth\z@ \ifdim#1=\z@\else
1043         \ifadl@zwhrule\else \vskip#1\fi\fi}}
1044 \def\adl@paintdashgap{\adl@dashgapcolor
1045     \leaders\hrule\@height\arrayrulewidth\hfill}\cr
1046     \noalign{\penalty\@M \vskip-\arrayrulewidth}\@gtempa}
1047

```

4.16.3 Vertical Line Coloring

`\arrayrulecolor` A bug of `colortbl`'s `\arrayrulecolor` and `\doublerulesepcolor` is that they are defined like;

`\CT@arc@` like;

`\doublerulesepcolor` `\ifdim\baselineskip=\z@ \noalign \fi{\gdef\CT@arc@{\color...}}`

`\CT@drsc@` This aims to do `\noalign{\gdef...}` in `array/tabular` and do `{\gdef...}` outside but has two problems : First, if they are in `>{...}` construct, they are expanded with `\noalign` inappropriately when the argument of `>` is expanded. Second, they may appear at a place where `\baselineskip` is 0 but is outside of `array/tabular` and will cause the misplaced `\noalign` error. To solve the second problem, we introduced `\adl@noalign` which is set to `\noalign` in the environment by our own `\@array`, and `\relax` outside. We also introduced `\adl@defcolor<cs><opt>` for the common job to define `<cs>` as `\color` with `<opt>`, in `\noalign` if necessary, by `\adl@idefcolor`. Thus `\arrayrulecolor` and `\doublerulesepcolor` are modified to define `\CT@arc@` and `\CT@drsc@` using `\adl@defcolor`, and our own `\dashgapcolor` is defined similarly to define `\adl@dashgapcolor`. Another macro `\nodashgapcolor` to nullify `\dashgapcolor` is also defined with `\adl@noalign` to reset `\adl@dashgapcolor` to `\relax`.

```

1048 \def\arrayrulecolor{\adl@defcolor\CT@arc@}
1049 \def\doublerulesepcolor{\adl@defcolor\CT@drsc@}
1050 \def\dashgapcolor{\adl@defcolor\adl@dashgapcolor}
1051 \def\adl@defcolor#1#2#{\adl@idefcolor{#1}{#2}}
1052 \def\adl@idefcolor#1#2#3{\adl@noalign{\gdef#1{\color#2{#3}}}}
1053 \let\adl@noalign\relax
1054 \def\nodashgapcolor{\adl@noalign{\gdef\adl@dashgapcolor{\relax}}}
1055

```

`\@classz` The tougher bug of `colortbl` is the expansion timing of `\arrayrulecolor` and `\doublerulesepcolor` in a `>`-argument. We have to modify `\@classz` to extract them from `\toks`

`\adl@act@classz` `\@tempcnta` as its original version does for `\columncolor`. Thus we inserted the invocation of `\adl@extract@arc` for `\arrayrulecolor`, `\adl@extract@drsc` for `\doublerulesepcolor`, and `\adl@extract@dgc` for `\dashgapcolor` just after the invocation of `\CT@extract`. Note that the other part of `\@classz` is not modified logically, but done for author's preference of indentation. Also note that both `\adl@act@classz` and `\adl@org@classz` are `\let`-equal to the modified `\@classz` because we have to be bug free even if `\ADLinactive` is in effect.

```

1056 \def\@classz{\@classx
1057     \@tempcnta\count@ \prepnext\tok
1058     \expandafter\CT@extract\the\toks\@tempcnta\columncolor!\@nil
1059     \expandafter\adl@extract@arc\the\toks\@tempcnta\arrayrulecolor!\@nil
1060     \expandafter\adl@extract@drsc
1061         \the\toks\@tempcnta\doublerulesepcolor!\@nil
1062     \expandafter\adl@extract@dgc\the\toks\@tempcnta\dashgapcolor!\@nil
1063     \@addtopreamble{%
1064         \setbox\z@\hbox\bgroup\bgroup
1065         \ifcase \@chnum
1066             \hskip\stretch{.5}\kern\z@

```

```

1067             \dollarbegin
1068             \insert@column
1069             \dollarend\hskip\stretch{.5}%
1070         \or \dollarbegin \insert@column \dollarend \hfill
1071         \or \hfill \kern\z@ \dollarbegin \insert@column \dollarend
1072         \or $\vcenter
1073             \@startpbox{\@nextchar}\insert@column \@endpbox $%
1074         \or \vtop \@startpbox{\@nextchar}\insert@column \@endpbox
1075         \or \vbox \@startpbox{\@nextchar}\insert@column \@endpbox
1076         \fi
1077     \egroup\egroup
1078     \beginngroup
1079         \CT@setup
1080         \CT@column@color
1081         \CT@row@color
1082         \CT@cell@color
1083         \CT@do@color
1084     \endgroup
1085     \@tempdima\ht\z@
1086     \advance\@tempdima\minrowclearance
1087     \vrule\@height\@tempdima\@width\z@
1088     \unhbox\z@}%
1089     \prepnext@tok}
1090 \let\adl@act@classz\@classz
1091 \let\adl@org@classz\@classz
1092

```

`\adl@def@extract` The definitions of `\adl@extract@x` ($x \in \{\text{arc}, \text{drsc}, \text{dgc}\}$) are quite similar to each other.
`\adl@extract@arc` For example `\adl@extract@arc` is defined as follows.
`\adl@extract@arc@b` `\def\adl@extract@arc#1\arrayrulecolor#2#3\@nil{%`
`\CT@arc@` `\if!#2\toks\@tempcnta{#1}\let\@tempa\relax%`
`\adl@extract@drsc` `\else\if[#2%`
`\adl@extract@drsc@b` `\def\@tempa{\adl@extract@arc@b{#1}#3\@nil}%`
`\CT@drsc@` `\else \def\CT@arc@{\color{#2}}%`
`\adl@extract@dgc` `\def\@tempa{\adl@extract@arc#1#3\@nil}%`
`\adl@extract@dgc@b` `\fi\fi \@tempa}`
`\adl@dashgapcolor` `\def\adl@extract@arc@b#1#2]#3{%`
`\def\CT@arc@{\color[#2]{#3}}%`
`\adl@extract@arc#1}`

This code extracts *all the* occurrences of `\arrayrulecolor[m]{ c }` from the token register and `\def`-ines `\CT@arc@` as `\color[m]{ c }`. Note that `\CT@extract` does a similar job for `\columncolor` but it mistakingly ignores the possibility that the token register has two or more `\columncolor`²⁸. Anyway, if we copy the code above and replace ‘arc’ with ‘drsc’, `\arrayrulecolor` with `\doublerulesepcolor`, and `\CT@arc@` with `\CT@drsc@`, we will have `\adl@extract@drsc(@b)` for `\doublerulesepcolor`. The code for `\adl@extract@dgc(@b)` will be also obtained similarly. However, having three relatives for a almost common job is too awful. Thus we introduce;

28. Fixing this bug is not our business.

`\adl@def@extract<key><umac><cmac>`

to define the macros `\adl@extract@key` and `\adl@extract@key@b` for the user interface macro `<umac>` in which a color macro `<cmac>` is defined with `\color`. For example, we will obtain `\adl@extract@arc@b` shown above by;

`\adl@def@extract{arc}\arrayrulecolor\CT@arc@`

Note that `\color` is made `\relax` in the preamble construction phase by `colortbl's \@mkpream` and regain its proper meaning after the phase.

```

1093 \def\adl@def@extract#1#2#3{%
1094     \expandafter\def\csname adl@extract@#1\endcsname##1#2##3\@nil{%
1095         \if!##2\toks\@tempcnta{##1}\let\@tempa\relax
1096         \else\if[##2%
1097             \def\@tempa{\@nameuse{adl@extract@#1@b}{##1}##3\@nil}%
1098         \else \def#3{\color{##2}}%
1099         \def\@tempa{\@nameuse{adl@extract@#1}##1##3\@nil}%
1100         \fi\fi \@tempa}
1101     \expandafter\def\csname adl@extract@#1@b\endcsname##1##2]##3{%
1102         \def#3{\color[##2]{##3}}%
1103         \@nameuse{adl@extract@#1}##1}}
1104 \adl@def@extract{arc}\arrayrulecolor\CT@arc@
1105 \adl@def@extract{drsc}\doublerulesepcolor\CT@drsc@
1106 \adl@def@extract{dgc}\dashgapcolor\adl@dashgapcolor
1107

```

4.16.4 Compatibility with longtable

`\LT@hline` Yet another compatibility issue is to cope with both `longtable` and `colortbl`. We redefine `\LT@hline` `\adl@LTidashline` `\LT@inactivehdl` in order to put `\CT@arc@` before line drawing and to push them in a group. Modified `\adl@LTidashline` first invokes `\adl@hclinesetup` and open `\adl@LTinactivehdl` `\noalign` because it is closed by `\adl@hclinesetup`. The contents of `\adl@LThdlrow` for `\adl@LTidashline` is simply `\adl@hcline` because it does `\multispan` now. The macro `\adl@LTixhline` is modified to paint the `\doublerulesep` gap by `\leaders\hrule` with color of `\CT@drsc@` if it is not `\relax`.

```

1108 \ifx\longtable\undefined\else
1109 \def\LT@hline{\noalign{\ifnum0='}\fi
1110     \gdef\adl@LThdlrow{\multispan{\LT@cols}\unskip{\CT@arc@
1111         \leaders\hrule\@height\arrayrulewidth\hfill}\cr}%
1112     \adl@LThdlrow}
1113 \def\adl@LTidashline[#1/#2]{\adl@hclinesetup\@ne\adl@columns
1114     \noalign{\ifnum0='}\fi
1115     \gdef\adl@LThdlrow{\adl@hcline\z@[#1/#2]}%
1116     \adl@LThdlrow}
1117 \def\adl@LTinactivehdl[#1/#2]{%
1118     \gdef\adl@LThdlrow{\multispan{\LT@cols}\unskip{\CT@arc@
1119         \leaders\hrule\@height\arrayrulewidth\hfill}\cr}%
1120     \adl@LThdlrow}
1121 \def\adl@LTixhline{%

```

```

1122      \ifx\CT@drsc@\relax \gdef\adl@LThdlrow{\noalign{
1123          \penalty-\@medpenalty \vskip\doublerulesep}}
1124      \else \gdef\adl@LThdlrow{\noalign{\penalty\@M}%
1125          \multispan{\LT@cols}\unskip{\CT@drsc@
1126          \leaders\hrule\@height\doublerulesep\hfill}}\cr}\fi
1127      \ifnum0='{ \fi}\adl@LThdlrow \noalign{\ifnum0='{ \fi
1128      \adl@hline\relax\doublerulesep \global\let\adl@LThdlrow\@empty}
1129 \fi
1130 \fi

```

Acknowledgments

The author thanks to Monty Hayes who gave the author the opportunity to make this style, and Weimin Zhang and Takahiro Kubota who pointed out bugs in early versions. He also thanks to the following people; Sebastian Rahtz and Graham Williams who kindly invited the style to T_EX CTAN and online catalogue compiled by Graham; Peter Ehrbar who showed the style was incompatible with `array` and kindly accepted the offer to be an alpha-user of v1.4 alone; Zsuzsanna Nagy who reported another incompatibility problem with `colortab`; Ralf Heydenreich who reported the bug causing that glues in a column have no effect; Yaxin Liu who reported the incompatibility bug of `array` and `\ADLinactivate`; Craig Leech who reported the incompatibility problem with `longtable`, which was also reported by Uwe Jehmlich, Torge Thielemann and Florian Weig, and had waited for two years and a half (!) for the solution; Klaus Dalinghaus who reported yet another incompatibility with `colortbl`; Morten Høgholm who reported the bug of m-type columns of `array` which had not manifested in five (!!) years since the author realeased the first `array`-compatible version; and Maïeul Rouquette who reported another bug of m-type columns of `longtable` with `array` which had peacefully hidden in the package for eleven years and a half (!!!) since the author made the bug fix shown above carelessly, yet another bug related to `longtable`, and most surprisingly a problem on intersections of horizontal and vertical (dash-)lines which has hidden for 23 years (!!!!) since the very first version of the package.

The base implementation of `array` and `tabular` environments, part of which the author gives new definitions referring original ones, are written by Leslie Lamport as a part of L^AT_EX-2.09 and L^AT_EX 2_ε (1997/12/01) to which Johannes Braams and other authors also contributed. The author also refers `array` package (v2.3m) written by Frank Mittelbach and David Carlisle; `colortab` package (v0.9) written by Timothy van Zandt; and `longtable` (v4.10) and `colortbl` (v0.1j) packages written by David Carlisle; to make the style compatible with those packages.

Index

Italicized number refers to the page where the specification and usage of corresponding entry are described, while underlined is for the implementation of the entry. To find a control sequence, remove prefixes \@, \adl@ and \ifadl@ from its name if it has one of them.

Symboles	
:	4
;	4
\adl@LTth\LT@firsthead	50, 56
\adl@LTth\LT@foot	50, 56
\adl@LTth\LT@head	50, 56
\adl@LTth\LT@lastfoot	50, 56
\adl@rowsL\LT@firsthead	50, 56
\adl@rowsL\LT@foot	50, 56
\adl@rowsL\LT@head	50, 56
\adl@rowsL\LT@lastfoot	50, 56
\adl@rowsR\LT@firsthead	50, 56
\adl@rowsR\LT@foot	50, 56
\adl@rowsR\LT@head	50, 56
\adl@rowsR\LT@lastfoot	50, 56
A	
\AC	7
\adl@act@endpbox	20, 46, 53
\adl@act@startpbox	20, 46, 53
\adl@act@vlineL	20, 46
\adl@act@vlineR	20, 46
\adl@act@argcr	20, 46
\adl@act@arrayclassz	20, 46
\adl@act@cdline	20, 46, 62
\adl@act@classz	20, 46, 63
\adl@act@cline	20, 46
\adl@act@cr	20, 46
\adl@act@CT@setup	60
\adl@act@endarray	20, 46
\adl@act@endpbox	20, 46
\adl@act@hline	20, 46
\adl@act@ihdashline	20, 46, 62
\adl@act@tabclassz	20, 46
\adl@activate	20, 60
\adl@activatepbox	29, 60
\@addamp	22
\adl@addvl	35, 39, 40, 56
\adl@addvL	41, 56
\adl@addvLR	41, 56
\ADLactivate	6, 15
\ADLdrawingmode	6, 44
\ADLinactivate	6, 15
\ADLnoshorthanded	7, 45
\ADLnullwide	5, 15
\ADLnullwidehline	7, 15
\ADLsomewide	5, 15
\ADLsomewidehline	7, 15
\afterassignment	22
\adl@argarraydashrule	23, 24, 25, 29, 30
\adl@argcr	19, 20, 31, 46
\Array	44
Array (environnement)	6
\array	44
array (environnement)	4
array (package)	3, 7
\@array	17, 63
\@@array	18
\adl@Array	44
\adl@array	17
\@arrayclassz	19, 20, 24, 46
\adl@arraydashrule	23, 24, 25, 29, 30
\adl@arrayinit	18, 48
\adl@arrayrestore	35, 37, 46
\@arrayrule	23, 24
\adl@arrayrule	23, 24, 25, 29, 30
\arrayrulecolor	7, 17, 63
\arrayrulewidth	5
\adl@arraysave	18, 46
\@arstrutbox	10, 31
B	
\adl@box	15, 20, 23, 25, 28, 43
C	
\c@LT@chunks	56
\CC@	46
\adl@CC@	46
\cdashline	4, 5, 34
\adl@cdlinea	34, 62
\adl@cdline	19, 20, 34, 46, 62
\adl@cdlineb	34, 62
\cellcolor	7
\@chclass	26

`\@cla` 16
`\adl@cla` 16, 34
`\adl@class@iiiorvii` 24, 25, 26
`\adl@class@start` 24, 25, 25
`\@classv` 26
`\adl@classv` 26
`\adl@classvfordash` 26
`\@classz` 19, 20, 23, 46, 63
`\@clb` 16
`\adl@clb` 16, 34
`\cleaders` 43
`\cline` 4, 32, 46, 61
`\@cline` 34
`\adl@colhtdp` 20, 22, 25, 26, 28, 28
`\adl@@colhtdp` 27, 60
`\color` 8, 25, 27
`colortab` (package) 3, 7
`colortbl` (package) 3, 7
`\adl@colsL` 18, 31, 37
`\adl@colsLsave` 18, 37
`\adl@colsR` 18, 31, 37
`\adl@colsRsave` 18, 37
`\columncolor` 7
`\adl@columns` 16, 22, 37, 48
`\adl@connect` 18, 31, 32, 39, 52
`\adl@@connect` 39
`\ifadl@connected` 14, 37, 41
counters :
 `LTchunksizes` 8
`\adl@cr` 19, 20, 31, 46
`\adl@@cr` 31, 35, 49
`\CT@arc@` 21, 25, 59, 61, 63, 64
`\CT@cell@color` 60
`\CT@column@color` 60
`\CT@do@color` 60
`\CT@drsc@` 61, 63, 64
`\CT@end` 61
`\adl@CT@end` 61
`\CT@row@color` 60
`\CT@setup` 60
`\adl@CT@setup` 60
`\CT@start` 61
`\adl@CT@start` 61
`\current@color` 27
`\adl@currentcolumn`
 ... 16, 18, 19, 21, 22, 29–31, 35, 37, 56
`\adl@currentcolumnsave` 16, 19, 37

D

`\adl@dash` 16, 37, 41
`\adl@dashcolor` 27
`\dashgapcolor` 8, 17, 63
`\adl@dashgapcolor@save` 61
`\adl@dashgapcolor` 21, 25, 59, 63, 64
`\dashlinedash` 4, 14, 33
`\dashlinegap` 4, 14, 33
`\adl@def@extract` 64
`\adl@defcolor` 63
`\adl@defflhdl` 35
`\adl@depth` 15, 18–20, 31, 35, 37, 49
`\adl@depthsave` 15, 19, 37
`\adl@discard` 18, 31, 48, 52, 57
`\documentstyle` 3
`\ifadl@doublerule` 14, 37
`\doublerulesepcolor` 7, 17, 63
`\adl@draw` 34, 41, 43, 62
`\adl@drawi` 43
`\adl@drawii` 43
`\adl@drawiii` 43
`\adl@drawvi` 35, 41, 56

E

`\EAC` 7
`\@elt` 18, 39
`\ENAC` 7
`\endArray` 44, 61
`\endarray` 35, 61
`\adl@endarray` 19, 20, 35, 46
`\endfirsthead` 50
`\endfoot` 50
`\endhead` 50
`\endlastfoot` 50
`\endLongtable` 44
`\endlongtable` 48, 49
`\adl@endmakevlr` 39
`\adl@endmakevlrconn` 39
`\adl@endmakevlrcut` 39
`\adl@endmbox` 22, 23, 28, 48
`\adl@@endmbox` 48
`\@endpbox` 19, 20, 28, 46, 48, 60
`\@@endpbox` 19, 20, 28, 46, 48, 53
`\endTabular` 44
`\endtabular` 35
`\endTabular*` 44
`\endtabular*` 35
environments :
 `longtable` 18, 47

\adl@LThdline	52		
\adl@LThdlrow	51		
\adl@LTheadL	55		
\adl@LTheadR	55		
\adl@LThfsave	50		
\adl@LTihdashline	48, 51, 65		
\adl@LTiisplit	57		
\adl@LTinactivate	48		
\adl@LTinactivehdl	48, 51, 65		
\adl@LTinit	55		
\adl@LTisplit	57		
\adl@LTixhline	52, 65		
\adl@LTKill	51		
\adl@LTKillend	51		
\adl@LTlastrow	49		
\adl@LTpagetotal	47, 53, 55		
\adl@LTrowdiscard	57		
\adl@LTrowrelax	57		
\adl@LTSplit	57		
\adl@LTSplitend	57		
\adl@LTstartpbox	48, 53		
\adl@LTth	50		
\adl@LTxhline	52		
\adl@LTxsplit	57		
\adl@LTYsplit	57		
M			
\adl@makev1r	39		
\adl@makev1rL	35, 37, 56		
\adl@makev1rR	35, 37		
\adl@mcaddamp	29		
\adl@mcargarraydashrule	29, 30		
\adl@mccarraydashrule	29, 30		
\adl@mccarrayrule	29, 30		
\@medpenalty	52		
\MessageBreak	44		
\@mkpream	22		
\adl@mkpream	22		
\multicolumn	4, 29, 60		
N			
\NAC	7		
\adl@ncol	16, 22, 25, 48		
\newcolumnntype	7		
\@nextchar	26		
\adl@noalign	17, 63		
\adl@nocolor	27		
\nodashgapcolor	8, 63		
\@notdefinable	44		
\adl@notdefinable	44		
O			
\adl@org@@endpbox	17, 19		
\adl@org@@startpbox	17, 19		
\adl@org@activate	60		
\adl@org@arrayclassz	17, 19		
\adl@org@classz	17, 19, 63		
\adl@org@ccline	17, 19, 32, 34		
\adl@org@endlongtable	48, 49		
\adl@org@endpbox	17, 19		
\adl@org@inactivate	60		
\adl@org@LT@echunk	48, 49		
\adl@org@LT@end@hd@ft	48, 50		
\adl@org@LT@kill	48, 51		
\adl@org@LT@make@row	48, 48		
\adl@org@LT@output	48, 54		
\adl@org@tabclassz	17, 19		
\output	47		
P			
packages :			
array	3, 7		
colortab	3, 7		
colortbl	3, 7		
longtable	3, 8, 47		
\PackageWarning	44		
\adl@paintdashgap	62		
\adl@preamble	29		
\adl@preaminit	22, 26, 28		
\adl@putlrc	23, 24, 25		
R			
\rowcolor	7		
\adl@rows	35, 37, 56, 57		
\adl@rowsL ...	18, 31, 33, 35, 37, 47, 50, 56		
\adl@rowsLsave	18, 37		
\adl@rowsR ...	18, 31, 33, 35, 37, 47, 50, 56		
\adl@rowsRsave	18, 37		
S			
\set@color	41		
\adl@setcolor	27		
\adl@startmbox	22, 23, 28		
\@startpbox	28, 48, 53		
\@@startpbox	19, 20, 28, 46, 48, 53		
T			
\@tabarray	18		
\@tabclassz	19, 20, 24, 46		
\Tabular	44		
Tabular (environnement)	6		

Historique

v1.0	
Général : The style was born on a good day ... (1993/04/01)	1
v1.05	
Général : Cope with <code>\</code> with negative optional vertical space. (1993/06/18)	1
v1.1	
Général : Save and restore the <code>\catcode</code> for ‘ <code>0</code> ’. (1993/06/24)	1
v1.2	
Général : Various changes shown below. (1998/07/16)	1
v1.2-1	
Général : Add this document.	1
v1.2-2	
Général : Cope with $\text{\LaTeX} 2_{\epsilon}$.	1
v1.2-3	
Général : Allow mixture of vertical solid- and dash-lines.	1
v1.2-4	
Général : Add the feature of explicit dash/gap specification.	1
v1.2-5	
Général : Fix some bugs and change codes.	1
v1.3	
Général : Fix one bug shown below. (1998/10/08)	1
<code>\adl@activatepbox</code> : <code>\def</code> -s for <code>\adl@mcarrrayrule</code> etc. are enclosed in a group.	29
v1.4	
Général : Make compatible with array package and add new features. (1999/06/25)	1
v1.4-1	
Général : The following are changes of this document.	1
Général : The history on the compatibility with <code>array</code> package.	3
Général : Explanation of package loading is added.	3
Général : Description of <code>\first/lasthdashline</code> is added.	4
Général : Description of the real width of vertical lines is added.	5
Général : Description of drawing mode is added.	5
Général : Description of (in)activation is added.	6
Général : Description of characters and commands of <code>array</code> package is added.	7
Général : Description about ‘ <code>!</code> ’ of array package is added.	9
Général : Reference to the section for drawing mode is added.	9
Général : Description on minimum length is added.	9
Général : Reference to the performance tuning section is added.	9
Général : The title of section 4.1 is changed.	10
Général : <code>\hfil</code> is replaced with <code>\hss</code> taking the possibility of negative wide columns into account.	10
Général : Section 4.12 is added.	42
Général : Section 4.13 is added.	44
Général : Thank to more people.	66
v1.4-2-1	
Général : The following are for the general compatibility with <code>array</code> .	1
<code>\ifadl@usingarypkg</code> : Introduced to know if <code>array</code> is loaded.	14
<code>\adl@ncol</code> : Introduced for new column counting in preamble construction.	16
<code>\adl@everyvbox</code> : Introduced for a tricky modification of <code>\@array</code> .	17
<code>\adl@array</code> : Introduced to save original definition of <code>\@array</code> .	17

<code>\@array</code> : Drastically modified to avoid copy-and-modify.	17
<code>\@@array</code> : Introduced because array uses it.	18
<code>\adl@arrayinit</code> : Modified for new column counting in preamble construction.	18
<code>\@mkpream</code> : Modified for new column counting and control sequence redefinition.	22
<code>\@addamp</code> : Modified for new column counting in preamble construction.	22
<code>\@testpach</code> : The version for array is introduced.	23
<code>\@classz</code> : Introduced because array uses it.	23
<code>\adl@class@start</code> : Introduced for class number identification.	24
<code>\adl@class@iiiorvii</code> : Introduced for class number identification.	24
<code>\adl@class@start</code> : Introduced for class number identification.	25
<code>\adl@class@iiiorvii</code> : Introduced for class number identification.	25
<code>\adl@arrayrule</code> : Modified to replace <code>\adl@columns</code> with <code>\adl@ncol</code>	25
<code>\adl@arraydashrule</code> : Modified to replace <code>\adl@columns</code> with <code>\adl@ncol</code>	25
<code>\adl@argarraydashrule</code> : Modified to replace <code>\adl@columns</code> with <code>\adl@ncol</code>	25
<code>\adl@xarraydashrule</code> : Modified to pretend p or @ depending on if array is in use.	25
<code>\adl@colhtdp</code> : Modified to refer <code>\adl@class@start</code> rather than L ^A T _E X's 6.	25
<code>\adl@colhtdp</code> : Initialized by calling <code>\adl@preaminit</code>	28
<code>\adl@vlineL</code> : Initialized by calling <code>\adl@preaminit</code>	28
<code>\adl@vlineR</code> : Initialized by calling <code>\adl@preaminit</code>	28
<code>\@endpbox</code> : Introduced because array uses it.	28
<code>\multicolumn</code> : Modified for several reason.	29
<code>\adl@mcaddamp</code> : Introduced for the complaint on multiple columns if with array.	29
<code>\adl@activatepbox</code> : Introduced to do nothing if with array.	29
<code>\adl@mcargarraydashrule</code> : Modified to pretend p or @ depending on if array is in use.	30
<code>\@xarraycr</code> : The version for array is introduced.	30
v1.4-2-2	
Général : The following are to control the effective width of vertical lines.	1
<code>\ifadl@zwvrule</code> : Introduced to indicate vertical lines have null width.	14
<code>\ADLnullwidehline</code> : Introduced to make vertical lines null wide.	15
<code>\ADLsomewidehline</code> : Introduced to make vertical lines <code>\arraydashline</code> wide.	15
<code>\adl@xarraydashrule</code> : Modified to add invisible rule of <code>\arrayrulewidth</code> wide if <code>\ADLsomewide</code>	25
<code>\adl@@v1</code> : Modified to make vertical line null wide only if <code>\ADLnullwide</code>	41
v1.4-2-3	
Général : The following are for inactivation of dash-line functions.	1
<code>\ifadl@inactive</code> : Introduced to indicate dash-line functions are inactive.	14
<code>\adl@org@arrayclassz</code> : Introduced to restore <code>\@arrayclassz</code>	17
<code>\adl@org@tabclassz</code> : Introduced to restore <code>\@tabclassz</code>	17
<code>\adl@org@classz</code> : Introduced to restore <code>\@classz</code>	17
<code>\adl@org@@startpbox</code> : Introduced to restore <code>\@@startpbox</code>	17
<code>\adl@org@@endpbox</code> : Introduced to restore <code>\@@endpbox</code>	17
<code>\adl@org@ccline</code> : Introduced to restore <code>\ccline</code>	17
<code>\adl@arrayinit</code> : Modified to call <code>\adl@inactivate</code>	18
<code>\adl@inactivate</code> : Introduced to inactivate <code>\@arrayclassz</code> etc.	19
<code>\adl@inactivev1</code> : Introduced to emulate ':' and ; by 	28
<code>\adl@inactivehdl</code> : Introduced to emulate <code>\hdashline</code> by <code>\hline</code>	33
<code>\adl@inactivecdl</code> : Introduced to emulate <code>\cdashline</code> by <code>\ccline</code>	34
<code>\adl@Array</code> : Introduced as the body of <code>\Array</code>	44
<code>\adl@Tabular</code> : Introduced as the body of <code>\Tabular</code>	44

\adl@Tabularstar : Introduced as the body of \Tabular*.	44
\adl@notdefinable : Introduced to check if \Array etc. are definable.	44
\Array : Introduced as the always-active \array.	44
\Tabular : Introduced as the always-active \tabular.	44
\Tabular* : Introduced as the always-active \tabular*.	44
\endArray : Introduced to \end the environment Array.	44
\endTabular : Introduced to \end the environment Tabular.	44
\endTabular* : Introduced to \end the environment Tabular*.	44
\ADLnoshorthand : Introduced to nullify macros for shorthand activation.	45
v1.4-2-4	
Général : The following are for drawing mode to cope with the bug of \xlearders.	1
\adl@hcline : Modified to use \adl@draw.	34
\adl@v1 : Modified to use \adl@draw.	41
\adl@vrule : Introduced to draw a dash for horizontal lines in \adl@draw.	42
\adl@hrule : Introduced to draw a dash for vertical lines in \adl@draw.	42
\adl@drawi : Introduced as \adl@draw in mode 1.	43
\adl@drawii : Introduced as \adl@draw in mode 2.	43
\adl@drawiii : Introduced as \adl@draw in mode 3.	43
\adl@draw : Introduced as the mode and axis independent line drawing macro.	43
\ADLdrawingmode : Introduced to specify drawing mode.	44
v1.4-2-5	
Général : The following are to implement dashed version of \firstline and \lasthline of array.	1
\hdashline : Modified to make \adl@hdashline usable for \first/lasthdashline.	33
\adl@hdashline : Modified to be usable for \first/lasthdashline.	33
\adl@ihdashline : Introduced as the substitute of old \adl@hdashline.	33
\firsthdashline : Introduced as the dashed version of \firstline.	35
\lasthdashline : Introduced as the dashed version of \lasthline.	35
\adl@defflhd1 : Introduced for the tricky definition of \adl@first/lasthdashline.	35
\adl@idefflhd1 : Introduced for the tricky definition of \adl@first/lasthdashline.	35
\adl@firsthdashline : Introduced as the body of \firsthdashline.	35
\adl@lasthdashline : Introduced as the body of \lasthdashline.	35
v1.4-2-6	
Général : The following are to fix the bug by which the depth of array/tabular was always zero.	1
\adl@finaldepth : Introduced to measure the depth of the last row.	15
\adl@org@ccline : Introduced to refer original version in modified \ccline.	17
\adl@ocr : Modified to set \adl@finaldepth.	31
\hline : Modified to set \adl@finaldepth to zero.	32
\ccline : Modified to set \adl@finaldepth to zero.	32
\adl@endarray : Modified to set the depth of array/tabular to \adl@finaldepth.	35
v1.4-2-7	
Général : The following are to rename macros for \cdashline.	1
\cdashline : Modified to call renamed \adl@cdline.	34
\adl@cdline : Renamed and modified to call renamed \adl@cdlinea/b.	34
\adl@cdlinea : Renamed.	34
\adl@cdlineb : Renamed.	34
v1.4-2-8	
Général : The following are to cope with very narrow or negative wide columns.	1

\adl@makev1rL : Modified to replace \hfil with \hss to prevent drawing vertical lines widen columns.	37
\adl@makev1rR : Modified to replace \hfil with \hss to prevent drawing vertical lines widen columns.	37
v1.4-2-9	
\adl@arrayinit : The bug of saving \adl@colsR is fixed.	18
v1.4-3	
Général : Released to CTAN on 2000/07/04.	1
v1.5	
Général : Make compatible with colortab, and fix bugs. (2000/07/12)	1
v1.5-1	
Général : The following are for the compatibility with colortab.	1
Général : The history on the compatibility with colortab package.	3
Général : Caution about loading order of colortab is added.	3
Général : Section 2.7 is added.	7
Général : Description of colortab commands is added.	7
Général : Caution about \AC/\EAC pair for vertical line coloring is added.	9
\adl@arrayinit : Use new macro \adl@arraysave to save registers/structures.	18
\adl@arraysave : Introduced to use in modified \CC@ of colortab.	18
\CC@ : Modified to save/restore globals before/after height measurement.	46
v1.5-2	
Général : The following are for bug fix of \adl@putlrc.	1
\adl@colhtdp : The pseudo-formal description of <i>\put-lrc</i> is modified.	20
\adl@putlrc : \adl@putlrc must do \unhbox\adl@box to make glues effective.	25
v1.5-3	
Général : The following are for bug fix of \adl@inactivate.	1
\adl@noalign : Move \adl@inactivate to \@array from \adl@arrayinit.	17
\adl@arrayinit : Move \adl@inactivate from \adl@arrayinit to \@array.	18
\adl@inactivate : Change \adl@inactivate caller to \@array.	19
Général : Thank to Yaxin Liu.	66
v1.54	
Général : Bug fixes. (2003/08/25)	1
v1.54-1	
Général : The following are for bug fix of \adl@@v1.	1
\adl@v1row : Rows for vertical lines are replaced by \adl@drawv1.	36
\adl@drawv1 : Introduced to draw vertical lines correctly if \ADLsomewide.	41
\adl@@v1 : Insert a negative skip to left/right of the line if \ADLsomewide.	41
v1.54-2	
Général : The following are for bug fix of activation.	1
\adl@noalign : Invoke \adl@activate if not \ifadl@inactive.	17
\adl@inactivate : Add \adl@argcr to inactivation.	19
\adl@activate : Introduced to activate \@arrayclassz etc. again.	20
\adl@act@arrayclassz : Introduced to activate \@arrayclassz etc. again.	46
v1.54-3	
Général : The following are miscellaneous modifications.	1
\adl@hcline : Omit \vskip if the space is 0.	34
v1.6	
Général : The following are for the compatibility with longtable. (2003/08/25)	1
Général : The history on the compatibility with longtable package.	3
Général : Caution about loading order of longtable is added.	3

Général : Description of <code>longtable</code> is added.	8
Général : Description of <code>discard</code> is added.	11
<code>\adl@discard</code> : Add initialization of <code>\adl@discard</code>	18
Général : Add a summary of activation/inactivation.	20
<code>\adl@cr</code> : Modified to insert <code>\adl@discard</code>	31
<code>\adl@Longtable</code> : Introduced as the body of <code>\Longtable</code>	44
<code>\Longtable</code> : Introduced as the always-active <code>\longtable</code>	44
<code>\endLongtable</code> : Introduced to <code>\end</code> the environment <code>Longtable</code>	44
<code>\ADLnoshorthanded</code> : <code>\Longtable</code> and <code>\endLongtable</code> are added.	45
Général : §4.15 is added.	47
Général : Thank to people for <code>longtable</code>	66
v1.7	
Général : The following are for the compatibility with <code>colortbl</code> . (2004/05/21)	1
Général : The history on the compatibility with <code>colortbl</code> package.	3
Général : Caution about loading order of <code>colortbl</code> is added.	3
Général : Description of <code>colortbl</code> and related commands is added.	7
Général : Comment on vertical line coloring with <code>colortbl</code> is added.	9
Général : Add notes for dash line coloring.	10
Général : A dash/gap specification d_j^i/g_j^i now has color.	11
<code>\endtabular</code> : Modified to refer proper <code>\endarray</code> depending on the existence of <code>colortbl</code>	35
Général : Codes for <code>longtable</code> is surrounded by <code>\ifx/\fi</code>	47
Général : §4.16 is added.	58
Général : Thank to Klaus Dalinghaus and refer original <code>colortbl</code>	66
v1.7-1	
Général : The following are for null-wide horizontal lines.	1
<code>\ifadl@zwhrule</code> : Introduced to indicate horizontal lines have null width.	14
<code>\ADLnullwide</code> : Introduced to make horizontal lines null wide.	15
<code>\ADLsomewide</code> : Introduced to make horizontal lines <code>\arraydashline</code> wide.	15
<code>\adl@inactivate</code> : Remove <code>\cline</code> because our own version is needed for null-wide.	19
<code>\hline</code> : Modified to shift up if null-wide.	32
<code>\cline</code> : Modified to shift up if null-wide.	32
<code>\adl@hdashline</code> : Modified for null-wide horizontal lines.	33
<code>\adl@ihdashline</code> : <code>\adl@hline</code> is moved to <code>\adl@hdashline</code> for null-wide lines.	33
<code>\adl@inactivehdl</code> : Modified to shift up if null-wide.	33
<code>\adl@cdline</code> : Modified to shift up if null-wide.	34
<code>\adl@inactivecdl</code> : Modified to invoke <code>\cline</code> rather than <code>\adl@orgcline</code> for null-wide.	34
<code>\adl@hcline</code> : Modified not to shift null-wide <code>\cdashline</code> down.	34
<code>\adl@LThdashline</code> : Keep original without shift up because it is done by <code>\adl@LThdline</code>	51
<code>\adl@LThdline</code> : Modified to shift up if null-wide.	52
v1.7-2	
Général : The following are to fix the bug of <code>\arrayrulecolor</code> etc. in <code>colortbl</code>	1
<code>\adl@noalign</code> : Introduced to fix a bug of <code>colortbl</code>	17
<code>\adl@noalign</code> : Make <code>\adl@noalign \let-equal</code> to <code>\noalign</code>	17
v1.7-3	
Général : The following are for vertical line coloring.	1
<code>\adl@xarraydashrule</code> : Modified to add color arguments to <code>\adl@vlineL/R</code>	25
<code>\adl@vlineL</code> : Color arguments are added.	27
<code>\adl@vlineR</code> : Color arguments are added.	27
<code>\adl@ivline</code> : Invocations of <code>\adl@setcolor</code> are added.	27

<code>\adl@setcolor</code> : Introduced to color vertical lines.	27
<code>\adl@nocolor</code> : Introduced to examine if coloring is specified.	27
<code>\adl@dashcolor</code> : Introduced as the temporary variable of color specification of dashes.	27
<code>\adl@gapcolor</code> : Introduced as the temporary variable of color specification of gaps.	27
<code>\adl@inactivevl</code> : Modified to color the <code>\vline</code> by the first argument.	28
<code>\adl@makeevlr</code> : Modified to initialize <code>\adl@dashcolor</code> and <code>\adl@gapcolor</code>	39
<code>\adl@iiimakeevlr</code> : Modified to check color identity.	39
<code>\adl@ivmakeevlr</code> : Modified not to see d and g which now have colors.	39
<code>\adl@addv1L</code> : Modified to add colors to δ and ξ	41
<code>\adl@addv1R</code> : Modified to add colors to δ and ξ	41
<code>\adl@@v1</code> : Modified to color dashes and gaps.	41
v1.71	
Général : The following are for bug fix for <code>array</code> 's m-columns. (2004/7/31)	1
<code>\@mkpream</code> : Modified to nullify <code>\adl@startmbox</code> and <code>\adl@endmbox</code> for <code>array</code> 's m-columns.	22
<code>\@classz</code> : Modified to call <code>\adl@startmbox</code> and <code>\adl@endmbox</code> for <code>array</code> 's m-columns.	23
<code>\adl@startmbox</code> : Introduced to the bug fix of <code>array</code> 's m-columns.	28
<code>\adl@endmbox</code> : Introduced to the bug fix of <code>array</code> 's m-columns.	28
Général : Thank to Morten Høgholm.	66
v1.72	
Général : Bug fix and revision of §2.4. (2016/03/19)	1
v1.72-1	
Général : The followings are for bug fix for footnotes in <code>longtable</code> 's m-columns.	1
<code>\LT@make@row</code> : Modified to add <code>\let</code> -assignments to <code>\adl@@endmbox</code> and <code>\adl@endbmox</code> so that footnotes are correctly processed at the closing of a m-type column.	48
<code>\adl@LTendmbox</code> : Added to process footnotes in m-type columns appropriately.	53
Général : Thank to Maïeul Rouquette.	66
v1.72-2	
Général : Revise §2.4 reflecting the fix of <code>\xleaders</code>	5
Général : Remove the caution about the dash segment dropping.	9
Général : Change the title of §4.2 and rephrase sentences according to the fix of <code>\xleader</code> 's problem.	13
v1.73	
Général : Bug fix. (2016/04/28)	1
Général : Thank to Maïeul Rouquette again.	66
v1.73-1	
Général : The followings are to fix the problem that the top edge a vertical (dash-)line is at the bottom of a horizontal line rather than it top.	1
Général : Add a paragraph describing the perfect contacts of vertical and horizontal lines.	4
Général : Add the definition of η_l and addition/subtraction of it for τ_k and β_k	12
Général : Add $\eta = \text{\adl@lastconn}$, its initialization and updates, and the addition to τ	37
<code>\adl@makeevlr</code> : Add $\eta = \text{\adl@lastconn} \leftarrow 0$	39
<code>\adl@iimakeevlr</code> : Modify the definition of <code>\adl@connect</code> to pass h to <code>\adl@@connect</code>	39
<code>\adl@iiimakeevlr</code> : Replace two occurrences of $\tau \leftarrow \beta$ with $\tau \leftarrow \beta + \eta$ and add $\eta \leftarrow 0$, where $\eta = \text{\adl@lastconn}$	39
<code>\adl@endmakeevlr</code> : Add $\eta = \text{\adl@lastconn} \leftarrow 0$	39
<code>\adl@@connect</code> : Add $\eta = \text{\adl@lastconn} \leftarrow h$ with the added argument h	39
v1.73-2	
Général : The followings are to fix the bug that <code>\hdashline</code> is not properly processed in a <code>array/tabular</code> environment if <code>longtable</code> is loaded.	1

<code>\LT@array</code> : Add <code>\let</code> -assignment of <code>\adl@LThdashline</code> to <code>\adl@hdashline</code> so that the longtable version of <code>\adl@hdashline</code> is effective only in <code>longtable</code> environment rather than globally.	48
<code>\adl@LThdashline</code> : Renamed from <code>\adl@hdashline</code> to make it effective only in longtable environments.	51