

L'extension FncyChap
V1.34

Ulf A. Lindgren

Table des matières

1	Description de l'extension	2
1.1	Chargement et utilisation classique	2
2	Nouvelles commandes	3
2.1	Vers la personnalisation du titre de chapitre	3
3	Aperçu des styles de chapitre	4
3.1	The chapter Sonny	4
3.2	The chapter Lenny	5
3.3	The chapter Glenn	5
3.4	The chapter Conny	6
3.5	The chapter Rejne	6
3.6	The chapter Bjarne	7
3.7	The chapter Bjornstrup	7
4	A simple example	8
5	Revision details	10

Chapitre 1

Description de l'extension

L'EXTENSION *fncychap* a été écrite afin que des titres de niveau chapitre puissent être altérés rapidement et que je puisse apprendre plus sur \LaTeX et \TeX . Je ne sais pas si cette extension est écrite de façon adéquate. Aussi, si quelqu'un lit cette documentation et essaye *fncychap*, je serais reconnaissant pour tout retour d'expérience. Ceci m'aidera à monter compétence dans l'écriture de commandes.

Dans toute publication, il est essentiel de se rappeler que la cohérence joue un rôle important. Ainsi, avec cette extension, il est possible de modifier l'apparence de chaque chapitre séparément dans un document. Ceci n'est cependant pas souhaitable : n'oubliez ici pas la modestie et la cohérence.

1.1 Chargement et utilisation classique

Cette extension est chargée en saisissant la ligne suivante en préambule

```
\usepackage[style]{fncychap}
```

Si l'option *style* est omise alors la définition par défaut des chapitres est utilisée. À l'origine, il existait six styles de chapitres prédéfinis, à savoir *Sonny*, *Lenny*, *Glenn*, *Conny*, *Rejne* et *Bjarne*. Ces noms correspondent à des prénoms suédois, à l'image sans doute d'IKEA¹. Chacun de ces styles dispose d'une configuration par défaut et, si elle est suffisante, il ne reste rien d'autre à faire.

Dans la version actuelle de *fncychap*, deux styles additionnels ont été ajoutés. Le premier se nomme *PetersLenny*, d'après le nom de son auteur Peter Osborn. Ce style se base sur celui de *Lenny* : Peter a finement ajusté la taille des filets pour chacun des chapitres numérotés (jusqu'à 20) et chacune des annexes (jusqu'à Z). Le second style a été défini par Jean-Marc François et il l'a nommé *Bjornstrup*.

À l'origine, *fncychap* ne dépendait d'aucune autre extension. Cependant, pour le style *Lenny*, une fonte postscript est utilisée par défaut ; mais ceci peut être facilement changé. J'encourage l'utilisation de cette fonte postscript par défaut car elle est redimensionnable de façon très importante, ce qui rend *Lenny* très agréable. Dans la version actuelle, si le style *Bjornstrup* de Jean-Marc est utilisé, l'extension *color* de la distribution de base sera chargée.

1. Marque déposée d'Ingvar Kamprad Emtaryd Agunnaryd.

Chapitre 2

Nouvelles commandes

EN parallèle des styles de chapitre, quelques commandes additionnelles sont mises à disposition afin de créer ses titres de chapitre personnalisés. Les commandes vont être décrites les unes à la suite des autres. Chaque commande est encadrée et placée sur une ligne séparée. Commençons donc ces descriptions.

`\mghrulefill{largeur}`

La commande ci-dessus est une version plus générale de la commande `\hrulefill` dans le sens où la largeur du filet peut être spécifiée. Cette commande est fournie pour décorer les titres de chapitre. Les titres se divisent en deux parties. La première définit `\chapapp` contenant le texte « Chapter »¹ ainsi que `\thechapter` contenant le numéro du chapitre. La seconde partie est le titre du chapitre donné par l'utilisateur. À partir d'ici, `\chapapp` et `\thechapter` seront respectivement nommé nom du chapitre et numéro du chapitre. Le titre donné par l'utilisateur sera nommé titre du chapitre.

2.1 Vers la personnalisation du titre de chapitre

Les nom, numéro et titre du chapitre peuvent être changés simplement. Introduisons ici les deux commandes suivantes :

`\ChNameUpperCase` et `\ChNameLowerCase`

qui passent respectivement le nom du chapitre en lettres majuscules (*uppercase*) ou en lettres minuscules (*lowercase*). Un cas particulier est ajouté pour le nom du chapitre, à savoir

`\ChNameAsIs`

qui affiche le format par défaut. Trois commandes similaires existent pour le titre du chapitre

`\ChTitleUpperCase`, `\ChTitleLowerCase` et `\ChTitleAsIs`

La largeur du filet des styles de chapitre prédéfinis peut être contrôlée par la commande

`\ChRuleWidth{largeur}`

en gardant en tête que la *largeur* doit avoir une unité, par exemple *pt*, *mm*, etc. Les éléments liés aux polices de caractères tels que la police, son corps, sa graisse peuvent être transmis par les commandes

`\ChNameVar{argument}`, `\ChNumVar{argument}` et `\ChTitleVar{argument}`

liées respectivement aux nom, numéro et titre du chapitre. L'*argument* de ces fonctions peut être par exemple `\ChNameVar{\huge\rm\centering}`.

1. N.D.T. : avec le chargement de *color* et de son option **french**, ce texte est « Chapitre ».

Aperçu des styles de chapitre

✖

THE chapter styles have default settings for all of the functions described in section 2.1. However, it can be changed using the commands. Note that if `\centering`, etc is used to format the text part of the chapter style then the result can be ugly. The chapter style *Bjarne* contains one additional command

`\TheAlphaChapter`

This command will write the chapter number using the corresponding word. `\TheAlphaChapter` have a capability of writing the words *ZERO* to *NINETYNINE*.

In the following sections the pre-defined styles are shown along with the default settings. Both the `\chapter` and `\chapter*` are given.

3.1 The chapter Sonny

The following settings have been used as default parameters

```
\ChNameVar{\Large\sf} \ChNumVar{\Huge} \ChTitleVar{\Large\sf}
\ChRuleWidth{0.5pt} \ChNameUpperCase
```

Contents	
1 Package description	2
1.1 Basic use and requirements	2
2 Commands provided	3
2.1 Toward customization of the chapter head	3
3 An overview of the chapter styles	5
3.1 The chapter Sonny	5
3.2 The chapter Lemmy	5
3.3 The chapter Glenn	5
3.4 The chapter Gump	6
3.5 The chapter Bjørn	6
3.6 The chapter Bjarne	7
4 An simple example	9

FIGURE 3.1 – The stared chapter style sonny

CHAPTER 1	
Package description	
<p>If this chapter a short introduction of the package will be given. The package has been written in order for me to learn more about L^AT_EX and TEX. There are no idea if this package is written in a good way. Thus, if anyone reads and later find something I would appreciate any feedback, good or bad. The reason is that it will help me gain insight in writing macros.</p> <p>In any publication it is important to remember that consistency plays a important role. That is, with this package one can change the appearance of each chapter in the publication. However, that is not desirable so don't forget modesty and consistency.</p>	
<h3>1.1 Basic use and requirements</h3>	
<p>The package is invoked by writing the following in the preamble of your document</p> <div><code>\usepackage[options]{sonny}</code></div> <p>If the option, <code>options</code>, is omitted then the default definition of chapter is used. There are six predefined chapter styles, namely <i>Sonny</i>, <i>Glenn</i>, <i>Gump</i>, <i>Bjørn</i> and <i>Bjarne</i>. The names corresponds to Swedish given names, almost surely (s.w.). like <i>BREA</i>. Each such style has a default configuration and if that configuration is sufficient, then this is all that is needed.</p> <p>The package does not rely on any other package. However, for the style <i>Lemmy</i> a postscript font is default, but this font can easily be changed. I encourage the use of the default postscript font since it is available in a truly large number, which makes <i>font-gyre</i>.</p>	

FIGURE 3.2 – The chapter style Sonny

3.2 The chapter Lenny

The following settings have been used as default parameters

```
\ChNameVar{\fontsize{14}{16}\usefont{OT1}{phv}{m}{n}\selectfont}
\ChNumVar{\fontsize{60}{62}\usefont{OT1}{ptm}{m}{n}\selectfont}
\ChTitleVar{\Huge\bfseries\rm}, \ChRuleWidth{1pt}
```

Contents

1 Package description	2
1.1 Basic use and requirements	2
2 Commands provided	3
2.1 Toward customization of the chapter head	3
3 An overview of the chapter styles	5
3.1 The chapter Sunny	5
3.2 The chapter Lenny	6
3.3 The chapter Glenn	6
3.4 The chapter Campy	7
3.5 The chapter Bizarre	7
3.6 The chapter Bizarre	8
4 An simple example	9

Chapter 1

Package description

In this chapter a short introduction of the package will be given. The package has been written in order for me to learn more about `BigTeX` and `TeX`. There are often if this package is written in a good way. Thus, if anyone reads and likes `Package description` I would appreciate any feedback, good or bad. The reason is that it will help me gain insight in writing macros.

In any publication it is important to remember that consistency plays a important role. That is, with this package one can change the appearance of each chapter in the publication. However, this is not desirable so don't forget consistency.

1.1 Basic use and requirements

The package is invoked by writing the following in the preamble of your document

```
\usepackage[style]{lenny}
```

If the option `style` is omitted then the default definition of chapter is used. There are six predefined chapter styles, namely `Sunny`, `Glenn`, `Campy`, `Bizarre` and `Bizarre`. The names corresponds to Swedish given names, almost every in `x` like `BREA`. Each style has a default configuration and if that configuration is sufficient, then this is all that is needed.

The package does not rely on any other package. However, for the style `Lenny` a postscript font is default, but this font can easily be changed. I encourage the use of the default postscript font since it is available in a truly large manner, which makes `lenny` better.

Very, rudimentary of Inger Kamper Elmholtz

FIGURE 3.3 – The stored chapter style Lenny

FIGURE 3.4 – The chapter style Lenny

Note : An alternative version of this chapter head exist entitled *PetersLenny*.

3.3 The chapter Glenn

The following settings have been used as default parameters

```
\ChNameVar{\bfseries\Large\sff}, \ChNumVar{\Huge}, \ChTitleVar{\bfseries\Large\rm},
\ChRuleWidth{1pt}, \ChNameUpperCase, \ChTitleUpperCase
```

CONTENTS

1 Package description	2
1.1 Basic use and requirements	2
2 Commands provided	3
2.1 Toward customization of the chapter head	3
3 An overview of the chapter styles	5
3.1 The chapter Sunny	5
3.2 The chapter Lenny	6
3.3 The chapter Glenn	6
3.4 The chapter Campy	7
3.5 The chapter Bizarre	7
3.6 The chapter Bizarre	8
4 An simple example	9

CHAPTER 1

PACKAGE DESCRIPTION

In this chapter a short introduction of the package will be given. The package has been written in order for me to learn more about `BigTeX` and `TeX`. There are often if this package is written in a good way. Thus, if anyone reads and likes `Package description` I would appreciate any feedback, good or bad. The reason is that it will help me gain insight in writing macros.

In any publication it is important to remember that consistency plays a important role. That is, with this package one can change the appearance of each chapter in the publication. However, this is not desirable so don't forget consistency.

1.1 Basic use and requirements

The package is invoked by writing the following in the preamble of your document

```
\usepackage[style]{lenny}
```

If the option `style` is omitted then the default definition of chapter is used. There are six predefined chapter styles, namely `Sunny`, `Glenn`, `Campy`, `Bizarre` and `Bizarre`. The names corresponds to Swedish given names, almost every in `x` like `BREA`. Each style has a default configuration and if that configuration is sufficient, then this is all that is needed.

The package does not rely on any other package. However, for the style `Lenny` a postscript font is default, but this font can easily be changed. I encourage the use of the default postscript font since it is available in a truly large manner, which makes `lenny` better.

Very, rudimentary of Inger Kamper Elmholtz

FIGURE 3.5 – The stored chapter style Glenn

FIGURE 3.6 – The chapter style Glenn

3.4 The chapter Conny

The following settings have been used as default parameters

```
\ChNameUpperCase \ChTitleUpperCase \ChNameVar{\centering\Huge\rm\bfseries}
\ChNumVar{\Huge} \ChRuleWidth{2pt} \ChTitleVar{\centering\Huge\rm}
```

CONTENTS	
1 Package description	2
1.1 Basic use and requirements	2
2 Commands provided	3
2.1 Forward introduction of the chapter head	3
3 An overview of the chapter styles	5
3.1 The chapter Sonny	5
3.2 The chapter Lemmy	5
3.3 The chapter Olm	5
3.4 The chapter Conny	6
3.5 The chapter Rejne	6
3.6 The chapter Blarne	7
4 An simple example	9

FIGURE 3.7 – The stared chapter style Conny

CHAPTER 1	
PACKAGE DESCRIPTION	
<p>This chapter a short introduction of the package will be given. The package has been written in order for me to learn more about \TeX and \LaTeX. I have no idea if this package is written in a good way. Thus, if anyone reads and starts <i>For the printer</i> I would appreciate any feedback, good or bad. The reason is that it will help me gain insight in writing macros.</p> <p>In any publication it is important to remember that consistency plays a important role. That is, with this package one can change the appearance of each chapter in the publication. However, this is not desirable so don't forget modesty and consistency.</p>	
<h3>1.1 Basic use and requirements</h3>	
<p>The package is loaded by writing the following in the preamble of your document</p>	
<pre>\usepackage[style]{forchapter}</pre>	
<p>If the option, <i>style</i>, is omitted then the default definition of chapter is used. There are six predefined chapter styles, namely <i>Sonny</i>, <i>Leomy</i>, <i>Olm</i>, <i>Conny</i>, <i>Rejne</i> and <i>Blarne</i>. The names corresponds to Swedish given names, almost every boy is like <i>Olle</i>. Each such style has a default configuration and if this configuration is sufficient, then this is all that is needed.</p> <p>The package does not rely on any other package. However, for the style <i>Lenny</i> a postscript font is default, but this font can easily be changed. I encourage the use of the default postscript font since it is available in a very large manner, which makes <i>Lenny</i> quite.</p>	
<p>For the printer of paper formatted in \LaTeX also</p>	

FIGURE 3.8 – The chapter style Conny

3.5 The chapter Rejne

The following settings have been used as default parameters

```
\ChNameVar{\centering\Huge\rm\bfseries}, \ChNumVar{\Huge}, \ChTitleVar{\centering\Huge\rm}
\ChNameUpperCase, \ChTitleUpperCase, \ChRuleWidth{1pt}
```

CONTENTS	
1 Package description	2
1.1 Basic use and requirements	2
2 Commands provided	3
2.1 Forward introduction of the chapter head	3
3 An overview of the chapter styles	5
3.1 The chapter Sonny	5
3.2 The chapter Lemmy	5
3.3 The chapter Olm	5
3.4 The chapter Conny	6
3.5 The chapter Rejne	7
3.6 The chapter Blarne	7
4 An simple example	9

FIGURE 3.9 – The stared chapter style Rejne

CHAPTER 1	
PACKAGE DESCRIPTION	
<p>This chapter a short introduction of the package will be given. The package has been written in order for me to learn more about \TeX and \LaTeX. I have no idea if this package is written in a good way. Thus, if anyone reads and starts <i>For the printer</i> I would appreciate any feedback, good or bad. The reason is that it will help me gain insight in writing macros.</p> <p>In any publication it is important to remember that consistency plays a important role. That is, with this package one can change the appearance of each chapter in the publication. However, this is not desirable so don't forget modesty and consistency.</p>	
<h3>1.1 Basic use and requirements</h3>	
<p>The package is loaded by writing the following in the preamble of your document</p>	
<pre>\usepackage[style]{forchapter}</pre>	
<p>If the option, <i>style</i>, is omitted then the default definition of chapter is used. There are six predefined chapter styles, namely <i>Sonny</i>, <i>Leomy</i>, <i>Olm</i>, <i>Conny</i>, <i>Rejne</i> and <i>Blarne</i>. The names corresponds to Swedish given names, almost every boy is like <i>Olle</i>. Each such style has a default configuration and if this configuration is sufficient, then this is all that is needed.</p> <p>The package does not rely on any other package. However, for the style <i>Lenny</i> a postscript font is default, but this font can easily be changed. I encourage the use of the default postscript font since it is available in a very large manner, which makes <i>Lenny</i> quite.</p>	
<p>For the printer of paper formatted in \LaTeX also</p>	

FIGURE 3.10 – The chapter style Rejne

3.6 The chapter Bjarne

The following settings have been used as default parameters

```
\ChNameUpperCase \ChNameVar{\raggedleft\normalsize\rm} \ChRuleWidth{1pt}
\ChTitleUpperCase \ChNumVar{\raggedleft \bfseries\Large} \ChTitleVar{\raggedleft \Large\rm}
```

CONTENTS

1 Package description	2
1.1 Basic use and requirements	3
2 Commands provided	3
2.1 Toward examination of the chapter head	3
3 An overview of the chapter styles	5
3.1 The chapter Bjarne	5
3.2 The chapter Lemmy	6
3.3 The chapter Glim	6
3.4 The chapter Camy	7
3.5 The chapter Bjorne	7
3.6 The chapter Bjorne	8
4 An simple example	9

FIGURE 3.11 – The stared chapter style Bjarne

CHAPTER
ONE

PACKAGE DESCRIPTION

If the option, `style`, is omitted then the default definition of chapter is used. There are six predefined chapter styles, namely `Bjarne`, `Lemmy`, `Glim`, `Camy`, `Bjorne` and `Bjorne`. The names corresponds to Swedish given names, almost surely (s.e.) like IKEA¹. Each such style has a default configuration and if that configuration is sufficient, then this is all that is needed. The package does not rely on any other package. However, for the style `Lemmy` a postscript font is needed, but this font can easily be changed. I encourage the use of the default postscript font since it is available in a truly huge manner, which makes `Lemmy` nice.

¹reg. trademark of Ingvar Kamprad Emtekt AB, Sweden

FIGURE 3.12 – The chapter style Bjarne

3.7 The chapter Bjornstrup

The following settings have been used as default parameters

```
\ChNumVar{\fontsize{76}{80}\usefont{OT1}{pzc}{m}{n}\selectfont}
\ChTitleVar{\raggedleft\Large\sffamily\bfseries}
```

Contents

1 Package description	2
1.1 Basic use and requirements	2
2 Commands provided	3
2.1 Toward examination of the chapter head	3
3 An overview of the chapter styles	5
3.1 The chapter Lemmy	5
3.2 The chapter Glim	6
3.3 The chapter Camy	6
3.4 The chapter Bjorne	7
3.5 The chapter Bjorne	7
3.6 The chapter Bjorne	8
4 An simple example	9
5 Revision details	11

FIGURE 3.13 – The stared chapter style Bjornstrup

1

Package description

The package `flapchp` has been written such that chapter level headings can be altered fast and for me to learn more about `PDFX` and `PDF`. I have no idea if this package is written in a good way. Thus, if anyone reads and tries `flapchp` I would appreciate any feedback. This will help me gain insight in writing macros.

In any publication it is important to remember that consistency plays a important role. That is, with this package one can change the appearance of each chapter in the publication. However, this is not desirable so don't forget modesty and consistency.

1.1 Basic use and requirements

The package is invoked by writing the following in the preamble of your document

```
\usepackage{flapchp}[flapchp]
```

If the option, `style`, is omitted then the default definition of chapter is used. Originally there were six predefined chapter styles, namely `Lemmy`, `Glim`, `Camy`, `Bjorne` and `Bjorne`. The names corresponds to Swedish given names, almost surely (s.e.) like IKEA¹. Each such style has a default configuration and if that configuration is sufficient, then this is all that is needed.

In the present release of `flapchp` two additional chapter definitions have been included. The first of these is named `PeterLemmy`, after the author Peter Olsson. This chapter definition is based on `Lemmy`. Peter has carefully reviewed the appearance of the book individually for each chapter (up to 20) and each appendix (up to 2). The second chapter head is a new one defined by Jean-Marc Francois and he named it `Bjornstrup`.

Originally, `flapchp` did not rely on any other package. However, for the style `Lemmy` a postscript font is needed, but this font can easily be changed. I encourage the use of the default postscript font since it is available in a truly huge manner, which makes `Lemmy` nice. In the current release and with the use of Jean-Marc `Bjornstrup` the other package from the base distribution will be invoked.

¹reg. trademark of Ingvar Kamprad Emtekt AB, Sweden

FIGURE 3.14 – The chapter style Bjornstrup

Note : It appears as if the rendering in YAP (dvi previewer in MikTeX) differs from dvips in that the gray box become foreground. Thus, the chapter number is partly hidden.

Chapitre 4

A simple example

If the pre defined styles does not fulfill your needs then you can modify the formating routines. The formatting is controlled by three commands. One might as well redefine the original chapter definitions using the `\secdef` and `\renewcommand`, see The L^AT_EX companion. However, at the time of creating this package I decided that this was easier. The command

```
\DOCH
```

formats the chapter name and number. The commands

```
\DOTI{#1}
```

and

```
\DOTIS{#1}
```

formats the chapter title for `\chapter` and `\chapter*` respectively. In order to modify these you will have to use the preamble along with the commands `\makeatletter` and `\makeatother`. The in addition some predefined parameters can be used. The predefined length variables are

```
\mylen, \myhi, \px, \py, \pxx, \pyy and \RW
```

note that `\RW` is special, since it is set by `\ChRuleWidth`. The formatting controlled by `\ChNameVar`, `\ChNumVar` and `\ChTitleVar` store their values in `\CNV`, `\CNoV` and `\CTV` respectively. Finally, The functions `\FmN{ }` and `\FmTi{ }` acts accordingly to `\Ch***AsIs`, `\Ch***UpperCase` and `\Ch***LowerCase`. Note that the stars indicate appropriate substitution of text, see section 2.1.

To illustrate this lets define a new chapter style in which the Chapter name and number in a `\fbox` and the chapter title centered. The `\fboxrule` is linked to the predefined length `\RW` so that it can be controlled by the command `\ChRuleWidth`. Try this example at a computer near you.

```
\makeatletter
\ChNameVar{\Large\rm}      % sets the style for name
\ChNumVar{\Huge}           % sets the style for digit
\ChTitleVar{\Large\rm\centering} % sets the style for title
\ChRuleWidth{4pt}         % Set RW=4pt
\ChNameUpperCase           % Make name uppercase
\renewcommand{\DOCH}{%
  \setlength{\fboxrule}{\RW} % Let fbox lines be controlled by
                             % \ChRuleWidth

  \fbox{\CNV\FmN{\@chapapp}\space \CNoV\thechapter}\par\nobreak
  \vskip 40\p@}
```

```

\renewcommand{\DOTI}[1]{%
  \CTV\FmTi{#1}\par\nobreak
  \vskip 40\p@}
\renewcommand{\DOTIS}[1]{%
  \CTV\FmTi{#1}\par\nobreak
  \vskip 40\p@}
\makeatother

```

That is all there is to it. Note that the commands `\DOTI` and `\DOTIS` can be redefined anywhere in the document, but that is not a good idea. Suppose that you want to use the `\TheAlphaChapter`. This can be done by initially chose the style *Bjarne* and then redefine `\DOCH`, `\DOTI` and `\DOTIS`.

Revision details

THIS is version 1.34, some minor problems have been addressed and two new predefined chapter heads have been incorporated. The upper case and lower case handling have been corrected. A bad behavior in changes between `\frontmatter`, `\mainmatter` and `\backmatter`, have been fixed.

In version 1.33 Rejne definition stretched text caused ugly gaps in the vrule aligned with the title text. A compatibility problem with the KOMA class 'scrbook.cls' the remedy is a redefinition of 'schapter' in line with that used in KOMA. This might not be good since it differs from the base definition. A spell error was corrected.

In version 1.3, a problem with appendices in the Bjarne style was corrected. Wrong behavior, for the commands `\frontmatter`, `\mainmatter` and `\backmatter` was dealt with.

In the release 1.11 of the current package. A bug fix of the Lenny option was included. The problem, reported by Diab Jerius, occurred (underfull vbox) when the option Lenny was used in conjunction with `\section`-command such that the section is typeset at the next page. This caused one line to be misplaced. The remedy was to box the chapter title.

In the release (1.1) of the current package. A modification was made such that it will work with the book class. The problem occurred when the fncychap styles Conny, Rejne, Bjarne or Glenn were used in conjunction with the L^AT_EX command `\tableofcontents`. The exact reason for the error is not yet found. The problem was reported by Olivier Guibe.

In the prior release there were no major improvements of the package. However, the package name was changed in order to conform with the (DOS) requirement of eight characters. I also received some feedback, informing me that the L^AT_EX base have to be post 1994/12/01. This information has been included in the package such that if an old base is used a warning will be written into the log.

Release history :

- Release 1** 1996/12/13 FancyChapters 1.0b
- Release 2** 1997/01/08 FncyChap 1.0 (Name change, base date option)
- Release 3** 1997/01/22 FncyChap 1.1 (Bug fix)
- Release 4** 1997/04/06 FncyChap 1.11 (Bug fix)
- Release 5** 2004/09/20 FncyChap 1.3 (Bug fix)
- Release 6** 2005/08/09 FncyChap 1.33 (Bug fix)
- Release 7** 2007/07/31 FncyChap 1.34 (Bug fix)