

L'extension xkeyval *

Hendri Adriaens

v2.7a (2014/12/03)

Résumé

Cette extension développe l'extension keyval et offre des commandes plus flexibles pour définir et assigner des valeurs à des clés. Elle fournit un système de pointeur et de prédéfinition. De plus, elle propose des commandes permettant aux classes et options d'extension de contenir des options de la forme clé=valeur. Un patch au noyau L^AT_EX est fourni pour éviter un développement prématuré des commandes dans les options de classe ou d'extension. Un système spécialisé pour assigner les clés PSTricks est donné par l'extension pst-xkey.

Contents

1	Introduction	2	10	Codes de catégorie	22
2	Chargement de xkeyval	3	11	Problèmes connus	23
3	Définition et gestion des clés	4	12	Extensions additionnelles	24
3.1	Clés ordinaires	4	12.1	xkvview	24
3.2	Clés commandes	5	12.2	xkvltxp	26
3.3	Clés à choix	6	12.3	pst-xkey	26
3.4	Clés booléennes	7	13	Exemples et documentation	27
3.5	Clés de vérification	8	14	Implémentation	28
3.6	Clés désactivantes	8	14.1	xkeyval.tex	28
4	Assignation des clés	9	14.2	xkeyval.sty	47
4.1	L'interface utilisateur	9	14.3	keyval.tex	51
4.2	Quelques détails	11	14.4	xkvtxhdr.tex	52
5	Pointeurs	12	14.5	xkvutils.tex	53
5.1	Sauvegarde de valeurs	12	14.6	xkvview.sty	61
5.2	Utilisation des valeurs sau- vegardées	13	14.7	xkvltxp.sty	65
6	Prédéfinition des clés	15	14.8	pst-xkey.tex	67
7	Traitement des options	17	14.9	pst-xkey.sty	68
8	Structures de commande	20	Références	68	
9	Alertes et erreurs	21	Remerciements	69	
			Historique	69	
			Index	71	

* Cette extension peut être téléchargée sur les sites miroirs du CTAN : [/macros/latex/contrib/xkeyval](http://macros/latex/contrib/xkeyval). Voir xkeyval.dtx pour plus d'informations sur l'installation de xkeyval dans votre distribution de T_EX ou L^AT_EX et sur la licence de cette extension.

1 Introduction

Cette extension développe l'extension `keyval` de David Carlisle et offre des commandes plus flexibles pour définir et assigner des valeurs à des clés. Se servir de clés dans la définition de la commande permet d'éviter les 9 arguments maximum et de réduire la confusion dans la syntaxe de votre commande comparé à ce que donne l'utilisation d'un grand nombre d'arguments (optionnels). Comparez par exemple les syntaxes possibles suivantes de la commande `\maboite` qui peut utiliser par exemple ses arguments pour dessiner une boîte contenant du texte.

```
\mybox[5pt][20pt]{some text}[red][white][blue]
\mybox[text=red,background=white,frame=blue,left=5pt,right=20pt]{some text}
```

Notez que pour être en mesure de spécifier le cadre coloré dans le premier exemple, il faut spécifier les autres couleurs. Ceci n'est pas nécessaire dans le second exemple et ces couleurs peuvent avoir des valeurs prédéfinies. Ces constats valent aussi pour les marges.

L'idée est que cette dernière fonction définit d'abord un ensemble de clés en utilisant les outils présentés en section 3 dans le préambule du document, dans une extension ou dans une classe. Ces clés peuvent effectuer une action selon la saisie de l'utilisation. La manière de soumettre la saisie de l'utilisateur aux commandes-clés se fait par l'utilisation de l'une des interfaces utilisateur décrites dans les sections 4, 5 et 6. La principale interface est fournie par la commande `\setkeys`. Par le biais de ces interfaces, il devient possible de simplifier la syntaxe des commandes et de définir par exemple la commande `\mybox` ci-dessus comme suit :

```
\define@key{mybox}{left}{\setlength\myleft{#1}}
\define@key{mybox}{background}{\def\background{#1}}
% et quelques autres clés
\def\mybox{\@ifnextchar[\@mybox{\@mybox[]}}
\def\@mybox[#1]#2{%
  \setkeys{mybox}{#1}%
  % quelques opérations pour composer #2
}
```

Notez que la combinaison de deux définitions `\mybox` et `\@mybox` peut être remplacée par `\newcommand\mybox[2][]{...}` en utilisant \LaTeX .

Les clés définies en utilisant `keyval` et `xkeyval` peuvent être gérées par cette extension. Les commandes de `xkeyval` permettent de passer en revue plusieurs ensembles (appelés « familles ») de clés. Ceci peut être utilisé, par exemple, pour créer des familles locales pour des commandes et des environnements qui ne peuvent pas accéder à des clés destinées à d'autres macros et environnements alors qu'en même temps une unique commande peut être utilisée pour (pré)configurer toutes les clés des différentes familles globalement.

L'extension est compatible avec le format *plain* de \TeX et redéfinit plusieurs commandes de `keyval` de fournir un moyen facile de basculer entre `keyval` et `xkeyval`. Cela pourrait être utile pour les auteurs d'extension qui ne peuvent pas encore compter sur la disponibilité de `xkeyval` dans certaines distributions. Après le chargement de `xkeyval`, le chargement `keyval` est empêché pour faire en sorte que les macros étendues de `xkeyval` ne seront pas redéfinies. Certaines commandes internes de `keyval` sont fournies dans le `keyval.tex` pour garantir la compatibilité avec les extensions qui utilisent ces commandes. La section 11 apporte plus d'informations sur ce sujet.

L'organisation de cette documentation est la suivante. La section 2 explique comment charger `xkeyval` et ce que l'extension fait quand il est chargé. La section 3 pré-

sente les commandes disponibles pour définir et gérer les clés. La section 4 poursuit en décrivant les commandes qui peuvent configurer les clés. La section 5 explique la syntaxe spéciale qui permet de sauvegarder et de copier les valeurs de clé. Dans la section 6, le système de préconfiguration est introduit. La section 10 explique comment `xkeyval` se protège des changements de code de catégorie de la virgule et du signe d'égalité faits par d'autres extensions. L'extension `xkeyval` fournit également des commandes pour déclarer et traiter des options de classe et d'extension qui peuvent prendre des valeurs : celles-ci sont examinées à la section 7. La section 8 donne un aperçu des structures ayant servi à créer les commandes internes de `xkeyval` traitant les clés, leurs valeurs, leurs préréglages, etc. Les sections 9 et 11 discutent respectivement des retours que peut faire l'extension `xkeyval` et des problèmes connus. La section 12 évoque plusieurs extensions complémentaires fournies avec `xkeyval`. La section 12.1 présente un utilitaire générant une vue d'ensemble des clés définies. Une extension du noyau de \TeX par rapport au système d'options de classes et d'extension est discutée dans la section 12.2. Cette extension fournit un moyen d'utiliser des commandes développables dans les options d'extension. La section 12.3 présente l'extension `pst-xkey` qui met à disposition un système d'options basé sur `xkeyval`, mais qui est spécialisée dans l'instanciation des clés de `PSTricks`.

Tout au long de cette documentation, vous trouverez des exemples avec une courte description. D'autres exemples peuvent être trouvés dans les fichiers d'exemples fournis avec cette extension. Voir la section 13 pour plus d'informations. Cette section fournit également les informations sur la façon de générer la documentation complète à partir du fichier source.

2 Chargement de `xkeyval`

✖To load the `xkeyval` package,¹ plain \TeX users do `\input xkeyval`. \LaTeX users do one of the following : `\usepackage{xkeyval}` or `\RequirePackage{xkeyval}`. The package does not have options. It is mandatory for \LaTeX users to load `xkeyval` at any point after the `\documentclass` command. Loading `xkeyval` from the class which is the document class itself is possible. The package will use the ϵ - \TeX engine when available. In particular, `\ifcstype` is used whenever possible to avoid filling \TeX 's hash tables with useless entries, for instance when searching for keys in families.

If `xkeyval` is loaded by `\RequirePackage` or `\usepackage`, the package performs two action immediately. These require `xkeyval` to be loaded at any point after `\documentclass` or by the document class itself.

First, it retrieves the document class of the document at hand and stores that (including the class extension) into the following macro.

```
\XKV@documentclass
```

`\XKV@documentclass` This macro could, for instance, contain `article.cls` and can be useful when using `\ProcessOptionsX*` in a class. See page 19.

Secondly, the global options submitted to the `\documentclass` command and stored by \LaTeX in `\@classoptionslist` are copied to the following macro.

```
\XKV@classoptionslist
```

`\XKV@classoptionslist` This macro will be used by `\ProcessOptionsX`. Options containing an equality sign

1. The `xkeyval` package consists of the files `xkeyval.tex`, `xkeyval.sty`, `keyval.tex`, `xkvtxhdr.tex`.

are deleted from the original list in `\@classoptionslist` to avoid packages, which do not use `xkeyval` and which are loaded later, running into problems when trying to copy global options using \LaTeX 's `\ProcessOptions`.

✖

3 Définition et gestion des clés

✖ This section discusses macros to define keys and some tools to manage keys. A useful extension to `xkeyval` is the `xkvview` package. This package defines commands to generate overviews of defined keys. See section 12.1 for more information.

✖

3.1 Clés ordinaires

✖ This section describes how to define ordinary keys.

```
\define@key [<prefix>]{<family>}{<key>}[<default>]{<function>}
```

`\define@key` This defines a macro of the form `\<prefix>@<family>@<key>` with one argument holding `<function>`. The default value for `<prefix>` is `KV`. This is the standard throughout the package to simplify mixing `keyval` and `xkeyval` keys. When `<key>` is used in a `\setkeys` command (see section 4) containing `key=value`, the macro `\<prefix>@<family>@<key>` receives `value` as its argument and will be executed. The argument can be accessed by `<function>` by using `#1` inside the function.

```
\define@key{family}{key}{The input is: #1}
```

`xkeyval` will generate an error when the user omits `=value` for a key in the options list of `\setkeys` (see section 4). To avoid this, the optional argument can be used to specify a default value.

```
\define@key{family}{key}[none]{The input is: #1}
```

This will additionally define a macro `\<prefix>@<family>@<key>@default` as a macro with no arguments and definition `\<prefix>@<family>@<key>{none}` which will be used when `=value` is missing for `key` in the options list. So, the last example comes down to doing

```
\def\KV@family@key#1{The input is: #1}
\def\KV@family@key@default{\KV@family@key{none}}
```

When `<prefix>` is specified and empty, the macros created by `\define@key` will have the form `\<family>@<key>`. When `<family>` is empty, the resulting form will be `\<prefix>@<key>`. When both `<prefix>` and `<family>` are empty, the form is `\<key>`. This combination of prefix and family will be called the header. The rules to create the header will be applied to all commands taking (optional) prefix and family arguments.

The intended use for `<family>` is to create distinct sets of keys. This can be used to avoid a macro setting keys meant for another macro only. The optional `<prefix>` can be used to identify keys specifically for your package. Using a package specific prefix reduces the probability of multiple packages defining the same key macros. This optional argument can also be used to set keys of some existing packages which use a

system based on keyval.²

We now define some keys to be used in examples throughout this documentation.

```
\define@key[my]{familya}{keya}[default]{#1}  
\define@key[my]{familya}{keyb}{#1}  
\define@key[my]{familyb}{keyb}{#1}  
\define@key[my]{familya}{keyc}{#1}
```

✕

3.2 Clés commandes

✕Command keys are specialized keys that, before executing any code, save the user input to a macro.

```
\define@cmdkey[⟨prefix⟩]{⟨family⟩}[⟨mp⟩]{⟨key⟩}[⟨default⟩]{⟨function⟩}
```

`\define@cmdkey` This has the effect of defining a key macro of the form `\⟨prefix⟩@⟨family⟩@⟨key⟩` that, when used, first saves the user input to a macro of the form `\⟨mp⟩⟨key⟩` and then executes `⟨function⟩`. `⟨mp⟩` is the macro prefix. If `⟨mp⟩` is not specified, the usual combination of `⟨prefix⟩` and `⟨family⟩`, together with the extra prefix `cmd`, will be used to create the macro prefix, namely `\cmd⟨prefix⟩@⟨family⟩@`.³ The two keys in the following example hence do exactly the same thing.⁴

```
\define@cmdkey{fam}{key}[none]{value: \cmdKV@fam@key}  
\define@key{fam}{key}[none]{\def\cmdKV@fam@key{#1}value: \cmdKV@fam@key}
```

The value `none` is again the default value that will be submitted to the key macro when the user didn't supply a value. (See also section 3.1 for more information.)

The following two lines also implement a key with the same key macro.

```
\define@cmdkey{fam}[my@]{key}[none]{value: \my@key}  
\define@key{fam}{key}[none]{\def\my@key{#1}value: \my@key}
```

Note that the key macro itself in the examples above is still `\KV@fam@key`, just as in the previous example.

A lot of packages define keys that only save their value to a macro so that it can be used later. Using the macro above, one can save some tokens in the package. Some more tokens can be saved by using the following macro.

```
\define@cmdkeys[⟨prefix⟩]{⟨family⟩}[⟨mp⟩]{⟨keys⟩}[⟨default⟩]
```

`\define@cmdkeys` This repeatedly calls (an internal of) `\define@cmdkey` for all keys in the list of `⟨keys⟩`. Note that it is not possible to specify a custom key function for the keys created by this command. The only function of those keys is to save user input in a macro. The first line and the last two lines of the following example create keys with the same internal key macro.

```
\define@cmdkeys{fam}[my@]{keya,keyb}[none]  
\define@key{fam}{keya}[none]{\def\my@keya{#1}}  
\define@key{fam}{keyb}[none]{\def\my@keyb{#1}}
```

2. Like PStricks, which uses a system originating from keyval, but which has been modified to use no families and `psset` as prefix.

3. Remember that some rules are applied when creating the header, the combination of `⟨prefix⟩` and `⟨header⟩`. See section 3.1.

4. Notice however, that the first key will be listed as a 'command key' by `xkvview` and the second as an 'ordinary key'. See section 12.1.



3.3 Clés à choix

✖Choice keys allow only a limited number of different values for user input. These keys are defined as follows.

```
\define@choicekey[⟨pre⟩]{⟨fam⟩}{⟨key⟩}[⟨bin⟩]{⟨al⟩}[⟨dft⟩]{⟨func⟩}
\define@choicekey* [⟨pre⟩]{⟨fam⟩}{⟨key⟩}[⟨bin⟩]{⟨al⟩}[⟨dft⟩]{⟨func⟩}
```

`\define@choicekey`
`\define@choicekey*`

The keys work the same as ordinary keys, except that, before executing anything, it is verified whether the user input #1 is present in the comma separated list `⟨al⟩`. The starred version first converts the input in #1 and `⟨al⟩` to lowercase before performing the check. If the input is not allowed, an error is produced and the key macro `⟨func⟩` will not be executed. If the input is allowed, the key macro `⟨func⟩` will be executed. `⟨dft⟩` is submitted to the key macro when the user didn't supply a value for the key. (See also section 3.1.)

The optional `⟨bin⟩` should contain either one or two control sequences (macros). The first one will be used to store the user input used in the input check (hence, in lowercase when the starred version was used). The original user input will always be available in #1. The second (if present) will contain the number of the input in the `⟨al⟩` list, starting from 0. The number will be set to -1 if the input was not allowed. The number can, for instance, be used in a `\ifcase` statement in `⟨func⟩`.

```
\define@choicekey*{fam}{align}[\val\nr]{left,center,right}{%
  \ifcase\nr\relax
    \raggedright
  \or
    \centering
  \or
    \raggedleft
  \fi
}
```

The example above only allows input values `left`, `center` and `right`. Notice that we don't need a `\else` case in the key macro above as the macro will not be executed when the input was not allowed.

```
\define@choicekey+ [⟨pre⟩]{⟨fam⟩}{⟨key⟩}[⟨bin⟩]{⟨al⟩}[⟨dft⟩]{⟨f1⟩}{⟨f2⟩}
\define@choicekey*+ [⟨pre⟩]{⟨fam⟩}{⟨key⟩}[⟨bin⟩]{⟨al⟩}[⟨dft⟩]{⟨f1⟩}{⟨f2⟩}
```

`\define@choicekey+`
`\define@choicekey*+`

These macros operate as their counterparts without the `+`, but allow for specifying two key macros. `⟨f1⟩` will be executed when the input was correct and `⟨f2⟩` will be executed when the input was not allowed. Again, the starred version executes the check after converting user input and `⟨al⟩` to lowercase.

```
\define@choicekey*+{fam}{align}[\val\nr]{left,center,right}{%
  \ifcase\nr\relax
    \raggedright
  \or
    \centering
  \or
    \raggedleft
  \fi
}{%
  \PackageWarning{mypack}{erroneous input ignored}%
}
```

The example above defines a key that is similar as the one in the previous example, but when input is not allowed, it will not generate a standard `xkeyval` warning, but will execute a custom function, which, in this case, generates a warning.

```
\XKV@cc[⟨bin⟩]{⟨input⟩}{⟨al⟩}{⟨func⟩}
\XKV@cc*[⟨bin⟩]{⟨input⟩}{⟨al⟩}{⟨func⟩}
\XKV@cc+[⟨bin⟩]{⟨input⟩}{⟨al⟩}{⟨func1⟩}{⟨func2⟩}
\XKV@cc*+[⟨bin⟩]{⟨input⟩}{⟨al⟩}{⟨func1⟩}{⟨func2⟩}
```

`\XKV@cc` Choice keys work by adding (an internal version⁵ of) the `\XKV@cc` macro to key macros. This macro has similar arguments as the `\define@choicekey` macro and the optional `*` and `+` have the same meaning. `⟨input⟩` holds the input that should be checked, namely, whether it is (in lowercase if `*` was used) in the list `⟨al⟩`. One can use this macro to create custom choice keys. See an example below.

```
\define@key{fam}{key}{%
  I will first check your input, please wait.\\
  \XKV@cc*+[⟨val⟩]{#1}{true,false}{%
    The input ⟨val⟩ was correct, we proceed.\\
  }{%
    The input ⟨val⟩ was incorrect and was ignored.\\
  }%
  I finished the input check.
}
```

Try to find out why this key cannot be defined with `\define@boolkey` which is introduced in the next section.

✖

3.4 Clés booléennes

✖ This section describes boolean keys which can be either true or false. A boolean key is a special version of a choice key (see section 3.3), where `⟨al⟩` takes the value `true`, `false` and comparisons are always done in lowercase mode (so, `True` is allowed input).

```
\define@boolkey[⟨pre⟩]{⟨fam⟩}{⟨mp⟩}{⟨key⟩}[⟨default⟩]{⟨func⟩}
\define@boolkey+[⟨pre⟩]{⟨fam⟩}{⟨mp⟩}{⟨key⟩}[⟨default⟩]{⟨func1⟩}{⟨func2⟩}
```

`\define@boolkey` This creates a boolean of the form `\if⟨pre⟩@⟨family⟩@⟨key⟩`^{3 6} if `⟨mp⟩` is not specified, using `\newif`⁷ (which initiates the conditional to `\iffalse`) and a key macro of the form `\⟨pre⟩@⟨family⟩@⟨key⟩` which first checks the validity of the user input. If the input was valid, it uses it to set the boolean and afterwards, it executes `⟨func⟩`. If the input was invalid, it will not set the boolean and `xkeyval` will generate an error. If `⟨mp⟩` is specified, it will create boolean of the form `\if⟨mp⟩⟨key⟩` (compare to command keys in section 3.2). The value `⟨default⟩` will be used by the key macro when the user didn't submit a value to the key. (See also section 3.1.)

5. See section 14 for details of the implementation of choice keys.

6. When you want to use this macro directly, either make sure that neither of the input parameters contain characters with a catcode different from 11 (hence no `-` for instance), reset the catcode of the offending characters internally to 11 or use `\csname... \endcsname` to construct macro names, (for instance, `\csname ifpre@some-fam@key\endcsname`). See for more information section 8.

7. The \LaTeX implementation `\newif` is used because it can be used in the replacement text of a macro, whereas the plain \TeX `\newif` is defined `\outer`.

If the + version of the macro is used, one can specify two key macros. If user input is valid, the macro will set the boolean and executes *func1*. Otherwise, it will not set the boolean and execute *func2*.

```
\define@boolkey{fam}[my@]{frame}{%
\define@boolkey+{fam}{shadow}{%
  \ifKV@fam@shadow
    \PackageInfo{mypack}{turning shadows on}%
  \else
    \PackageInfo{mypack}{turning shadows off}%
  \fi
}{%
\PackageWarning{mypack}{erroneous input ignored}%
}
```

The first example creates the boolean `\ifmy@frame` and defines the key macro `\KV@fam@frame` to only set the boolean (if input is correct). The second key informs the user about changed settings or produces a warning when input was incorrect.

One can also define multiple boolean keys with a single command.

```
\define@boolkeys[<pre>]{<fam>}[<mp>]{<keys>}[<default>]
```

`\define@boolkeys` This macro creates a boolean key for every entry in the list *keys*. As with the command `\define@cmdkeys`, the individual keys cannot have a custom function. The boolean keys created with this command are only meant to set the state of the boolean using the user input. Concluding,

```
\define@boolkeys{fam}[my@]{keya,keyb,keyc}
```

is an abbreviation for

```
\define@boolkey{fam}[my@]{keya}{%
\define@boolkey{fam}[my@]{keyb}{%
\define@boolkey{fam}[my@]{keyc}{%
```

✖

3.5 Clés de vérification

✖

```
\key@ifundefined[<prefix>]{<families>}{<key>}{<undefined>}{<defined>}
```

`\key@ifundefined` This macro executes *undefined* when *key* is not defined in a family listed in *families* using *prefix* (which is KV by default) and *defined* when it is. If *defined* is executed, `\XKV@tfam` holds the first family in the list *families* that holds *key*. If *undefined* is executed, `\XKV@tfam` contains the last family of the list *families*.

```
\key@ifundefined[my]{familya,familyb}{keya}{'keya' not defined}{'keya' defined}
```

This example results in 'keya' defined and `\XKV@tfam` holds *familya*.

✖

3.6 Clés désactivantes

✖ It is also possible to disable keys after use as to prevent the key from being used again.


```
\disable@keys[\<prefix>]{\<family>}{\<keys>}
```

\disable@keys When you disable a key, the use of this key will produce a warning in the log file. Disabling a key that hasn't been defined will result in an error message.

```
\disable@keys[my]{familya}{keya,keyb}
```

This would make keya and keyb produce a warning when one tries to set these keys.

✖

4 Assignment des clés

4.1 L'interface utilisateur

✖ This section describes the available macros for setting keys. All of the macros in this section have an optional argument *<prefix>* which determines part of the form of the keys that the macros will be looking for. See section 3. This optional argument takes the value KV by default.

```
\setkeys[\<prefix>]{\<families>}[\<na>]{\<keys>}
```

\setkeys This macro sets keys of the form $\backslash\langle prefix \rangle @ \langle family \rangle \langle key \rangle$ ³ where *<family>* is an element of the list *<families>* and key is an element of the options list *<keys>* and not of *<na>*. The latter list can be used to specify keys that should be ignored by the macro. If a key is defined by more families in the list *<families>*, the first family from the list defining the key will set it. No errors are produced when *<keys>* is empty. If *<family>* is empty, the macro will set keys of the form $\backslash\langle prefix \rangle @ \langle key \rangle$. If *<prefix>* is specified and empty, the macro will set keys of the form $\backslash\langle family \rangle @ \langle key \rangle$. If both *<prefix>* and *<family>* are empty, the macro will set keys of the form $\backslash\langle key \rangle$.

```
\setkeys[my]{familya,familyb}{keya=test}
\setkeys[my]{familya,familyb}{keyb=test}
\setkeys[my]{familyb,familya}{keyb=test}
```

In the example above, line 1 will set keya in family familya. This effectively means that the value test will be submitted to the key macro `\my@familya@keya`. The next line will set keyb in familya. The last one sets keyb in family familyb. As the keys used here, directly output their value, the above code results in typesetting the word test three times.

When input is lacking for a key, `\setkeys` will check whether there is a default value for that key that can be used instead. If that is not the case, an error message will be generated. See also section 3.

```
\setkeys[my]{familya}{keya}
\setkeys[my]{familya}{keyb}
```

The first line of the example above does not generate an error as this key has been defined with a default value (see section 3.1). The second line does generate an error message. See also section 9 for all possible error messages generated by `xkeyval`.

When you want to use commas or equality signs in the value of a key, surround the value by braces, as shown in the example below.

```
\setkeys[my]{familya}{keya={some=text,other=text}}
```

It is possible to nest `\setkeys` commands in other `\setkeys` commands or in key definitions. The following, for instance,

```
\define@key[my]{familyb}{keyc}{#1}
\setkeys[my]{familyb}{keyc=a\setkeys[my]{familya}{keya=~and b},keyb=~and c}
```

returns a and b and c.

```
\setkeys*[\<prefix>]{\<families>}[\<na>]{\<keys>}
```

`\setkeys*` The starred version of `\setkeys` sets keys which it can locate in the given families and will not produce errors when it cannot find a key. Instead, these keys and their values will be appended to a list of remaining keys in the macro `\XKV@rm` after the use of `\setkeys*`. This list will also contain keys and values coming from nested `\setkeys*` commands in the order as they have been submitted. Keys listed in `\<na>` will be ignored fully and will not be appended to the `\XKV@rm` list.

```
\setkeys*[my]{familyb}{keya=test}
```

Since `keya` is not defined in `familyb`, the value in the example above will be stored in `\XKV@rm` (so `\XKV@rm` expands to `keya=test`) for later use and no errors are raised.

```
\setrmkeys[\<prefix>]{\<families>}[\<na>]
```

`\setrmkeys` The macro `\setrmkeys` sets the remaining keys given by the list `\XKV@rm` stored previously by a `\setkeys*` (or `\setrmkeys*`) command in `\<families>`. `\<na>` again lists keys that should be ignored. It will produce an error when a key cannot be located.

```
\setrmkeys[my]{familya}
```

This submits `keya=test` from the previous `\setkeys*` command to `familya`. `keya` will be set.

```
\setrmkeys*[\<prefix>]{\<families>}[\<na>]
```

`\setrmkeys*` The macro `\setrmkeys*` acts as the `\setrmkeys` macro but now, as with `\setkeys*`, it ignores keys that it cannot find and puts them again on the list stored in `\XKV@rm`. Keys listed in `\<na>` will be ignored fully and will not be appended to the list in `\XKV@rm`.

```
\setkeys*[my]{familyb}{keya=test}
\setrmkeys*[my]{familyb}
\setrmkeys[my]{familya}
```

In the example above, the second line tries to set `keya` in `familyb` again and no errors are generated on failure. The last line finally sets `keya`.

The combination of `\setkeys*` and `\setrmkeys` can be used to construct complex macros in which, for instance, a part of the keys should be set in multiple families and the rest in another family or set of families. Instead of splitting the keys or the inputs, the user can supply all inputs in a single argument and the two macros will perform the splitting and setting of keys for your macro, given that the families are well chosen.

```
\setkeys+[\<prefix>]{\<families>}[\<na>]{\<keys>}
\setkeys*+[\<prefix>]{\<families>}[\<na>]{\<keys>}
\setrmkeys+[\<prefix>]{\<families>}[\<na>]
\setrmkeys*+[\<prefix>]{\<families>}[\<na>]
```

`\setkeys+` These macros act as their counterparts without the `+`. However, when a key in $\langle keys \rangle$ is defined by multiple families, this key will be set in *all* families in $\langle families \rangle$. This can, for instance, be used to set keys defined by your own package and by another package with the same name but in different families with a single command.

```
\setkeys+[my]{familya,familyb}{keyb=test}
```

The example above sets `keyb` in both families.

✖

4.2 Quelques détails

✖ Several remarks should be made with respect to processing the user input. Assuming that `keya` up to `keyd` are properly defined, one could do the following.

```
\setkeys{family}{keya= test a, keyb={test b,c,d}, , keyc=end}
```

From values consisting entirely of a `{ }` group, the outer braces will be stripped off internally.⁸ This allows the user to ‘hide’ any commas or equality signs that appear in the value of a key. This means that when using braces around `value`, `xkeyval` will not terminate the `value` when it encounters a comma in `value`. For instance, see the value of `keyb` in the example above. The same holds for the equality sign. Notice further that any spaces around the characters `=` and `,` (in the top level group) are removed and that empty entries will silently be ignored. This makes the example above equivalent to the example below.

```
\setkeys{family}{keya=test a,keyb={test b,c,d},keyc=end}
```

Further, when executing a key macro, the following `xkeyval` internals are available.

`\XKV@prefix`

The prefix, for instance `my`.

`\XKV@fams`

The list of families to search, for instance `familya,familyb`.

`\XKV@tfam`

The current family, for instance `familya`.

`\XKV@header`

The header which is a combination of the prefix and the current family, for instance `my@familya@`.

`\XKV@tkey`

The current key name, for instance `keya`.

`\XKV@na`

The keys that should not be set, for instance `keyc,keyd`.

You can use these internals and create, for example, dynamic options systems in which user input to `\setkeys` will be used to create new keys which can be used in the very same `\setkeys` command. The extract package [1] provides an example for this.

✖

8. `xkeyval` actually strips off 3 levels of braces : one by using `keyval`'s `\KV@@sp@def` and two in internal parsings. `keyval` strips off only 2 levels : one by using `\KV@@sp@def` and one in internal parsings. This difference has not yet been shown to cause problems for existing packages or new implementations. If this appears to be a problem in the future, effort will be done to solve it.

5 Pointeurs

✖ The `xkeyval` package provides a pointer mechanism. Pointers can be used to copy values of keys. Hence, one can reuse the value that has been submitted to a particular key in the value of another key. This section will first describe how `xkeyval` can be made to save key values. After that, it will explain how to use these saved values again. Notice already that the commands `\savevalue`, `\gsavevalue` and `\usevalue` can only be used in `\setkeys` commands.

✖

5.1 Sauvegarde de valeurs

`\savevalue` ✖ Saving a value for a particular key can be accomplished by using the `\savevalue` command with the key name as argument.

```
\setkeys[my]{familya}{\savevalue{keya}=test}
```

This example will set `keya` as we have seen before, but will additionally define the macro `\XKV@my@familya@keya@value` to expand to `test`. This macro can be used later on by `xkeyval` to replace pointers. In general, values of keys will be stored in macros of the form `\XKV@<prefix>@<family>@<key>@value`. This implies that the pointer system can only be used within the same family (and prefix). We will come back to that in section 5.2.

`\gsavevalue` Using the global version of this command, namely `\gsavevalue`, will define the value macro `\XKV@my@family@key@value` globally. In other words, the value macro won't survive after a `\begingroup... \endgroup` construct (for instance, an environment), when it has been created in this group using `\savevalue` and it will survive afterwards if `\gsavevalue` is used.

```
\setkeys[my]{familya}{\gsavevalue{keya}=test}
```

This example will globally define `\XKV@my@familya@keya@value` to expand to `test`.

Actually, in most applications, package authors do not want to require users to use the `\savevalue` form when using the pointer system internally. To avoid this, the `xkeyval` package also supplies the following commands.

```
\savekeys[<prefix>]{<family>}{<keys>}
\gsavekeys[<prefix>]{<family>}{<keys>}
```

`\savekeys` The `\savekeys` macro stores a list of keys for which the values should always be saved
`\gsavekeys` to a macro of the form `\XKV@<prefix>@<family>@save`. This will be used by `\setkeys` to check whether a value should be saved or not. The global version will define this internal macro globally so that the settings can escape groups (and environments). The `\savekeys` macro works incrementally. This means that new input will be added to an existing list for the family at hand if it is not in yet.

```
\savekeys[my]{familya}{keya,keyc}
\savekeys[my]{familya}{keyb,keyc}
```

The first line stores `keya, keyc` to `\XKV@my@familya@save`. The next line changes the content of this macro to `keya, keyc, keyb`.

```
\delsavekeys[<prefix>]{<family>}{<keys>}
\gdelsavekeys[<prefix>]{<family>}{<keys>}
```

```
\unsavekeys[\<prefix>]{\<family>}
\gunsavekeys[\<prefix>]{\<family>}
```

`\delsavekeys` The `\delsavekeys` macro can be used to remove some keys from an already defined list of save keys. No errors will be raised when one of the keys in the list *<keys>* was not in the list. The global version `\gdelsavekeys` does the same as `\delsavekeys`, but will also make the resulting list global. The `\unsavekeys` macro can be used to clear the entire list of key names for which the values should be saved. The macro will make `\XKV@<prefix>@<family>@save` undefined. `\gunsavekeys` is similar to `\unsavekeys` but makes the internal macro undefined globally.

```
\savekeys[my]{familya}{keya,keyb,keyc}
\delsavekeys[my]{familya}{keyb}
\unsavekeys[my]{familya}
```

The first line of this example initializes the list to contain `keya,keyb,keyc`. The second line removes `keyb` from this list and hence `keya,keyc` remains. The last line makes the list undefined and hence clears the settings for this family.

`\global` It is important to notice that the use of the global version `\gsavekeys` will only have effect on the definition of the macro `\XKV@<prefix>@<family>@save`. It will not have an effect on how the key values will actually be saved by `\setkeys`. To achieve that a particular key value will be saved globally (like using `\gsavevalue`), use the `\global` specifier in the `\savekeys` argument.

```
\savekeys[my]{familya}{keya,\global{keyc}}
```

This example does the following. The argument `keya,\global{keyc}` is saved (locally) to `\XKV@my@familya@save`. When `keyc` is used in a `\setkeys` command, the associated value will be saved globally to `\XKV@my@familya@keya@value`. When `keya` is used, its value will be saved locally.

All macros discussed in this section for altering the list of save keys only look at the key name. If that is the same, old content will be overwritten with new content, regardless whether `\global` has been used in the content. See the example below.

```
\savekeys[my]{familya}{\global{keyb},keyc}
\delsavekeys[my]{familya}{keyb}
```

The first line changes the list in `\XKV@my@familya@save` from `keya,\global{keyc}` to `keya,keyc,\global{keyb}`. The second line changes the list to `keya,keyc`.

✘

5.2 Utilisation des valeurs sauvegardées

`\usevalue` ✘The syntax of a pointer is `\usevalue{keyname}` and can only be used inside `\setkeys` and friends. `xkeyval` will replace a pointer by the value that has been saved for the key that the pointer is pointing to. If no value has been saved for this key, an error will be raised. The following example will demonstrate how to use pointers (using the keys defined in section 3.1).

```
\setkeys[my]{familya}{\savevalue{keya}=test}
\setkeys[my]{familya}{keyb=\usevalue{keya}}
```

The value submitted to `keyb` points to `keya`. This has the effect that the value recorded for `keya` will replace `\usevalue{keya}` and this value (here `test`) will be submitted to the key macro of `keyb`.

Since the saving of values is prefix and family specific, pointers can only locate values that have been saved for keys with the same prefix and family as the key for which the pointer is used. Hence this

```
\setkeys{my}{familya}{\savevalue{keya}=test}
\setkeys{my}{familyb}{keyb=\usevalue{keya}}
```

will never work. An error will be raised in case a key value points to a key for which the value cannot be found or has not been stored.

It is possible to nest pointers as the next example shows.

```
\setkeys{my}{familya}{\savevalue{keya}=test}
\setkeys{my}{familya}{\savevalue{keyb}=\usevalue{keya}}
\setkeys{my}{familya}{keyc=\usevalue{keyb}}
```

This works as follows. First `\xkeyval` records the value `test` in a macro. Then, `keyb` uses that value. Besides that, the value submitted to `keyb`, namely `\usevalue{keya}` will be recorded in another macro. Finally, `keyc` will use the value recorded previously for `keyb`, namely `\usevalue{keya}`. That in turn points to the value saved for `keya` and that value will be used.

It is important to stress that the pointer replacement will be done before \TeX or \LaTeX performs the expansion of the key macro and its argument (which is the value that has been submitted to the key). This allows pointers to be used in almost any application. (The exception is grouped material, to which we will come back later.) When programming keys (using `\define@key` and friends), you won't have to worry about the expansion of the pointers which might be submitted to your keys. The value that will be submitted to your key macro in the end, will not contain pointers. These have already been expanded and been replaced by the saved values.

A word of caution is necessary. You might get into an infinite loop if pointers are not applied with care, as the examples below show. The first example shows a direct back link.

```
\setkeys{my}{familya}{\savevalue{keya}=\usevalue{keya}}
```

The second example shows an indirect back link.

```
\setkeys{my}{familya}{\savevalue{keya}=test}
\setkeys{my}{familya}{\savevalue{keyb}=\usevalue{keya}}
\setkeys{my}{familya}{\savevalue{keya}=\usevalue{keyb}}
```

In these cases, an error will be issued and further pointer replacement is canceled.

As mentioned already, pointer replacement does not work inside grouped material, `{...}`, if this group is not around the entire value (since that will be stripped off, see section 1). The following, for instance, will not work.

```
\setkeys{my}{familya}{\savevalue{keya}=test}
\setkeys{my}{familya}{keyb=\parbox{2cm}{\usevalue{keya}}}
```

The following provides a working alternative for this situation.

```
\setkeys{my}{familya}{\savevalue{keya}=test}
\setkeys{my}{familya}{keyb=\begin{minipage}{2cm}\usevalue{keya}\end{minipage}}
```

In case there is no appropriate alternative, we can work around this restriction, for instance by using a value macro directly.

```
\setkeys{my}{familya}{\savevalue{keya}=test}
\setkeys{my}{familya}{keyb=\parbox{2cm}{\XKV@my@familya@keya@value}}
```

When no value has been saved for `keya`, the macro `\XKV@my@familya@keya@value` is undefined. Hence one might want to do a preliminary check to be sure that the macro exists.

Pointers can also be used in default values. We finish this section with an example which demonstrates this.

```
\define@key{fam}{keya}{keya: #1}
\define@key{fam}{keyb}[\usevalue{keya}]{keyb: #1}
\define@key{fam}{keyc}[\usevalue{keyb}]{keyc: #1}
\setkeys{fam}{\savevalue{keya}=test}
\setkeys{fam}{\savevalue{keyb}}
\setkeys{fam}{keyc}
```

Since user input is lacking in the final two commands, the default value defined for those keys will be used. In the first case, the default value points to `keya`, which results in the value `test`. In the second case, the pointer points to `keyb`, which points to `keya` (since its value has been saved now) and hence also in the final command, the value `test` will be submitted to the key macro of `keyc`.

✕

6 Prédéfinition des clés

✕ In contrast to the default value system where users are required to specify the key without a value to assign it its default value, the presetting system does not require this. Keys which are preset will be set automatically by `\setkeys` when the user didn't use those keys in the `\setkeys` command. When users did use the keys which are also preset, `\setkeys` will avoid setting them again. This section again uses the key definitions of section 3.1 in examples.

```
\presetkeys [⟨prefix⟩]{⟨family⟩}{⟨head keys⟩}{⟨tail keys⟩}
\gpresetkeys [⟨prefix⟩]{⟨family⟩}{⟨head keys⟩}{⟨tail keys⟩}
```

`\presetkeys`
`\gpresetkeys`

This macro will save *⟨head keys⟩* to `\XKV@⟨prefix⟩@⟨family⟩@preseth` and *⟨tail keys⟩* to `\XKV@⟨prefix⟩@⟨family⟩@presett`. Savings are done locally by `\presetkeys` and globally by `\gpresetkeys` (compare `\savekeys` and `\gsavekeys`, section 5.1). The saved macros will be used by `\setkeys`, when they are defined, whenever *⟨family⟩* is used in the *⟨families⟩* argument of `\setkeys`. Head keys will be set before setting user keys, tail keys will be set afterwards. However, if a key appears in the user input, this particular key will not be set by any of the preset keys.

The macros work incrementally. This means that new input for a particular key replaces already present settings for this key. If no settings were present yet, the new input for this key will be appended to the end of the existing list. The replacement ignores the fact whether a `\savevalue` or an `=` has been specified in the key input. We could do the following.

```
\presetkeys{fam}{keya=red,\savevalue{keyb},keyc}{}
\presetkeys{fam}{\savevalue{keya},keyb=red,keyd}{}
\setkeys{fam}{keya}
```

After the first line of the example, the macro `\XKV@KV@fam@preseth` will contain `keya=red,\savevalue{keyb},keyc`. After the second line of the example, the macro will contain `\savevalue{keya},keyb=red,keyc,keyd`. The *⟨tail keys⟩* remain empty throughout the example.

```
\delpresetkeys[\<prefix>]{\<family>}{\<head keys>}{\<tail keys>}
\gdelpresetkeys[\<prefix>]{\<family>}{\<head keys>}{\<tail keys>}
```

\delpresetkeys
\gdelpresetkeys

These commands can be used to (globally) delete entries from the presets by specifying the key names for which the presets should be deleted. Continuing the previous example, we could do the following.

```
\delpresetkeys{fam}{keya,keyb}{}
```

This redefines the list of head presets `\XKV@KV@fam@preseth` to contain `keyc`, `keyd`. As can be seen from this example, the exact use of a key name is irrelevant for successful deletion.

```
\unpresetkeys[\<prefix>]{\<family>}
\gunpresetkeys[\<prefix>]{\<family>}
```

\unpresetkeys
\gunpresetkeys

These commands clear the presets for `<family>` and works just as `\unsavekeys`. It makes `\XKV@<prefix>@<family>@preseth` and `\XKV@<prefix>@<family>@presett` undefined. The global version will make the macros undefined globally.

Two type of problems in relation to pointers could appear when specifying head and tail keys incorrectly. This will be demonstrated with two examples. In the first example, we would like to set `keya` to `blue` and `keyb` to copy the value of `keya`, also when the user has changed the preset value of `keya`. Say that we implement the following.

```
\savekeys[my]{familya}{keya}
\presetkeys[my]{familya}{keya=blue,keyb=\usevalue{keya}}{}
\setkeys[my]{familya}{keya=red}
```

This will come down to executing

```
\savekeys[my]{familya}{keya}
\setkeys[my]{familya}{keyb=\usevalue{keya},keya=red}
```

since `keya` has been specified by the user. At best, `keyb` will copy a probably wrong value of `keya`. In the case that no value for `keya` has been saved before, we get an error. We observe that the order of keys in the simplified `\setkeys` command is wrong. This example shows that the `keyb=\usevalue{keya}` should have been in the tail keys, so that it can copy the user input to `keya`.

The following example shows what can go wrong when using presets incorrectly and when `\setkeys` contains pointers.

```
\savekeys[my]{familya}{keya}
\presetkeys[my]{familya}{}{keya=red}
\setkeys[my]{familya}{keyb=\usevalue{keya}}
```

This will come down to executing the following.

```
\savekeys[my]{familya}{keya}
\setkeys[my]{familya}{keyb=\usevalue{keya},keya=red}
```

This results in exactly the same situation as we have seen in the previous example and hence the same conclusion holds. In this case, we conclude that the `keya=red` argument should have been specified in the head keys of the `\presetkeys` command so that `keyb` can copy the value of `keya`.

For most applications, one could use the rule of thumb that preset keys containing pointers should go in the tail keys. All other keys should go in head keys. There might, however, be applications thinkable in which one would like to implement the preset system as shown in the two examples above, for instance to easily retrieve values used in the last use of a macro or environment. However, make sure that keys in that case receive an initialization in order to avoid errors of missing values.

For completeness, the working examples are below.

```
\savekeys [my] {familya} {keya}
\presetkeys [my] {familya} {keya=blue} {keyb=\usevalue {keya}}
\setkeys [my] {familya} {keya=red}
\presetkeys [my] {familya} {keya=red} {}
\setkeys [my] {familya} {keyb=\usevalue {keya}}
```

Other examples can be found in the example files. See section 13.

✕

7 Traitement des options de l'extension

✕ The macros in this section can be used to build \LaTeX class or package options systems using `xkeyval`. These are comparable to the standard \LaTeX macros without the trailing `X`. See for more information about these \LaTeX macros the documentation of the source [2] or a \LaTeX manual (for instance, the \LaTeX Companion [3]). The macros in this section have been built using `\define@key` and `\setkeys` and are not available to \TeX users.

The macros below allow for specifying the $\langle family \rangle$ (or $\langle families \rangle$) as an optional argument. This could be useful if you want to define global options which can be reused later (and set locally by the user) in a macro or environment that you define. If no $\langle family \rangle$ (or $\langle families \rangle$) is specified, the macro will insert the default family name which is the filename of the file that is calling the macros. The macros in this section also allow for setting an optional prefix. When using the filename as family, uniqueness of key macros is already guaranteed. In that case, you can omit the optional $\langle prefix \rangle$. However, when you use a custom prefix for other keys in your package and you want to be able to set all of the keys later with a single command, you can use the custom prefix also for the class or package options system.

Note that both $[\langle arg \rangle]$ and $<\langle arg \rangle>$ denote optional arguments to the macros in this section. This syntax is used to identify the different optional arguments when they appear next to each other.

```
\DeclareOptionX[\langle prefix \rangle]<\langle family \rangle>{\langle key \rangle} [\langle default \rangle] {\langle function \rangle}
```

`\DeclareOptionX` Declares an option (i.e., a key, which can also be used later on in the package in `\setkeys` and friends). This macro is comparable to the standard \LaTeX macro `\DeclareOption`, but with this command, the user can pass a value to the option as well. Reading that value can be done by using `#1` in $\langle function \rangle$. This will contain $\langle default \rangle$ when no value has been specified for the key. The value of the optional argument $\langle default \rangle$ is empty by default. This implies that when the user does not assign a value to $\langle key \rangle$ and when no default value has been defined, no error will be produced. The optional argument $\langle family \rangle$ can be used to specify a custom family for the key. When the argument is not used, the macro will insert the default family name.

```
\newif\iflandscape
```

```
\DeclareOptionX{landscape}{\landscapetrue}
\DeclareOptionX{parindent}[20pt]{\setlength\parindent{#1}}
```

Assuming that the file containing the example above is called `myclass.cls`, the example is equivalent to

```
\newif\iflandscape
\define@key{myclass.cls}{landscape}[]{\landscapetrue}
\define@key{myclass.cls}{parindent}[20pt]{\setlength\parindent{#1}}
```

Notice that an empty default value has been inserted by `xkeyval` for the `landscape` option. This allows for the usual \TeX options use like

```
\documentclass[landscape]{myclass}
```

without raising No value specified for key ‘landscape’ errors.

These examples also show that one can also use `\define@key` (or friends, see section 3) to define class or package options. The macros presented here are supplied for the ease of package programmers wanting to convert the options section of their package to use `xkeyval`.

```
\DeclareOptionX*{<function>}
```

`\DeclareOptionX*`

This macro can be used to process any unknown inputs. It is comparable to the \TeX macro `\DeclareOption*`. Use `\CurrentOption` within this macro to get the entire input from which the key is unknown, for instance `unknownkey=value` or `somevalue`. These values (possibly including a key) could for example be passed on to another class or package or could be used as an extra class or package option specifying for instance a style that should be loaded.

```
\DeclareOptionX*{\PackageWarning{mypackage}{‘\CurrentOption’ ignored}}
```

The example produces a warning when the user issues an option that has not been declared.

```
\ExecuteOptionsX[<prefix>]<families>>[<na>]{<keys>}
```

`\ExecuteOptionsX`

This macro sets keys created by `\DeclareOptionX` and is basically a copy of `\setkeys`. The optional argument `<na>` specifies keys that should be ignored. The optional argument `<families>` can be used to specify a list of families which define `<keys>`. When the argument is not used, the macro will insert the default family name. This macro will not use the declaration done by `\DeclareOptionX*` when undeclared options appear in its argument. Instead, in this case the macro will raise an error. This mimics \TeX ’s `\ExecuteOptions`’ behavior.

```
\ExecuteOptionsX{parindent=0pt}
```

This initializes `\parindent` to 0pt.

```
\ProcessOptionsX[<prefix>]<families>>[<na>]
```

`\ProcessOptionsX`

This macro processes the keys and values passed by the user to the class or package. The optional argument `<na>` can be used to specify keys that should be ignored. The optional argument `<families>` can be used to specify the families that have been used to define the keys. Note that this macro will not protect macros in the user inputs (like `\thepage`) as will be explained in section 12.2. When used in a class file, this macro will ignore unknown keys or options. This allows the user to use global options in the `\documentclass` command which can be copied by packages loaded afterwards.

```
\ProcessOptionsX*[\<prefix>]\<families>[\<na>]
```

`\ProcessOptionsX*` The starred version works like `\ProcessOptionsX` except that it also copies user input from the `\documentclass` command. When the user specifies an option in the document class which also exists in the local family (or families) of the package issuing `\ProcessOptionsX*`, the local key will be set as well. In this case, #1 in the `\DeclareOptionX` macro will contain the value entered in the `\documentclass` command for this key. First the global options from `\documentclass` will set local keys and afterwards, the local options, specified with `\usepackage`, `\RequirePackage` or `\LoadClass` (or friends), will set local keys, which could overwrite the global options again, depending on the way the options sections are constructed. This macro reduces to `\ProcessOptionsX` only when issued from the class which forms the document class for the file at hand to avoid setting the same options twice, but not for classes loaded later using for instance `\LoadClass`. Global options that do not have a counterpart in local families of a package or class will be skipped.

It should be noted that these implementations differ from the \TeX implementations of `\ProcessOptions` and `\ProcessOptions*`. The difference is in copying the global options. The \TeX commands always copy global options if possible. As a package author doesn't know beforehand which document class will be used and with which options, the options declared by the author might show some unwanted interactions with the global options. When the class and the package share the same option, specifying this option in the `\documentclass` command will force the package to use that option as well. With `\ProcessOptionsX`, `xkeyval` offers a package author to become fully independent of the global options and be sure to avoid conflicts with any class. Have a look at the example class, style and `.tex` file below and observe the effect of changing to `\ProcessOptionsX*` in the style file.⁹

```
% myclass.cls
\RequirePackage{xkeyval}
\define@boolkey{myclass.cls}%
  [cls]{bool}{-}
\ProcessOptionsX
\LoadClass{article}
```

```
% mypack.sty
\define@boolkey{mypack.sty}%
  [pkg]{bool}{-}
\ProcessOptionsX
```

```
% test.tex
\documentclass[bool=true]{myclass}
\usepackage{mypack}
\begin{document}\parindent0pt
\ifclsbool class boolean true \else class boolean false\fi\\
\ifpkgbool package boolean true \else package boolean false\fi
\end{document}
```

See section 13 for more examples.

The use of `\ProcessOptionsX*` in a class file might be tricky since the class could also be used as a basis for another package or class using `\LoadClass`. In that case, depending on the options system of the document class, the behavior of the class loaded with `\LoadClass` could change compared to the situation when it is loaded by `\documentclass`. But since it is technically possible to create two classes that cooperate, the `xkeyval` package allows for the usage of `\ProcessOptionsX*` in class files. Notice that using \TeX 's `\ProcessOptions` or `\ProcessOptions*`, a class file cannot copy document class options.

9. See section 3.4 for information about `\define@boolkey`.

In case you want to verify whether your class is loaded with `\documentclass` or `\LoadClass`, you can use the `\XKV@documentclass` macro which contains the current document class.

A final remark concerns the use of expandable macros in class or package options values. Due to the construction of the \TeX option processing mechanism, this is not possible. However, the `xkeyval` bundle includes a patch for the \TeX kernel which solves this problem. See section 14.7 for more information.

✖

8 Liste des structures de commande

✖ This section provides a list of all reserved internal macro structures used for key processing. Here `pre` denotes a prefix, `fam` denotes a family and `key` denotes a key. These vary per application. The other parts in internal macro names are constant. The macros with additional `XKV` prefix are protected in the sense that all `xkeyval` macros disallow the use of the `XKV` prefix. Package authors using `xkeyval` are responsible for protecting the other types of internal macros.

`\pre@fam@key`

Key macro. This macro takes one argument. This macro will execute the *function* of `\define@key` (and friends) on the value submitted to the key macro through `\setkeys`.

`\cmdpre@fam@key`

The macro which is used by `\define@cmdkey` to store user input in when no custom macro prefix was specified.

`\ifpre@fam@key`, `\pre@fam@keytrue`, `\pre@fam@keyfalse`

The conditional created by `\define@boolkey` with parameters `pre`, `fam` and `key` if no custom macro prefix was specified. The `true` and `false` macros are used to set the conditional to `\iftrue` and `\iffalse` respectively.

`\pre@fam@key@default`

Default value macro. This macro expands to `\pre@fam@key{default value}`. This macro is defined through `\define@key` and friends.

`\XKV@pre@fam@key@value`

This macro is used to store the value that has been submitted through `\setkeys` to the key macro (without replacing pointers).

`\XKV@pre@fam@save`

Contains the names of the keys that should always be saved when they appear in a `\setkeys` command. This macro is defined by `\savekeys`.

`\XKV@pre@fam@preseth`

Contains the head presets. These will be submitted to `\setkeys` before setting user input. Defined by `\presetkeys`.

`\XKV@pre@fam@presett`

Contains the tail presets. These will be submitted to `\setkeys` after setting user input. Defined by `\presetkeys`.

An important remark should be made. Most of the macros listed above will be constructed by `xkeyval` internally using `\csname . . . \endcsname`. Hence almost any input to the macros defined by this package is possible. However, some internal macros might be used outside `xkeyval` macros as well, for instance the macros of the form

`\ifpre@fam@key` and `\cmdpre@fam@key`. To be able to use these macros yourself, none of the input parameters should contain non-letter characters. If you feel that this is somehow necessary anyway, there are several strategies to make things work.

Let us consider as example the following situation (notice the hyphen - in the family name).

```
\define@boolkey{some-fam}{myif}
\setkeys{some-fam}{myif=false}
```

Using these keys in a `\setkeys` command is not a problem at all. However, if you want to use the `\ifKV@some-fam@myif` command itself, you can do either

```
\edef\savedhyphencatcode{\the\catcode'\-}%
\catcode'\-=11\relax
\def\mymacro{%
  \ifKV@some-fam@myif
    % true case
  \else
    % false case
  \fi}
\catcode'\-=\savedhyphencatcode
```

or

```
\def\mymacro{%
  \csname ifKV@some-fam@myif\endcsname
    % true case
  \else
    % false case
  \fi}
```

✖

9 Alertes et erreurs

✖There are several points where `xkeyval` performs a check and could produce a warning or an error. All possible warnings or and error messages are listed below with an explanation. Here `pre` denotes a prefix, `name` denotes the name of a key, `fam` denotes a family, `fams` denotes a list of families and `val` denotes some value. These vary per application. Note that messages 1 to 7 could result from erroneous key setting through `\setkeys`, `\setrmkeys`, `\ExecuteOptionsX` and `\ProcessOptionsX`.

- 1) value ‘val’ is not allowed (error)
The value that has been submitted to a key macro is not allowed. This error can be generated by either a choice or a boolean key.
- 2) ‘name’ undefined in families ‘fams’ (error)
The key name is not defined in the families in `fams`. Probably you mistyped name.
- 3) no key specified for value ‘val’ (error)
`xkeyval` found a value without a key, for instance something like `=value`, when setting keys.
- 4) no value recorded for key ‘name’ (error)
You have used a pointer to a key for which no value has been saved previously.

- 5) back linking pointers; pointer replacement canceled (error)
You were back linking pointers. Further pointer replacements are canceled to avoid getting into an infinite loop. See section 5.2.
- 6) no value specified for key ‘name’ (error)
You have used the key ‘name’ without specifying any value for it (namely, `\setkeys{fam}{name}` and the key does not have a default value. Notice that `\setkeys{fam}{name=}` submits the empty value to the key macro and that this is considered a legal value.
- 7) key ‘name’ has been disabled (warning)
The key that you try to set has been disabled and cannot be used anymore.
- 8) ‘XKV’ prefix is not allowed (error)
You were trying to use the XKV prefix when defining or setting keys. This error can be caused by any `xkeyval` macro having an optional prefix argument.
- 9) key ‘name’ undefined (error)
This error message is caused by trying to disable a key that does not exist. See section 3.6.
- 10) no save keys defined for ‘pre@fam@’ (error)
You are trying to delete or undefine save keys that have not been defined yet. See section 5.1.
- 11) no presets defined for ‘pre@fam@’ (error)
You are trying to delete or undefine presets that have not been defined yet. See section 6.
- 12) `xkeyval` loaded before `\documentclass` (error)
Load `xkeyval` after `\documentclass` (or in the class that is the document class). See section 7.

✖

10 Codes de catégorie

✖Some packages change the catcode of the equality sign and the comma. This is a problem for `keyval` as it then does not recognize these characters anymore and cannot parse the input. This problem can play up on the background. Consider for instance the following example and note that the `graphicx` package is using `keyval` and that Turkish `babel` will activate the equality sign for shorthand notation.

```
\documentclass{article}
\usepackage{graphicx}
\usepackage[turkish]{babel}
\begin{document}
\includegraphics[scale=.5]{rose.eps}
\end{document}
```

The `babel` package provides syntax to temporarily reset the catcode of the equality sign and switch shorthand back on after using `keyval` (in the `\includegraphics` command), namely `\shorthandoff{=}` and `\shorthandon{=}`. But having to do this every time `keyval` is invoked is quite cumbersome. Besides that, it might not always be clear to the user what the problem is and what the solution.

For these reasons, `xkeyval` performs several actions with user input before trying to parse it.¹⁰ First of all, it performs a check whether the characters `=` and `,` appear in the input with unexpected catcodes. If so, the `\@selective@sanitize` macro is used to sanitize these characters only in the top level. This means that characters inside (a) group(s), `{ }`, will not be sanitized. For instance, when using Turkish `babel`, it is possible to use `=` shorthand notation even in the value of a key, as long as this value is inside a group.

```
\documentclass{article}
\usepackage{graphicx}
\usepackage[turkish]{babel}
\usepackage{xkeyval}
\makeatletter
\define@key{fam}{key}{#1}
\begin{document}
\includegraphics[scale=.5]{rose.eps}
\setkeys{fam}{key=some =text}
\end{document}
```

In the example above, the `\includegraphics` command does work. Further, the first equality sign in the `\setkeys` command will be sanitized, but the second one will be left untouched and will be typeset as `babel` shorthand notation.

The commands `\savekeys` and `\disable@keys` are protected against catcode changes of the comma. The commands `\setkeys` and `\presetkeys` are protected against catcode changes of the comma and the equality sign. Note that \TeX option macros (see section 7) are not protected as \TeX does not protect them either.

✖

11 Problèmes connus

✖ This package redefines `keyval`'s `\define@key` and `\setkeys`. This is risky in general. However, since `xkeyval` extends the possibilities of these commands while still allowing for the `keyval` syntax and use, there should be no problems for packages using these commands after loading `xkeyval`. The package prevents `keyval` to be loaded afterwards to avoid these commands from being redefined again into the simpler versions. For packages using internals of `keyval`, like `\KV@@sp@def`, `\KV@do` and `\KV@errx`, these are provided separately in `keyval.tex`.

The advantage of redefining these commands instead of making new commands is that it is much easier for package authors to start using `xkeyval` instead of `keyval`. Further, it eliminates the confusion of having multiple commands doing similar things.

A potential problem lies in other packages that redefine either `\define@key` or `\setkeys` or both. Hence particular care has been spend to check packages for this. Only one package has been found to do this, namely `pst-key`. This package implements a custom version of `\setkeys` which is specialized to set `PSTricks` [4, 5] keys of the form `\psset@somekey`. `xkeyval` also provides the means to set these kind of keys (see page 5) and work is going on to convert `PSTricks` packages to be using a specialization of `xkeyval` instead of `pst-key`. This specialization is available in the `pst-xkey` package, which is distributed with the `xkeyval` bundle and is described in section 12.3. However,

10. Notice that temporarily resetting catcodes before reading the input to `\setkeys` won't suffice, as it will not help solving problems when input has been read before and has been stored in a token register or a macro.

since a lot of authors are involved and since it requires a change of policy, the conversion of PSTricks packages might take some time. Hence, at the moment of writing, xkeyval will conflict with pst-key and the PSTricks packages still using pst-key, which are pst-ob3d, pst-stru and pst-uml.

Have a look at the PSTricks website [4] to find out if the package that you want to use has been converted already. If not, load an already converted package (like psticks-add) after loading the old package to make them work.

✖

12 Extensions additionnelles

12.1 xkvview

✖The xkeyval bundle includes a viewer utility, called xkvview,¹¹ which keeps track of the keys that are defined. This utility is intended for package programmers who want to have an overview of the keys defined in their package(s). All keys defined after loading the package will be recorded in a database. It provides the following commands to display (part of) the database.

```
\xkvview{<options>}
```

\xkvview When *<options>* is empty, the entire database will be typeset in a table created with the longtable package. The columns will, respectively, contain the key name, the prefix, the family, the type (ordinary, command, choice or boolean) and the presence of a default value for every key defined after loading xkvview.

options There are several options to control the output of this command. This set of options can be used to set up criteria for the keys that should be displayed. If a key does not satisfy one or more of them, it won't be included in the table. For instance, the following example will display all keys with family fama, that do not have a default value. Notice that xkvview codes 'no default value' with [none].

prefix

family

type

default

```
\documentclass{article}
\usepackage{xkvview}
\makeatletter
\define@key{fama}{keya}[default]{}
\define@cmdkey{fama}{keyb}{}
\define@choicekey{famb}{keyc}{a,b}{}
\define@boolkey{famb}{keyd}{}
\makeatother
\begin{document}
\xkvview{family=fama,default=[none]}
\end{document}
```

In the following examples in this section, the same preamble will be used, but will not be displayed explicitly in the examples.

option One can select the columns that should be included in the table using the columns option. The following example includes the columns prefix and family in the table (additional to the key name column).

columns

```
\xkvview{columns={prefix,family}}
```

The remaining columns are called type and default.

option If you want to refer to an option, \xkvview can automatically generate labels using

vlabels

11. The xkvview package is contained in the file xkvview.sty.

the scheme $\langle prefix \rangle - \langle family \rangle - \langle keyname \rangle$. Here is an example.

```
\xkvview{vlabels=true}
Find more information about the keya
option on page~\pageref{KV-fama-keya}.
```

options The package can also write (part of) the database to a file. The selection of the in-
file formation happens in the same way as discussed above. When specifying a filename
wcolsep with the option `file`, the body of the table that is displayed, will also be written to this
weol file. Entries will be separated by `wcolsep` which is `&` by default and every row will be
concluded by `weol` which is `\\` by default. The output in the file can then be used as ba-
sis for a custom table, for instance in package documentation. The following displays
a table in the dvi and also writes the body to `out.tex`.

```
\xkvview{file=out}
```

`out.tex` contains

```
keya&KV&fama&ordinary&default\\
keyb&KV&fama&command&[none]\\
keyc&KV&famb&choice&[none]\\
keyd&KV&famb&boolean&[none]\\
```

The following example generates a table with entries separated by a space and no
end-of-line content.

```
\xkvview{file=out,wcolsep=\space,weol=}
```

Now `out.tex` contains

```
keya KV fama ordinary default
keyb KV fama command [none]
keyc KV famb choice [none]
keyd KV famb boolean [none]
```

option When post-processing the table generated in this way, one might want to re-
wlabels fer to entries again as well. When setting `wlabels` to true, the labels with names
 $\langle prefix \rangle - \langle family \rangle - \langle keyname \rangle$ will be in the output file. The following

```
\xkvview{file=out,wlabels=true}
```

will result in the following content in `out.tex`

```
keya&KV&fama&ordinary&default\label{KV-fama-keya}\\
keyb&KV&fama&command&[none]\label{KV-fama-keyb}\\
keyc&KV&famb&choice&[none]\label{KV-famb-keyc}\\
keyd&KV&famb&boolean&[none]\label{KV-famb-keyd}\\
```

option Finally, when you only want to generate a file and no output to the dvi, set the `view`
view option to false.

```
\xkvview{file=out,view=false}
```

This example only generate `out.tex` and does not put a table in the dvi.



12.2 xkvltxp

✖The package and class option system of \TeX contained in the kernel performs some expansions while processing options. This prevents doing for instance

```
\documentclass[title=My title,author=\textsc{Me}]{myclass}
```

given that myclass uses xkeyval and defines the options title and author.

This problem can be overcome by redefining certain kernel commands. These redefinitions are contained in the xkvltxp package.¹² If you want to allow the user of your class to be able to specify expandable macros in the package options, the user will have to do `\RequirePackage{xkvltxp}` on the first line of the \TeX file. If you want to offer this functionality in a package, the user can use the package in the ordinary way with `\usepackage{xkvltxp}`. This package then has to be loaded before loading the package which will use this functionality. A description of the patch can be found in the source code documentation.

The examples below summarize this information. The first example shows the case in which we want to allow for macros in the `\documentclass` command.

```
\RequirePackage{xkvltxp}
\documentclass[title=My title,author=\textsc{Me}]{myclass}
\begin{document}
\end{document}
```

The second example shows the case in which we want to allow for macros in a `\usepackage` command.

```
\documentclass{article}
\usepackage{xkvltxp}
\usepackage[footer=page~\thepage.]{mypack}
\begin{document}
\end{document}
```

Any package or class using xkeyval and xkvltxp to process options can take options that contain macros in their value without expanding them prematurely. However, you can of course not use macros in options which are not of the `key=value` form since they might in the end be passed on to or copied by a package which is not using xkeyval to process options, which will then produce errors. Options of the `key=value` form will be deleted from `\@classoptionslist` (see section 7) and form no threat for packages loaded later on. Finally, make sure not to pass options of the `key=value` form to packages not using xkeyval to process options since they cannot process them. For examples see section 13.

✖

12.3 pst-xkey

✖The pst-xkey package¹³ implements a specialized version of the options system of xkeyval designed for PSTricks [4, 5]. This system gives additional freedom to PSTricks package authors since they won't have to worry anymore about potentially redefining keys of one of the many other PSTricks packages. The command `\psset` is redefined to set keys in multiple families. Reading the documentation of the xkeyval package (especially section 11) first is recommended.

12. The xkvltxp package consists of the file `xkvltxp.sty`.

13. The pst-xkey package consists of the files `pst-xkey.tex` and `pst-xkey.sty`. To load pst-xkey \TeX users do `\input pst-xkey`, \LaTeX users do `\RequirePackage{pst-xkey}` or `\usepackage{pst-xkey}`.

Keys defined in the original distribution of PSTricks have the macro structure `\psset@somekey` (where `psset` is literal). These can be (re)defined by

```
\define@key[psset]{}{somekey}{function}
```

Notice especially that these keys are located in the so-called ‘empty family’. For more information about `\define@key` and friends, see section 3.

When writing a PSTricks package, let’s say `pst-new`, you should locate keys in a family which contains the name of your package. If you only need one family, you should define keys using

```
\define@key[psset]{pst-new}{somekey}{function}
```

If you want to use multiple families in your package, you can do

```
\define@key[psset]{pst-new-a}{somekey}{function}
\define@key[psset]{pst-new-b}{anotherkey}{function}
```

`\pst@addfams`
`\pst@famlist`

It is important that you add all of the families that you use in your package to the list in `\pst@famlist`. This list of families will be used by `\psset` to scan for keys to set user input. You can add your families to the list using

```
\pst@addfams{<families>}
```

For instance

```
\pst@addfams{pst-new}
```

or

```
\pst@addfams{pst-new-a,pst-new-b}
```

Only one command is needed to set PSTricks keys.

```
\psset [<families>] {<keys>}
```

`\psset`

This command will set `<keys>` in `<families>` using `\setkeys+` (see section 4). When `<families>` is not specified, it will set `<keys>` in all families in `\pst@famlist` (which includes the empty family for original PSTricks keys).

```
\psset{somekey=red,anotherkey}
\psset[pst-new-b]{anotherkey=green}
```

✕

13 Exemples et documentation

✕To generate the package and example files from the source, find the source of this package, the file `xkeyval.dtx`, in your local \TeX installation or on CTAN and run it with \LaTeX .

```
latex xkeyval.dtx
```

This will generate the package files (`xkeyval.tex`, `xkeyval.sty`, `xkvltxp.sty`, `keyval.tex`, `xkvtxhdr.tex`, `xkvview.sty`, `pst-xkey.tex` and `pst-xkey.sty`) and the example files.

The file `xkvex1.tex` provides an example for $\text{T}_{\text{E}}\text{X}$ users for the macros described in sections 3, 4, 5 and 6. The file `xkvex2.tex` provides an example for $\text{L}_{\text{A}}\text{T}_{\text{E}}\text{X}$ users for the same macros. The files `xkvex3.tex`, `xkveca.cls`, `xkvecb.cls`, `xkvesa.sty`, `xkvesb.sty` and `xkvesc.sty` together form an example for the macros described in section 7. The set of files `xkvex4.tex`, `xkveca.cls`, `xkvecb.cls`, `xkvesa.sty`, `xkvesb.sty` and `xkvesc.sty` provides an example for sections 7 and 12.2. These files also demonstrate the possibilities of interaction between packages or classes not using `xkeyval` and packages or classes that do use `xkeyval` to set options.

To (re)generate this documentation, perform the following steps.

```
latex xkeyval.dtx
latex xkeyval.dtx
bibtex xkeyval
makeindex -s gglo.ist -o xkeyval.gls xkeyval.glo
makeindex -s gind.ist -o xkeyval.ind xkeyval.idx
latex xkeyval.dtx
latex xkeyval.dtx
```

✕

14 Implémentation

14.1 `xkeyval.tex`

✕Avoid loading `xkeyval.tex` twice.

```
1 (*xkvtx)
2 \csname XKeyValLoaded\endcsname
3 \let\XKeyValLoaded\endinput
```

Adjust some catcodes to define internal macros.

```
4 \edef\XKVcatcodes{%
5   \catcode'\noexpand\@the\catcode'\@relax
6   \catcode'\noexpand\=\the\catcode'\=relax
7   \catcode'\noexpand\,\the\catcode'\,\relax
8   \catcode'\noexpand\:\the\catcode'\:\relax
9   \let\noexpand\XKVcatcodes\relax
10 }
11 \catcode'\@11\relax
12 \catcode'\=12\relax
13 \catcode'\,12\relax
14 \catcode'\:12\relax
```

Load some basic utilities.

```
15 \input xkvutils
```

Initializations.

```
16 \newcount\XKV@depth
17 \newif\ifXKV@st
18 \newif\ifXKV@sng
19 \newif\ifXKV@pl
20 \newif\ifXKV@knf
21 \newif\ifXKV@rkf
22 \newif\ifXKV@inpox
23 \newif\ifXKV@preset
24 \let\XKV@rm\@empty
```

Load L^AT_EX primitives if necessary and provide information.

```

25 \ifx\ProvidesFile\@undefined
26   \message{2014/12/03 v2.7a key=value parser (HA)}
27   \input xkvtxhdr
28 \else
29   \ProvidesFile{xkeyval.tex}[2014/12/03 v2.7a key=value parser (HA)]
30   \@addtofilelist{xkeyval.tex}
31 \fi

```

`\XKV@warn` Warning and error macros. We redefine the keyval error macros to use the xkeyval ones.
`\XKV@err` This avoids redefining them again when we redefine the `\XKV@warn` and `\XKV@err`
`\KV@err` macros in `xkeyval.sty`.

```

\KV@errx 32 \def\XKV@warn#1{\message{xkeyval warning : #1}}
33 \def\XKV@err#1{\errmessage{xkeyval error : #1}}
34 \def\KV@errx{\XKV@err}
35 \let\KV@err\KV@errx

```

`\XKV@ifstar` Checks whether the following token is a * or +. Use `\XKV@ifnextchar` to perform the
`\XKV@ifplus` action safely and ignore catcodes.

```

36 \def\XKV@ifstar#1{\@ifnextcharacter*{\@firstoftwo{#1}}}
37 \def\XKV@ifplus#1{\@ifnextcharacter+{\@firstoftwo{#1}}}

```

`\XKV@makepf` `{<prefix>}`

This macro creates the prefix, like `prefix@` in `\prefix@family@key`. First it deletes spaces from the input and checks whether it is empty. If not empty, an @-sign is added. The use of the XKV prefix is forbidden to protect internal macros and special macros like saved key values.

```

38 \def\XKV@makepf#1{%
39   \KV@@sp\def\XKV@prefix{#1}%
40   \def\XKV@resa{XKV}%
41   \ifx\XKV@prefix\XKV@resa
42     \XKV@err{'XKV' prefix is not allowed}%
43     \let\XKV@prefix\@empty
44   \else
45     \edef\XKV@prefix{\ifx\XKV@prefix\@empty\else\XKV@prefix @\fi}%
46   \fi
47 }

```

`\XKV@makehd` `{<family>}`

Creates the header, like `prefix@family@` in `\prefix@family@key`. If `<family>` is empty, the header reduces to `prefix@`.

```

48 \def\XKV@makehd#1{%
49   \expandafter\KV@@sp\def\expandafter\XKV@header\expandafter{#1}%
50   \edef\XKV@header{%
51     \XKV@prefix\ifx\XKV@header\@empty\else\XKV@header @\fi
52   }%
53 }

```

`\XKV@srstate` `{<postfix1>}{<postfix2>}`

Macro to save and restore xkeyval internals to allow for nesting `\setkeys` commands. It executes a for loop over a set of xkeyval internals and does, for instance, `\let\XKV@na@i\XKV@na` to prepare for stepping a level deeper. If `<prefix2>` is empty,

we step a level deeper. If $\langle prefix1 \rangle$ is empty, we go a level up. The non-empty argument is always $@\romannumeral\XKV@depth$. Notice that this also helps to keep changes to boolean settings (for instance by $\XKV@cc*$) local to the execution of that key.

```

54 \def\XKV@srstate#1#2{%
55   \ifx\@empty#2\@empty\advance\XKV@depth\@ne\fi
56   \XKV@for@n{\XKV@prefix,\XKV@fams,\XKV@tkey,\XKV@na,%
57     if\XKV@st,if\XKV@pl,if\XKV@knf,CurrentOption}\XKV@resa{%
58     \expandafter\let\csname\XKV@resa#1\expandafter
59       \endcsname\csname\XKV@resa#2\endcsname
60   }%
61   \ifx\@empty#1\@empty\advance\XKV@depth\m@ne\fi
62 }

```

$\XKV@testopta$ $\{\langle function \rangle\}$

$\XKV@t@stopta$ Tests for the presence of an optional star or plus and executes $\langle function \rangle$ afterwards.

```

63 \def\XKV@testopta#1{%
64   \XKV@ifstar{\XKV@sttrue\XKV@t@stopta{#1}}%
65   {\XKV@stfalse\XKV@t@stopta{#1}}%
66 }
67 \def\XKV@t@stopta#1{\XKV@ifplus{\XKV@pltrue#1}{\XKV@plfalse#1}}

```

$\XKV@testoptb$ $\{\langle function \rangle\}$

$\XKV@t@stoptb$ First check for an optional prefix. Afterwards, set the $\langle prefix \rangle$, set the header, remove spaces from the $\langle family \rangle$ and execute $\langle function \rangle$.

```

68 \def\XKV@testoptb#1{\@testopt{\XKV@t@stoptb#1}{KV}}
69 \def\XKV@t@stoptb#1[#2]#3{%

```

Set prefix.

```

70   \XKV@makepf{#2}%

```

Set header.

```

71   \XKV@makehd{#3}%

```

Save family name for later use.

```

72   \KV@@sp@def\XKV@tfam{#3}%
73   #1%
74 }

```

$\XKV@testoptc$ $\{\langle function \rangle\}$

$\XKV@t@stoptc$ Test for an optional $\langle prefix \rangle$. Then, set the $\langle prefix \rangle$, sanitize comma's in the list of $\langle families \rangle$ and remove redundant spaces from this list. Finally, check for optional key names that should not be set and execute $\langle function \rangle$.

```

75 \def\XKV@testoptc#1{\@testopt{\XKV@t@stoptc#1}{KV}}
76 \def\XKV@t@stoptc#1[#2]#3{%
77   \XKV@makepf{#2}%
78   \XKV@checksanitizetb{#3}\XKV@fams
79   \expandafter\XKV@sp@deflist\expandafter
80     \XKV@fams\expandafter{\XKV@fams}%
81   \@testopt#1}%
82 }

```

$\XKV@testoptd$ $\{\langle function \rangle\}$

$\XKV@t@stoptd$ Use $\XKV@testoptb$ first to find $\langle prefix \rangle$ and the $\langle family \rangle$. Then check for optional

$\langle mp \rangle$ ('macro prefix'). Next eat the $\langle key \rangle$ name and check for an optional $\langle default \rangle$ value.

```
83 \def\XKV@testoptd#1#2{%
84   \XKV@testoptb{%
85     \edef\XKV@tempa{#2\XKV@header}%
86     \def\XKV@tempb{\@testopt{\XKV@t@stoptd#1}}%
87     \expandafter\XKV@tempb\expandafter{\XKV@tempa}%
88   }%
89 }
90 \def\XKV@t@stoptd#1[#2]#3{%
```

\ifXKV@st gives the presence of an optional default value.

```
91   \@ifnextchar[{\XKV@sttrue#1{#2}{#3}}{\XKV@stfalse#1{#2}{#3}[]}%
92 }
```

```
\XKV@ifcmd { $\langle tokens \rangle$ }{ $\langle macro \rangle$ }{ $\langle cmd \rangle$ }{ $\langle yes \rangle$ }{ $\langle no \rangle$ }
```

\XKV@@ifcmd This macro checks whether the $\langle tokens \rangle$ contains the macro specification $\langle macro \rangle$. If so, the argument to this macro will be saved to $\langle cmd \rangle$ and $\langle yes \rangle$ will be executed. Otherwise, the content of $\langle tokens \rangle$ is saved to $\langle cmd \rangle$ and $\langle no \rangle$ is executed. This macro will, for instance, be used to distinguish key and $\backslash global\{key\}$ and retrieve key in the latter case.

```
93 \def\XKV@ifcmd#1#2#3{%
94   \def\XKV@@ifcmd##1#2##2##3\@nil##4{%
95     \def##4{##2}\ifx##4\@nnil
96       \def##4{##1}\expandafter\@secondoftwo
97     \else
98       \expandafter\@firstoftwo
99     \fi
100   }%
101   \XKV@@ifcmd#1#2{\@nil}\@nil#3%
102 }
```

```
\XKV@getkeyname  $\langle keyvalue \rangle \langle bin \rangle$ 
```

Utility macro to retrieve the key name from $\langle keyvalue \rangle$ which is of the form key=value, $\backslash savevalue\{key\}=value$ or $\backslash gsavevalue\{key\}=value$, possibly without value. $\backslash ifXKV@rkV$ will record whether this particular value should be saved. $\backslash ifXKV@sg$ will record whether this value should be saved globally or not. The key name will be stored in $\langle bin \rangle$.

```
103 \def\XKV@getkeyname#1#2{\expandafter\XKV@g@tkeyname#1=\@nil#2}
```

```
\XKV@g@tkeyname  $\langle key \rangle = \langle value \rangle \backslash @nil \langle bin \rangle$ 
```

Use $\backslash XKV@ifcmd$ several times to check the syntax of $\langle value \rangle$. Save $\langle key \rangle$ to $\langle bin \rangle$.

```
104 \long\def\XKV@g@tkeyname#1=#2\@nil#3{%
105   \XKV@ifcmd{#1}\savevalue#3{\XKV@rkVtrue\XKV@sgfalse}{%
106     \XKV@ifcmd{#1}\gsavevalue#3%
107     {\XKV@rkVtrue\XKV@sgtrue}{\XKV@rkVfalse\XKV@sgfalse}%
108   }%
109 }
```

```
\XKV@getsg  $\langle key \rangle \langle bin \rangle$ 
```

Utility macro to check whether key or $\backslash global\{key\}$ has been specified in $\langle key \rangle$. The key name is saved to $\langle bin \rangle$

```

110 \def\XKV@getsg#1#2{%
111   \expandafter\XKV@ifcmd\expandafter{#1}\global#2\XKV@sgtrue\XKV@sfalse
112 }

\XKV@define@default {<key>}{<default>}
Defines the default value macro for <key> and given \XKV@header.
113 \def\XKV@define@default#1#2{%
114   \expandafter\def\csname\XKV@header#1@default\expandafter
115     \endcsname\expandafter{\csname\XKV@header#1\endcsname{#2}}%
116 }

\define@key [<prefix>]{<family>}
Macro to define a key in a family. Notice the use of the KV prefix as default prefix. This
is done to allow setting both keyval and xkeyval keys with a single command. This top
level command first checks for an optional <prefix> and the mandatory <family>.
117 \def\define@key{\XKV@testoptb\XKV@define@key}

\XKV@define@key {<key>}
Check for an optional default value. If none present, define the key macro, else conti-
nue to eat the default value.
118 \def\XKV@define@key#1{%
119   \@ifnextchar[{\XKV@d@fine@key{#1}}{%
120     \long\expandafter\def\csname\XKV@header#1\endcsname###1%
121   }%
122 }

\XKV@d@fine@key {<key>}[<default>]
Defines the key macro and the default value macro.
123 \def\XKV@d@fine@key#1[#2]{%
124   \XKV@define@default{#1}{#2}%
125   \expandafter\def\csname\XKV@header#1\endcsname##1%
126 }

\define@cmdkey [<prefix>]{<family>}[<mp>]{<key>}
Define a command key. Test for optional <prefix>, mandatory <family>, optional <mp>
'macro prefix' and mandatory <key> name.
127 \def\define@cmdkey{\XKV@testoptd\XKV@define@cmdkey{cmd}}

\XKV@define@cmdkey {<mp>}{<key>}[<default>]{<function>}
Define the default value macro and the key macro. The key macro first defines the
control sequence formed by the <mp> and <key> to expand to the user input and then
executes the <function>.
128 \def\XKV@define@cmdkey#1#2[#3]#4{%
129   \ifXKV@st\XKV@define@default{#2}{#3}\fi
130   \def\XKV@tempa{\expandafter\def\csname\XKV@header#2\endcsname###1}%
131   \begingroup\expandafter\endgroup\expandafter\XKV@tempa\expandafter
132     {\expandafter\def\csname#1#2\endcsname{##1}#4}%
133 }

\define@cmdkeys [<prefix>]{<family>}[<mp>]{<keys>}
Define multiple command keys.
134 \def\define@cmdkeys{\XKV@testoptd\XKV@define@cmdkeys{cmd}}

```



```

\XKV@define@cmdkeys  {\<mp>}{\<keys>}{\<default>}
Loop over \<keys> and define a command key for every entry.
135 \def\XKV@define@cmdkeys#1#2[#3]{%
136   \XKV@sp@deflist\XKV@tempa{#2}%
137   \XKV@for@o\XKV@tempa\XKV@tempa{%
138     \edef\XKV@tempa{\noexpand\XKV@define@cmdkey{#1}{\XKV@tempa}}%
139     \XKV@tempa[#3]{}%
140   }%
141 }

\define@choicekey  *+[\<prefix>]{\<family>}
Choice keys. First check optional star, plus and prefix and store the family.
142 \def\define@choicekey{\XKV@testopta{\XKV@testoptb\XKV@define@choicekey}}

\XKV@define@choicekey  {\<key>}
Check for optional storage bins for the input and the number of the input in the list of
allowed inputs.
143 \def\XKV@define@choicekey#1{\@testopt{\XKV@d@fine@choicekey{#1}}{}}

\XKV@d@fine@choicekey  {\<key>}{\<bin>}{\<allowed>}
Store the storage bin and the list of allowed inputs for later use. After that, check for an
optional default value.
144 \def\XKV@d@fine@choicekey#1[#2]#3{%
145   \toks@{#2}%
146   \XKV@sp@deflist\XKV@tempa{#3}\XKV@toks\expandafter{\XKV@tempa}%
147   \@ifnextchar[{\XKV@d@fine@ch@icekey{#1}}{\XKV@d@fine@ch@ic@key{#1}}%
148 }

\XKV@d@fine@ch@icekey  {\<key>}{\<default>}
Define the default value macro if a default value was specified.
149 \def\XKV@d@fine@ch@icekey#1[#2]{%
150   \XKV@define@default{#1}{#2}%
151   \XKV@d@fine@ch@ic@key{#1}%
152 }

\XKV@d@fine@ch@ic@key  {\<key>}
Eat correct number of arguments.
153 \def\XKV@d@fine@ch@ic@key#1{%
154   \ifXKV@pl\XKV@afterelsefi
155     \expandafter\XKV@d@f@ne@ch@ic@k@y
156   \else\XKV@afterfi
157     \expandafter\XKV@d@f@ne@ch@ic@key
158   \fi
159   \csname\XKV@header#1\endcsname
160 }

\XKV@d@f@ne@ch@ic@key  \<key macro>{\<function>}
Eat one argument and pass it on to the macro that will define the key macro.
161 \def\XKV@d@f@ne@ch@ic@key#1#2{\XKV@d@f@n@ch@ic@k@y#1{#2}}

\XKV@d@f@ne@ch@ic@k@y  \<key macro>{\<function1>}{\<function2>}
Eat two arguments and pass these on to the macro that will define the key macro.
\<function1> will be executed on correct input, \<function2> on incorrect input.
162 \def\XKV@d@f@ne@ch@ic@k@y#1#2#3{\XKV@d@f@n@ch@ic@k@y#1{#2}{#3}}

```

`\XKV@d@f@n@@ch@ic@k@y` $\langle key macro \rangle \{ \langle function \rangle \}$
 Create the key macros. `\XKV@checkchoice` will be used to check the choice and execute one of its mandatory arguments.

```

163 \def\XKV@d@f@n@@ch@ic@k@y#1#2{%
164   \edef#1##1{%
165     \ifXKV@st\noexpand\XKV@sttrue\else\noexpand\XKV@stfalse\fi
166     \ifXKV@pl\noexpand\XKV@pltrue\else\noexpand\XKV@plfalse\fi
167     \noexpand\XKV@checkchoice[\the\toks@]{##1}{\the\XKV@toks}%
168   }%
169   \def\XKV@tempa{\def#1###1}%
170   \expandafter\XKV@tempa\expandafter{#1{##1}#2}%
171 }

```

`\define@boolkey` $+[\langle prefix \rangle]\{\langle family \rangle\}[\langle mp \rangle]\{\langle key \rangle\}$
 Define a boolean key. This macro checks for an optional `+`, an optional $\langle prefix \rangle$, the mandatory $\langle family \rangle$, an optional $\langle mp \rangle$ ('macro prefix') and the mandatory $\langle key \rangle$ name.

```

172 \def\define@boolkey{\XKV@t@stopta{\XKV@testoptd\XKV@define@boolkey{}}

```

`\XKV@define@boolkey` $\{\langle mp \rangle\}\{\langle key \rangle\}[\langle default \rangle]$
 Decide to eat 1 or 2 mandatory arguments for the key macro. Further, construct the control sequence for the key macro and the one for the if.

```

173 \def\XKV@define@boolkey#1#2[#3]{%
174   \ifXKV@pl\XKV@afterelsefi
175   \expandafter\XKV@d@f@ne@boolkey
176   \else\XKV@afterfi
177   \expandafter\XKV@d@fine@boolkey
178   \fi
179   \csname\XKV@header#2\endcsname{#2}{#1#2}{#3}%
180 }

```

`\XKV@d@fine@boolkey` $\langle key macro \rangle \{ \langle key \rangle \} \{ \langle if name \rangle \} \{ \langle default \rangle \} \{ \langle function \rangle \}$
 Eat one mandatory key function and pass it. Insert 'setting the if'.

```

181 \def\XKV@d@fine@boolkey#1#2#3#4#5{%
182   \XKV@d@f@ne@b@olkey#1{#2}{#3}{#4}%
183   {\csname#3\XKV@resa\endcsname#5}%
184 }

```

`\XKV@d@f@ne@boolkey` $\langle key macro \rangle \{ \langle key \rangle \} \{ \langle if name \rangle \} \{ \langle default \rangle \} \{ \langle func1 \rangle \} \{ \langle func2 \rangle \}$
 Eat two mandatory key functions and pass them. Insert 'setting the if'.

```

185 \def\XKV@d@f@ne@boolkey#1#2#3#4#5#6{%
186   \XKV@d@f@ne@b@olkey#1{#2}{#3}{#4}%
187   {\csname#3\XKV@resa\endcsname#5}{#6}%
188 }

```

`\XKV@d@f@ne@b@olkey` $\langle key macro \rangle \{ \langle key \rangle \} \{ \langle if name \rangle \} \{ \langle default \rangle \} \{ \langle function \rangle \}$
 Create the if, the default value macro (if a default value was present) and the key macro. We use `\XKV@checkchoice` internally to check the input and `\XKV@resa` to store the user input and pass it to setting the conditional.

```

189 \def\XKV@d@f@ne@b@olkey#1#2#3#4#5{%
190   \expandafter\newif\csname if#3\endcsname
191   \ifXKV@st\XKV@define@default{#2}{#4}\fi
192   \ifXKV@pl

```

```

193     \def#1##1{\XKV@pltrue\XKV@sttrue
194         \XKV@checkchoice[\XKV@resa]{##1}{true,false}#5%
195     }%
196     \else
197         \def#1##1{\XKV@plfalse\XKV@sttrue
198             \XKV@checkchoice[\XKV@resa]{##1}{true,false}#5%
199         }%
200     \fi
201 }

\define@boolkeys [\langle prefix\rangle]{\langle family\rangle}[\langle mp\rangle]{\langle keys\rangle}
Define multiple boolean keys without user specified key function. The key will, of
course, still set the if with user input.
202 \def\define@boolkeys{\XKV@plfalse\XKV@testoptd\XKV@define@boolkeys{}}

\XKV@define@boolkeys {\langle mp\rangle}{\langle keys\rangle}[\langle default\rangle]
Loop over the list of \langle keys\rangle and create a boolean key for every entry.
203 \def\XKV@define@boolkeys#1#2[#3]{%
204     \XKV@sp@deflist\XKV@tempa{#2}%
205     \XKV@for@o\XKV@tempa\XKV@tempa{%
206         \expandafter\XKV@d@fine@boolkeys\expandafter{\XKV@tempa}{#1}{#3}%
207     }%
208 }

\XKV@d@fine@boolkeys {\langle key\rangle}{\langle mp\rangle}{\langle default\rangle}
Use \XKV@d@f@one@b@olkey internally to define the if, the default value macro (if
present) and the key macro.
209 \def\XKV@d@fine@boolkeys#1#2#3{%
210     \expandafter\XKV@d@f@one@b@olkey\csname\XKV@header#1\endcsname
211     {#1}{#2#1}{#3}{\csname#2#1\XKV@resa\endcsname}}%
212 }

\XKV@cc This macro is used inside key macros to perform input checks. This is the user interface
to \XKV@checkchoice and we only use the latter internally to avoid slow parsings of
optional * and +.
213 \def\XKV@cc{\XKV@testopta{\@testopt\XKV@checkchoice{}}}

\XKV@checkchoice [\langle bin\rangle]{\langle input\rangle}{\langle allowed\rangle}
Checks whether \langle bin\rangle contains at least one control sequence and converts \langle input\rangle and
\langle allowed\rangle to lowercase if requested. If \langle bin\rangle is empty, perform the fast \in@ check im-
mediately. Else, determine whether the bin contains one or two tokens. For the first
alternative, we can still use the fast \in@ check. Notice that this macro uses settings for
\ifXKV@st and \ifXKV@pl.
214 \def\XKV@checkchoice[#1]#2#3{%
215     \def\XKV@tempa{#1}%
216     \ifXKV@st\lowercase{\fi
217     \ifx\XKV@tempa\@empty
218         \def\XKV@tempa{\XKV@ch@ckch@ice\@nil{#2}{#3}}%
219     \else
220         \def\XKV@tempa{\XKV@ch@ckchoice#1\@nil{#2}{#3}}%
221     \fi
222     \ifXKV@st}\fi\XKV@tempa
223 }

```

`\XKV@ch@ckchoice` $\langle bin1 \rangle \langle bin2 \rangle \backslash @nil \{ \langle input \rangle \} \{ \langle allowed \rangle \}$
 Check whether $\langle bin2 \rangle$ is empty. In that case, only the $\langle input \rangle$ should be saved and we can continue with the fast `\in@` check. If not, also the number of the input in the $\langle allowed \rangle$ list should be saved and we need to do a slower while type of loop.

```

224 \def\XKV@ch@ckchoice#1#2\@nil#3#4{%
225   \def\XKV@tempa{#2}%
226   \ifx\XKV@tempa\@empty\XKV@afterelsefi
227     \XKV@ch@ckch@ice#1{#3}{#4}%
228   \else\XKV@afterfi
229     \XKV@@ch@ckchoice#1#2{#3}{#4}%
230   \fi
231 }
```

`\XKV@ch@ckch@ice` $\langle bin \rangle \{ \langle input \rangle \} \{ \langle allowed \rangle \}$
 Checks whether $\langle input \rangle$ is in the list $\langle allowed \rangle$ and perform actions accordingly.

```

232 \def\XKV@ch@ckch@ice#1#2#3{%
233   \def\XKV@tempa{#1}%

  If we have a  $\langle bin \rangle$ , store the input there.

234   \ifx\XKV@tempa\@nnil\let\XKV@tempa\@empty\else
235     \def\XKV@tempa{\def#1{#2}}%
236   \fi
237   \in@{, #2, }{, #3, }%
238   \ifin@
```

The $\langle input \rangle$ is allowed.

```

239   \ifXKV@pl

  If we have a +, there are two functions. Execute the first.

240     \XKV@addtomacro@n\XKV@tempa\@firstoftwo
241   \else
```

Else, we have one function; execute it.

```

242     \XKV@addtomacro@n\XKV@tempa\@firstofone
243   \fi
244   \else
```

If we have a +, there are two functions. Execute the second.

```

245   \ifXKV@pl
246     \XKV@addtomacro@n\XKV@tempa\@secondoftwo
247   \else
```

Else, raise an error and gobble the one function.

```

248     \XKV@toks{#2}%
249     \XKV@err{value ‘\the\XKV@toks’ is not allowed}%
250     \XKV@addtomacro@n\XKV@tempa\@gobble
251   \fi
252   \fi
253   \XKV@tempa
254 }
```

`\XKV@@ch@ckchoice` $\langle bin1 \rangle \langle bin2 \rangle \{ \langle input \rangle \} \{ \langle allowed \rangle \}$
 Walk over the $\langle allowed \rangle$ list and compare each entry with the $\langle input \rangle$. The input is saved in $\langle bin1 \rangle$, the number of the $\langle input \rangle$ in the $\langle allowed \rangle$ list (starting at zero) is saved in $\langle bin2 \rangle$. If the $\langle input \rangle$ is not allowed, $\langle bin2 \rangle$ will be defined to contain -1.

```

255 \def\XKV@@ch@ckchoice#1#2#3#4{%
```

Save the current value of the counter as to avoid disturbing it. We don't use a group as that takes a lot of memory and requires some more tokens (for global definitions).

```
256 \edef\XKV@tempa{\the\count@}\count@\z@
```

The input.

```
257 \def\XKV@tempb{#3}%
```

Define the while loop.

```
258 \def\XKV@tempc##1,{%
```

```
259 \def#1{##1}%
```

```
260 \ifx#1\@nnil
```

The *<input>* was not in *<allowed>*. Set the number to -1.

```
261 \def#1{#3}\def#2{-1}\count@\XKV@tempa
```

```
262 \ifXKV@pl
```

Execute the macro for the case that input was not allowed.

```
263 \let\XKV@tempd\@secondoftwo
```

```
264 \else
```

If that function does not exist, raise a generic error and gobble the function to be executed on good input.

```
265 \XKV@toks{#3}%
```

```
266 \XKV@err{value ‘\the\XKV@toks’ is not allowed}%
```

```
267 \let\XKV@tempd\@gobble
```

```
268 \fi
```

```
269 \else
```

```
270 \ifx#1\XKV@tempb
```

We found *<input>* in *<allowed>*. Save the number of the *<input>* in the list *<allowed>*.

```
271 \edef#2{\the\count@}\count@\XKV@tempa
```

```
272 \ifXKV@pl
```

```
273 \let\XKV@tempd\XKV@@ch@ckch@ice
```

```
274 \else
```

```
275 \let\XKV@tempd\XKV@@ch@ckch@ic@
```

```
276 \fi
```

```
277 \else
```

Increase counter and check next item in the list *<allowed>*.

```
278 \advance\count@\@ne
```

```
279 \let\XKV@tempd\XKV@tempc
```

```
280 \fi
```

```
281 \fi
```

```
282 \XKV@tempd
```

```
283 }%
```

Start the while loop.

```
284 \XKV@tempc#4,\@nil,%
```

```
285 }
```

```
\XKV@@ch@ckch@ice <text>\@nil,
```

```
\XKV@@ch@ckch@ic@ Gobble remaining <text> and execute the proper key function.
```

```
286 \def\XKV@@ch@ckch@ice#1\@nil,{\@firstoftwo}
```

```
287 \def\XKV@@ch@ckch@ic#1\@nil,{\@firstofone}
```

`\key@ifundefined` This macro allows checking if a key is defined in a family from a list of families. Check for an optional prefix.

```
288 \def\key@ifundefined{\@testopt\XKV@key@ifundefined{KV}}
```

`\XKV@key@ifundefined` [*<prefix>*]{*<fams>*}

This macro is split in two parts so that `\XKV@p@x` can use only the main part of the macro. First we save the prefix and the list of families.

```
289 \def\XKV@key@ifundefined[#1]#2{%
290   \XKV@makepf{#1}%
291   \XKV@checksantizeb{#2}\XKV@fams
292   \expandafter\XKV@sp@deflist\expandafter
293     \XKV@fams\expandafter{\XKV@fams}%
294   \XKV@key@if@ndefined
295 }
```

`\XKV@key@if@ndefined` {*<key>*}

Loop over the list of families until we find the key in a family.

```
296 \def\XKV@key@if@ndefined#1{%
297   \XKV@knftrue
298   \KV@sp@def\XKV@tkey{#1}%
299   \XKV@whilst\XKV@fams\XKV@tfam\ifXKV@knf\fi%
```

Set the header.

```
300   \XKV@makehd\XKV@tfam
```

Check whether the macro for the key is defined.

```
301   \XKV@ifundefined{\XKV@header\XKV@tkey}{-}{\XKV@knffalse}%
302 }
```

Execute one of the final two arguments depending on state of `\XKV@knf`.

```
303 \ifXKV@knf
304   \expandafter\@firstoftwo
305 \else
306   \expandafter\@secondoftwo
307 \fi
308 }
```

`\disable@keys` [*<prefix>*]{*<family>*}

Macro that make a key produce a warning on use.

```
309 \def\disable@keys{\XKV@testoptb\XKV@disable@keys}
```

`\XKV@disable@keys` {*<keys>*}

Workhorse for `\disable@keys` which redefines a list of key macro to produce a warning.

```
310 \def\XKV@disable@keys#1{%
311   \XKV@checksantizeb{#1}\XKV@tempa
312   \XKV@for@o\XKV@tempa\XKV@tempa{%
313     \XKV@ifundefined{\XKV@header\XKV@tempa}{%
314       \XKV@err{key ‘\XKV@tempa’ undefined}%
315     }{%
316       \edef\XKV@tempb{%
317         \noexpand\XKV@warn{key ‘\XKV@tempa’ has been disabled}%
318       }
319       \XKV@tempa\XKV@tempb
320     }%
321   }%
322 }
```

```

318     }%
319     \XKV@ifundefined{\XKV@header\XKV@tempa @default}{-%
320         \edef\XKV@tempc{\noexpand\XKV@define@key{\XKV@tempa}}%
321     }{%
322         \edef\XKV@tempc{\noexpand\XKV@define@key{\XKV@tempa} []}%
323     }%
324     \expandafter\XKV@tempc\expandafter{\XKV@tempb}%
325 }%
326 }%
327 }

\presetkeys  [⟨prefix⟩]{⟨family⟩}
\gpresetkeys This provides the presetting system. The macro works incrementally : keys that have
              been preset before will overwrite the old preset values, new ones will be added to the
              end of the preset list.
328 \def\presetkeys{\XKV@stfalse\XKV@testoptb\XKV@presetkeys}
329 \def\gpresetkeys{\XKV@sttrue\XKV@testoptb\XKV@presetkeys}

\XKV@presetkeys {⟨head presets⟩}{⟨tail presets⟩}
              Execute the merging macro \XKV@pr@setkeys for both head and tail presets.
330 \def\XKV@presetkeys#1#2{%
331     \XKV@pr@setkeys{#1}{preseth}%
332     \XKV@pr@setkeys{#2}{presett}%
333 }

\XKV@pr@setkeys {⟨presets⟩}{⟨postfix⟩}
              Check whether presets have already been defined. If not, define them and do not start
              the merging macro. Otherwise, create the control sequence that stores these presets
              and start merging.
334 \def\XKV@pr@setkeys#1#2{%
335     \XKV@ifundefined{\XKV@\XKV@header#2}{-%
336         \XKV@checksantizea{#1}\XKV@tempa
337         \ifXKV@st\expandafter\global\fi\expandafter\def\csname
338             XKV@\XKV@header#2\expandafter\endcsname\expandafter{\XKV@tempa}%
339     }{%
340         \expandafter\XKV@merge\csname XKV@\XKV@header
341             #2\endcsname{#1}\XKV@getkeyname
342     }%
343 }

\delpresetkeys [⟨prefix⟩]{⟨family⟩}
\gdelpresetkeys Macros to remove entries from presets.
344 \def\delpresetkeys{\XKV@stfalse\XKV@testoptb\XKV@delpresetkeys}
345 \def\gdelpresetkeys{\XKV@sttrue\XKV@testoptb\XKV@delpresetkeys}

\XKV@delpresetkeys {⟨head key list⟩}{⟨tail key list⟩}
              Run the main macro for both head and tail presets.
346 \def\XKV@delpresetkeys#1#2{%
347     \XKV@d@l@presetkeys{#1}{preseth}%
348     \XKV@d@l@presetkeys{#2}{presett}%
349 }

```

`\XKV@d@lpresetkeys` $\{\langle key\ list\rangle\}\{\langle postfix\rangle\}$
Check whether presets have been saved and if so, start deletion algorithm. Supply the macro `\XKV@getkeyname` to retrieve key names from entries.

```

350 \def\XKV@d@lpresetkeys#1#2{%
351   \XKV@ifundefined{XKV@\XKV@header#2}{%
352     \XKV@err{no presets defined for ‘\XKV@header’}%
353   }{%
354     \expandafter\XKV@delete\csname XKV@\XKV@header
355       #2\endcsname{#1}\XKV@getkeyname
356   }%
357 }

```

`\unpresetkeys` $[\langle prefix\rangle]\{\langle family\rangle\}$
`\gunpresetkeys` Removes presets for a particular family.

```

358 \def\unpresetkeys{\XKV@stfalse\XKV@testoptb\XKV@unpresetkeys}
359 \def\gunpresetkeys{\XKV@sttrue\XKV@testoptb\XKV@unpresetkeys}

```

`\XKV@unpresetkeys` Undefine the preset macros. We make them undefined since this will make them appear undefined to both versions of the macro `\XKV@ifundefined`. Making the macros `\relax` would work in the case that no ε -TeX is available (hence using `\ifx\csname`), but doesn't work when ε -TeX is used (and using `\ifcsname`).

```

360 \def\XKV@unpresetkeys{%
361   \XKV@ifundefined{XKV@\XKV@header preseth}{%
362     \XKV@err{no presets defined for ‘\XKV@header’}%
363   }{%
364     \ifXKV@st\expandafter\global\fi\expandafter\let
365       \csname XKV@\XKV@header preseth\endcsname\@undefined
366     \ifXKV@st\expandafter\global\fi\expandafter\let
367       \csname XKV@\XKV@header preset\endcsname\@undefined
368   }%
369 }

```

`\savekeys` $[\langle prefix\rangle]\{\langle family\rangle\}$
`\gsavekeys` Store a list of keys of a family that should always be saved. The macro works incrementally and avoids duplicate entries in the list.

```

370 \def\savekeys{\XKV@stfalse\XKV@testoptb\XKV@savekeys}
371 \def\gsavekeys{\XKV@sttrue\XKV@testoptb\XKV@savekeys}

```

`\XKV@savekeys` $\{\langle key\ list\rangle\}$
Check whether something has been saved before. If not, start merging.

```

372 \def\XKV@savekeys#1{%
373   \XKV@ifundefined{XKV@\XKV@header save}{%
374     \XKV@checksantizeb{#1}\XKV@tempa
375     \ifXKV@st\expandafter\global\fi\expandafter\def\csname XKV@%
376       \XKV@header save\expandafter\endcsname\expandafter{\XKV@tempa}%
377   }{%
378     \expandafter\XKV@merge\csname XKV@\XKV@header
379       save\endcsname{#1}\XKV@getsg
380   }%
381 }

```

`\delsavekeys` $[\langle prefix\rangle]\{\langle family\rangle\}$
`\gdelsavekeys` Remove entries from the list of save keys.


```

382 \def\delsavekeys{\XKV@stfalse\XKV@testoptb\XKV@delsavekeys}
383 \def\gdelsavekeys{\XKV@sttrue\XKV@testoptb\XKV@delsavekeys}

\XKV@delsavekeys  {\<key list>}
Check whether save keys are defined and if yes, start deletion algorithm. Use the macro
\XKV@getsg to retrieve key names from entries.

384 \def\XKV@delsavekeys#1{%
385   \XKV@ifundefined{\XKV@\XKV@header save}{%
386     \XKV@err{no save keys defined for ‘\XKV@header’}%
387   }{%
388     \expandafter\XKV@delete\csname XKV@\XKV@header
389       save\endcsname{#1}\XKV@getsg
390   }%
391 }

\unsavekeys  [ <prefix> ] { <family> }
\gunsavekeys Similar to \unpresetkeys, but removes the ‘save keys list’ for a particular family.

392 \def\unsavekeys{\XKV@stfalse\XKV@testoptb\XKV@unsavekeys}
393 \def\gunsavekeys{\XKV@sttrue\XKV@testoptb\XKV@unsavekeys}

\XKV@unsavekeys  Workhorse for \unsavekeys.

394 \def\XKV@unsavekeys{%
395   \XKV@ifundefined{\XKV@\XKV@header save}{%
396     \XKV@err{no save keys defined for ‘\XKV@header’}%
397   }{%
398     \ifXKV@st\expandafter\global\fi\expandafter\let
399     \csname XKV@\XKV@header save\endcsname\@undefined
400   }%
401 }

\setkeys  *+ [ <prefix> ] { <families> }
Set keys. The starred version does not produce errors, but appends keys that cannot
be located to the list in \XKV@rm. The plus version sets keys in all families that are
supplied.

402 \def\setkeys{\XKV@testopta{\XKV@testoptc\XKV@setkeys}}

\XKV@setkeys  [ <na> ] { <key=value list> }
Workhorse for \setkeys.

403 \long\def\XKV@setkeys[#1]#2{%
404   \XKV@checksantizea{#2}\XKV@resb
405   \let\XKV@naa\@empty

Retrieve a list of key names from the user input.

406   \XKV@for@o\XKV@resb\XKV@tempa{%
407     \expandafter\XKV@g@tkeyname\XKV@tempa=\@nil\XKV@tempa
408     \XKV@addtolist@x\XKV@naa\XKV@tempa
409   }%

Initialize the remaining keys, but only for the outermost level of \setkeys.

410   \ifnum\XKV@depth=\z@\let\XKV@rm\@empty\fi

Now scan the list of families for preset keys and set user input keys.

411   \XKV@usepresetkeys{#1}{preseth}%
412   \expandafter\XKV@s@tkeys\expandafter{\XKV@resb}{#1}%

```

```

413 \XKV@usepresetkeys{#1}{presett}%
414 \let\CurrentOption\@empty
415 }

\XKV@usepresetkeys {<na>}{<postfix>}
Loop over the list of families and check them for preset keys. If present, set them right
away, taking into account the keys which are set by the user, available in the \XKV@naa
list.
416 \def\XKV@usepresetkeys#1#2{%
417 \XKV@presetttrue
418 \XKV@for@eo\XKV@fams\XKV@tfam{%
419 \XKV@makehd\XKV@tfam
420 \XKV@ifundefined{XKV@\XKV@header#2}{-}{%
421 \XKV@toks\expandafter\expandafter\expandafter
422 {\csname XKV@\XKV@header#2\endcsname}%
423 \@expandtwoargs\XKV@s@tkeys{\the\XKV@toks}%
424 {\XKV@naa\ifx\XKV@naa\@empty\else,\fi#1}%
425 }%
426 }%
427 \XKV@presettfalse
428 }

\XKV@s@tkeys {<key=value list>}{<na>}
This macro starts the loop over the key=value list. Do not set keys in the list <na>.
429 \long\def\XKV@s@tkeys#1#2{%
Define the list of key names which should be ignored.
430 \XKV@sp@deflist\XKV@na{#2}%
Loop over the key=value list.
431 \XKV@for@n{#1}\CurrentOption{%
Split key and value.
432 \expandafter\XKV@s@tk@ys\CurrentOption==\@nil
433 }%
434 }

\XKV@s@tk@ys <key>=<value>=#3\@nil
Split key name and value (if present). If #3 non-empty, there was no =<value>.
435 \long\def\XKV@s@tk@ys#1=#2=#3\@nil{%
Check for \savevalue and \gsavevalue and remove spaces from around the key
name.
436 \XKV@g@tkeyname#1=\@nil\XKV@tkey
437 \expandafter\KV@@sp@def\expandafter\XKV@tkey\expandafter{\XKV@tkey}%
If the key is empty and a value has been specified, generate an error.
438 \ifx\XKV@tkey\@empty
439 \XKV@toks{#2}%
440 \ifcat$\the\XKV@toks$\else
441 \XKV@err{no key specified for value ‘\the\XKV@toks’}%
442 \fi
443 \else

```

If in the `\XKV@na` list, ignore the key.

```

444 \expandafter\in@{\XKV@tkey,}{,\XKV@na,}%
445 \ifin@ \else
446 \XKV@knftrue
447 \KV@sp@def\XKV@tempa{#2}%
448 \ifXKV@preset\XKV@s@tk@ys@{#3}\else
449 \ifXKV@pl

```

If a command with a `+` is used, set keys in all families on the list.

```

450 \XKV@for@eo\XKV@fams\XKV@tfam{%
451 \XKV@makehd\XKV@tfam
452 \XKV@s@tk@ys@{#3}%
453 }%
454 \else

```

Else, scan the families on the list but stop when the key is found or when the list has run out.

```

455 \XKV@whilst\XKV@fams\XKV@tfam\ifXKV@knf\fi{%
456 \XKV@makehd\XKV@tfam
457 \XKV@s@tk@ys@{#3}%
458 }%
459 \fi
460 \fi
461 \ifXKV@knf
462 \ifXKV@inpox

```

We are in the options section. Try to use the macro defined by `\DeclareOptionX*`.

```

463 \ifx\XKV@doxs\relax

```

For classes, ignore unknown (possibly global) options. For packages, raise the standard \LaTeX error.

```

464 \ifx\@current\@clsextension\else
465 \let\CurrentOption\XKV@tkey\@unknownoptionerror
466 \fi

```

Pass the option through `\DeclareOptionX*`.

```

467 \else\XKV@doxs\fi
468 \else

```

If not in the options section, raise an error or add the key to the list in `\XKV@rm` when `\setkeys*` has been used.

```

469 \ifXKV@st
470 \XKV@addtolist@o\XKV@rm\CurrentOption
471 \else
472 \XKV@err{'\XKV@tkey' undefined in families '\XKV@fams'}%
473 \fi
474 \fi
475 \else

```

Remove global options set by the document class from `\@unusedoptionlist`. Global options set by other packages or classes will be removed by `\ProcessOptionsX*`.

```

476 \ifXKV@inpox\ifx\XKV@testclass\XKV@documentclass
477 \expandafter\XKV@useoption\expandafter{\CurrentOption}%
478 \fi\fi
479 \fi
480 \fi

```

```

481 \fi
482 }

```

`\XKV@s@tk@ys@` `{⟨ind⟩}`

This macro coordinates the work of setting a key. *⟨ind⟩* is an indicator for the presence of a user submitted value for the key. If empty, no value was present.

```

483 \def\XKV@s@tk@ys@#1{%

```

Check whether the key macro exists.

```

484 \XKV@ifundefined{\XKV@header\XKV@tkey}{-}{%
485 \XKV@knffalse

```

Check global setting by `\savekeys` to know whether or not to save the value of the key at hand.

```

486 \XKV@ifundefined{XKV@\XKV@header save}{-}{%
487 \expandafter\XKV@testsavekey\csname XKV@\XKV@header
488 save\endcsname\XKV@tkey
489 }%

```

Save the value of a key.

```

490 \ifXKV@rkv
491 \ifXKV@s@tk@ys@#1\@empty\XKV@afterelsefi
492 \csname XKV@\XKV@header\XKV@tkey @value\endcsname\XKV@tempa
493 \fi

```

Replace pointers by saved values.

```

494 \expandafter\XKV@replacepointers\expandafter{\XKV@tempa}%

```

If no value was present, use the default value macro, if one exists. Otherwise, issue an error.

```

495 \ifx\@empty#1\@empty\XKV@afterelsefi
496 \XKV@ifundefined{\XKV@header\XKV@tkey @default}{-}{%
497 \XKV@err{no value specified for key ‘\XKV@tkey’}%
498 }{%
499 \expandafter\expandafter\expandafter\XKV@default
500 \csname\XKV@header\XKV@tkey @default\endcsname\@nil
501 }%
502 \else\XKV@afterfi

```

Save state in case the key executes `\setkeys` or `\XKV@cc`.

```

503 \XKV@srstate{@\romannumeral\XKV@depth}{-}%

```

Execute the key.

```

504 \csname\XKV@header\XKV@tkey\expandafter
505 \endcsname\expandafter{\XKV@tempa}\relax

```

Restore the current state.

```

506 \XKV@srstate{-}{@\romannumeral\XKV@depth}%
507 \fi
508 }%
509 }

```

`\XKV@testsavekey` `⟨save key list⟩⟨key name⟩`

This macro checks whether the key in macro *⟨key name⟩* appears in the save list in macro *⟨save key list⟩*. Furthermore, it checks whether or not to save the key globally. In other words, that `\global{key}` is in the list.

```

510 \def\XKV@testsavekey#1#2{%
511   \ifXKV@rk\else
512     \XKV@for@o#1\XKV@resa{%
513       \expandafter\XKV@ifcmd\expandafter{\XKV@resa}\global\XKV@resa{%
514         \ifx#2\XKV@resa
515           \XKV@rkvtrue\XKV@sgtrue
516         \fi
517       }{%
518         \ifx#2\XKV@resa
519           \XKV@rkvtrue\XKV@sgfalse
520         \fi
521       }%
522     }%
523   \fi
524 }

```

\XKV@replacepointers *{⟨key=value list⟩}*

\XKV@r@placepointers Replaces all pointers by their saved values. The result is stored in \XKV@tempa. We feed the replacement and the following tokens again to the macro to replace nested pointers. It stops when no pointers are found anymore. We keep a list of pointers replaced already for this key in \XKV@resa so we can check whether we are running in circles.

```

525 \long\def\XKV@replacepointers#1{%
526   \let\XKV@tempa\@empty
527   \let\XKV@resa\@empty
528   \XKV@r@placepointers#1\usevalue\@nil
529 }
530 \long\def\XKV@r@placepointers#1\usevalue#2{%
531   \XKV@addtomacro@n\XKV@tempa{#1}%
532   \def\XKV@tempb{#2}%
533   \ifx\XKV@tempb\@nnil\else\XKV@afterfi
534     \XKV@ifundefined{XKV@\XKV@header#2@value}{%
535       \XKV@err{no value recorded for key ‘#2’ ; ignored}%
536       \XKV@r@placepointers
537     }{%
538       \@expandtwoargs\in@{,#2,}{,\XKV@resa,}%
539       \ifin@\XKV@afterelsefi
540       \XKV@err{back linking pointers ; pointer replacement canceled}%
541     \else\XKV@afterfi
542       \XKV@addtolist@x\XKV@resa{#2}%
543       \expandafter\expandafter\expandafter\XKV@r@placepointers
544       \csname XKV@\XKV@header#2@value\endcsname
545     \fi
546   }%
547 \fi
548 }

```

\XKV@default *⟨token⟩⟨tokens⟩*

This macro checks the \prefix@fam@key@default macro. If the macro has the form as defined by keyval or xkeyval, it is possible to extract the default value and save that (if requested) and replace pointers. If the form is incorrect, just execute the macro and forget about possible pointers. The reason for this check is that certain packages (like fancyrb) abuse the ‘default value system’ to execute code instead of setting keys by redefining default value macros. These macros do not actually contain a default value

and trying to extract that would not work.

```
549 \def\XKV@default#1#2\@nil{%
```

Retrieve the first token in the macro.

```
550 \expandafter\edef\expandafter\XKV@tempa
551 \expandafter{\expandafter\@gobble\string#1}%
```

Construct the name that we expect on the basis of the keyval and xkeyval syntax of default values.

```
552 \edef\XKV@tempb{\XKV@header\XKV@tkey}%
```

Sanitize \XKV@tempb to reset catcodes for comparison with \XKV@tempa.

```
553 \@onelevel@sanitize\XKV@tempb
554 \ifx\XKV@tempa\XKV@tempb
```

If it is safe, extract the value. We temporarily redefine the key macro to save the default value in a macro. Saving the default value itself directly to a macro when defining keys would of course be easier, but a lot of packages rely on this system created by keyval, so we have to support it here.

```
555 \begingroup
556 \expandafter\def\csname\XKV@header\XKV@tkey\endcsname##1{%
557 \gdef\XKV@tempa{##1}%
558 }%
559 \csname\XKV@header\XKV@tkey @default\endcsname
560 \endgroup
```

Save the default value to a value macro if either the key name has been entered in a \savekeys macro or the starred form has been used.

```
561 \XKV@ifundefined{\XKV@\XKV@header save}{-}{%
562 \expandafter\XKV@testsavekey\csname \XKV@\XKV@header
563 save\endcsname\XKV@tkey
564 }%
565 \ifXKV@rkv
566 \ifXKV@sg\expandafter\global\fi\expandafter\let
567 \csname \XKV@\XKV@header\XKV@tkey @value\endcsname\XKV@tempa
568 \fi
```

Replace the pointers.

```
569 \expandafter\XKV@replacepointers\expandafter
570 {\XKV@tempa}\XKV@afterelsefi
```

Save internal state.

```
571 \XKV@srstate{@\romannumeral\XKV@depth}{-}%
```

Execute the key with the (possibly changed) default value.

```
572 \expandafter#1\expandafter{\XKV@tempa}\relax
```

Restore internal state.

```
573 \XKV@srstate{-}{@\romannumeral\XKV@depth}%
574 \else\XKV@afterfi
```

Save internal state.

```
575 \XKV@srstate{@\romannumeral\XKV@depth}{-}%
```

Execute the key with the default value.

```
576 \csname\XKV@header\XKV@tkey @default\endcsname\relax
```

Restore the state.

```
577 \XKV@srstate{}{@\romannumeral\XKV@depth}%
578 \fi
579 }
```

`\setrmkeys` **+ [$\langle prefix \rangle$] { $\langle families \rangle$ }*

Set remaining keys stored in `\XKV@rm`. The starred version creates a new list in `\XKV@rm` in case there are still keys that cannot be located in the families specified. Care is taken again not to expand fragile macros. Use `\XKV@testopa` again to handle optional arguments.

```
580 \def\setrmkeys{\XKV@testopa{\XKV@testoptc\XKV@setrmkeys}}
```

`\XKV@setrmkeys` [*$\langle na \rangle$*]

Submits the keys in `\XKV@rm` to `\XKV@setkeys`.

```
581 \def\XKV@setrmkeys[#1]{%
582 \def\XKV@tempa{\XKV@setkeys[#1]}%
583 \expandafter\XKV@tempa\expandafter{\XKV@rm}%
584 }
```

Reset catcodes.

```
585 \XKVcatcodes
586 </xkvtex>
```

✖

14.2 xkeyval.sty

✖ Initialize the package.

```
587 <*xkvlatex>
588 \NeedsTeXFormat{LaTeX2e}[1995/12/01]
589 \ProvidesPackage{xkeyval}
590 [2014/12/03 v2.7a package option processing (HA)]
```

Initializations. Load `xkeyval.tex`, adjust some catcodes to define internal macros and initialize the `\DeclareOptionX*` working macro.

```
591 \ifx\XKeyValLoaded\endinput\else\input xkeyval \fi
592 \edef\XKVcatcodes{%
593 \catcode'\noexpand\=\the\catcode'\=\relax
594 \catcode'\noexpand\,\the\catcode'\,\relax
595 \let\noexpand\XKVcatcodes\relax
596 }
597 \catcode'\=12\relax
598 \catcode'\,12\relax
599 \let\XKV@doxs\relax
```

`\XKV@warn` Warning and error macros.

```
\XKV@err 600 \def\XKV@warn#1{\PackageWarning{xkeyval}{#1}}
601 \def\XKV@err#1{\PackageError{xkeyval}{#1}\@ehc}
```

Retrieve the document class from `\@filelist`. This is the first filename in the list with a class extension. Use a while loop to scan the list and stop when we found the first filename which is a class. Also stop in case the list is scanned fully.

```
602 \XKV@whilst\@filelist\XKV@tempa\ifx\XKV@documentclass\undefined\fi{%
```

```

603 \filename@parse\XKV@tempa
604 \ifx\filename@ext\@clsextension
605 \XKV@ifundefined{opt@\filename@area\filename@base.\filename@ext
606 }{}{%
607 \edef\XKV@documentclass{%
608 \filename@area\filename@base.\filename@ext
609 }%
610 }%
611 \fi
612 }

```

If we didn't find the document class, raise an error, otherwise filter global options.

```

613 \ifx\XKV@documentclass\@undefined
614 \XKV@err{xkeyval loaded before \protect\documentclass}%
615 \let\XKV@documentclass\@empty
616 \let\XKV@classoptionslist\@empty
617 \else
618 \let\XKV@classoptionslist\@classoptionslist

```

Code to filter key=value pairs from \@classoptionslist without expanding options.

```

619 \def\XKV@tempa#1{%
620 \let\@classoptionslist\@empty
621 \XKV@for@n{#1}\XKV@tempa{%
622 \expandafter\in@\expandafter=\expandafter{\XKV@tempa}%
623 \ifin@\else\XKV@addtolist@o\@classoptionslist\XKV@tempa\fi
624 }%
625 }
626 \expandafter\XKV@tempa\expandafter{\@classoptionslist}
627 \fi

```

```

\XKV@testopte {\function}
\XKV@t@stopte Macros for \ExecuteOptionsX and \ProcessOptionsX for testing for optional argu-
\XKV@t@st@pte ments and inserting default values. Execute \function after preforming the checks.
\XKV@t@st@pte
628 \def\XKV@testopte#1{%
629 \XKV@ifstar{\XKV@sttrue\XKV@t@stopte#1}{\XKV@stfalse\XKV@t@stopte#1}%
630 }
631 \def\XKV@t@stopte#1{\@testopt{\XKV@t@st@pte#1}{KV}}
632 \def\XKV@t@st@pte#1[#2]{%
633 \XKV@makepf{#2}%
634 \@ifnextchar<{\XKV@t@st@pte#1}%
635 {\XKV@t@st@pte#1<\@currname.\@currentx>}%
636 }
637 \def\XKV@t@st@pte#1<#2>{%
638 \XKV@sp@deflist\XKV@fams{#2}%
639 \@testopt#1{}%
640 }

```

Macros for class and package writers. These are mainly shortcuts to \define@key and \setkeys. The \LaTeX macro \@fileswith@ptions is set to generate an error. This is the case when a class or package is loaded in between \DeclareOptionX and \ProcessOptionsX commands.

\DeclareOptionX *
Declare a package or class option.


```

641 \def\DeclareOptionX{%
642   \let\@fileswith@ptions\@badrequireerror
643   \XKV@ifstar\XKV@d@x\XKV@d@x
644 }

\XKV@d@x This macro defines \XKV@doxs to be used for unknown options.
645 \long\def\XKV@d@x#1{\XKV@toks{#1}\edef\XKV@doxs{\the\XKV@toks}}

\XKV@d@x Insert default prefix and family name (which is the filename of the class or package)
\XKV@@d@x and add empty default value if none present. Execute \define@key.
\XKV@@@d@x
646 \def\XKV@d@x{\@testopt\XKV@@d@x{KV}}
647 \def\XKV@@d@x[#1]{%
648   \@ifnextchar<{\XKV@@@d@x[#1]}{\XKV@@@d@x[#1]<\@currname.\@current>}}%
649 }
650 \def\XKV@@@d@x[#1]<#2>#3{\@testopt{\define@key[#1]{#2}{#3}}{}}

\ExecuteOptionsX [<prefix>]{<families>}[<na>]{<key=value list>}
This macro sets keys to specified values and uses \XKV@setkeys to do the job. Insert
default prefix and family name if none provided. Use \XKV@t@stopte to handle option-
al arguments and reset \ifXKV@st and \ifXKV@pl first to avoid unexpected behavior
when \setkeys*+ (or a friend) has been used before \ExecuteOptionsX.
651 \def\ExecuteOptionsX{\XKV@stfalse\XKV@plfalse\XKV@t@stopte\XKV@setkeys}

\ProcessOptionsX * [<prefix>]{<families>}
Processes class or package using xkeyval. The starred version copies class options sub-
mitted by the user as well, given that they are defined in the local families which are
passed to the macro. Use \XKV@testopte to handle optional arguments.
652 \def\ProcessOptionsX{\XKV@plfalse\XKV@testopte\XKV@pox}

\XKV@pox [<na>]
Workhorse for \ProcessOptionsX and \ProcessOptionsX*.
653 \def\XKV@pox[#1]{%
654   \let\XKV@tempa\@empty

Set \XKV@inpox : indicates that we are in \ProcessOptionsX to invoke a special rou-
tine in \XKV@s@tkeys.
655   \XKV@inpoxtrue

Set \@fileswith@ptions again in case no \DeclareOptionX has been used. This will
be used to identify a call to \setkeys from \ProcessOptionsX.
656   \let\@fileswith@ptions\@badrequireerror
657   \edef\XKV@testclass{\@currname.\@current}%

If xkeyval is loaded by the document class, initialize \@unusedoptionlist.
658   \ifx\XKV@testclass\XKV@documentclass
659     \let\@unusedoptionlist\XKV@classoptionslist
660     \XKV@ifundefined{ver@xkvltxp.sty}{\}%
661     \onelevel@sanitize\@unusedoptionlist
662   }%
663   \else

Else, if the starred version is used, copy global options in case they are defined in local
families. Do not execute this in the document class to avoid setting keys twice.
664   \ifXKV@st

```

```

665     \def\XKV@tempb##1,{%
666       \def\CurrentOption{##1}%
667       \ifx\CurrentOption\@nnil\else
668         \XKV@g@tkeyname##1=\@nil\CurrentOption
669         \XKV@key@if@undefined{\CurrentOption}{-}{%

```

If the option also exists in local families, add it to the list for later use and remove it from \@unusedoptionlist.

```

670         \XKV@useoption{##1}%
671         \XKV@addtolist@n\XKV@tempa{##1}%
672       }%
673     \expandafter\XKV@tempb
674   \fi
675 }%
676 \expandafter\XKV@tempb\XKV@classoptionslist,\@nil,%
677 \fi
678 \fi

```

Add current package options to the list.

```

679 \expandafter\XKV@addtolist@o\expandafter
680 \XKV@tempa\csname opt@ \@currname.\@current\endcsname

```

Set options. We can be certain that global options can be set since the definitions of local options have been checked above. Note that \DeclareOptionX* will not consume global options when \ProcessOptionsX* is used.

```

681 \def\XKV@tempb{\XKV@setkeys[#1]}%
682 \expandafter\XKV@tempb\expandafter{\XKV@tempa}%

```

Reset the macro created by \DeclareOptionX* to avoid processing future unknown keys using \XKV@doxs.

```

683 \let\XKV@doxs\relax

```

Reset the \XKV@rm macro to avoid processing remaining options with \setrmkeys.

```

684 \let\XKV@rm\@empty

```

Reset \ifXKV@inpox : not in \ProcessOptionsX anymore.

```

685 \XKV@inpoxfalse

```

Reset \@fileswith@pti@ns to allow loading of classes or packages again.

```

686 \let\@fileswith@pti@ns\@@fileswith@pti@ns
687 \AtEndOfPackage{\let\@unprocessedoptions\relax}%
688 }

```

\XKV@useoption {<option>}

Removes an option from \@unusedoptionlist.

```

689 \def\XKV@useoption#1{%
690   \def\XKV@resa{#1}%
691   \XKV@ifundefined{ver@xkvltxp.sty}{-}{%
692     \@onelevel@sanitize\XKV@resa
693   }%
694   \@expandtwoargs\@removeelement{\XKV@resa}%
695   {\@unusedoptionlist}\@unusedoptionlist
696 }

```

The options section. Postponed to the end to allow for using xkeyval options macros. All options are silently ignored.

```

697 \DeclareOptionX*{%
698   \PackageWarning{xkeyval}{Unknown option ‘\CurrentOption’}%
699 }
700 \ProcessOptionsX

Reset catcodes.
701 \XKVcatcodes
702 </xkvlatex>

✖

```

14.3 keyval.tex

✖ Since the xkeyval macros handle input in a very different way than keyval macros, it is not wise to redefine keyval primitives (like \KV@do and \KV@split) used by other packages as a back door into \setkeys. Instead, we load the original primitives here for compatibility to existing packages using (parts of) keyval. Most of the code is original, but slightly adapted to xkeyval. See the keyval documentation for information about the macros below.

```

703 < *xkvkeyval>
704 %%
705 %% Based on keyval.sty.
706 %%
707 \def\XKV@tempa#1{%
708 \long\def\KV@@sp@def##1##2{%
709   \futurelet\XKV@resa\KV@@sp@d##2\@nil\@nil#1\@nil\relax##1}%
710 \long\def\KV@@sp@d{%
711   \ifx\XKV@resa\@sptoken
712     \expandafter\KV@@sp@b
713   \else
714     \expandafter\KV@@sp@b\expandafter#1%
715   \fi}%
716 \long\def\KV@@sp@b#1##1 \@nil{\KV@@sp@c##1}%
717 }
718 \XKV@tempa{ }
719 \long\def\KV@@sp@c#1\@nil#2\relax#3{\XKV@toks{#1}\edef#3{\the\XKV@toks}}
720 \long\def\KV@do#1,{%
721   \ifx\relax#1\@empty\else
722     \KV@split#1==\relax
723     \expandafter\KV@do\fi}
724 \long\def\KV@split#1=#2=#3\relax{%
725   \KV@@sp@def\XKV@tempa{#1}%
726   \ifx\XKV@tempa\@empty\else
727     \expandafter\let\expandafter\XKV@tempc
728       \csname\KV@prefix\XKV@tempa\endcsname
729     \ifx\XKV@tempc\relax
730       \XKV@err{'\XKV@tempa' undefined}%
731     \else
732       \ifx\@empty#3\@empty
733         \KV@default
734       \else
735         \KV@@sp@def\XKV@tempb{#2}%
736         \expandafter\XKV@tempc\expandafter{\XKV@tempb}\relax
737       \fi

```

```

738   \fi
739 \fi}
740 \def\KV@default{%
741   \expandafter\let\expandafter\XKV@tempb
742     \csname\KV@prefix\XKV@tempa @default\endcsname
743   \ifx\XKV@tempb\relax
744     \XKV@err{No value specified for key '\XKV@tempa'}%
745   \else
746     \XKV@tempb\relax
747   \fi}
748 \def\KV@def#1#2[#3]{%
749   \long\@namedef{KV@#1@#2@default\expandafter}\expandafter
750     {\csname KV@#1@#2\endcsname{#3}}%
751   \long\@namedef{KV@#1@#2}##1}
752 </xkvkeyval>

```

✕

14.4 xkvtxhdr.tex

✕This section generates `xkvtxhdr.tex` which contains some standard \TeX macros taken from `latex.ltx`. This will only be loaded when not using `xkeyval.sty`.

```

753 <*xkvheader>
754 %%
755 %% Taken from latex.ltx.
756 %%
757 \message{2005/02/22 v1.1 xkeyval TeX header (HA)}
758 \def\@nnil{\@nil}
759 \def\@empty{}
760 \def\newif#1{%
761   \count@\escapechar \escapechar\m@ne
762   \let#1\iffalse
763   \if#1\iftrue
764     \if#1\iffalse
765     \escapechar\count@}
766 \def\@if#1#2{%
767   \expandafter\def\csname\expandafter\@gobbletwo\string#1%
768     \expandafter\@gobbletwo\string#2\endcsname
769     {\let#1#2}}
770 \long\def\@ifnextchar#1#2#3{%
771   \let\reserved@d=#1%
772   \def\reserved@a{#2}%
773   \def\reserved@b{#3}%
774   \futurelet\@let@token\@ifnch}
775 \def\@ifnch{%
776   \ifx\@let@token\@sptoken
777     \let\reserved@c\@xifnch
778   \else
779     \ifx\@let@token\reserved@d
780       \let\reserved@c\reserved@a
781     \else
782       \let\reserved@c\reserved@b
783     \fi
784   \fi

```

```

785 \reserved@c}
786 \def\ :{\let\sptoken= } \ : % this makes \sptoken a space token
787 \def\ :{\@xifnch} \expandafter\def\ : {\futurelet\@let@token\@ifnch}
788 \let\kernel@ifnextchar\@ifnextchar
789 \long\def\@testopt#1#2{%
790 \kernel@ifnextchar[{\#1}{\#1[{\#2}]}]}
791 \long\def\@firstofone#1{\#1}
792 \long\def \@gobble #1{}
793 \long\def \@gobbletwo #1#2{}
794 \def\@expandtwoargs#1#2#3{%
795 \edef\reserved@a{\noexpand#1{\#2}{\#3}}\reserved@a}
796 \edef\@backslashchar{\expandafter\@gobble\string\}
797 \newif\ifin@
798 \def\in@#1#2{%
799 \def\in@@##1#2##3\in@@{%
800 \ifx\in@@##2\in@false\else\in@true\fi}%
801 \in@@#2#1\in@\in@@}
802 \def\strip@prefix#1>{}
803 \def \@onelevel@sanitize #1{%
804 \edef #1{\expandafter\strip@prefix
805 \meaning #1}%
806 }
807 </xkvheader>

```

✖

14.5 xkvutils.tex

✖ Avoid loading xkvutils.tex twice.

```

808 (*xkvutils)
809 \csname XKeyValUtilsLoaded\endcsname
810 \let\XKeyValUtilsLoaded\endinput
811 \edef\XKeyValUtilsCatcodes{%
812 \catcode'\noexpand\@the\catcode'\@relax
813 \let\noexpand\XKeyValUtilsCatcodes\relax
814 }
815 \catcode'\@=11\relax

```

This package uses a private token to avoid conflicts with other packages that use \TeX scratch token registers in key macro definitions (for instance, graphicx, keys angle and scale).

```

816 \newtoks\XKV@toks
817 \newtoks\XKV@tempa@toks

```

\@firstoftwo Two utility macros from the latex.ltx needed for executing \XKV@ifundefined in the sequel.

```

818 \long\def\@firstoftwo#1#2{\#1}
819 \long\def\@secondoftwo#1#2{\#2}

```

\XKV@afterfi Two utility macros to move execution of content of a conditional branch after the \fi.
\XKV@afterelsefi This avoids nesting conditional structures too deep.

```

820 \long\def\XKV@afterfi#1\fi{\fi#1}
821 \long\def\XKV@afterelsefi#1\else#2\fi{\fi#1}

```

`\XKV@ifundefined` `{\csname}\{\undefined}\{\defined}}`

Executes `\undefined` if the control sequence with name `\csname` is undefined, else it executes `\defined`. This macro uses ϵ -TeX if possible to avoid filling TeX's hash when checking control sequences like key macros in the rest of the package. The use of `\XKV@afterelsefi` is necessary here to avoid TeX picking up the second `\fi` as end of the main conditional when `\ifcsname` is undefined. For `\XKV@afterelsefi` this `\fi` is hidden in the group used to define `\XKV@ifundefined` in branch of the case that `\ifcsname` is defined. Notice the following. Both versions of the macro leave the tested control sequence undefined. However, the first version will execute `\undefined` if the control sequence is undefined or `\relax`, whereas the second version will only execute `\undefined` if the control sequence is undefined. This is no problem for the applications in this package.

```
822 \ifx\ifcsname\@undefined\XKV@afterelsefi
823   \def\XKV@ifundefined#1{%
824     \begingroup\expandafter\expandafter\expandafter\endgroup
825       \expandafter\ifx\csname#1\endcsname\relax
826       \expandafter\@firstoftwo
827     \else
828       \expandafter\@secondoftwo
829     \fi
830   }
831 \else
832   \def\XKV@ifundefined#1{%
833     \ifcsname#1\endcsname
834       \expandafter\@secondoftwo
835     \else
836       \expandafter\@firstoftwo
837     \fi
838   }
839 \fi
```

Check whether keyval has been loaded and if not, load keyval primitives and prevent keyval from being loaded after xkeyval.

```
840 \XKV@ifundefined{ver@keyval.sty}{
841   \input keyval
842   \expandafter\def\csname ver@keyval.sty\endcsname{1999/03/16}
843 }{}
```

`\@ifnextcharacter` Check the next character independently of its catcode. This will be used to safely perform `\@ifnextcharacter+` and `\@ifnextcharacter*`. This avoids errors in case any other package changes the catcode of these characters.
`\@ifncharacter` Contributed by Donald Arseneau.

```
844 \long\def\@ifnextcharacter#1#2#3{%
845   \@ifnextchar\bgroup
846   {\@ifnextchar{#1}{#2}{#3}}%
847   {\@ifncharacter{#1}{#2}{#3}}%
848 }
849 \long\def\@ifncharacter#1#2#3#4{%
850   \if\string#1\string#4%
851     \expandafter\@firstoftwo
852   \else
853     \expandafter\@secondoftwo
```

```

854 \fi
855 {#2}{#3}#4%
856 }

\XKV@for@n {<list>}<cmd>{<function>}
Fast for-loop. <list> is not expanded. Entries of <list> will be stored in <cmd> and at every
iteration <function> is executed.
Contributed by Morten Høgholm.
857 \long\def\XKV@for@n#1#2#3{%
858 \XKV@tempa@toks{#1}\edef#2{\the\XKV@tempa@toks}%
859 \ifx#2\@empty
860 \XKV@for@break
861 \else
862 \expandafter\XKV@f@r
863 \fi
864 #2{#3}#1,\@nil,%
865 }

\XKV@f@r <cmd>{<function>}<entry>,
Looping macro.
866 \long\def\XKV@f@r#1#2#3,{%
867 \XKV@tempa@toks{#3}\edef#1{\the\XKV@tempa@toks}%
868 \ifx#1\@nnil
869 \expandafter\@gobbletwo
870 \else
871 #2\expandafter\XKV@f@r
872 \fi
873 #1{#2}%
874 }

\XKV@for@break <text>\@nil,
Macro to stop the for-loop.
875 \long\def\XKV@for@break #1\@nil,{\fi}

\XKV@for@o <listcmd><cmd>{<function>}
<listcmd> is expanded once before starting the loop.
876 \long\def\XKV@for@o#1{\expandafter\XKV@for@n\expandafter{#1}}

\XKV@for@en {<list>}<cmd>{<function>}
As \XKV@for@n, but this macro will execute <function> also when <list> is empty. This
is done to support packages that use the ‘empty family’, like PSTricks.
877 \long\def\XKV@for@en#1#2#3{\XKV@f@r#2{#3}#1,\@nil,}

\XKV@for@eo <listcmd><cmd>{<function>}
As \XKV@for@o, but this macro will execute <function> also when <listcmd> is empty.
878 \long\def\XKV@for@eo#1#2#3{%
879 \def#2{\XKV@f@r#2{#3}}\expandafter#2#1,\@nil,%
880 }

\XKV@whilst <listcmd><cmd>{<if>\fi}{<function>}
<listcmd> is expanded once. Execution of <function> stops when either the list has ran
out of elements or <if> is not true anymore. When using \iftrue for <if>, the execution

```

of the macro is the same as that of `\XKV@for@o`, but contains an additional check at every iteration and is hence less efficient than `\XKV@for@o` in that situation.

```
881 \long\def\XKV@whilst#1#2#3\fi#4{%
```

Check whether the condition is true and start iteration.

```
882   #3\expandafter\XKV@wh@list#1,\@nil,\@nil\@@#2#3\fi{#4}{}\fi
883 }
```

```
\XKV@wh@list <entry>,<text>\@@<cmd><if>\fi{<function>}{<previous>}
```

Performs iteration and checks extra condition. This macro is not optimized for the case that the list contains a single element. At the end of every iteration, the current *<entry>* will be stored in *<previous>* for the next iteration. The previous entry is necessary when stepping out of the loop.

```
884 \long\def\XKV@wh@list#1,#2\@@#3#4\fi#5#6{%
```

Define the running *<cmd>*.

```
885   \def#3{#1}%
```

If we find the end of the list, stop.

```
886   \ifx#3\@nnil
887     \def#3{#6}\expandafter\XKV@wh@l@st
888   \else
```

If the condition is met, execute *<function>* and continue. Otherwise, define the running command to be the previous entry (which inflicted the condition becoming false) and stop.

```
889     #4%
890     #5\expandafter\expandafter\expandafter\XKV@wh@list
891   \else
892     \def#3{#6}\expandafter\expandafter\expandafter\XKV@wh@l@st
893   \fi
894 \fi
895 #2\@@#3#4\fi{#5}{#1}%
896 }
```

```
\XKV@wh@l@st <text>\@@<cmd><if>\fi{<function>}{<previous>}
```

Macro to gobble remaining input.

```
897 \long\def\XKV@wh@l@st#1\@@#2#3\fi#4#5{}
```

```
\XKV@addtomacro@n <macro>{<content>}
```

Adds *<content>* to *<macro>* without expanding it.

```
898 \long\def\XKV@addtomacro@n#1#2{%
899   \XKV@tempa@toks\expandafter{#1#2}%
900   \edef#1{\the\XKV@tempa@toks}%
901 }
```

```
\XKV@addtomacro@o <macro>{<content>}
```

Adds *<content>* to *<macro>* after expanding the first token of *<content>* once. Often used to add the content of a macro to another macro.

```
902 \def\XKV@addtomacro@o#1#2{%
903   \expandafter\XKV@addtomacro@n\expandafter#1\expandafter{#2}%
904 }
```


`\XKV@addtolist@n` $\langle cmd \rangle \{ \langle content \rangle \}$
 Adds $\langle content \rangle$ to the list in $\langle cmd \rangle$ without expanding $\langle content \rangle$. Notice that it is assumed that $\langle cmd \rangle$ is not undefined.

```

905 \def\XKV@addtolist@n#1#2{%
906   \ifx#1\@empty
907     \XKV@addtomacro@n#1{#2}%
908   \else
909     \XKV@addtomacro@n#1{,#2}%
910   \fi
911 }
```

`\XKV@addtolist@o` $\langle cmd \rangle \{ \langle content \rangle \}$
 Adds $\langle content \rangle$ to the list in $\langle cmd \rangle$ after expanding the first token in $\langle content \rangle$ once.

```

912 \def\XKV@addtolist@o#1#2{%
913   \ifx#1\@empty
914     \XKV@addtomacro@o#1#2%
915   \else
916     \XKV@addtomacro@o#1{\expandafter,#2}%
917   \fi
918 }
```

`\XKV@addtolist@x` $\langle cmd \rangle \{ \langle content \rangle \}$
 Adds $\langle content \rangle$ to the list in $\langle cmd \rangle$ after a full expansion of both $\langle cmd \rangle$ and $\langle content \rangle$.

```

919 \def\XKV@addtolist@x#1#2{\edef#1{#1\ifx#1\@empty\else,\fi#2}}
```

`\@selective@sanitize` $[\langle level \rangle] \{ \langle character string \rangle \} \{ \langle cmd \rangle \}$
`\@selective@sanitize` Converts selected characters, given by $\langle character string \rangle$, within the first-level expansion of $\langle cmd \rangle$ to category code 12, leaving all other tokens (including grouping braces) untouched. Thus, macros inside $\langle cmd \rangle$ do not lose their function, as it is the case with `\@onelevel@sanitize`. The resulting token list is again saved in $\langle cmd \rangle$.
 Example : `\def\cs{ ~{\fi}~}` and `\@selective@sanitize{!~}\cs` will change the catcode of ‘~’ to *other* within `\cs`, while `\fi` and ‘~’ will remain unchanged. As the example shows, unbalanced conditionals are allowed.
 Remarks : $\langle cmd \rangle$ should not contain the control sequence `\bgroup`; however, `\csname` `bgroup\endcsname` and `\egroup` are possible. The optional $\langle level \rangle$ command controls up to which nesting level sanitizing takes place inside groups; 0 will only sanitize characters in the top level, 1 will also sanitize within the first level of braces (but not in the second), etc. The default value is 10000.

```

920 \def\@selective@sanitize{\@testopt\@selective@sanitize\M}
921 \def\@selective@sanitize[#1]#2#3{%
922   \begingroup
923     \count@#1\relax\advance\count@\@ne
924     \XKV@toks\expandafter{#3}%
925     \def#3{#2}\@onelevel@sanitize#3%
926     \edef#3{{#3}{\the\XKV@toks}}%
927     \expandafter\@selective@sanitize\expandafter#3#3%
928     \expandafter\XKV@tempa@toks\expandafter{#3}%
929     \expandafter\endgroup\expandafter\toks@\expandafter{\the\XKV@tempa@toks}%
930     \edef#3{\the\toks@}%
931 }
```

`\@selective@sanitize` $\{ \langle cmd \rangle \} \{ \langle sanitized character string \rangle \} \{ \langle token list \rangle \}$
 Performs the main work. Here, the characters in $\langle sanitized character string \rangle$ are already

converted to catcode 12, $\langle token\ list\rangle$ is the first-level expansion of the original contents of $\langle cmd\rangle$. The macro basically steps through the $\langle token\ list\rangle$, inspecting each single token to decide whether it has to be sanitized or passed to the result list. Special care has to be taken to detect spaces, grouping characters and conditionals (the latter may disturb other expressions). However, it is easier and more efficient to look for T_EX primitives in general – which are characterized by a \backslash meaning that starts with a backslash – than to test whether a token equals specifically $\backslash if$, $\backslash else$, $\backslash fi$, etc. Note that $\backslash @s@l@o@ctive@sanitize$ is being called recursively if $\langle token\ list\rangle$ contains grouping braces.

```

932 \def\@s@l@o@ctive@sanitize#1#2#3{%
933   \def\@i{\futurelet\@tok\@ii}%
934   \def\@ii{%
935     \expandafter\@iii\meaning\@tok\relax
936     \ifx\@tok\@s@l@o@ctive@sanitize
937       \let\@cmd\@gobble
938     \else
939       \ifx\@tok\@sptoken
940         \XKV@toks\expandafter{#1}\edef#1{\the\XKV@toks\space}%
941         \def\@cmd{\afterassignment\@i\let\@tok= }%
942       \else
943         \let\@cmd\@iv
944       \fi
945     \fi
946     \@cmd
947   }%
948   \def\@iii#1#2\relax{\if#1\@backslashchar\let\@tok\relax\fi}%
949   \def\@iv#1{%
950     \toks@\expandafter{#1}\XKV@toks{##1}%
951     \ifx\@tok\bgroup
952       \advance\count@\m@ne
953       \ifnum\count@>\z@
954         \begingroup
955           \def#1{\expandafter\@s@l@o@ctive@sanitize
956             \csname\string#1\endcsname{#2}}%
957           \expandafter#1\expandafter{\the\XKV@toks}%
958           \XKV@toks\expandafter\expandafter\expandafter
959             {\csname\string#1\endcsname}%
960           \edef#1{\noexpand\XKV@toks{\the\XKV@toks}}%
961           \expandafter\endgroup#1%
962         \fi
963         \edef#1{\the\toks@\the\XKV@toks}%
964         \advance\count@\@ne
965         \let\@cmd\@i
966       \else
967         \edef#1{\expandafter\string\the\XKV@toks}%
968         \expandafter\in@\expandafter{#1}{#2}%
969         \edef#1{\the\toks@\ifin#1\else
970           \ifx\@tok\@sptoken\space\else\the\XKV@toks\fi\fi}%
971         \edef\@cmd{\noexpand\@i\ifx\@tok\@sptoken\the\XKV@toks\fi}%
972       \fi
973       \@cmd
974     }%
975     \let#1\@empty\@i#3\@s@l@o@ctive@sanitize

```

```

976 }

\XKV@checksantizea {<content>}<cmd>
Check whether <content>, to be saved to macro <cmd> unexpanded, contains the characters = or , with wrong catcodes. If so, it sanitizes them before saving <content> to <cmd>.

977 \long\def\XKV@checksantizea#1#2{%
978   \XKV@ch@cksantize{#1}#2=%
979   \ifin@ \else\XKV@ch@cksantize{#1}#2,\fi
980   \ifin@ \@selective@santize[0]{,=#2\fi
981 }

\XKV@checksantizeb {<content>}<cmd>
Similar to \XKV@checksantizea, but only checks commas.

982 \def\XKV@checksantizeb#1#2{%
983   \XKV@ch@cksantize{#1}#2,%
984   \ifin@ \@selective@santize[0],#2\fi
985 }

\XKV@ch@cksantize {<character string>}<cmd><token>
This macro first checks whether at least one <token> is in <character string>. If that is the case, it checks whether the character has catcode 12. Note that the macro will conclude that the character does not have catcode 12 when it is used inside a group {}, but that is not a problem, as we don't expect <token> (namely , or =) inside a group, unless this group is in a key value. But we won't worry about those characters anyway since the relevant user key macro will have to process that. Further, it is assumed that all occurrences of <token> in <character string> have the same catcode. <cmd> is used as a temporary macro and will contain <character string> at the end of the macro.

986 \long\def\XKV@ch@cksantize#1#2#3{%
987   \XKV@tempa@toks{#1}\edef#2{\the\XKV@tempa@toks}%
988   \@onelevel@santize#2%

Check whether there is at least one = present.

989   \@expandtwoargs\in@#3{#2}%
990   \ifin@

If so, try to find it. If we can't find it, the character(s) has (or have) the wrong catcode. In that case sanitizing is necessary. This actually occurs, because the input was read by TEX before (and for instance stored in a macro or token register).

991   \long\def#2##1#3##2\@nil{%
992     \XKV@tempa@toks{##2}\edef#2{\the\XKV@tempa@toks}%
993     \ifx#2\@empty\else\in@false\fi
994   }%
995   #2#1#3\@nil
996   \fi
997   \XKV@tempa@toks{#1}\edef#2{\the\XKV@tempa@toks}%
998 }

\XKV@sp@deflist <cmd>{<token list>}
Defines <cmd> as <token list> after removing spaces surrounding elements of the list in <token list>. So, keya, key b becomes keya,key b. This is used to remove spaces from around elements in a list. Using \zap@space for this job, would also remove the

```

spaces inside elements and hence changing key or family names with spaces. This method is slower, but does allow for spaces in key and family names, just as keyval did. We need this algorithm at several places to be able to perform `\in@{,key,}{, . . . ,}`, without having to worry about spaces in between commas and key names.

```

999 \def\XKV@sp@deflist#1#2{%
1000   \let#1\@empty
1001   \XKV@for@n{#2}\XKV@resa{%
1002     \expandafter\KV@sp@def\expandafter\XKV@resa\expandafter{\XKV@resa}%
1003     \XKV@addtomacro@o#1{\expandafter,\XKV@resa}%
1004   }%
1005   \ifx#1\@empty\else
1006     \def\XKV@resa,##1\@nil{\def#1{##1}}%
1007     \expandafter\XKV@resa#1\@nil
1008   \fi
1009 }
```

`\XKV@merge` *<list>{<new items>}{<filter>}*

This is a merging macro. For a given new item, the old items are scanned. If an old item key name matches with a new one, the new one will replace the old one. If not, the old one will be appended (and might be overwritten in a following loop). If, at the end of the old item loop the new item has not been used, it will be appended to the end of the list. This macro works irrespective of special syntax. The *<filter>* is used to filter the key name from the syntax, eg `\global{key}`. All occurrences of a particular key in the existing list will be overwritten by the new item. This macro is used to make `\savekeys` and `\presetkeys` incremental. The *<filter>* is `\XKV@getsg` and `\XKV@getkeyname` respectively.

```

1010 \def\XKV@merge#1#2#3{%
1011   \XKV@checksantizea{#2}\XKV@tempa
```

Start the loop over the new presets. At every iteration, one new preset will be compared with old presets.

```

1012   \XKV@for@o\XKV@tempa\XKV@tempa{%
1013     \XKV@pltrue
```

Retrieve the key name of the new item at hand.

```

1014     #3\XKV@tempa\XKV@tempb
```

Store the (partially updated) old list in a temp macro and empty the original macro.

```

1015     \let\XKV@tempc#1%
1016     \let#1\@empty
```

Start a loop over the old list.

```

1017     \XKV@for@o\XKV@tempc\XKV@tempc{%
```

Retrieve the key name of the old key at hand.

```

1018       #3\XKV@tempc\XKV@tempd
1019       \ifx\XKV@tempb\XKV@tempd
```

If the key names are equal, append the new item to the list and record that this key should not be added to the end of the presets list.

```

1020         \XKV@plfalse
1021         \XKV@addtolist@o#1\XKV@tempa
1022       \else
```

If the key names are not equal, then just append the current item to the list.

```
1023      \XKV@addtolist@o#1\XKV@tempc
1024      \fi
1025    }%
```

If, after checking the old item, no old item has been overwritten then append the new item to the end of the existing list.

```
1026      \ifXKV@pl\XKV@addtolist@o#1\XKV@tempa\fi
1027    }%
```

If requested, save the new list globally.

```
1028      \ifXKV@st\global\let#1#1\fi
1029 }
```

`\XKV@delete` $\langle list \rangle \{ \langle delete \rangle \} \langle filter \rangle$

Delete entries $\langle delete \rangle$ by key name from a $\langle list \rangle$ of presets or save keys using $\langle filter \rangle$. For `\delpresetkeys`, this is the macro `\XKV@getkeyname` and for `\delsavekeys`, it is the macro `\XKV@getsg`.

```
1030 \def\XKV@delete#1#2#3{%
```

Sanitize comma's.

```
1031   \XKV@checksanitizetb{#2}\XKV@tempa
```

Copy the current list and make the original empty.

```
1032   \let\XKV@tempb#1%
1033   \let#1\@empty
```

Run over the current list.

```
1034   \XKV@for@o\XKV@tempb\XKV@tempb{%
```

Get the key name to identify the current entry.

```
1035     #3\XKV@tempb\XKV@tempc
```

If the current key name is in the list, do not add it anymore.

```
1036     \@expandtwoargs\in@{,\XKV@tempc,}\{,\XKV@tempa,}%
1037     \ifin@\else\XKV@addtolist@o#1\XKV@tempb\fi
1038   }%
```

Save globally is necessary.

```
1039     \ifXKV@st\global\let#1#1\fi
1040 }
```

Finalize.

```
1041 \XKeyValUtilsCatcodes
1042 \</xkvutils>
```

✖

14.6 xkvview.sty

✖ This section provides a small utility for package developers. It provides several macros to generate overviews of the keys that are defined in a package or a collection of packages. It is possible to get an overview for a specific family, but also to get a complete overview of all keys that have been defined after loading this package.

```
1043 \*xkvview)
1044 \NeedsTeXFormat{LaTeX2e}[1995/12/01]
```

```

1045 \ProvidesPackage{xkvview}%
1046 [2008/08/10 v1.5 viewer utility for xkeyval (HA)]
1047 \RequirePackage{xkeyval}
1048 \RequirePackage{longtable}
1049 \DeclareOptionX*{%
1050   \PackageWarning{xkvview}{Unknown option ‘\CurrentOption’}%
1051 }
1052 \ProcessOptionsX

  Initializations.

1053 \newif\ifXKV@vwkey
1054 \newif\ifXKV@colii
1055 \newif\ifXKV@coliii
1056 \newif\ifXKV@coliv
1057 \newif\ifXKV@colv
1058 \newwrite\XKV@out
1059 \let\XKV@db\@empty

  Setup options and presets.

1060 \define@cmdkeys[XKV]{xkvview}[XKV@]{%
1061   prefix,family,type,default,file,columns,wcolsep,weol}{\@nil}
1062 \define@boolkeys[XKV]{xkvview}[XKV@]{view,vlabels,wlabels}[true]
1063 \presetkeys[XKV]{xkvview}{prefix,family,type,default,file,%
1064   columns,wcolsep=&,weol=\\,view,vlabels=false,wlabels=false}{%

\XKV@tabulate   {<key>}{<type>}{<default>}
\XKV@t@bulate   Adds the input information to the main database in \XKV@db.

1065 \def\XKV@tabulate#1#2#3{%
1066   \def\XKV@tempa{#3}%
1067   \@onelevel@sanitize\XKV@tempa
1068   \XKV@addtolistx\XKV@db{#1=\ifx\XKV@prefix\@empty\else\expandafter
1069     \XKV@t@bulate\XKV@prefix\fi=\XKV@tfam=#2=\XKV@tempa}%
1070 }
1071 \def\XKV@t@bulate#1@{#1}

\XKV@define@key   Redefine the internals of key defining macros to record information in the database.
\XKV@d@fine@k@y 1072 \def\XKV@define@key#1{%
\XKV@define@cmdkey 1073   \@ifnextchar[{\XKV@d@fine@k@y{#1}}{%
\XKV@d@fine@ch@icekey 1074     \XKV@tabulate{#1}{ordinary}{[none]}%
\XKV@d@fine@ch@ic@key 1075     \expandafter\def\csname\XKV@header#1\endcsname###1%
\XKV@d@f@ne@b@olkey 1076   }%
1077 }
1078 \def\XKV@d@fine@k@y#1[#2]{%
1079   \XKV@tabulate{#1}{ordinary}{#2}%
1080   \XKV@define@default{#1}{#2}%
1081   \expandafter\def\csname\XKV@header#1\endcsname##1%
1082 }
1083 \def\XKV@define@cmdkey#1#2[#3]#4{%
1084   \ifXKV@st
1085     \XKV@tabulate{#2}{command}{#3}%
1086     \XKV@define@default{#2}{#3}%
1087   \else
1088     \XKV@tabulate{#2}{command}{[none]}%
1089   \fi
1090   \def\XKV@tempa{\expandafter\def\csname\XKV@header#2\endcsname###1}%

```

```

1091 \begingroup\expandafter\endgroup\expandafter\XKV@tempa\expandafter
1092 {\expandafter\def\csname#1#2\endcsname{##1}#4}%
1093 }
1094 \def\XKV@d@fine@ch@icekey#1[#2]{%
1095 \XKV@tabulate{#1}{choice}{#2}%
1096 \XKV@define@default{#1}{#2}%
1097 \XKV@d@fine@ch@ic@key{#1}%
1098 }
1099 \def\XKV@d@fine@ch@ic@key#1{%
1100 \XKV@tabulate{#1}{choice}{[none]}%
1101 \ifXKV@pl\XKV@afterelsefi
1102 \expandafter\XKV@d@f@ne@ch@ic@k@y
1103 \else\XKV@afterfi
1104 \expandafter\XKV@d@f@ne@ch@ic@key
1105 \fi
1106 \csname\XKV@header#1\endcsname
1107 }
1108 \def\XKV@d@f@ne@b@olkey#1#2#3#4#5{%
1109 \expandafter\newif\csname if#3\endcsname
1110 \ifXKV@st
1111 \XKV@tabulate{#2}{boolean}{#4}%
1112 \XKV@define@default{#2}{#4}%
1113 \else
1114 \XKV@tabulate{#2}{boolean}{[none]}%
1115 \fi
1116 \ifXKV@pl
1117 \def#1##1{\XKV@pltrue\XKV@sttrue
1118 \XKV@checkchoice[\XKV@resa]{##1}{true,false}#5%
1119 }%
1120 \else
1121 \def#1##1{\XKV@plfalse\XKV@sttrue
1122 \XKV@checkchoice[\XKV@resa]{##1}{true,false}#5%
1123 }%
1124 \fi
1125 }

\mkvview {<options>}
The main macro. Produces a long table and/or writes to a target file.
1126 \def\mkvview#1{%
Process all options.
1127 \setkeys[XKV]{mkvview}{#1}%
1128 \ifx\XKV@default@nnil\else\@onelevel@sanitize\XKV@default\fi

If no column information, display all columns.
1129 \ifx\XKV@columns@nnil
1130 \count@5
1131 \XKV@coliittrue\XKV@coliiittrue\XKV@colivtrue\XKV@colvtrue
1132 \else

Check how much and which columns should be displayed.
1133 \count@\@ne
1134 \@expandtwoargs\in@{,prefix,}{,\XKV@columns,}%
1135 \ifin@\advance\count@\@ne\XKV@coliittrue\else\XKV@coliifalse\fi
1136 \@expandtwoargs\in@{,family,}{,\XKV@columns,}%

```

```

1137 \ifin@advance\count@{@ne\XKV@coliiittrue\else\XKV@coliiifalse\fi
1138 \@expandtwoargs\in@{,type,}{,\XKV@columns,}%
1139 \ifin@advance\count@{@ne\XKV@colivtrue\else\XKV@colivfalse\fi
1140 \@expandtwoargs\in@{,default,}{,\XKV@columns,}%
1141 \ifin@advance\count@{@ne\XKV@colvtrue\else\XKV@colvfalse\fi
1142 \fi
1143 \ifXKV@view

```

Construct long table header.

```

1144 \protected@edef\XKV@tempa{\noexpand\begin{longtable}[l]{%
1145 *{the\count@ l}\normalfont Key\ifXKV@colii&\normalfont Prefix%
1146 \fi\ifXKV@coliii&\normalfont Family\fi\ifXKV@coliv&\normalfont
1147 Type\fi\ifXKV@colv&\normalfont Default\fi\\noexpand\hline
1148 \noexpand\endfirsthead\noexpand\multicolumn{the\count@}{l}{%
1149 \normalfont\emph{Continued from previous page}}\\noexpand\hline
1150 \normalfont Key\ifXKV@colii&\normalfont Prefix\fi\ifXKV@coliii
1151 &\normalfont Family\fi\ifXKV@coliv&\normalfont Type\fi
1152 \ifXKV@colv&\normalfont Default\fi\\noexpand\hline\noexpand
1153 \endhead\noexpand\hline\noexpand\multicolumn{the\count@}{r}{%
1154 \normalfont\emph{Continued on next page}}\\noexpand\endfoot
1155 \noexpand\hline\noexpand\endlastfoot
1156 }%
1157 \XKV@toks\expandafter{\XKV@tempa}%
1158 \fi

```

Open the target file for writing if a file name has been specified.

```

1159 \ifx\XKV@file\@nnil\else\immediate\openout\XKV@out\XKV@file\fi

```

Parse the entire database to find entries that match the criteria.

```

1160 \XKV@for@o\XKV@db\XKV@tempa{%
1161 \XKV@vwkeytrue\expandafter\XKV@xkvview\XKV@tempa\@nil
1162 }%

```

Finish the long table and typeset it.

```

1163 \ifXKV@view
1164 \addto@hook\XKV@toks{\end{longtable}}%
1165 \begingroup\ttfamily\the\XKV@toks\endgroup
1166 \fi

```

Close the target file.

```

1167 \ifx\XKV@file\@nnil\else\immediate\closeout\XKV@out\fi
1168 }

```

\XKV@xkvview <key>=<prefix>=<family>=<type>=<default>\@nil

Parse a row in the database to get individual column entries. Select the requested columns and store the table row in the token or write it to the target file.

```

1169 \def\XKV@xkvview#1=#2=#3=#4=#5\@nil{%

```

Check whether the current entry satisfies all criteria.

```

1170 \ifx\XKV@prefix\@nnil\else
1171 \def\XKV@tempa{#2}%
1172 \ifx\XKV@tempa\XKV@prefix\else\XKV@vwkeyfalse\fi
1173 \fi
1174 \ifx\XKV@family\@nnil\else
1175 \def\XKV@tempa{#3}%
1176 \ifx\XKV@tempa\XKV@family\else\XKV@vwkeyfalse\fi

```



```

1177 \fi
1178 \ifx\XKVV@type\@nnil\else
1179   \def\XKV@tempa{#4}%
1180   \ifx\XKV@tempa\XKVV@type\else\XKVV@vwkeyfalse\fi
1181 \fi
1182 \ifx\XKVV@default\@nnil\else
1183   \def\XKV@tempa{#5}%
1184   \ifx\XKV@tempa\XKVV@default\else\XKVV@vwkeyfalse\fi
1185 \fi
1186 \ifXKVV@vwkey

```

If output should go to the dvi, construct the table row and add it to the token.

```

1187 \ifXKVV@view
1188   \edef\XKV@tempa{%
1189     #1\ifXKVV@colii&#2\fi\ifXKVV@coliii&#3\fi
1190     \ifXKVV@coliv&#4\fi\ifXKVV@colv&#5\fi
1191     \ifXKVV@vlabels\noexpand\label{#2-#3-#1}\fi
1192   }%
1193   \expandafter\addto@hook\expandafter
1194     \XKV@toks\expandafter{\XKV@tempa\}%
1195 \fi
1196 \ifx\XKVV@file\@nnil\else

```

When writing, construct the line and write it to file. Notice that `xkeyval` removes braces and spaces, so `wcolsep={ }` won't make a space between column entries, but `wcolsep=\space` will.

```

1197   \immediate\write\XKVV@out{%
1198     #1\ifXKVV@colii\XKVV@wcolsep#2\fi
1199     \ifXKVV@coliii\XKVV@wcolsep#3\fi
1200     \ifXKVV@coliv\XKVV@wcolsep#4\fi
1201     \ifXKVV@colv\XKVV@wcolsep#5\fi
1202     \ifXKVV@vlabels\string\label{#2-#3-#1}\fi
1203     \expandafter\noexpand\XKVV@weol
1204   }%
1205 \fi
1206 \fi
1207 }
1208 </xkvview>

```

✖

14.7 xkvltxp.sty

✖ This section redefines some kernel macros as to avoid expansions of options at several places to allow for macros in key values in class and package options. It uses a temporary token register and some careful expansions. Notice that `\@unusedoptionlist` is sanitized after creation by `xkeyval` to avoid `\@removeelement` causing problems with macros and braces. See for more information about the original versions of the macros below the kernel source documentation [2].

```

1209 <*xkvltxpatch>
1210 %%
1211 %% Based on latex.ltx.
1212 %%
1213 \NeedsTeXFormat{LaTeX2e}[1995/12/01]

```

```

1214 \ProvidesPackage{xkvltxp}[2014/05/25 v1.3 LaTeX2e kernel patch (HA)]
    Load utilities needed in this package.
1215 \input xkvutils
    Start redefining internal LATEX macros.
1216 \def\@pass@options#1#2#3{%
1217   \def\reserved@a{#2}%
1218   \def\reserved@b{\CurrentOption}%
1219   \ifx\reserved@a\reserved@b
1220     \@ifundefined{opt@#3.#1}{\@temptokena\expandafter{#2}}{%
1221       \@temptokena\expandafter\expandafter\expandafter
1222         {\csname opt@#3.#1\endcsname}%
1223       \@temptokena\expandafter\expandafter\expandafter{%
1224         \expandafter\the\expandafter\@temptokena\expandafter,#2}%
1225     }%
1226   \else
1227     \@ifundefined{opt@#3.#1}{\@temptokena{#2}}{%
1228       \@temptokena\expandafter\expandafter\expandafter
1229         {\csname opt@#3.#1\endcsname}%
1230       \@temptokena\expandafter{\the\@temptokena,#2}%
1231     }%
1232   \fi
1233   \expandafter\xdef\csname opt@#3.#1\endcsname{\the\@temptokena}%
1234 }
1235 \def\OptionNotUsed{%
1236   \ifx\@current\@clsextension
1237     \let\reserved@a\CurrentOption
1238     \@onelevel@sanitize\reserved@a
1239     \xdef\@unusedoptionlist{%
1240       \ifx\@unusedoptionlist\@empty\else\@unusedoptionlist,\fi
1241       \reserved@a}%
1242   \fi
1243 }
1244 \def\@use@option{%
1245   \let\reserved@a\CurrentOption
1246   \@onelevel@sanitize\reserved@a
1247   \@expandtwoargs\@removeelement\reserved@a
1248   \@unusedoptionlist\@unusedoptionlist
1249   \csname ds@\CurrentOption\endcsname
1250 }

```

\@fileswith@pti@ns

```

1251 \def\@fileswith@pti@ns#1[#2]#3[#4]{%
1252   \XKV@sp@deflist\XKV@resb{#2}%
1253   \ifx#1\@clsextension
1254     \ifx\@classoptionslist\relax
1255       \let\@classoptionslist\XKV@resb
1256       \def\reserved@a{%
1257         \@onefilewithoptions#3[#2][#4]#1%
1258         \@documentclasshook}%
1259     \else
1260       \def\reserved@a{%
1261         \@onefilewithoptions#3[#2][#4]#1}%
1262     \fi

```

```

1263 \else
1264 \def\reserved@b##1,{%
1265 \ifx\@nil##1\relax\else
1266 \ifx\relax##1\relax\else
1267 \noexpand\@onefilewithoptions##1%
1268 [\XKV@resb] [#4]\noexpand\@pkgextension
1269 \fi
1270 \expandafter\reserved@b
1271 \fi}%
1272 \edef\reserved@a{\zap@space#3 \@empty}%
1273 \edef\reserved@a{\expandafter\reserved@b\reserved@a,\@nil,}%
1274 \fi
1275 \reserved@a}

1276 \let\@@fileswith@ptions\@fileswith@ptions
1277 </xkvltxpatch>

```

✖

14.8 pst-xkey.tex

✖Avoid loading pst-xkey.tex twice.

```

1278 (*pxktex)
1279 \csname PSTXKeyLoaded\endcsname
1280 \let\PSTXKeyLoaded\endinput
1281 \edef\PSTXKeyCatcodes{%
1282 \catcode'\noexpand\@the\catcode'\@relax
1283 \let\noexpand\PSTXKeyCatcodes\relax
1284 }
1285 \catcode'\@=11\relax

```

Load xkeyval when not already done by pst-xkey.sty and provide information.

```

1286 \ifx\ProvidesFile\@undefined
1287 \message{2005/11/25 v1.6 PSTricks specialization of xkeyval (HA)}
1288 \ifx\XKeyValLoaded\endinput\else\input xkeyval \fi
1289 \else
1290 \ProvidesFile{pst-xkey.tex}
1291 [2005/11/25 v1.6 PSTricks specialization of xkeyval (HA)]
1292 \@addtofilelist{pst-xkey.tex}
1293 \RequirePackage{xkeyval}
1294 \fi

```

\pst@famlist Initialize the list of families.

```

1295 \def\pst@famlist{}

```

\pst@addfams Adds the family to \pst@famlist if it was not in yet.

```

1296 \def\pst@addfams#1{%
1297 \XKV@for@n{#1}\XKV@tempa{%
1298 \@expandtwoargs\in@{,\XKV@tempa,}{,\pst@famlist,}%
1299 \ifin@\else\edef\pst@famlist{\pst@famlist,\XKV@tempa}\fi
1300 }%
1301 }

```

\psset Set keys. Uses xkeyval's \setkeys+.

\pss@t

```

1302 \def\psset{%
1303   \expandafter\@testopt\expandafter\pss@t\expandafter{\pst@famlist}%
1304 }
1305 \def\pss@t[#1]#2{\setkeys+[psset]{#1}{#2}\ignorespaces}

\@psset This macro defined by pstricks.tex is internally used as a shortcut. We have to re-
define this as well to avoid problems.

1306 \def\@psset#1,\@nil{%
1307   \edef\XKV@tempa{\noexpand\setkeys+[psset]{\pst@famlist}}%
1308   \XKV@tempa{#1}%
1309 }

Finalize.
1310 \PSTXKeyCatcodes
1311 </pxktex>
✖

```

14.9 pst-xkey.sty

✖Initialize the package.

```

1312 (*pxklatex)
1313 \NeedsTeXFormat{LaTeX2e}[1995/12/01]
1314 \ProvidesPackage{pst-xkey}
1315   [2005/11/25 v1.6 package wrapper for pst-xkey.tex (HA)]

Load required package.
1316 \ifx\PSTXKeyLoaded\endinput\else\input pst-xkey \fi

Ignore options.
1317 \DeclareOptionX*{%
1318   \PackageWarning{pst-xkey}{Unknown option ‘\CurrentOption’}%
1319 }
1320 \ProcessOptionsX
1321 </pxklatex>

```

Références

- [1] Hendri Adriaens. extract package. CTAN:/macros/latex/contrib/extract.
- [2] Johannes Braams, David Carlisle, Alan Jeffrey, Leslie Lamport, Frank Mittelbach, Chris Rowley, and Rainer Schöpf. The \LaTeX sources. CTAN:/macros/latex/base, 2003.
- [3] Frank Mittelbach and Michel Goossens. *The \LaTeX Companion*. Tools and Techniques for Computer Typesetting. Addison-Wesley, Boston, Massachusetts, 2 edition, 2004. With Johannes Braams, David Carlisle, and Chris Rowley.
- [4] Herbert Voß. PSTricks website. <http://www.pstricks.de>.
- [5] Timothy Van Zandt et al. PSTricks package, v1.04, 2004/06/22. CTAN:/graphics/pstricks.

✖

Remerciements

✂The author is grateful to Carsten Heinz, Morten Høgholm, Josselin Noirel, Heiko Oberdiek, Will Robertson, Till Tantau, Herbert Voß and Joseph Wright for help and suggestions. Thanks go to Donald Arseneau for contributing the robust `\ifnextcharacter` macro, to Morten Høgholm for contributing a fast for-loop macro and to David Carlisle for modifications to support `\par`. Special thanks go to Uwe Kern for his ideas for improving the functionality of this package, a lot of useful comments on the package and the documentation and for contributing the `\@selective@sanitize` macro.

Historique

Cet historique n'affiche que les modifications récentes.

v2.0	<i>(2005/01/30)</i>
Général : Made <code>\setkeys</code> nestable	1
<code>\XKV@addtolist@n</code> : Simplified	57
<code>\XKV@addtolist@o</code> : Simplified	57
<code>\XKV@default</code> : Repaired adding extra braces when executing default value	45
<code>\XKV@ifundefined</code> : Made none ϵ -TeX version not leave <code>\relax</code>	54
<code>\XKV@r@placepointers</code> : Simplified	45
v2.1	<i>(2005/02/08)</i>
Général : Added 'immediate' versions of several macros	1
v2.2	<i>(2005/02/14)</i>
Général : Added viewer utility	1
Improved nesting mechanism	1
v2.3	<i>(2005/02/22)</i>
Général : Added choice keys	1
Increased efficiency of loops	1
Updated viewer utility	1
v2.4	<i>(2005/03/31)</i>
Général : Added 'default value' column to <code>xkvview</code> tables	1
Added nesting protection for conditionals	1
Changed <code>\define@boolkey</code> to have a key function	1
Extended boolean keys	1
Extended choice keys	1
Inserted <code>pst-xkey</code> in <code>xkeyval</code> source	1
Removed command keys	1
Revised documentation and examples	1
Simplified some code	1
Updated <code>xkvview</code>	1
<code>\XKV@s@tk@ys</code> : Added <code>\global</code> to make <code>\XKV@rm</code> survive when <code>\setkeys</code> executed in a group.	42
<code>\XKV@wh@list</code> : Avoid using grouping	56
v2.5	<i>(2005/05/07)</i>
Général : Added <code>\define@boolkeys</code> , <code>\define@cmdkey</code> and <code>\define@cmdkeys</code>	1
Restructured documentation	1
Simplified <code>\setkeys</code> internals	1
Solved small bug in <code>\setkeys</code> which allowed other families to take over save key or preset key settings if the key was defined in multiple families	1
Updated <code>xkvview</code>	1
<code>\XKV@d@f@ne@boolkey</code> : Removed <code>\relax</code>	34

\XKV@d@fine@boolkey : Removed \relax	34
v2.5	(2005/05/21)
Général : Added default value examples to docs	1
Reimplemented xkvview and added several options	1
v2.5a	(2005/05/31)
\@s@lective@sanitize : Added missing ‘%’	57
v2.5b	(2005/06/20)
Général : Made retrieving document class more robust	1
v2.5c	(2005/07/10)
\XKV@define@cmdkey : Avoid initializing control sequence as \relax	32, 62
v2.5d	(2005/08/12)
Général : Added missing \filename@area in document class retrieval in xkeyval.sty	1
v2.5e	(2005/11/25)
Général : Updated docs	1
\psset : Added \ignorespaces as in pstricks.tex	67
v2.5f	(2006/11/18)
\XKV@setkeys : Added reset of \CurrentOption	41
\XKV@srstate : Added XKV@tkey and XKV@rm to solve bugs	29
v2.5g	(2006/12/19)
Général : Altered policy for handling \XKV@rm in nested \setkeys* commands : all	
unknown keys will be recorded, not only the once from the outermost \setkeys*	1
\XKV@s@tk@ys : Removed \global again for consistent approach of \XKV@rm and to	
allow groups to keep \XKV@rm local	42
\XKV@setkeys : Avoid reset of \XKV@rm in nested \setkeys commands	41
\XKV@srstate : Removed XKV@rm again on user request	29
v2.6	(2008/08/10)
\@s@lective@sanitize : protecting assignments from #	57
Général : Added \KV@def to keyval.tex as it is used by some packages	51
\XKV@addtomacro@n : protecting assignments from #	56
\XKV@addtomacro@o : protecting assignments from #	56
\XKV@ch@cksanitize : protecting assignments from #	59
\XKV@f@r : protecting assignments from #	55
\XKV@for@n : protecting assignments from #	55
\XKV@t@bulate : Solved bug occurring with empty prefix	62
v2.6a	(2008/08/13)
\@s@lective@sanitize : Use private scratch register	57
\XKV@addtomacro@n : Use private scratch register	56
\XKV@addtomacro@o : Use private scratch register	56
\XKV@ch@cksanitize : Use private scratch register	59
\XKV@f@r : Use private scratch register	55
\XKV@for@n : Use private scratch register	55
v2.6b	(2012/10/14)
\XKV@srstate : Added CurrentOption to fix class options not being removed from	
\@unusedoptionlist when \setkeys is nested in \ProcessOptionsX	29
v2.6c	(2014/04/27)
Général : Added support for \par to support similar changes in keyval	1
v2.6d	(2014/05/09)
Général : Implemented fix conform fix in keyval	1
v2.7a	(03/12/2014)
\XKV@r@placepointers : Removed erroneous \@empty	45
v2.7	(2014/05/25)
Général : Moved several utility macros to xkvutils	1

Index

Les numéros en italique renvoient à la page où se trouve l'entrée correspondante; les numéros soulignés renvoient à la ligne de code de la définition; les numéros en romain renvoient aux lignes de code où l'entrée est utilisée.

Symboles	
<code>\@@fileswith@pti@ns</code>	686, 1276
<code>\@badrequireerror</code>	642, 656
<code>\@classoptionslist</code>	618, 620, 623, 626, 1254, 1255
<code>\@clsextension</code>	464, 604, 1236, 1253
<code>\@current</code> ...	464, 635, 648, 657, 680, 1236
<code>\@currname</code>	635, 648, 657, 680
<code>\@documentclasshook</code>	1258
<code>\@filelist</code>	602
<code>\@fileswith@pti@ns</code>	642, 656, 686, <u>1251</u> , 1276
<code>\@firstofone</code>	242, 287, 791
<code>\@firstoftwo</code>	36, 37,
98, 240, 286, 304, <u>818</u> , 826, 836, 851	
<code>\@ifncharacter</code>	<u>844</u>
<code>\@ifnextcharacter</code>	36, 37, <u>844</u>
<code>\@onefilewithoptions</code> .	1257, 1261, 1267
<code>\@onelevel@sanitize</code> .	553, 661, 692,
803, 925, 988, 1067, 1128, 1238, 1246	
<code>\@pass@ptions</code>	1216
<code>\@pkgextension</code>	1268
<code>\@psset</code>	<u>1306</u>
<code>\@removeelement</code>	694, 1247
<code>\@selective@sanitize</code>	927, <u>932</u>
<code>\@selective@sanitize</code>	<u>920</u>
<code>\@secondoftwo</code>	96, 246, 263, 306, <u>818</u> , 828, 834, 853
<code>\@selective@sanitize</code>	<u>920</u> , 980, 984
<code>\@unknownoptionerror</code>	465
<code>\@unprocessedoptions</code>	687
<code>\@unusedoptionlist</code>	659, 661, 695, 1239, 1240, 1248
<code>\@use@ption</code>	1244
C	
columns (option)	24
<code>\CurrentOption</code>	414, 431,
432, 465, 470, 477, 666–669, 698,	
1050, 1218, 1237, 1245, 1249, 1318	
D	
<code>\DeclareOptionX</code> <i>17</i> , <u>641</u> , 697, 1049, 1317	
<code>\DeclareOptionX*</code>	<i>18</i>
default (option)	24
<code>\define@boolkey</code>	7, <u>172</u>
<code>\define@boolkey+</code>	7
<code>\define@boolkeys</code>	8, <u>202</u> , 1062
<code>\define@choicekey</code>	6, <u>142</u>
<code>\define@choicekey*</code>	6
<code>\define@choicekey*+</code>	6
<code>\define@choicekey+</code>	6
<code>\define@cmdkey</code>	5, <u>127</u>
<code>\define@cmdkeys</code>	5, <u>134</u> , 1060
<code>\define@key</code>	4, <u>117</u> , 650
<code>\delpresetkeys</code>	<i>16</i> , <u>344</u>
<code>\delsavekeys</code>	<i>13</i> , <u>382</u>
<code>\disable@keys</code>	9, <u>309</u>
<code>\documentclass</code>	614
E	
<code>\ExecuteOptionsX</code>	<i>18</i> , <u>651</u>
F	
family (option)	24
file (option)	25
<code>\filename@area</code>	605, 608
<code>\filename@base</code>	605, 608
<code>\filename@ext</code>	604, 605, 608
<code>\filename@parse</code>	603
G	
<code>\gdelpresetkeys</code>	<i>16</i> , <u>344</u>
<code>\gdelsavekeys</code>	<i>13</i> , <u>382</u>
<code>\global</code>	<i>13</i>
<code>\gpresetkeys</code>	<i>15</i> , <u>328</u>
<code>\gsavekeys</code>	<i>12</i> , <u>370</u>
<code>\gsavevalue</code>	<i>12</i> , 106
<code>\gunpresetkeys</code>	<i>16</i> , 358
<code>\gunsavekeys</code>	<i>13</i> , <u>392</u>
I	
<code>\ifXKV@inpox</code>	22, 462, 476
<code>\ifXKV@knf</code>	20, 299, 303, 455, 461
<code>\ifXKV@pl</code> .	19, 154, 166, 174, 192, 239,
245, 262, 272, 449, 1026, 1101, 1116	
<code>\ifXKV@preset</code>	23, 448
<code>\ifXKV@rkx</code>	21, 490, 511, 565
<code>\ifXKV@sg</code>	18, 491, 566
<code>\ifXKV@st</code>	17, 129, 165,
191, 216, 222, 337, 364, 366, 375,	
398, 469, 664, 1028, 1039, 1084, 1110	
<code>\ifXKV@colii</code> 1054, 1145, 1150, 1189, 1198	
<code>\ifXKV@coliii</code>	1055, 1146, 1150, 1189, 1199
<code>\ifXKV@coliv</code> 1056, 1146, 1151, 1190, 1200	

\ifXKVV@colv	1057, 1147, 1152, 1190, 1201
\ifXKVV@view	1143, 1163, 1187
\ifXKVV@vlabels	1191
\ifXKVV@vwkey	1053, 1186
\ifXKVV@wlabels	1202
\ignorespaces	1305
\immediate	1159, 1167, 1197
K	
\key@ifundefined	8, <u>288</u>
\KV@sp@b	712, 714, 716
\KV@sp@c	716, 719
\KV@sp@d	709, 710
\KV@sp@def	39, 49, 72, 298, 437, 447, 708, 725, 735, 1002
\KV@def	748
\KV@default	733, 740
\KV@do	720, 723
\KV@err	<u>32</u>
\KV@errx	<u>32</u>
\KV@prefix	728, 742
\KV@split	722, 724
O	
\OptionNotUsed	1235
options:	
columns	24
default	24
family	24
file	25
prefix	24
type	24
view	25
vlabels	24
wcolsep	25
weol	25
wlabels	25
P	
\PackageError	601
\PackageWarning	600, 698, 1050, 1318
prefix (option)	24
\presetkeys	15, <u>328</u> , 1063
\ProcessOptionsX	18, <u>652</u> , 700, 1052, 1320
\ProcessOptionsX*	19
\pss@t	<u>1302</u>
\psset	27, <u>1302</u>
\pst@addfams	27, <u>1296</u>
\pst@famlist	
	27, <u>1295</u> , 1298, 1299, 1303, 1307
\PSTXKeyLoaded	1280, 1316
S	
\savekeys	12, <u>370</u>
\savevalue	12, 105
\setkeys	9, <u>402</u> , 1127, 1305, 1307
\setkeys*	10
\setkeys*+	11
\setkeys+	11
\setrmkeys	10, <u>580</u>
\setrmkeys*	10
T	
type (option)	24
U	
\unpresetkeys	16, <u>358</u>
\unsavekeys	13, <u>392</u>
\usevalue	13, 528, 530
V	
view (option)	25
vlabels (option)	24
W	
wcolsep (option)	25
weol (option)	25
wlabels (option)	25
\write	1197
X	
\XKeyValLoaded	3, 591, 1288
\XKeyValUtilsCatcodes	811, 813, 1041
\XKeyValUtilsLoaded	810
\XKV@@@@dx	646
\XKV@@ch@ckch@ic@	275, <u>286</u>
\XKV@@ch@ckch@ice	273, <u>286</u>
\XKV@@ch@ckch@choice	229, <u>255</u>
\XKV@@d@x	646
\XKV@@ifcmd	93
\XKV@@t@st@pte	628
\XKV@addtolist@n	671, <u>905</u>
\XKV@addtolist@o	470, 623, 679, <u>912</u> , 1021, 1023, 1026, 1037
\XKV@addtolist@x	408, 542, <u>919</u> , 1068
\XKV@addtomacro@n	240, 242, 246, 250, 531, <u>898</u> , 903, 907, 909
\XKV@addtomacro@o	902, 914, 916, 1003
\XKV@afterelsefi	154, 174, 226, 495, 539, 570, <u>820</u> , 822, 1101
\XKV@afterfi	156, 176, 228, 502, 533, 541, 574, <u>820</u> , 1103
\XKV@cc	7, <u>213</u>
\XKV@cc*	7
\XKV@cc*+	7
\XKV@cc+	7
\XKV@ch@ckch@ice	218, 227, <u>232</u>
\XKV@ch@ckch@choice	220, <u>224</u>
\XKV@ch@cksanitize	978, 979, 983, <u>986</u>

\XKV@checkchoice	\XKV@g@tkeyname . 103, <u>104</u> , 407, 436, 668
.. 167, 194, 198, 213, <u>214</u> , 1118, 1122	\XKV@getkeyname <u>103</u> , 341, 355
\XKV@checksanitizea 336, 404, <u>977</u> , 1011	\XKV@getsg <u>110</u> , 379, 389
\XKV@checksanitizeb	\XKV@ifcmd <u>93</u> , 105, 106, 111, 513
..... 78, 291, 311, 374, <u>982</u> , 1031	\XKV@ifplus <u>36</u> , 67
\XKV@classoptionslist	\XKV@ifstar <u>36</u> , 64, 629, 643
..... 3, 616, 618, 659, 676	\XKV@ifundefined
\XKV@d@f@n@ch@ic@k@y ... 161, 162, <u>163</u> 301, 313, 319, 335, 351,
\XKV@d@f@ne@b@olkey	361, 373, 385, 395, 420, 484, 486,
..... 182, 186, <u>189</u> , 210, <u>1072</u>	496, 534, 561, 605, 660, 691, <u>822</u> , 840
\XKV@d@f@ne@boolkey 175, <u>185</u>	\XKV@key@if@defined 294, 296, 669
\XKV@d@f@ne@ch@ic@k@y .. 155, <u>162</u> , <u>1102</u>	\XKV@key@ifundefined 288, 289
\XKV@d@f@ne@ch@ic@key .. 157, <u>161</u> , <u>1104</u>	\XKV@makehd <u>48</u> , 71, 300, 419, 451, 456
\XKV@d@fine@boolkey 177, <u>181</u>	\XKV@makepf <u>38</u> , 70, 77, 290, 633
\XKV@d@fine@boolkeys 206, <u>209</u>	\XKV@merge 340, 378, <u>1010</u>
\XKV@d@fine@ch@ic@key	\XKV@na 430, 444
..... 147, 151, <u>153</u> , <u>1072</u>	\XKV@naa 405, 408, 424
\XKV@d@fine@ch@icekey .. 147, <u>149</u> , <u>1072</u>	\XKV@pox 652, <u>653</u>
\XKV@d@fine@choicekey 143, <u>144</u>	\XKV@pr@setkeys 331, 332, <u>334</u>
\XKV@d@fine@k@y 119, 123, <u>1072</u>	\XKV@prefix . 39, 41, 43, 45, 51, 1068, 1069
\XKV@d@fine@key <u>123</u>	\XKV@presetkeys 328, 329, <u>330</u>
\XKV@d@l@presetkeys 347, 348, <u>350</u>	\XKV@r@placepointers <u>525</u>
\XKV@d@x 643, <u>646</u>	\XKV@replacepointers 494, <u>525</u> , 569
\XKV@default 499, <u>549</u>	\XKV@rm 24, 410, 470, 583, 684
\XKV@define@boolkey 172, <u>173</u>	\XKV@s@tk@ys 432, <u>435</u>
\XKV@define@boolkeys 202, <u>203</u>	\XKV@s@tk@ys@ 448, 452, 457, <u>483</u>
\XKV@define@choicekey 142, <u>143</u>	\XKV@s@tkeys 412, 423, <u>429</u>
\XKV@define@cmdkey . 127, <u>128</u> , 138, <u>1072</u>	\XKV@savekeys 370, 371, <u>372</u>
\XKV@define@cmdkeys 134, <u>135</u>	\XKV@setkeys 402, <u>403</u> , 582, 651, 681
\XKV@define@default <u>113</u> , 124,	\XKV@setrmkeys 580, <u>581</u>
129, 150, 191, 1080, 1086, 1096, 1112	\XKV@sp@deflist 79,
\XKV@define@key 117, <u>118</u> , 320, 322, <u>1072</u>	136, 146, 204, 292, 430, 638, <u>999</u> , 1252
\XKV@delete 354, 388, <u>1030</u>	\XKV@srstate
\XKV@delpresetkeys 344, 345, <u>346</u> <u>54</u> , 503, 506, 571, 573, 575, 577
\XKV@delsavekeys 382, 383, <u>384</u>	\XKV@t@st@pte <u>628</u>
\XKV@depth 16, 55,	\XKV@t@stopta <u>63</u> , 172
61, 410, 503, 506, 571, 573, 575, 577	\XKV@t@stoptb <u>68</u>
\XKV@disable@keys 309, <u>310</u>	\XKV@t@stoptc <u>75</u>
\XKV@documentclass	\XKV@t@stoptd <u>83</u>
..... 3, 476, 602, 607, 613, 615, 658	\XKV@t@stopte <u>628</u> , 651
\XKV@d@x 643, <u>645</u>	\XKV@tempa@toks 817, 858,
\XKV@d@xs 463, 467, 599, 645, 683	867, 899, 900, 928, 929, 987, 992, 997
\XKV@err <u>32</u> , 42, 249,	\XKV@testclass 476, 657, 658
266, 314, 352, 362, 386, 396, 441,	\XKV@testopta <u>63</u> , 142, 213, 402, 580
472, 497, 535, 540, <u>600</u> , 614, 730, 744	\XKV@testoptb <u>68</u> , 84,
\XKV@f@r 862, <u>866</u> , 877, 879	117, 142, 309, 328, 329, 344, 345,
\XKV@f@ms 78, 80,	358, 359, 370, 371, 382, 383, 392, 393
291, 293, 299, 418, 450, 455, 472, 638	\XKV@testoptc <u>75</u> , 402, 580
\XKV@for@break 860, <u>875</u>	\XKV@testoptd <u>83</u> , 127, 134, 172, 202
\XKV@for@en <u>877</u>	\XKV@testopte <u>628</u> , 652
\XKV@for@eo 418, 450, <u>878</u>	\XKV@testsavekey 487, <u>510</u> , 562
\XKV@for@n 56, 431, 621, <u>857</u> , 876, 1001, 1297	\XKV@unpresetkeys 358, 359, <u>360</u>
\XKV@for@o 137, 205, 312,	\XKV@unsavekeys 392, 393, <u>394</u>
406, 512, <u>876</u> , 1012, 1017, 1034, 1160	\XKV@useoption 477, 670, <u>689</u>

\XKV@usepresetkeys	411, 413, <u>416</u>	\XKVV@out	1058, 1159, 1167, 1197
\XKV@warn	<u>32</u> , 317, <u>600</u>	\XKVV@prefix	1170, 1172
\XKV@wh@l@st	887, 892, <u>897</u>	\XKVV@t@bulate	<u>1065</u>
\XKV@wh@list	882, <u>884</u>	\XKVV@tabulate ...	<u>1065</u> , 1074, 1079,
\XKV@whilist	299, 455, 602, <u>881</u>		1085, 1088, 1095, 1100, 1111, 1114
\XKVV@columns	1129, 1134, 1136, 1138, 1140	\XKVV@type	1178, 1180
\XKVV@db	1059, 1068, 1160	\XKVV@wcolsep	1198–1201
\XKVV@default	1128, 1182, 1184	\XKVV@weol	1203
\XKVV@family	1174, 1176	\XKVV@xkvview	1161, <u>1169</u>
\XKVV@file	1159, 1167, 1196	\xkvview	24, <u>1126</u>