

Browser default actions

AGENDA

1. Browser default actions
 2. How to prevent default actions
-

1. Browser default actions

#	Event	Default action
1	mousedown	starts the selection
2	click on <code><input type="checkbox" /></code>	check/uncheck the input
3	click on anchor tag <code><a></code>	redirect to the target link
4	submit - click on button/input type submit, ...	browser submit the form
5	keydown	add character into a field or other actions
6

2. How to prevent default actions

#	For	How
1	HTML onevent attributes	return false;
2	JS onevent properties	return false;
3	JS addEventListener	event.preventDefault()

```
<!-- it won't redirect to Google when you click on this link -->  
<a href="https://google.com" onclick="return false;">Go to Google</a>
```

```
anchorElement.onclick = function() {  
  // same as above  
  return false;  
}
```

```
form.addEventListener('submit', function(event) {  
  // prevent form submit trigger (browser reload)  
  event.preventDefault();  
})
```

Read about passive events: <https://javascript.info/default-browser-action#the-passive-handler-option>

Tham khảo

- <https://javascript.info/default-browser-action>
- <https://developer.mozilla.org/en-US/docs/Web/API/Event/preventDefault>

Khoá học Javascript cho người mới bắt đầu 2021 🎉

- Tác giả: **Hậu Nguyễn** - Founder Easy Frontend
- Khoá học chỉ được published trên Udemy, không thông qua trung gian.
- Khoá học không bán dạng videos upload trên Google Drive hay bất cứ hình thức nào tương tự.
- Khoá học có nhóm discord để hỗ trợ trong quá trình học tập.

☎️ Liên hệ tác giả để được hỗ trợ:

- ✅ Facebook: <https://www.facebook.com/nvhauesmn/>
- ✅ Fanpage: <https://www.facebook.com/learn.easyfrontend>
- ✅ Youtube Channel: <https://www.youtube.com/easyfrontend>