



Incident report analysis

Instructions

As you continue through this course, you may use this template to record your findings after completing an activity or to take notes on what you've learned about a specific tool or concept. You can also use this chart as a way to practice applying the NIST framework to different situations you encounter.

Summary	A multimedia company suffered a distributed denial-of-service (DDoS) attack that lasted two hours. The attack used a flood of ICMP packets ("pings") to saturate the internal network, causing services to become unresponsive and blocking employee access to necessary resources. The incident team managed to contain it by blocking ICMP traffic and prioritizing the restoration of critical services.
Identify	This phase manages security risks through audits to recognize breaches or leaks. Type of attack: Distributed denial-of-service (DDoS) attack using ICMP packet flood (ping flood). Affected systems: The organization's internal network and all network services hosted on it. Vulnerability identified: An unconfigured firewall that allowed an unlimited number of ICMP packets to pass through from external sources.
Protect	It involves developing a strategy to protect internal assets through policies, training, and tools. Firewall Configuration: A new rate limiting rule for incoming ICMP packets was implemented. Identity Verification: Source IP address verification was enabled on the

	firewall to detect and reject packets with spoofed addresses. Advanced Filtering: An IDS/IPS (Intrusion Detection/Prevention System) was installed to filter ICMP traffic based on signatures of suspicious behavior.
Detect	It focuses on analyzing potential incidents and improving the efficiency of detection. Network Monitoring: Specialized network monitoring software was deployed to detect anomalous traffic patterns. Signature Analysis: The IDS/IPS system will identify sudden bursts of ICMP traffic before they saturate bandwidth, generating early warnings for analysts.
Respond	Includes the steps to contain, analyze, and mitigate the impact of an attack. Immediate Containment: All incoming ICMP packets were blocked during the event to stop the saturation. Service Management: All non-critical network services were temporarily taken offline to reduce the load on the infrastructure. Technical Analysis: Traffic logs were collected during the attack to identify the origin and specific characteristics of the malicious packets.
Recover	Builds a plan to restore affected systems and data after an attack. Gradual Restoration: Critical network services were restored first to minimize the impact on the business, followed by secondary services once stability was confirmed. Process Improvement: The incident data was used to update the DDoS response playbook, ensuring that the firewall remains correctly configured in the future.

Reflections/Notes: