Rebuttal Figures — Additional Experiments

1 BERT experiments (dense attention)



(a) Mean error

(b) Covariance error

Figure 1: **Convergence rate $|\beta|$ versus horizon H across BERT-base-uncased's layers** 0–11 **and all Wikipedia text distributions.** Markers represent (layer, text configuration) pairs; shapes denote text sources (Wikipedia EN/DE/ZH) and colors indicate layers. Larger $|\beta|$ implies faster convergence. The convergence rate $|\beta|$ is estimated via log-log linear regression of the per-token mean (left) or covariance (right) error against n, with $n \in [1000, 5000]$ i.i.d. sampled keys and $k \in [500, 1000]$ Monte Carlo repetitions. Star markers denote the configurations whose detailed convergence curves are displayed in Figure 2. The dashed line is a linear fit across all points.



(a) Mean error

(b) Covariance error

Figure 2: **Convergence curves for starred layers.** Mean error (left) and covariance error (right) versus subsample size n for the three starred configurations from Figure 1, using BERT-base-uncased (dense attention). Markers show the averaged ℓ_2 errors over $k = 500$–1000 subsamples, with ± 3 standard-error bands. Log–log linear fits yield power-law exponents $|\beta|$ (legend), with error scaling as $n^{-|\beta|}$. From dark red to light orange as the horizon H increases, confirming the slow-down predicted by Theorem 5.3.

2 Downstream classification experiment



Figure 3: **End-to-end error convergence versus number of keys per query n.** BigBird-RoBERTa-base fine-tuned for 3 epochs with mean pooling on the arxiv-classification task (11 categories, dense accuracy 86.4%). RMSE ($\beta = 0.27$, $R^2 = 0.999$), pooling error ($\beta = 0.30$, $R^2 = 1.000$) and logit error ($\beta = 0.37$, $R^2 = 0.999$) all follow a sub-parametric power-law regime $n^{-\beta}$ with $\beta < \frac{1}{2}$, consistent with Theorem 5.3.



Figure 4: **Normalized error rates versus n.** RMSE ($\beta = 0.27$), pooling error ($\beta = 0.30$), logit error ($\beta = 0.37$) and disagreement rate with the dense model ($\beta = 0.46$) all exhibit sub-parametric convergence, with downstream metrics converging more rapidly than embedding-level metrics. Shaded bands show ± 3 standard-error intervals.



Figure 5: **Classification accuracy and agreement rate versus n.** Accuracy (fraction of correctly classified examples) and agreement rate with the dense model (fraction of examples where the sparse and dense models predict the same label). The reference accuracy (dashed line) is 86.4%. The agreement rate converges to 1 as expected, and the accuracy approaches the dense model's performance with diminishing returns: with only 25% of keys ($n = 1101$ out of 4096), the model already achieves 84.5% accuracy, and doubling the number of keys from $n = 1101$ to $n = 2124$ yields only a +0.7% accuracy gain.

3 Windowed sampling experiment



(a) RMSE error

(b) Covariance error

Figure 6: **Convergence rate $|\beta|$ versus horizon H under non-i.i.d. windowed sampling.** BigBird-RoBERTa's layers 0–11 on English Wikipedia, under two sampling strategies: fixed-random (EN window, $r = 50$ random tokens outside a sliding window of size $n-r-1$) and hybrid (EN hybrid 50/50, half window and half random tokens). Colors indicate layers. The negative trend (fit slope $R = -0.65$) confirms that the slow-down driven by H persists under structured, non-i.i.d. sampling.