

Vendor: VMware

Exam Code: 2V0-622D

Exam Name: VMware Certified Professional 6.5 -
Data Center Virtualization Delta

Question 98—Question 110

[Click to Download All 140 Q&As From Lead2pass](#)

QUESTION 98

When upgrading a standalone vCenter Single Sign-On Server version 5.5 to version 6.5, which will be the final deployment type?

- A. There is no option to do this type of upgrade.
- B. It will be an external Platform Services Controller.
- C. It will be an embedded Platform Services Controller with vCenter Server
- D. It will be a Standalone vCenter Server.

Answer: B

QUESTION 99

Which feature of vSphere networking protects hosts from losing connection to vCenter Server as a result of misconfiguration of the management network?

- A. NIC Teaming
- B. Private VLAN
- C. Rollback
- D. Health Check

[2V0-622D Dumps](#) [2V0-622D Exam Questions](#) [2V0-622D VCE](#) [2V0-622D PDF](#)

Get Full Version [2V0-622D](#) Q&As From Lead2pass: <https://www.lead2pass.com/2v0-622d.html>

Answer: C

Explanation:

By rolling configuration changes back, vSphere protects hosts from losing connection to vCenter Server as a result from misconfiguration of the management network.

<https://docs.vmware.com/en/VMware->

[vSphere/6.5/com.vmware.vsphere.networking.doc/GUID-8BA411A4-8582-4C02-8489-D3D7D09A9BF0.html](https://docs.vmware.com/en/VMware-vSphere/6.5/com.vmware.vsphere.networking.doc/GUID-8BA411A4-8582-4C02-8489-D3D7D09A9BF0.html)

QUESTION 100

VCSA backup can be backed up and sent to different location via several different protocols. Which are three of the supported protocols? (Choose three.)

- A. CIFS
- B. SCP
- C. HTTP
- D. FTPS
- E. AFP

Answer: BCD

Explanation:

<https://www.vladan.fr/vmware-vcsa-6-5-backup-and-restore-how-to/>

QUESTION 101

For Virtual Machine Compatibility upgrade, a VM needs to be in which power state?

- A. Maintenance mode
- B. Suspended
- C. Powered Off
- D. Powered On

Answer: C

Explanation:

[https://pubs.vmware.com/vsphere-](https://pubs.vmware.com/vsphere-51/index.jsp?topic=%2Fcom.vmware.vsphere.upgrade.doc%2FGUID-60768C2F-72E1-42E0-8A17-CA76849F2950.html)

[51/index.jsp?topic=%2Fcom.vmware.vsphere.upgrade.doc%2FGUID-60768C2F-72E1-42E0-8A17-CA76849F2950.html](https://pubs.vmware.com/vsphere-51/index.jsp?topic=%2Fcom.vmware.vsphere.upgrade.doc%2FGUID-60768C2F-72E1-42E0-8A17-CA76849F2950.html)

QUESTION 102

Which component must be deployed before using encrypted virtual machines in a vSphere 6.5 environment?

- A. vCenter Server must use CA signed certificates
- B. a host with supported Trusted Platform Module
- C. supported password vault
- D. External Key Management Server

Answer: D

Explanation:

<https://docs.vmware.com/en/VMware-vSphere/6.5/com.vmware.vsphere.security.doc/GUID-E6C5CE29-CD1D-4555-859C-A0492E7CB45D.html>

QUESTION 103

Which system traffic type cannot be configured with Network I/O Control (NIOC) bandwidth allocation?

- A. Virtual SAN traffic
- B. ESXi host Management traffic
- C. vSphere Replication traffic
- D. Software FCoE Adapter traffic

Answer: D

QUESTION 104

Which is the minimum number of hosts required for a VMware vSAN cluster to be able to apply a vSAN RAID5 storage policy?

- A. six hosts
- B. three hosts
- C. four hosts
- D. five hosts

Answer: C

Explanation:

<https://cormachogan.com/2016/02/15/vsan-6-2-part-2-raid-5-and-raid-6-configurations/>

[2V0-622D Dumps](#)

[2V0-622D Exam Questions](#)

[2V0-622D VCE](#)

[2V0-622D PDF](#)

Get Full Version [2V0-622D](#) Q&As From Lead2pass: <https://www.lead2pass.com/2v0-622d.html>

QUESTION 105

Which three TCP/IP stacks are built in at the VMkernel level in vSphere 6 x? (Choose three.)

- A. Fault Tolerance
- B. vMotion
- C. Provisioning
- D. Management
- E. Default

Answer: ABC

Explanation:

<https://docs.vmware.com/en/VMware->

[vSphere/6.5/com.vmware.vsphere.networking.doc/GUID-D4191320-209E-4CB5-A709-C8741E713348.html](https://docs.vmware.com/en/VMware-)

QUESTION 106

In vSphere 6.5, a virtual machine is thinly-provisioned on a VMFS6 datastore. The administrator deleted a large file within the guest OS. The freed blocks in the datastore are no longer needed by the VM.

Which feature in vSphere 6.5 allows the backing storage to automatically reclaim the freed blocks?

- A. ATS
- B. Defrag
- C. UNMAP
- D. Auto Reclaim

Answer: C

Explanation:

Explanation:

VAAI UNMAP was introduced in vSphere 5.0 to allow the ESXi host to inform the backing storage that files or VMs had been moved or deleted from a Thin Provisioned VMFS datastore. This allowed the backing storage to reclaim the freed blocks. There was no way of doing this previously, resulting in many customers with a considerable amount of stranded space on their Thin Provisioned VMFS datastores.

QUESTION 107

A new virtual machine cannot reach its default gateway.

- The vSphere administrator checks that the virtual machine's vmnic is connected to the correct portgroup, and that the portgroup is on the correct virtual switch
- This is the only virtual machine on this portgroup
- Other virtual machines that are on the host and connected to the same Distributed switch are running as normal
- The Distributed Switch has only one uplink

Which could be the cause of this issue?

- A. Block All Ports has been selected on the Distributed Switch.
- B. The wrong VLAN ID has been added to the portgroup.
- C. The VLAN has not been configured in virtual machine hardware settings.
- D. The physical adapter is down.

Answer: D

QUESTION 108

Which two requirements must be met before enabling vSphere HA Application Monitoring for a virtual machine? (Choose two.)

- A. VMware Tools must be installed on the VM.
- B. The vSphere Guest SDK must be installed on the VMs needing Application Monitoring.
- C. Application Monitoring requires that vCenter Server is linked to a working instance of vRealize Operations Manager and the End Points Operations agent has been installed on the guest.
- D. Application Monitoring is only supported on Linux operating systems.
- E. Application Monitoring is only supported on Windows operating systems.

Answer: AE

QUESTION 109

Which is true when assigning global permissions in a single vSphere Single Sign-On domain in a multi-site configuration?

[2V0-622D Dumps](#) [2V0-622D Exam Questions](#) [2V0-622D VCE](#) [2V0-622D PDF](#)

Get Full Version [2V0-622D](#) Q&As From Lead2pass: <https://www.lead2pass.com/2v0-622d.html>

- A. Users assigned global permissions will be able to access objects and solutions across all Single Sign-On domains in an organization.
- B. Users assigned global permissions will be able to access objects and solutions only in the same Single Sign-On site.
- C. Users assigned global permissions will have administrator access across all objects and solutions in a Single Sign-On domain.
- D. Users assigned global permissions will be able to access objects and solutions within that Single Sign-On domain.

Answer: A

QUESTION 110

During Fibre Channel adapter setup of a ESXi host, which configuration guideline should be considered?

- A. Do not mix Fibre Channel adapter models to access the same LUN from a single host unless the default queue depth has been changed.
- B. Do not mix Fibre Channel adapters from different vendors in a single host.
- C. Use Fibre Channel adapters from different vendors in a single host.
- D. Set the queue depth to 16 if using a mix of different vendors' Fibre Channel adapters in all hosts in the cluster.

Answer: B