

## E1.9 – section B: Operating Systems- - Sample model answers to exam questions 2014

**Question 1**(a) *New computed example*

[R= Running, - = waiting]

Round Robin with time slice of 3 ms

|   |   |   |   |   |   |   |   |   |   |   |    |    |    |    |    |    |    |    |    |    |
|---|---|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|----|----|----|----|
| A | R | R | R |   |   |   |   |   |   |   |    |    |    |    |    |    |    |    |    |    |
| B |   |   | - | R | R |   |   |   |   |   |    |    |    |    |    |    |    |    |    |    |
| C |   |   |   |   |   | R | R | R |   |   |    |    |    |    |    |    |    |    |    |    |
| D |   |   |   |   |   |   | - | - | R | R | R  | -  | -  | R  | R  |    |    |    |    |    |
| E |   |   |   |   |   |   | - | - | - | - | -  | R  | R  |    |    |    |    |    |    |    |
|   | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 |

$$AWT = (0+1+0+4+4)/5 = 1.8\text{ms}; \quad ATT = 24/5 = 4.8\text{ms}$$

Advantages: Simple to implement and fair

Disadvantages: Difficult to determine appropriate time quantum:

- Too small: good response time, but large overheads (scheduler is called too often)
- Too large: bad response time

**[3] [2 for correct solution, + 1 for adv/disadvantages]**Priority scheduling with pre-emption

|   |   |   |   |   |   |   |   |   |   |   |    |    |    |    |    |    |    |    |    |    |
|---|---|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|----|----|----|----|
| A | R | R | - | - | R |   |   |   |   |   |    |    |    |    |    |    |    |    |    |    |
| B |   |   | R | R |   |   |   |   |   |   |    |    |    |    |    |    |    |    |    |    |
| C |   |   |   |   |   | R | - | - | - | - | -  | -  | -  | R  | R  |    |    |    |    |    |
| D |   |   |   |   |   |   | R | - | - | R | R  | R  | R  |    |    |    |    |    |    |    |
| E |   |   |   |   |   |   |   | R | R |   |    |    |    |    |    |    |    |    |    |    |
|   | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 |

$$AWT = 10/5 = 2\text{ms} \quad ATT = 26/5 = 5.2\text{ms}$$

Advantages:

Takes into account external factors regarding the importance of the various processes

Disadvantages:

Might result (quite probable) in starvation of low-priority processes – this can be avoided using an *aging* procedure; processes that wait for too long have their priorities gradually increased.**[2] [2; 1 for correct solution, + 1 for adv/disadvantages]**SJF

|   |   |   |   |   |   |   |   |   |   |   |    |    |    |    |    |    |    |    |    |    |
|---|---|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|----|----|----|----|
| A | R | R | R |   |   |   |   |   |   |   |    |    |    |    |    |    |    |    |    |    |
| B |   |   | - | R | R |   |   |   |   |   |    |    |    |    |    |    |    |    |    |    |
| C |   |   |   |   |   | R | R | R |   |   |    |    |    |    |    |    |    |    |    |    |
| D |   |   |   |   |   |   | - | - | - | - | R  | R  | R  | R  | R  |    |    |    |    |    |
| E |   |   |   |   |   |   |   | - | R | R |    |    |    |    |    |    |    |    |    |    |
|   | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 |

$$\text{Avg waiting time: } (0+1+0+4+1) / 5 = 1.2 \text{ ms, Avg turnaround time: } 22/5 = 4.4 \text{ ms}$$

**[2; 1 for correct solution, + 1 for adv/disadvantages]**

Advantages: Allows new short jobs to get a good service; Good handling of interactive processes since it results in a short response time

Disadvantages: Knowing the length of next CPU burst is difficult; frequently this is predicted utilising previous lengths as estimates, or is user-specified; can result in long waits (including starvation) for long processes.

(b) *[new computed example]*

Optimal page replacement algorithm (7 page faults)

|        |   |   |   |   |   |   |   |   |   |   |
|--------|---|---|---|---|---|---|---|---|---|---|
|        | 1 | 4 | 5 | 6 | 9 | 4 | 1 | 5 | 4 | 7 |
| Frame1 | 1 | 1 | 1 | 1 | 1 |   |   | 5 |   | 7 |
| Frame2 | - | 4 | 4 | 4 | 4 |   |   | 4 |   | 4 |
| Frame3 | - | - | 5 | 6 | 9 |   |   | 9 |   | 9 |

There are multiple correct ways of doing the last two replacements [2]

FIFO page replacement algorithm (9 page faults)

|        |   |   |   |   |   |   |   |   |   |   |
|--------|---|---|---|---|---|---|---|---|---|---|
|        | 1 | 4 | 5 | 6 | 9 | 4 | 1 | 5 | 4 | 7 |
| Frame1 | 1 | 1 | 1 | 6 | 6 | 6 | 1 | 1 |   | 1 |
| Frame2 | - | 4 | 4 | 4 | 9 | 9 | 9 | 5 |   | 5 |
| Frame3 | - | - | 5 | 5 | 5 | 4 | 4 | 4 |   | 7 |

**[2]**

LRU (Least recently used) page replacement algorithm (9 page faults)

|        | 1 | 4 | 5 | 6 | 9 | 4 | 1 | 5 | 4 | 7 |
|--------|---|---|---|---|---|---|---|---|---|---|
| Frame1 | 1 | 1 | 1 | 6 | 6 | 6 | 1 | 1 |   | 7 |
| Frame2 | - | 4 | 4 | 4 | 9 | 9 | 9 | 5 |   | 5 |
| Frame3 | - | - | 5 | 5 | 5 | 4 | 4 | 4 |   | 4 |

[2]

(c) [Bookwork]

Turn is a character variable; Interested\_A and Interested\_B are boolean variables initially set to FALSE;

```
Interested_A = TRUE;
Turn = 'B';
while (interested_B = TRUE
      AND Turn = 'B')
    Do_nothing;
Critical_A;
Interested_A = FALSE;
```

```
Interested_B = TRUE;
Turn = 'A';
while (interested_A = TRUE
      AND Turn = 'A')
    Do_nothing;
Critical_B;
interested_B = FALSE;
```

[1 point for setting the interest variables, 1 point for setting the turn variables, 1 point for setting the loop conditions correctly and 1 point for setting the interest variables to false after [4]

(d) [Bookwork]

First-fit: allocate first memory section that is big enough. Advantages: fast allocation method. Disadvantages: can be very inefficient

Best-fit: allocate the smallest section that is enough. Advantages: less inefficient in terms of space than first-fit. Disadvantages: tends to produce lots of remaining tiny fragments, and requires search through the entire list of memory sections

Worst fit: allocate the largest section that is available. Advantages: after allocating the request, the remainder of that section might still be usable. Disadvantages: requires search through the entire list of sections

[1 point per correct algorithm, and its advantages/disadvantages]

[3]