



Workshop Resources

Cursor Workshop

Kickoff



Workshop Resources

Setting the stage with our goals, agenda, and constraints



Housekeeping Notes



Meeting

Camera on is helpful

Raise hand is great for getting attention

Chat will be monitored for questions



Slides & Materials

Available at [LeadingEDJE/Courses or Workshop](#)



Stuck? Confused? Curious?

There's multiple of us here for a reason

Who We Are

At Leading EDJE, we believe technology is the most powerful tool for transforming businesses and unlocking human potential.

As strategists, innovators, and partners, we don't just solve problems — we craft bespoke solutions that positively disrupt your business.



Introductions



Bryce Amacker



Matt Eland



Dave Michels

Learning Goals

Understand concepts and terminology
related to **AI assisted development**

Proficiency in using Cursor for **greenfield**
and **brownfield** development

Apply appropriate solutions for **enhancing**
Cursor's context in your project in ways
that are compliant with company practices

AI Assisted Development Philosophy

We believe that AI tooling can help developers become more productive when writing code, be more effective at navigating and maintaining code that is new to them, and find specialized solutions in areas that challenge the developer's own expertise.

Ultimately, AI tooling provides developers new options to consider when trying to provide quality technical solutions in timelines that support the needs of the business.

Agenda

Time	Content
8 – 9:15 AM	Introductions, Terminology, and Setup Verification
9:30 – 10:30 AM	Tooling Discussion and Demonstration
10:45 – 11:30 AM	Cursor for Greenfield Development
11:30 AM – 12:30 PM	Lunch Break
12:30 – 1:15 PM	Context Discussion and Sample App Exploration
1:15 – 2 PM	Cursor for Brownfield Development
2:15 – 3:45 PM	Advanced AI Integration
4 – 5 PM	Final discussions and topics of interest

Terminology

Laying a foundation for the rest of today's discussions and demos

Context

Editor Context


- The current active file is app.js
- Look at all files inside the Services directory

Setting Context

- It is early December in 2025
- We are in Columbus, Ohio
- This codebase is a production codebase that does X

Process Context

- It is critical that the application log error diagnostic information
- Run tests after making any change



Agents in Cursor

Improve loading display layout

[Create PR](#)[Review](#)

Now · +46 -39 · Auto

At present the loading display in `Games.razor` causes the existing layout to flow around the spinner and looks unprofessional. I'd like a more consistent layout during the loading experience that doesn't cause the text on the page to move around when the spinner goes away.

Explored 2 files 1 search

The `if-else` chain causes layout shifts. Reserving space for the content area and overlaying the spinner to prevent movement. Updating the layout:

`Games.razor` +46 -39

```
<div style="position: relative; min-height: 200px;">
  @if (isLoading)
  {
    <div style="display: flex; justify-content: center; align-items: center; min-height: 200px;">
      <MudProgressCircular Indeterminate="true"/>
    </div>
  }
</div>
```

Checking for linting errors:

No linter errors found in `Games.razor`

Updated the loading display to prevent layout shifts.

Changes made:

1. **Reserved space container:** Wrapped the conditional content in a `div` with `min-height: 200px` to reserve space and prevent shifts.
2. **Centered spinner:** During loading, the spinner is centered in a flex container within the reserved space.
3. **Independent conditions:** Replaced the `if-else` chain with separate `if` statements so each state renders independently.



The container maintains a minimum height during loading, so when the spinner disappears and the table or empty state appears, the layout stays stable. The spinner is centered in the reserved area for a consistent look.

The page should now maintain a stable layout during loading transitions.

1 File Edited [Review](#)

`Games.razor` +46 -39

Agents in Cursor



Tools and Tool Calling

```

public class ChatService(ChatOptions options, ILogger<ChatService> logger,
IChatHistoryService chatHistoryService) : IChatService
{
    private readonly ChatOptions _options = options ?? throw new
ArgumentNullException(nameof(options));

    private AIAgent CreateAgent(string systemPrompt)
    {
        return new AzureOpenAIClient(
            new Uri(_options.Endpoint),
            new ApiKeyCredential(_options.ApiKey))
            .GetChatClient(_options.Deployment)
            .CreateAIAgent(instructions: systemPrompt)
            .AsBuilder()
            .UseOpenTelemetry(sourceName: "agent-framework-source")
            .Build();
    }
}

```

Search tokens...

```

public class ChatService ( ChatOptions options , ILogger < ChatService > logger
, IChatHistoryService chatHistoryService ) : IChatService { private
readonly ChatOptions _ options = options ?? throw new ArgumentNullException
( nameof ( options )); private AIAgent CreateAgent ( string systemPrompt )
{ return new AzureOpenAIClient ( new Uri (
options . Endpoint ), new ApiKeyCredential ( _ options . ApiKey ))
. GetChatClient ( _ options . Deployment ) . CreateAIAgent
( instructions : systemPrompt ) . AsBuilder ( ) .
UseOpenTelemetry ( sourceName : " agent - framework - source " ) .
Build ( ); } }


```

Tokens


<https://santoshkanumuri.github.io/token-visualizer/>

Agent Mode vs Editor Mode

AGENT MODE



EDITOR MODE



Multiple Agents in Parallel

The screenshot displays the 'Agents' application interface. At the top, a navigation bar includes 'Agents', 'Editor', and a menu with 'File', 'Edit', 'Selection', 'View', 'Go', 'Run', 'Terminal', and 'Help'. Below the navigation bar, there is a 'Search Agents' input field and a 'New Agent' button. The main content area is divided into two sections: 'IN PROGRESS' and 'OLDER'. The 'IN PROGRESS' section lists two tasks: 'Implement dependency injection for kernel memory' (with a sub-task 'Updating the documentation files to include Redis ...') and 'Enhancing indexer application with Spectre.Console' (with a sub-task 'Editing IndexingOrchestrator.cs'). The 'OLDER' section lists five tasks: 'Update RulesSearchService construction' (1d), 'Update tests and documentation for indexing' (1d), 'Change indexer database file path' (1d), 'Azure credential configuration issue' (1d), and 'Fixing 404 error in document indexing' (2d). A 'Show more' link is also present. The 'ARCHIVED' section is currently empty. On the right side, a detailed view of the 'Implement dependency injection for kernel memory' task is shown. It includes a 'Create PR' button, a 'Review' button, and a status bar indicating 'Now · +573 -60 · Auto'. The task description asks: 'Can you update the documentation for the solution, indexer, and webapi to mention the Redis dependency and provide brief instructions for docker / podman running the image locally with persistence?'. Below this, it states 'Searching for documentation files to update with Redis dependency and setup instructions:' and 'Explored 1 file 3 searches'. It then lists 'Updating the documentation files to include Redis dependency and setup instructions:' followed by 'Reading README.md' and 'Reading KERNEL_MEMORY.md'. At the bottom, there is a section for 'README.md' with the text: 'You should receive a `PONG` response.', '### Accessing RedisInsight (Web UI)', and 'Open yo'.

Can work locally or in cloud

Locally you can share the same files or use git worktrees

Get Started

Models

Cursor supports all frontier coding models from all major model providers.

Name ^	Default Context	Max Mode	Capabilities
 Claude 4.1 Opus	-	200k	∞ 🗨️ 🖼️
 Claude 4.5 Sonnet 	200k	1M	∞ 🗨️ 🖼️
 Composer 1	200k	-	∞ 🖼️
 Gemini 2.5 Pro	200k	1M	∞ 🗨️ 🖼️
 GPT-5.1 	272k	-	∞ 🗨️ 🖼️
 GPT-5.1 Codex 	272k	-	∞ 🗨️ 🖼️
 Grok Code	256k	-	∞ 🗨️

Show more models

Models

Differences

Effectiveness

Speed

Cost

Context Window

Capabilities

Thinking

Images

Tools

<https://cursor.com/docs/models>


Prompts

Write a method that can take in a string representing a name and return the first, last, and middle name. Create unit tests for this as well.

Write and test a method that takes in a string parameter called name representing the user's full name. Return an object representing the different parts of the name.

For example, "Bruce Wayne" would return an object with a FirstName of "Bruce" a LastName of "Wayne", and an empty string for the MiddleName.

Resources



SYSTEMS ARCHITECTURE
DOCUMENTATION




CODE STANDARDS AND
REVIEW PROCESS



FEATURE
SPECIFICATIONS

Model Context Protocol (MCP)




+

•

○

Tooling

AI Developer Productivity Tools and Cursor



Cursor

What's new in Cursor?

Composer Model


High speed

High quality output

Agent view

Optimized UI for multiple agents

Good for agent-focused workflows



Cursor vs Copilot

CURSOR

- Separate IDE (forked from VS Code)
- Can run in cloud if with per-use billing
- Heavy focus on context
- Has Enterprise editions
- Support for MCP, Agent, Plan, and Ask
- Supports many models
- Generally feels faster

COPILOT

- VS Code Extension
- GitHub Cloud Runners
- Heavy focus on GitHub Integration
- Focus on Enterprise-level Features
- Support for MCP, Agents, and Ask
- Supports many models

Other IDEs like Cursor

VS Code
w. Copilot

Claude
Code

Antigravity

Windsurf

Zed Editor

TabbyML

Void

Tabnine

Individual Plans

Hobby Free

Includes:

- ✓ One-week Pro trial
- ✓ Limited Agent requests
- ✓ Limited Tab completions

Download

Pro \$16/mo.

Everything in Hobby, plus:

- ✓ Extended limits on Agent
- ✓ Unlimited Tab completions
- ✓ Background Agents
- ✓ Maximum context windows

Get Pro

Pro+ **Recommended** \$60/mo.

Everything in Pro, plus:

- ✓ 3x usage on all OpenAI, Claude, Gemini models

Get Pro+

Ultra \$200/mo.

Everything in Pro, plus:

- ✓ 20x usage on all OpenAI, Claude, Gemini models
- ✓ Priority access to new features

Get Ultra

Cursor Editions

Business Plans

Teams

\$32/user/mo.

Everything in Pro, plus:

- ✓ Centralized team billing
- ✓ Usage analytics and reporting
- ✓ Org-wide privacy mode controls
- ✓ Role-based access control
- ✓ SAML/OIDC SSO

Get Teams

Enterprise

Custom

Everything in Teams, plus:

- ✓ Pooled usage
- ✓ Invoice/PO billing
- ✓ SCIM seat management
- ✓ AI code tracking API and audit logs
- ✓ Granular admin and model controls
- ✓ Priority support and account management

Contact Sales

Cursor Editions

Cursor Setup

Installing and Configuring Cursor



Download Cursor
Available for macOS, Windows, and Linux.

Download for Windows ↴

1.7 Latest



🍏 macOS	
Mac (ARM64)	↴
Mac (x64)	↴
Mac Universal	↴

🪟 Windows	
Windows (x64) (System)	↴
Windows (x64) (User)	↴
Windows (ARM64) (System)	↴
Windows (ARM64) (User)	↴

🐧 Linux	
Linux .deb (ARM64)	↴
Linux .deb (x64)	↴
Linux RPM (ARM64)	↴
Linux RPM (x64)	↴
Linux AppImage (ARM64)	↴



Welcome to Cursor

The AI Code Editor

Sign Up

Log In

[Skip and continue](#)



Sign in

Email

Continue

OR


 Continue with Google

 Continue with GitHub


 Continue with Apple

Don't have an account? [Sign up](#)

Cursor and Code Sharing



Disabling Code Sharing



Other Helpful Settings

M matt.eland@gmail.com
Pro Plan

Search settings Ctrl+F

- ⚙️ General
- ∞ Agents
- Tab
- 📦 Models

- ☁️ Cloud Agents
- 🔗 Tools & MCP

- 📋 Rules, Memories, Commands
- 📄 Indexing & Docs
- 🌐 Network
- >> Beta

📖 Docs



General

Manage Account

Manage your account and billing

Open

Upgrade to Ultra

Run parallel agents, get maximum value with 20x usage limits, and early access to advanced features.

Upgrade

Preferences

Default Layout

Modify your default layout to focus Agent or the editor



Agent

Editor

Editor Settings

Configure font, formatting, minimap and more

Open

Keyboard Shortcuts

Configure keyboard shortcuts

Open

Import Settings from VS Code

Import settings, extensions, and keybindings from VS Code

Import

Reset "Don't Ask Again" Dialogs

See warnings and tips that you've hidden

Show

Notifications

System Notifications

Show system notifications when Agent completes or needs attention



System Tray Icon

Show Cursor in system tray



Completion Sound

Play a sound when Agent finishes responding



Privacy

Privacy Mode

Your code data will not be trained on or used to improve the product. Code may be stored to provide features such as Background Agent.

Privacy Mode



User Settings > Workbench > Activity Bar > Orientation

Java-Specific Configuration



Extension Pack for Java

vscjava microsoft.com | 1,800,000 | (1)

Popular extensions for Java development that provides Java IntelliSense, debugging, testing,...

Installing

☒ Auto Update

[DETAILS](#) [FEATURES](#) [CHANGELOG](#)

Extension Pack (7)



Language Support for Java(TM) by Red Hat

Java Linting, Intellisense, formatting, refactor...

Red Hat

Installing



Debugger for Java

A lightweight Java debugger for Visual Studi...

vscjava

Installing



Project Manager for Java

Manage Java projects in Visual Studio Code

vscjava

Installing

Extension Pack for Java

Extension Pack for Java is a collection of popular extensions that can help write, test and debug Java applications in Visual Studio Code. Check out [Java in VS Code](#) to get started.

Extensions Included

By installing Extension Pack for Java, the following extensions are installed:

Marketplace

Identifier	vscjava.vscod java-pack
Version	0.30.4
Published	2021-09-03, 00:30:16
Last Released	2025-10-26, 23:51:11

Categories

Programming Languages	
Linters	Debuggers
Formatters	Snippets
Extension Packs	

Resources

[Marketplace](#)
[Repository](#)
[License](#)

Setting up Java for Cursor

Java Installation

Before setting up Cursor itself, you will need Java installed on your machine.

⚠ **Cursor does not ship with a Java compiler, so you need to install a JDK if you haven't already.**

- **Windows:** Download and install a JDK (e.g., OpenJDK, Oracle JDK, Microsoft Build of OpenJDK). Set JAVA_HOME and add JAVA_HOME\bin to your PATH.
- **macOS:** Install via Homebrew (`brew install openjdk`) or download an installer. Ensure JAVA_HOME points to the installed JDK.
- **Linux:** Use your package manager (`sudo apt install openjdk-17-jdk` or equivalent) or install via SDKMAN.

To check installation, run:

```
1 java -version
2 javac -version
```



If Cursor does not detect your JDK, configure it manually in settings.json. Then, restart Cursor to apply changes.

```
1 {
2   "java.jdt.ls.java.home": "/path/to/jdk",
3   "java.configuration.runtimes": [
4     {
5       "name": "JavaSE-17",
6       "path": "/path/to/jdk-17",
7       "default": true
8     }
9   ]
10 }
```

Java Troubleshooting

<https://cursor.com/docs/configuration/languages/java>

Setup & Troubleshooting

We'll do our rounds and make sure you're set up and ready to go

Feedback & Contact Form



<https://forms.gle/SrTzVzFnsDz4kiA18>

Break

Time	Content
8 – 9:15 AM	Introductions, Terminology, and Setup Verification
9:30 – 10:30 AM	Tooling Discussion and Demonstration
10:45 – 11:30 AM	Cursor for Greenfield Development
11:30 AM – 12:30 PM	Lunch Break
12:30 – 1:15 PM	Context Discussion and Sample App Exploration
1:15 – 2 PM	Cursor for Brownfield Development
2:15 – 3:45 PM	Advanced AI Integration
4 – 5 PM	Final discussions and topics of interest

+

•

○

Cursor Basics

Getting oriented in the Cursor IDE

TACTICAL

WEAPONS

HELM

NAVIGATION

COMMS

ENGINEERING

SENSOR CONTACTS	
◆ USS Valor	161 km
◆ USS Horizon	275 km
◆ Unknown	822 km
◆ Unknown	900 km
◆ Unknown	1368 km
◆ Unknown	2271 km
◆ Unknown	2412 km
◆ Unknown	2591 km

SCAN TARGET

No target selected

SCAN

SENSOR RANGE

+

3000 km

-

ALERT STATUS

NORMAL

YELLOW

RED



Our Morning Demo:
Warp Me!

Tab Completions

```
0 references
20 public override async Task HandleAsync(Cancellation token ct)
21 {
22     var rulesets :RulesetDto[] = await RulesetsService.GetRulesetsAsync(ct);
23
24
25     // Return a bad request if the rulesets are null or empty
26     if (rulesets == null || rulesets.Length == 0) CR ←
    {
        await Send.BadRequestAsync(ct);
        return;
    }
```

Sidebar Chat

(Ctrl+L)

The image shows a screenshot of the Visual Studio Code editor. The main editor window displays a C# file named `Program.cs` within the `JAIMES AF.slnx` solution. The code is for an ASP.NET Core web application using Aspire. The sidebar on the right contains a 'New Chat' window with the prompt 'Refactor this code to reduce the Cyclomatic Complexity and improve the readability'. The chat window shows a list of past chats, including 'Fixing incorrect EF migrations', 'Application not showing aspire dashboard', and 'Configure .NET Aspire project startup'. The bottom status bar shows the current file is `Program.cs` and the solution is `JAIMES AF.slnx`.

```
using FastEndpoints;
using FastEndpoints.Swagger;
using MattEland.Jaimes.Repositories;
using MattEland.Jaimes.ServiceDefaults;
using System.Diagnostics;
using MattEland.Jaimes.ApiService.Helpers;
using MattEland.Jaimes.ServiceDefinitions.Services;
using MattEland.Jaimes.Services;

namespace MattEland.Jaimes.ApiService;

public class Program
{
    public static async Task Main(string[] args)
    {
        WebApplicationBuilder builder = WebApplication.CreateBuilder(args);

        // Add service defaults & Aspire client integrations.
        builder.AddServiceDefaults();

        // Add services to the container.
        builder.Services.AddProblemDetails();

        // Learn more about configuring OpenAPI at https://aka.ms/aspnet/openapi
        builder.Services.AddOpenApi();

        // Add Swagger services
        builder.Services.AddEndpointsApiExplorer();


        builder.Services.AddFastEndpoints().SwaggerDocument();

        // Register a shared ActivitySource instance with the same name used by OpenTelemetry
        builder.Services.AddSingleton(new ActivitySource(builder.Environment.ApplicationName ?? "Jaimes.ApiService"));

        // Configure ChatOptions from configuration and register instance for DI
        ChatOptions chatOptions = builder.Configuration.GetSection(key: "ChatService").Get<ChatOptions>() ?? throw new InvalidConfigurationException("ChatService configuration is missing or invalid");
        builder.Services.AddSingleton(chatOptions);

        // Add Jaimes repositories and services
        builder.Services.AddJaimesRepositories(builder.Configuration);
    }
}
```

Specifying Context @



gram.cs 1

ListGamesEndpoint.cs

ListRulesetsEndpoint.cs

@ Games.razor

@ NewGame.razor M x

plan.plan.md

add-c

JAIMES AF.Web > Components > Pages > @ NewGame.razor

You, 1 second ago | 1 author (You)

1 @page "/games/new" You, 4 minutes ago • Enables game deletion ...

2

3 @rendermode InteractiveServer

4

5 <PageTitle>Create New Game</PageTitle>

6

7 <MudPaper Class="pa-4">

8 <MudText Typo="Typo.h4">Create New Game</MudText>

9 <MudContainer MaxWidth="MaxWidth.Medium" Class="mt-4">

10 <MudPaper Class="pa-4">

11 <MudText Typo="Typo.h4" Class="mb-4">Create New Game</MudText>

12 @if (isLoading)

13 {

14 <MudProgressCircular Indeterminate="true" Class="my-4" />

15 } else if (!string.IsNullOrEmpty(errorMessage))

16 {

17 <MudAlert Severity="Severity.Error" Class="mb-4">@errorMessage</MudAlert>

18 }

19

20 @if (!isLoading)

21 {

22 <MudForm>

23 <MudSelect @bind-Value="selectedScenarioId"

24 Label="Scenario"

25 Variant="Variant.Outlined"

26 Class="mb-4"

27 Disabled="isCreating">

28 @foreach (var scenario in scenarios)

29 {

Implement new game page functionality

Implement the New Game page in such a way that it allows the user to specify the details necessary to create a new game. Once the user clicks a Create button the page should call to the `NewGameEndpoint.cs` and then navigate to `GameDetails.razor` to display the details of the new game once created.

Agent Auto

@ NewGame.razor +59 -4

@using MattEland.Jaimes.ServiceDefinitions.Responses

@rendermode InteractiveServer

<PageTitle>Create New Game</PageTitle>

Checking for linting errors:

Found 1 error in 1 file

Removing the unnecessary using directive:

@ NewGame.razor -1

@using MattEland.Jaimes.ServiceDefinitions.Responses

@rendermode InteractiveServer

No linter errors found

Checking how buttons are used in other components to ensure consistency:

Grepped MudButton.*OnClick in JAIMES AF.Web

Updating the button to match the pattern used in other components:

@ NewGame.razor +2 -2

<MudProgressCircular Class="ms-n1" Size="Size.Small" Indeterminate="true" />

Chat: Agent

Cursor Allowlist

M

matt.eland@gmail.com

Pro Plan

Search settings Ctrl+F

⚙️ General

∞ Agents

➔ Tab

📦 Models

☁️ Cloud Agents

🔗 Tools & MCP

📋 Rules, Memories, Commands

📖 Indexing & Docs

🌐 Network

➤ Beta

📖 Docs

Auto-Run

Auto-Run Mode

Choose how Agent runs tools like command execution, MCP, and file writes.

Use Allowlist

Command Allowlist

Commands that can run automatically

npm test X

cd X

mvn X

MCP Allowlist

MCP tools that can run automatically. Format: 'server:tool', 'server:*' for all tools from a server, '*:tool' for a tool from any server, or '*:*' for all tools from all servers

e.g., filesystem:read_file

Browser Protection

Prevent Agent from automatically running Browser tools



File-Deletion Protection

Prevent Agent from deleting files automatically



Dotfile Protection

Prevent Agent from modifying dot files like .gitignore automatically



External-File Protection

Prevent Agent from creating or modifying files outside of the workspace automatically



Implement game deletion and new game link + ⌚ ...

Determine a scope of changes for adding the ability to delete existing games and a link to a new games page.

This new game link should be present in all cases and should also be linked to from the (no games) message. It should navigate the browser to /games/new and should not immediately create a game or call the API.

The delete game link should occur at the right edge of each row, use an appropriate icon and color, and require the user to confirm before deletion. Actual deletion should occur via the API using a DELETE verb and a new endpoint.

⚙️ Plan Auto @ 🌐 🖼️ ⬆️

Read GamesServices

Searched What MudBlazor components are used for icons and buttons in the web UI? (J...

Read GameDetails.razor

Grepped MudDialog|Dialog|Confirm in JAIMES AF.Web

Read JaimesDbContext.cs

Checking the Message entity structure and reviewing an endpoint test to understand the testing pattern:

Explored 1 directory 2 files

Creating the plan:

⚙️ add-delete-games-and-new-game-link.plan.md 🔖 ⌵

Add Delete Games and New Game Link

Add ability to delete games with confirmation dialog, and add a "New Game" link that navigates to /games/new without creating a game. The delete button appears at the right edge of each game row, and the new game link is always visible including in the empty state.

6 To-dos

☐ Add DeleteGameAsync method to IGameService interface and implement in GameService

☐ Create DeleteGameEndpoint with DELETE /games/{gameId:guid} route

☐ Add tests for DeleteGameEndpoint

... 3 more

View Plan Auto Build Ctrl+⌘

Add Delete Games and New Game Link

Backend Changes

1. Service Layer

- File: JAIMES AF.ServiceDefinitions/Services/IGameService.cs
- Add method: Task DeleteGameAsync(Guid gameId, CancellationToken cancellationToken = default)
- File: JAIMES AF.Services/Services/GameService.cs
- Implement DeleteGameAsync method
- Find game by ID, validate it exists
- Delete game (Messages will cascade delete automatically per EF Core configuration)

2. API Endpoint

- New File: JAIMES AF.ApiServices/Endpoints/DeleteGameEndpoint.cs
- FastEndpoints endpoint using the standard pattern
- Route: DELETE /games/{gameId:guid}
- Call GameService.DeleteGameAsync
- Return 204 No Content on success, 404 if game not found

3. Testing

- New File: JAIMES AF.Tests/Endpoints/DeleteGameEndpointTests.cs
- Test successful deletion
- Test 404 when game doesn't exist
- Follow pattern from ListGamesEndpointTests.cs

Frontend Changes

1. Games List Page

- File: JAIMES AF.Web/Components/Pages/Games.razor
- Add "New Game" button/link at top (always visible, before the table)

Chat: Plan

Fixing incorrect EF migrations

+🕒⋮

I think the ApiService has an incorrect set of migrations. When the application starts I get this exception: "There is already an object named 'Rulesets' in the database.".

I think this comes from a bad series of EF migrations. What should I do to resolve this?

🗨 Ask ▾

Auto ▾

@🌐🖼️⬆

Investigating the EF migrations issue. Checking migrations and how they're applied.

Explored 1 directory 3 files

Checking the migrations for duplicate table creation:

Explored 1 file 2 searches

Checking other migrations for duplicate table creation:

Explored 2 files 1 search

Checking the migration history and the model snapshot:

Explored 2 files >

The error "There is already an object named 'Rulesets' in the database" usually means the `Rulesets` table exists, but the `__EFMigrationsHistory` table is missing or incomplete, so EF tries to re-run `InitialCreate`.

Diagnosis

Your migrations look correct:

- `20251029024204_InitialCreate.cs` creates the `Rulesets` table
- Later migrations only modify data or add columns; none recreate the table

The issue is likely a mismatch between the database state and the migration history.

Chat: Ask

Enhance game visuals for reversi

[Create PR](#)[Review](#)

28m · +381 -67 · Auto



Okay, this is awesome, but I have a couple of requests. First, can you make the preview dots the same size as the pieces?

Secondly, the orange text when the AI is thinking is hard to read on a white background.



- Added hover tracking with `mouseenter` and `mouseleave` listeners
- Modified `BoardCell` to support a highlighted state for capture preview
- Updated piece rendering to show purple gradient when highlighted

All linting errors are resolved, and the code is ready to use. The game now provides clearer visual feedback for valid moves and potential captures.





This is great, but can we make the potential move ones not have a gradient, just have a large circle?

∞ Agent ▾ Auto ▾



Chat with Visuals

Model Selection



Model Selection

M matt.eland@gmail.com
Free Plan

Search settings Ctrl+F

- General
- Agents
- Tab
- Models**
- Cloud Agents
- Tools & MCP
- Rules, Memories, Commands
- Indexing & Docs
- Network
- Beta
- Docs

Models

Add or search model

Composer 1	☒
Sonnet 4.5	☒
GPT-5 Codex	☒
GPT-5	☒
Haiku 4.5	☒
Grok Code	☒
Gemini 2.5 Flash	☒
Sonnet 4.5	☐
GPT-5 Codex High	☐
GPT-5 Codex Fast	☐

[View All Models](#)

API Keys

OpenAI API Key ☐

You can put in [your OpenAI key](#) to use OpenAI models at cost.



Enter your OpenAI API Key

Override OpenAI Base URL ☐

Change the base URL for OpenAI API requests.

Demo

Building a Greenfield
Application with Cursor



Othello.js Prompt

I want to create a browser-based game that runs on Vanilla JavaScript.

This game should implement the classic game of Othello / Reversi where a player controls the white pieces and can place a piece on the game board, then an AI opponent thinks, then places a black piece on the board. These moves can potentially flip pieces that are surrounded by the color that was placed on horizontal, vertical, or diagonal axes.

The game should display the current score in terms of piece count at all times and should end when all spaces are occupied, announcing which player won.

Tests are important and the game should look polished and professional.

Please scaffold and create this project and its tests.

Othello.js Prompt

I want to create a browser-based Othello/Reversi game using vanilla JavaScript (no frameworks). The game should:

- Run directly in a browser by opening index.html (no build step required)
- Work with `<script>` tags, not Node.js modules
- Include tests that can run with Jest/Node.js separately
- Have clearly visible gridlines separating each cell
- Show valid moves with clear visual indicators
- Display pieces prominently on the board

Othello.js Prompt

Create a browser-based Othello game with:

- Clear visual gridlines so each cell is distinctly visible
- Prominent display of game pieces (white and black circles)
- Highlighted valid moves that are easy to see
- Real-time score display
- Smooth gameplay with click handlers that work after each AI move
- Professional, polished UI with good contrast and visibility

Othello.js Prompt

...and please ensure:

- The game is immediately playable when opening index.html in a browser
- All cells have visible borders/gridlines
- Valid moves are clearly highlighted
- Click handlers work correctly after AI moves
- The code works in browser environment (not just Node.js for tests)

Othello Java 21 Prompt

I want to create an Othello/Reversi game using Java 21

The game should:

- Include a grid with clear gridlines separating each cell
- Allow the player to select which tile they want to move
- Have an AI opponent that selects a valid move with the maximum number of pieces captured
- Flip each piece as it is placed or captured
- Display the current score with the player controlling white and the AI controlling black
- Display a message at the end of the game (when no moves remain)
- Include valid Junit tests

Feedback & Contact Form



<https://forms.gle/SrTzVzFnsDz4kiA18>

Break

Time	Content
8 – 9:15 AM	Introductions, Terminology, and Setup Verification
9:30 – 10:30 AM	Tooling Discussion and Demonstration
10:45 – 11:30 AM	Cursor for Greenfield Development
11:30 AM – 12:30 PM	Lunch Break
12:30 – 1:15 PM	Context Discussion and Sample App Exploration
1:15 – 2 PM	Cursor for Brownfield Development
2:15 – 3:45 PM	Advanced AI Integration
4 – 5 PM	Final discussions and topics of interest

Context Engineering

When you want AI to do things your way

Context Window

The page:

- Loads available scenarios and players on initialization
- Allows selection via dropdowns
- Calls the `NewGameEndpoint` when Create is clicked
- Navigates to `GameDetails.razor` with the new game ID after successful creation
- Handles errors and loading states

Follows the same patterns as `Games.razor` and `GameDetails.razor` for consistency.

This generates an exception at runtime on loading the NewGame page:

> Missing <MudPopoverProvider />, please add it to your layout. See <https://mudblazor.com/getting-started/installation#manual-installation>

17.1% context used

Active Rules
AGENTS.md

∞ Agent ▾ Auto ▾



Checking the layout file and adding the missing MudBlazor provider:


Explored 1 file 1 search ▾

Read MainLayout.razor

Searched files `**/*Layout*.razor` in JAIMES AF.Web

`MudPopoverProvider` is already in the layout. Checking the app structure and MudBlazor configuration:

Explored 2 files 1 search



Ways of Injecting Context in Cursor

Conversational
prompt

Code and
Comments

Agents.md

Rules

Memories

Team-specific
Context

User-specific
Context

Indexed
Documents

Commands

External tools /
MCP Servers

```
1 Matt Eland, 2 weeks ago | 1 author (Matt Eland)
2 Agents Orientation
3 Purpose
4
5 This file provides minimal, machine-oriented hints and common symbols to help AI assistants (Copilot, GitHub
6 Copilot, and other agents) understand the repository structure and naming conventions.
7
8 Key service interfaces and locations
9
10 - `IGameService` -> `JAIMES AF.Services/Services/IGameService.cs`
11 - `IScenariosService` -> `JAIMES AF.Services/Services/IScenariosService.cs`
12 - `IPlayersService` -> `JAIMES AF.Services/Services/IPlayersService.cs`
13 - `ChatService` -> `JAIMES AF.Services/Services/ChatService.cs`
14
15 Common DTOs and Mappers
16
17 - DTOs: `Services/Models/*.cs` (e.g., `GameDto`, `ScenarioDto`, `PlayerDto`)
18 - Mappers: `Services/Services/*Mapper.cs` (e.g., `GameMapper`, `MessageMapper`)
19
20 API endpoints
21
22 - `JAIMES AF.ApiService/Endpoints/*.cs` - small endpoint classes
23 - Request/Response models in `JAIMES AF.ApiService/Requests` and `Responses`
24
25 EF Core entities
26
27 - `JAIMES AF.Repositories/Entities/*.cs` - EF Core entities
28 - `JaimesDbContext` - in `JAIMES AF.Repositories/JaimesDbContext.cs`
29
30 Testing
31
32 - Tests are in `JAIMES AF.Tests/` with folders for endpoints, repositories, and services.
33
34 Development notes
35
36 - Target: `.NET9`
37 - DI registration: `ServiceCollectionExtensions.cs` in each layer registers services and repositories.
38 - Keep endpoints thin and delegate to services.
39
40 Alternate filenames agents may check
41
42 - `github/copilot_instructions.md`
```

Agents.md

Single context file in your repository root folder.

PHP	8	You are an expert in Java programming, Spring Boot, Spring Framework, Maven, JUnit, and related Java technologies.
JavaScript	6	
TailwindCSS	5	Code Style and Structure
Laravel	5	- Write clean, efficient, and well-documented Java code with accurate Spring Boot examples.
C#	4	- Use Spring Boot best practices and conventions throughout your code.
Web Development	4	- Implement RESTful API design patterns when creating web services.
Game Development	4	- Use descriptive method and variable names following camelCase convention.
Expo	4	- Structure Spring Boot applications: controllers, services, repositories, models, configurations.
React Native	4	Spring Boot Specifics
Flutter	4	- Use Spring Boot starters for quick project setup and dependency management.
Tailwind	4	- Implement proper use of annotations (e.g., @SpringBootApplication, @RestController,
Testing	4	

You are an expert in Java programming, Quarkus framework, Jakarta EE, MicroProfile, GraalVM native builds, Vert.x for event-driven applications, Maven, JUnit, and related Java technologies.

Code Style and Structure

- Write clean, efficient, and well-documented Java code using Quarkus best practices.
- Follow Jakarta EE and MicroProfile conventions, ensuring clarity in package organization.
- Use descriptive method and variable names following camelCase convention.
- Structure your application with consistent organization (e.g., resources, services, repositories, entities, configuration).

Quarkus Specifics

- Leverage Quarkus Dev Mode for faster development cycles.
- Use Quarkus annotations (e.g.,

Pre-built Agent Files

<https://cursor.directory>

<https://agents.md>

User Rules ?

Manage your custom user rules and preferences

+ Add Rule

Style request, response language, tone...

//

Cancel

Done

I prefer avoiding use of the var keyword and using target-typed new syntax wherever possible.

...

User-Specific Context

Centralized Agent Controls

Capability	Individual Plans	Teams	Enterprise
Privacy Mode	User choice	Enforce org-wide	<u>Enforce org-wide</u>
<u>Team Rules</u>		Enforceable + Optional	Enforceable + Optional
<u>Hooks for Logging, Auditing, and more</u>	✓	MDM Distribution	<u>MDM & Server-side distribution</u>

Team-Specific Context

Project-Specific Context

M matt.eland@gmail.com
Pro Plan

Search settings Ctrl+F

⚙ General

∞ Agents

→ Tab

📦 Models

☁ Cloud Agents

🔧 Tools & MCP

📋 Rules, Memories, Commands

📖 Indexing & Docs

🌐 Network

>> Beta

📖 Docs

Pattern Matched

These rules are applied when working with files that match their patterns

blazor-rules.mdc

*.razor

Guidelines for dependency injection registration

dependency-injection.mdc

["**/ServiceCollectionExtensions.cs", "**/Program.cs", "**/RepositoryServiceCollectionExtensions.cs"]

Guidelines for API endpoints using FastEndpoints

endpoints.mdc

["**/Endpoints/*.cs", "**/ApiService/**/*.cs"]

Guidelines for EF Core entity classes

entities.mdc

["**/Entities/*.cs", "**/Repositories/Entities/*.cs"]

Guidelines for Kernel Memory Redis configuration and tag field management

kernel-memory-redis.mdc

["**/Program.cs", "**/ServiceCollectionExtensions.cs", "**/DocumentIndexer.cs", "**/RulesSearchService.cs"]

Guidelines for mapper classes that convert between entities and DTOs

mappers.mdc

["**/Mapping/*.cs", "**/Mappers/*.cs", "**/Services/Mapping/*.cs"]

Guidelines for EF Core migrations and database changes

migrations.mdc

["**/Migrations/*.cs", "**/Repositories/Migrations/*.cs", "**/JaimesDbContext.cs"]

Guidelines for service interfaces and implementations

service-interfaces.mdc

["**/ServiceDefinitions/Services/*.cs", "**/Services/*.cs"]

.cursor/rules/blazor-rules.mdc

.cursor/rules/**/*.razor

Guidelines for dependency injection registration

.cursor/rules/dependency-injection.mdc

.cursor/rules/["**/ServiceCollectionExtensions.cs", ".cursor/rules/**/*.Program.cs", ".cursor/rules/**/*.RepositoryServiceCollectionExtensions.cs"]

Guidelines for API endpoints using FastEndpoints

.cursor/rules/endpoints.mdc

.cursor/rules/["**/Endpoints/*.cs", ".cursor/rules/**/*.ApiService/**/*.cs"]

Guidelines for EF Core entity classes

.cursor/rules/entities.mdc

.cursor/rules/["**/Entities/*.cs", ".cursor/rules/**/*.Repositories/Entities/*.cs"]

I'm getting started using Cursor on my codebase and want to generate an agents.md file and relevant context files for the major areas of my application. These files should include details on how to work with each area, things to watch out for, and the best way to work with these files so Cursor can be successful in the future.

∞ Agent ▾ Auto ▾



Local ▾

Shift Tab to plan

Cursor can generate Context Files

Commands

Project Commands

Commands specific to this workspace

+ Add Command

build

Verify the solution builds by running `dotnet build`.

runtests

Test the solution by running `"dotnet test"` and verifying that the solution build...

test

Write tests to support your work and ensure the tests pass by using the `dotnet t...`

Command Examples

/test – ensure you add relevant tests for these changes and these tests pass

/tdd – follow test-driven development (TDD) while making these changes

/docs – please update any relevant documentation

/context – please update any relevant context files to reflect our decisions here

/maintain – ensure code is simple and maintainable with low cyclomatic complexity

/dry – look for places where there is code duplication and consolidate when possible

Commands

Project Commands

Commands specific to this workspace

+ Add Command

test-command

test-command

User Commands

Your personal commands from ~/.cursor/commands and ~/.claude/commands

+ Add Command

No User Commands

Create personal commands to reuse frequently

Add Command

.cursor > commands > test-command.md > # test-command

```
1 # test-command
2
3 Make your answer as silly as possible.
4
```

Enhance content for GameDetails page

+ ⌚ ...

I need more content on the @ GameDetails.razor page. /test-command

Reviewing the GameDetails page and its code-behind to understand the structure before adding more content.

Explored 3 files 2 searches

Adding more content to the GameDetails page with a fun, silly twist.

@ GameDetails.razor +40 -1

```
<MudPaper Elevation="2" Class="pa-4 mb-4">
  <MudText Typo="Typo.h6" Class="mb-3"> 🎮 Game Information Card 🎮 </
  <MudGrid>
    <MudItem xs="12" sm="6" md="4">
      <MudText Class="mb-1"><b>ID</b> Game ID:</b></MudText>
      <MudText Class="mb-2" Style="font-family: monospace; font-s
```

Adding an empty state for when there are no messages and enhancing the message input area:

File-Specific Context

Apply to Specific Files ▾

["**/ServiceCollectionExtensions.cs" ×

**/Program.cs" ×

**/RepositoryServiceCollectionExtensions.cs"] ×

Matt Eland, 6 days ago | 1 author (Matt Eland)

```
1 ---
2 globs: ["**/ServiceCollectionExtensions.cs", "**/Program.cs", "**/RepositoryServiceCollectionExtensions.cs"]
3 alwaysApply: false
4 description: Guidelines for dependency injection registration
5 ---
6
7 # Dependency Injection Guidelines
8
9 When working with DI registration:
10
11 ## Registration Location
12 - Each project has its own `ServiceCollectionExtensions.cs` (or similar)
13 - Services are registered in `Program.cs` using extension methods
14 - Keep registration logic organized by layer
15
16 ## Service Lifetimes
17 - **Scoped**: Most application services (created once per request)
18 - **Singleton**: Configuration, shared services (created once for application lifetime)
19 - **Transient**: Lightweight, stateless services (created each time requested)
20
21 ## Registration Patterns
22 - Register interfaces, not concrete types (when using interfaces)
23 - Use extension methods to organize registrations
24 - Group related registrations together
25
26 ## Example Pattern
27 ```csharp
28 // ServiceCollectionExtensions.cs
29 public static class ServiceCollectionExtensions
30 {
31     public static IServiceCollection AddApplicationServices(this IServiceCollection services)
32     {
33         services.AddScoped<IGameService, GameService>();
34         services.AddScoped<IScenariosService, ScenariosService>();
35         services.AddScoped<IPlayersService, PlayersService>();
36
37         return services;
38     }
39 }
```

Directory-Specific Context

```
Apply to Specific Files ▾ ["/**/Mapping/*.cs" ×] ["/**/Mappers/*.cs" ×] ["/**/Services/Mapping/*.cs"] ×

Matt Eland, 6 days ago | 1 author (Matt Eland)
--- Matt Eland, 6 days ago • Add guidelines for various project layers inclu...
1 globs: ["/**/Mapping/*.cs", "**/Mappers/*.cs", "**/Services/Mapping/*.cs"]
2 alwaysApply: false
3 description: Guidelines for mapper classes that convert between entities and DTOs
4 ---
5
6
7 # Mapper Guidelines
8
9 When working with mapper classes:
10
11 ## Purpose
12 Mappers convert between:
13 - Repository entities (from `JAIMES AF.Repositories/Entities`)
14 - DTOs (from `MattEland.Jaimes.Domain`)
15 - Response models (from `JAIMES AF.ServiceDefinitions/Responses`)
16
17 ## Mapperly (Preferred Approach)
18
19 **Always prefer Mapperly** for mapping when possible. Mapperly generates compile-time code that is fast and type-safe.
20
21 ### When to Use Mapperly
22 - When source and target properties have matching names (or can be mapped with `[MapProperty]`)
23 - When mapping between classes with similar structures
24 - When you need collection mapping (automatically handled)
25
26 ### When NOT to Use Mapperly
27 - Generally, Mapperly can handle most cases, even complex ones, using `[UserMapping]` for custom implementations
28
29 **Note**: If a DTO is currently a record with positional parameters, consider converting it to a class to enable Mapperly
30 maintaining manual mappers.
31
32 **Note**: For complex navigation property mappings (e.g., `Game.Ruleset.Name` → `GameDto.RulesetName`), use `[UserMapping]`
33 while still benefiting from Mapperly's collection mapping and other features.
34
35 ### Mapperly Best Practices
36
37 1. **Use `[Mapper]` attribute** on static partial classes
38 2. **Use `[MapProperty]`** for property name mismatches:
39     ```csharp
40     [MapProperty(nameof(Source.Id), nameof(Target.SourceId))]
41     ```
```


Apply Intelligently ▾

Governs usage of the C# var keyword

```
1 ---
2 alwaysApply: false
3 description: Governs usage of the C# var keyword
4 ---
5 The C# var keyword is only acceptable in foreach statements. For all other variable declarations, always specify the created type. Use the C# target-typed new
   feature when possible to reduce repetition in code.
```

Auto-Applied Context

Context Inclusion Modes



Always Apply



Apply Intelligently if agent decides to



Apply to Specific Files using patterns



Apply Manually using @ mentions

Context Recommendations

Rules embedded in code are **easy to maintain**

Use **example Agent files** with tweaks as needed or have Cursor draft it

Have Cursor **generate context files** for you

Context for major areas – APIs, front-end, tests, persistence layer, etc.

Context for key files of interest or challenge

When you have struggles and overcome challenges, **ask Cursor to improve** your context or agent files based on what it learned

Memories
Saves useful context across Chats

Memories
Learn your preferences automatically based on Chats



Saved Memories
Review or remove individual Memories

Hide

No Memories Yet

Memories will appear as you use the Agent

Memories

Memories are automatically generated rules based on your conversations in Chat. These memories are scoped to your project and maintain context across sessions.

You can manage memories from [Cursor Settings](#) → Rules.

How memories are created

1. **Sidecar observation:** Cursor uses a sidecar approach where another model observes your conversations and automatically extracts relevant memories. This happens passively in the background as you work. Background-generated memories require user approval before being saved, ensuring trust and control over what gets remembered.
2. **Tool calls:** Agent can directly create memories using tool calls when you explicitly ask it to remember something or when it notices important information that should be preserved for future sessions.

Memories

```
2025-11-11 15:45:59.565 [info] Finishing sync (hasUpdates: false, isErr: false)
2025-11-11 15:45:59.609 [info] Finished indexing repository.
2025-11-11 15:45:59.609 [info] Indexing job successfully done or aborted.
2025-11-11 15:49:20.148 [error] Error getting submodules: A system error occurred (ENOENT: no such file or directory,
open 'c:\Dev\JAIMES-AF\.gitmodules')
2025-11-11 15:49:55.515 [info] Get user commits took 76.19350000005215ms for 10 commits
2025-11-11 15:50:47.509 [info] multiCodebaseIndexingJob dispose
2025-11-11 15:50:47.509 [info] Aborting indexing job.
2025-11-11 15:50:47.509 [info] Setting global status from status tracker: synced
2025-11-11 15:50:47.509 [info] Doing a startup handshake.
2025-11-11 15:50:47.517 [info] Finished computing merkle tree in 2.3660999992862344 ms.
2025-11-11 15:50:47.518 [info] Doing the initial handshake with hash:
ee8a3b5430d186213363ab47fd203d0805b3a0454cf581e41c932767da134ac8
2025-11-11 15:50:47.519 [info] Computed simhash vector of length: 256
2025-11-11 15:50:47.519 [info] Path key hash: 0b0718901b86cdf8022640a6911753a08c9a8f3a1d4727d37ac63e5aade6a30
2025-11-11 15:50:47.519 [info] Handshake start
2025-11-11 15:50:47.660 [info] Handshake timing: 142.035000000149, response: {"status":"STATUS_SUCCESS","codebases":
[{"codebaseId":"17505526-9e8b-43db-9335-77c9c68a47af","status":"STATUS_OUT_OF_SYNC","copyTaskHandle":""}]}
2025-11-11 15:50:47.660 [info] Handshake result: {"status":"STATUS_SUCCESS","codebases":
[{"codebaseId":"17505526-9e8b-43db-9335-77c9c68a47af","status":"STATUS_OUT_OF_SYNC","copyTaskHandle":""}]}
2025-11-11 15:50:47.660 [info] Starting fast remote sync.
2025-11-11 15:50:47.661 [info] Total num embeddable files: 146
2025-11-11 15:50:47.662 [info] Root hash: ee8a3b5430d186213363ab47fd203d0805b3a0454cf581e41c932767da134ac8
2025-11-11 15:50:47.662 [info] In the out of sync case.
2025-11-11 15:50:47.664 [info] Waiting on semaphore to be released 1
2025-11-11 15:50:47.877 [info] Waiting on semaphore to be released 1
2025-11-11 15:50:48.080 [info] Waiting on semaphore to be released 1
2025-11-11 15:50:48.283 [info] Waiting on semaphore to be released 1
2025-11-11 15:50:48.283 [info] [startSync]: sending sync merkle subtree batch of size 2
2025-11-11 15:50:48.493 [info] setting numJobsToGo to 2
2025-11-11 15:50:48.493 [info] [startSync]: numJobs: 2
2025-11-11 15:50:48.494 [info] Uploading 2 files.
2025-11-11 15:50:48.494 [info] Total number of files to embed: 146
2025-11-11 15:50:48.494 [info] Not aborted
2025-11-11 15:50:48.494 [info] Starting while loop.
2025-11-11 15:50:48.499 [info] syncing batch of 2 files and 3005 bytes
2025-11-11 15:50:50.778 [info] Completed job successfully: 17505526-9e8b-43db-9335-77c9c68a47af .\JAIMES AF.
Web\Components\Layout\MainLayout.razor
2025-11-11 15:50:50.778 [info] Completed job successfully: 17505526-9e8b-43db-9335-77c9c68a47af .\JAIMES AF.
Web\Components\Pages\NewGame.razor
2025-11-11 15:50:50.821 [info] Finishing sync (hasUpdates: true, isErr: false)
2025-11-11 15:50:51.070 [info] Finished indexing repository.
2025-11-11 15:50:51.070 [info] Indexing job successfully done or aborted.
2025-11-11 15:51:51.268 [error] Error getting submodules: A system error occurred (ENOENT: no such file or directory,
```

Indexing

Indexing & Docs

Indexing & Docs

Codebase

Codebase Indexing ?

Embed codebase for improved contextual understanding and knowledge. Embeddings and metadata are stored in the cloud, but all code is stored locally.

100%

381 files

Sync

Delete Index

Index New Folders

Automatically index any new folders with fewer than 50,000 files



Ignore Files in .cursorignore

Files to exclude from indexing in addition to .gitignore. [View included files.](#)

Edit

Index Repositories for Instant Grep BETA

Automatically index repositories to speed up Grep searches. All data is stored locally.



Docs

Crawl and index custom resources and developer docs

+ Add Doc

- AG-UI Docs

Indexed 12/5/25, 2:17 PM



Tools & MCP Servers

M matt.eland@gmai...
Free Plan

Search settings Ctrl+F

⚙️ General

∞ Agents

→ Tab

📦 Models

☁️ Cloud Agents

🔗 Tools & MCP

📋 Rules, Memories, ...

📖 Indexing & Docs

🌐 Network

>> Beta

📖 Docs 🌐

Tools

Browser



Browser Automation



Ready (Chrome detected)

Installed MCP Servers

No MCP Tools

Add a custom MCP tool here or configure project-specific tools in `<project-root>/cursor/mcp.json`

Add Custom MCP

Tips for Improving Context

Focus

Keep things focused on the task you want the agent to accomplish

New

Start new conversations when ready to move on to new focuses

Filter

Ignore irrelevant file types and directories so they're not indexed

Improve

If you find certain areas are tricky, you may need more rules or tweaks to agent files



Adding Context

Adding Context to our Sample Project

Feedback & Contact Form



<https://forms.gle/SrTzVzFnsDz4kiA18>

Break

Time	Content
8 – 9:15 AM	Introductions, Terminology, and Setup Verification
9:30 – 10:30 AM	Tooling Discussion and Demonstration
10:45 – 11:30 AM	Cursor for Greenfield Development
11:30 AM – 12:30 PM	Lunch Break
12:30 – 1:15 PM	Context Discussion and Sample App Exploration
1:15 – 2 PM	Cursor for Brownfield Development
2:15 – 3:45 PM	Advanced AI Integration
4 – 5 PM	Final discussions and topics of interest

Brownfield Development

Let's see what happens if we just work on production code without any added context



This afternoon's codebase

What do we get out of the box?

Switch to the 'workspace/no-rules' branch and start a new Agent session with the 'step6-historical-feature.md' prompt.

This branch is from a previous point in time for our repo, before the feature described in the prompt was implemented.

You can either commit changes locally or git stash these results to compare them with an implementation with additional context we'll do later

Demo

Let's try AI assisted development with zero changes!

Discussion

What happened?

What was good?

What wasn't?

What ways of trying to fix this might work?

Which are the best options to try first?

Feedback & Contact Form



<https://forms.gle/SrTzVzFnsDz4kiA18>

Break

Time	Content
8 – 9:15 AM	Introductions, Terminology, and Setup Verification
9:30 – 10:30 AM	Tooling Discussion and Demonstration
10:45 – 11:30 AM	Cursor for Greenfield Development
11:30 AM – 12:30 PM	Lunch Break
12:30 – 1:15 PM	Context Discussion and Sample App Exploration
1:15 – 2 PM	Cursor for Brownfield Development
2:15 – 3:45 PM	Advanced AI Integration
4 – 5 PM	Final discussions and topics of interest

Advanced AI Integration

Time to add in some contextual sprinkles to see how we can improve things

The background image shows a construction site at sunset. Several tall cranes are visible, their silhouettes against a sky transitioning from blue to orange. Scaffolding and other construction structures are visible in the foreground and midground. A semi-transparent dark rectangle is overlaid on the left side of the image, containing the text.

Project-specific Scaffolding and Prompts

Writing a good AGENTS/Rules.md

Every time you use an Agent, it is seeing your codebase for the first time. This means you should tell it the:

- **What** – is this codebase? What are the features? Where are they defined?
- **Why** – do we have this codebase? What is its purpose? Why are things organized the way they are?
- **How** – do we use/build it? How do you style code? How do you run tests? How do you validate changes?

These rule files are included in *every single chat*, so we want them to be universally applicable to the project. High level, curated rules beats targeted 'hotfix' instructions that might only be applicable in narrow cases.

Bad AGENTS/Rules examples

1. Database Schema Instructions

When creating new database tables:

- Always include `created_at` and `updated_at` timestamps
- Use UUID primary keys, not auto-increment integers
- Add indexes on foreign keys
- Follow naming pattern: `user_profiles`, not `userProfiles`

Why bad: Only relevant when doing database work, wastes context otherwise.

3. One-Time Setup Instructions

Setting up the development environment:

1. Install Node.js 18+
2. Run ``npm install``
3. Copy `.env.example` to `.env`
4. Set up local PostgreSQL
5. Run migrations with ``npm run migrate``

Why bad: Setup happens once, not in every session. Bloats every conversation.

2. Detailed Code Style Guidelines

Code Style:

- Use 2 spaces for indentation
- Max line length 80 characters
- Prefer `const` over `let`
- [50 more formatting rules...]

Why bad: Linters do this better/faster, bloats context.

Teach the LLM to learn from examples.

Better AGENTS/Rules examples

1. Project Structure Overview

Project Structure:

- /apps/web - Next.js customer dashboard
- /apps/api - Go API server
- /apps/admin - Internal admin panel
- /packages/ui - Shared React components
- /packages/db - Database schemas and migrations

This is a pnpm monorepo. Always work from the root directory.

Why good: Helps Claude navigate and understand scope, relevant to all tasks.

3. Technology Stack

Tech Stack:

- Frontend: Next.js 14, TypeScript, TailwindCSS
- Backend: Go 1.21, PostgreSQL 15
- Infrastructure: Docker, deployed on AWS ECS
- Package manager: pnpm (not npm/yarn)

Why good: Informs all technical decisions, always relevant.

2. Progressive Disclosure Pointers

Documentation:

- Database conventions: see `agent_docs/database_design.md`
- API patterns: see `agent_docs/api_guidelines.md`
- Testing approach: see `agent_docs/testing_strategy.md`
- Deployment: see `agent_docs/deployment.md`

Read relevant docs before starting work on those areas.

Why good: Agent only reads what it needs, when it needs it.

Building Rules for your codebase

Create verbose repo overview



Generate rules with supplemented best practices document + artifact




Evaluate rules by re-creating existing features.
Refine as necessary.

Building Rules for your codebase

Start by building a comprehensive architecture document of your codebase. This can be done manually, or by utilizing Agents to break down your codebase piece by piece.

📁 product-mfe Give me a high-level overview of this repository. I want you to identify the primary components of the system. Determine what it is meant to do, how it does it. Identify common patterns used in the repo. Identify the main services and describe what they do. Create an architecture diagram of the repo.

∞ Agent ▾ gpt-5-codex ▾



Great, now I want you to dig into each one of the components that you identified, and break them out in more granular analysis. Collate this more granular investigation back into the initial high level review you made. Basically dig into the smaller parts and add them back in. Also, be sure to 'escape' mermaid components with parenthesis like this: "Fragments (styles/content/scripts)"

∞ Agent ▾ gpt-5-codex ▾



Ok, I now want you to convert this to a markdown file in the root of the repo, named 'ARCHITECTURE.md'. This should include the diagrams and findings you've made. This should have a consistent structure for all services. Include the mermaid diagrams, but also include a simple ascii tree diagram of the different components and their purpose.

∞ Agent ▾ gpt-5-codex ▾ 1x



Step 0: Switch to 'no-rules' branch

There are 2 prepared branches for this exercise:

- workshop/no-rules
- workshop/with-rules (if you want to skip to the end of the exercise)

workshop/no-rules is a branch made at an older commit in the repo, missing newer features we will use Cursor to re-implement

workshop/with-rules is the same, but with the Rule files we're about to make already prepared

Step 1: Create overview file

This is an example command for starting your ARCHITECTURE.md document. This example is very generic and provides no repo-specific details, but the more direction you can give here, the better.

This command will try to analyze the repo from higher to lower levels, consolidating all the information it finds into a single file named 'ARCHITECTURE.md'

Start a new Agent Session and run the command `/create-overview`.

Learning Rule-Building Principles

LLMs are stateless, they see your codebase for the first time every chat.

We want to give them enough context to start building the way we expect them to, but we don't want them to read the entire codebase every single chat.

- Teach the LLM *how to learn things* about the repo on its own, instead of giving the answer
- Keep Rules concise, reference existing code instead of hard-coding examples.
- Build progressive rules, link to other rules instead of fitting it all in one place.
- [This blog post](#) is a great resource for how to build effective rules.

Step 2: Create Initial Rules


We've got 2 great pieces of context for building Rules, the `ARCHITECTURE.md` for our repo and best practices defined in the `writing-good-rules.md` document.

- Create a new Agent Session and run the command `/create-rules`.
- This will give us the initial set of rules for our codebase, using the initial analysis as a starting point and the best practices document as a guide.
- This is a good starting point, but we will need to review and curate these rules for best results.
- Once you have finished, make a backup of the `.cursor/rules` outside of your repo (easier than dealing with git commands with a whole room of people)

Validate Rules with Known Implementation

How do we know if these rules are good?

Test them out on something we know the 'right' answer to!



Step 3: Let's recreate the feature - with Rules

Now that we know what results look like with no guidance, let's see how our Cursor Rules change the implementation.

Create a new Agent and run the prompt in the file '`historical-feature.md`'.

This version will automatically follow the generated rules built from the previous 'create-rules' command.

Comparing Human vs Agent MRs

Cursor Agents can use git to compare their implementation with the real merge commit.

This gives us a workflow for improving our rules to enforce code that is more similar to historical MRs.

Run prompt '**compare-with-real-feature.md**' in the same session as step 3.

Comparison: My Implementation vs. Commit b497ebd

Files Comparison

File	My Implementation	Real Commit
ANFStoreAttrDeleteService.java	✓ Created	✓ Created
ANFStoreAttrValDeleteService.java	✗ Not created	✓ Created
ANFStoreAttrValRepository.java	✓ Added findByStoreAttr_StoreAttrId()	✗ No changes
Controller	Added 1 endpoint	Added 2 endpoints
Tests	Service + Controller tests	Service + Controller tests

Step 4: Rule Refinement

Now that we have identified the differences between the Agent and Human MRs, we can analyze our rule set to identify what areas we can improve.

Run the prompt in `'analyze-rules-from-implementation.md'` in the same session as before.

This will let the Agent compare its own analysis against the real feature and where the rules came up short for its version of the feature.

Context

Thought for 3s

Checking the SemanticSlicer package namespace and fixing the import:

Searched web drittich.SemanticSlicer NuGet package namespace C#

Auto-Ran command: dotnet

```
$ dotnet list "JAIMES AF.Workers.DocumentChunking/JAIME:
DocumentChunking.csproj" package
```



Plan, @ for context, / for commands

∞ Agent ▾ Auto ▾ 1×

38.9% context used

Active Rules
sonarqube_mcp_instructions
testing
AGENTS.md





Tools and Tool Calling

MCP Servers

Installed MCP Servers

G

GitKraken

c:\Users\matt.eland\AppData\Roaming\Cursor\User\globalStorage\eamodio.gitlens\gk.exe mcp --host=cursor --source=gitlens --scheme=cursor

git_add_or_commit

git_blame

git_branch

git_checkout

git_log_or_diff

git_push

git_stash

git_status

git_worktree

gitkraken_workspace_list

issues_add_comment

issues_assigned_to_me

issues_get_detail

pull_request_assigned_to_me

pull_request_create

pull_request_create_review

pull_request_get_comments

pull_request_get_detail

repository_get_file_content

code_review_branch

Show less ▾

L

linear

npx -y mcp-remote https://mcp.linear.app/sse

Show less

+

New MCP Server

Add a Custom MCP Server

Browser MCP Support

Tools

Browser

Browser Automation

Ready (Chrome detected)

Google Chrome 

Show Localhost Links in Browser

Automatically open localhost links in the Browser Tab



Featured MCPs

Browse MCPs or [post a MCP](#) to reach 250,000+ monthly active developers.

[Add new](#) + ← →

**Atono**
Atono's MCP server connects your AI coding assistant directly to your product backlog, pulling your...

**Endgame**
Deployment superpowers for Cursor. Fast + Self-healing + Free - endgame.dev...

**Mailtrap Email Sending**
Integrates with Mailtrap Email Platform to enable sending transactional emails via API.

**MailerSend MCP**
Access the transactional messaging MailerSend API and services directly from your AI coding environment or...

Search 1800+ MCPs

**Ashra MCP Server**
Extract structured data from any website with a simple SDK call. No scraping code, no...

**Compresto MCP**
A Model Context Protocol (MCP) server for Compresto, providing AI assistants with...

**Caiyun Weather**
Caiyun Weather is a weather data service that provides real-time weather...

**Encore**
Encore turns Cursor into more than a coding tool. The open source framework lets you...

**urlDNA**
Scan and analyze potentially malicious URLs using the urlDNA

**Pearl**
The Pearl MCP Server expands the ecosystem of MCP-compatible tools by...

**AWS Knowledge MCP**
A fully managed remote MCP server that provides up-to-date documentation, code...

**AWS API MCP Server**
The AWS API MCP Server enables AI assistants to interact with AWS services...


External MCP Servers


<https://cursor.directory/mcp>

Cursor CLI

Getting started

```
1 # Install
2 curl https://cursor.com/install -fsS | bash
3
4 # Run interactive session
5 cursor-agent
```





Cloud Agents

Bugbot

 **Cursor** bot reviewed 2 days ago

backend/server/src/bugbotGithub/applyBugbotPRReview.ts

```
228 - const reviewCommentsResponse = await octokit.request('GET /repos/{owner},
228 + const reviewCommentsResponse = await octokit.request('GET /repos/{owner},
229     owner: repository.owner,
230     repo: repository.repo,
231     pull_number: pullRequest.issueNumber,
232 - review_id: commentResponse.data.id,
232 + since: new Date(Date.now() - 10000).toISOString(), // Only get recent co
233 });
```

 **Cursor** bot 2 days ago

Bug: PR Comments Fetching Misses New Inline Comments (Potential edge case)
By switching to all PR comments and relying on a fixed 10s since filter without pagination, Bugbot can miss new inline comments — either due to timing delays or because they aren't included in the first batch of results.

 [Fix in Cursor](#) [Fix in Web](#)

Bugbot Add-on

Free

\$0

Includes:

- ✓ Limited code reviews each month
- ✓ Unlimited access to Cursor Ask
- ✓ Cursor connection to auto-fix bugs
- ✓ GitHub integration

Try Bugbot

Pro

\$32/user/mo.

Everything in Free, plus:

- ✓ 14 day individual trial
- ✓ Unlimited reviews on up to 200 PRs/month
- ✓ Access to Bugbot Rules

Get Bugbot Pro

Teams

\$32/user/mo.

Everything in Pro, plus:

- ✓ 14-day team trial
- ✓ Unlimited code reviews on all PRs
- ✓ Analytics and reporting dashboard
- ✓ Advanced rules and settings

Get Bugbot Teams

Enterprise

Custom

Everything in Teams, plus:

- ✓ 30-day org-wide trial
- ✓ Advanced analytics and reporting
- ✓ Priority support and account management

Contact Sales

Bugbot Editions

Hands-on Exercise

Add targeted context, then repeat some of our steps from earlier

Discussion

How did this go?



What was most effective?



Did anything not help as much as you thought it might?

Feedback & Contact Form



<https://forms.gle/SrTzVzFnsDz4kiA18>

Break

Time	Content
8 – 9:15 AM	Introductions, Terminology, and Setup Verification
9:30 – 10:30 AM	Tooling Discussion and Demonstration
10:45 – 11:30 AM	Cursor for Greenfield Development
11:30 AM – 12:30 PM	Lunch Break
12:30 – 1:15 PM	Context Discussion and Sample App Exploration
1:15 – 2 PM	Cursor for Brownfield Development
2:15 – 3:45 PM	Advanced AI Integration
4 – 5 PM	Final discussions and topics of interest

Demo

Generating and Improving Test Coverage

Bonus Content?

As time allows

+

•

○

Conclusion

Final thoughts, recommendations, and next steps / resources

Recommendations for Long-Term Success

1

Store context in project-specific rules

2

Bootstrap your initial context, then review it

3

Start in a narrowly scoped manner and expand

4

Update documentation and context as things change

5

Get Cursor's help flagging weak areas

Injecting Context in Cursor

Conversational
prompt

Code and
Comments

Agents.md

Rules

Memories

Commands

Team-specific
Context

User-specific
Context

Indexed
Documents

External tools /
MCP Servers

Adopting AI Tooling

01

Start with a specific scope in mind

- Team / Project
- Codebase
- Tooling

02

Pick work items that are well-defined, speced out, and deal with common technologies

03

Plan in advance for testing and code review

04

Provide relevant context and instructions for how to operate (tests, docs, building code, etc.)

05

Consider pre-built Agent files as a starting point

Onboarding new developers with AI in mind



AI USE IS EXPECTED,
BUT NOT A SUBSTITUTE
FOR COMMON SENSE



TESTING IS CRITICAL



CODE REVIEWS BECOME
EVEN MORE IMPORTANT



THE WHOLE TEAM
ALWAYS OWNS
SOFTWARE QUALITY



DON'T TRUST THE AI

Additional Resources

<https://blog.LearningEDJE.com>

<https://cursor.com/docs>

<https://cursor.directory/learn>

<https://Agents.md>

Get In Touch



Bryce Amacker



Matt Eland



Dave Michels

Open Q&A



Feedback & Contact Form



<https://forms.gle/SrTzVzFnsDz4kiA18>