
Practical:1	Implementation and Time analysis of sorting algorithms. Bubble sort, Selection
Date :01/07/2026	sort, Insertion sort, Merge sort and Quick sort

Aim:

To implement and analyze different sorting algorithms such as **Bubble Sort, Selection Sort, Insertion Sort, Merge Sort, and Quick Sort.**

Objective :- To implement five major sorting algorithms (Bubble Sort, Selection Sort, Insertion Sort, Merge Sort, and Quicksort) in C++ using arrays, and to evaluate their combined time and space complexity characteristics.

SORTING ALGORITHMS

1. Bubble Sort

1. Start.
2. Read the array and size n.
3. Compare adjacent elements.
4. If the first element is greater than the next element, swap them.
5. Repeat the comparison for the remaining elements.
6. After each pass, the largest element moves to the end.
7. Repeat until the array is sorted.
8. Stop.

2. Selection Sort

1. Start.
2. Read the array and size n.
3. Select the first unsorted position.
4. Find the minimum element in the remaining array.
5. Swap the minimum element with the current position.
6. Move to the next position.
7. Repeat until the array is sorted.
8. Stop.

3. Insertion Sort

1. Start.
2. Read the array and its size.
3. Select the next element as key.
4. Compare the key with the elements in the sorted portion.
5. Shift larger elements one position to the right.
6. Insert the key in its correct position.
7. Repeat for all elements.
8. Stop.

4. Merge Sort

1. Start.
2. Divide the array into two halves.
3. Recursively sort the left half.
4. Recursively sort the right half.
5. Merge the two sorted halves.
6. Repeat until the complete array is sorted.
7. Stop.

5. Quick Sort

1. Start.
2. Select the last element as the pivot.
3. Partition the array around the pivot.
4. Place smaller elements before the pivot.
5. Place larger elements after the pivot.
6. Recursively sort the left and right portions.
7. Stop.

Program:-

```
#include <iostream>

using namespace std;

//Function to print array elements

void printArray(int arr[], int size) {

    for (int i = 0; i < size; i++) {
```

```
cout<< arr[i]<<" ";

}

cout<<endl;

}

//1.BubbleSort

voidbubbleSort(intarr[],intn){ for

(int i = 0; i < n - 1; i++) {

for(intj=0;j<n-i-1;j++){ if

(arr[j] > arr[j + 1]) {

int temp = arr[j];

arr[j]=arr[j+1];

arr[j+1] =temp;

}

}

}

}

//2.SelectionSort

voidselectionSort(intarr[],intn){

for (int i = 0; i < n - 1; i++) {

intminIndex =i;

for(intj=i+1;j<n;j++){ if

(arr[j] < arr[minIndex]) {

minIndex= j;
```

```

    }

    }

    int temp = arr[minIndex];

    arr[minIndex] = arr[i];

    arr[i] = temp;

    }

    }

//3.InsertionSort

void insertionSort(int arr[], int n) {

    for (int i = 1; i < n; i++) {

        int key = arr[i];

        int j = i - 1;

        while (j >= 0 && arr[j] > key) { arr[j +

        1] = arr[j];

        j--;

        }

        arr[j + 1] = key;

    }

}

//Merge helper function

void merge(int arr[], int left, int mid, int right) { int n1

= mid - left + 1;

    int n2 = right - mid;

```

```
int L[100], R[100];

for(int i=0; i<n1; i++) L[i]
= arr[left + i];

for(int j=0; j<n2; j++) R[j]
= arr[mid + 1 + j]; int i =
0, j = 0, k = left;

while(i<n1 && j<n2) { if
(L[i] <= R[j]) {
arr[k]=L[i]; i++;

} else {
arr[k]=R[j];
j++;

}

k++;

}

while(i<n1){
arr[k] = L[i];
i++;
k++;

}

while(j < n2){
arr[k]= R[j];
```

```

j++;

k++;

}

}

//4.MergeSort

void mergeSort(int arr[], int left, int right) { if
(left < right) {
    int mid = left + (right - left) / 2;
    mergeSort(arr, left, mid);
    mergeSort(arr, mid + 1, right);
    merge(arr, left, mid, right);
}
}

//Partition function for QuickSort

int partition(int arr[], int low, int high) { int
pivot = arr[high];
int i = low - 1;
for (int j = low; j < high; j++) { if
(arr[j] < pivot) {
    i++;
    int temp = arr[i]; arr[i]
    = arr[j];
    arr[j] = temp;
}
}
}

```

```

    }

    }

    int temp = arr[i + 1];

    arr[i+1]=arr[high];

    arr[high] = temp;

    return i + 1;

}

//5.QuickSort

void quickSort(int arr[], int low, int high) {
    if
    (low < high) {

        int pi = partition(arr, low, high);

        quickSort(arr, low, pi - 1);

        quickSort(arr, pi + 1, high);

    }

}

int main() {

    int originalArr[] = {64, 34, 25, 12, 22, 11, 90};

    int n = sizeof(originalArr) / sizeof(originalArr[0]);

    int arr[100];

    cout << "Original Array:";

    printArray(originalArr, n);

```

```

//Bubble Sort

```

```
for(int i=0;i<n;i++) arr[i]
= originalArr[i];

bubbleSort(arr, n);

cout<<"\n1.BubbleSortResult:"; printArray(arr,
n);

//SelectionSort

for(int i=0;i<n;i++) arr[i]
= originalArr[i];

selectionSort(arr, n);

cout<<"2.SelectionSortResult:"; printArray(arr,
n);

//Insertion Sort

for(int i=0;i<n;i++) arr[i]
= originalArr[i];

insertionSort(arr, n);

cout<<"3.InsertionSortResult:"; printArray(arr,
n);

//Merge Sort

for(int i=0;i<n;i++) arr[i]
= originalArr[i];

mergeSort(arr,0,n-1);

cout<<"4.MergeSortResult:";

printArray(arr,n);
```

```
//QuickSort

for(int i=0;i<n;i++) arr[i]

= originalArr[i];

quickSort(arr, 0, n - 1);

cout<<"5.QuicksortResult:";

printArray(arr, n);

return 0;

}
```

Output:

```
Output
Original Array: 64 34 25 12 22 11 90

1. Bubble Sort Result: 11 12 22 25 34 64 90
2. Selection Sort Result: 11 12 22 25 34 64 90
3. Insertion Sort Result: 11 12 22 25 34 64 90
4. Merge Sort Result: 11 12 22 25 34 64 90
5. Quicksort Result: 11 12 22 25 34 64 90

=== Code Execution Successful ===
```

Analysis:-

The algorithms tested can be naturally grouped into two categories based on their design patterns: **Quadratic-time basic sorts** $O(n^2)$ and **Logarithmic-time advanced divide-and-conquer sorts** $O(n \log n)$

TimeComplexitySummary

Bubble, Selection, and Insertion Sort utilize nested loop structures. In average and worst-case setups, they complete roughly n^2 computational comparison loops, giving them an $O(n^2)$ quadratic rate of growth. Insertion and optimized Bubble Sort perform exceptionally well $O(n)$ if the dataset is already mostly sorted.

Merge Sort and Quick Sort split the data into smaller fractions continuously. This divide-and-conquer strategy dramatically cuts down operations to an $O(n \log n)$ average rate.

Quick Sort can degrade to $O(n^2)$ if the pivot choice consistently isolates single elements. Instead of balanced splits

Sorting Algorithms	Time Complexity			Space Complexity
	Best Case	Average Case	Worst Case	Worst Case
Bubble Sort	$O(N)$	$\Theta(N^2)$	$O(N^2)$	$O(1)$
Selection Sort	$O(N^2)$	$\Theta(N^2)$	$O(N^2)$	$O(1)$
Insertion Sort	$O(N)$	$\Theta(N^2)$	$O(N^2)$	$O(1)$
Quick Sort	$O(N \log N)$	$\Theta(N \log N)$	$O(N^2)$	$O(N)$
Merge Sort	$O(N \log N)$	$\Theta(N \log N)$	$O(N \log N)$	$O(N)$

Space Complexity Summary

- Bubble, Selection, and Insertion Sort** require $O(1)$ space because they arrange elements completely in-place without generating extra lists.
- Merge Sort** requires a linear auxiliary footprint of $O(n)$ memory to construct temporary arrays during active array blending operations.
- Quick Sort** uses an execution stack footprint of $O(\log n)$ on average to keep track of recursive partition boundaries.

Conclusion:-

This practical highlights the direct real-world trade-off between algorithmic simplicity and scalability:

For Small Datasets: Simple algorithms like **Insertion Sort** and **Bubble Sort** are optimal because they require negligible implementation complexity and execute completely in place ($O(1)$ auxiliary space).

For Large Datasets: Divide-and-conquer algorithms like **Merge Sort** and **Quick Sort** are vastly superior because their $O(n \log n)$ runtime allows them to process massive files cleanly. **Merge Sort** guarantees reliable stability but requires a higher memory profile ($O(n)$), while **Quick Sort** offers highly rapid in-place processing under typical runtime conditions.