Measuring the Cost of Privacy and Robustness in Federated Learning

Anurag Lnu | MS Computer Science, Rochester Institute of Technology

Working title retained from the milestone reports; advisor confirmation remains open. Working report, updated 21 October 2026. The fixed study completed all 360 cells and passed independent reconciliation. The additional source-bound reader reproduced all saved analysis exactly. Final study review and its validation correction are complete. Submission layout, advisor requirements and final delivery remain open; this is a working report. The refreshed PDF includes the verified dashboard checkpoint. The disease-specific follow-up has not been selected or trained; the results below describe the historical any-finding study.

Abstract

Privacy and robust aggregation must be chosen together in a federated-learning platform. This capstone measures their interaction using FedLearn components on patient-separated, content-audited NIH ChestX-ray14 features. A prospectively frozen 360-cell study compares clipped uniform mean and coordinate-wise trimmed mean, central privacy targets and own-data/own-update attacks, with bounded head, cohort and clipping sensitivities. All 7,200 rounds completed; independent decoding and replay verified all models and both evaluation splits. The ten-seed primary effect is +0.002266 AUROC (conditional paired 95% interval [+0.000704,+0.003828]), yet private trimming has lower absolute utility in the primary attacked setting. Larger heads increase modeled payload without improving the matched clean private point mean; clipping changes the aggregation ordering. Operating-point and patient-weight checks materially change interpretation. The contribution is reproducible, conditional platform guidance and inspectable execution; clinical validity and patient-level or whole-study privacy are not established.

1. Problem and contribution

A federated-learning platform needs to choose aggregation, privacy and training settings together. A rule that resists malicious updates without privacy noise may lose that advantage once its sensitivity determines how much noise must be added. A larger trainable head may increase communication and alter optimization as well as changing the dimension of the noise. An experiment that hides either effect can produce a recommendation that does not survive implementation.

This capstone studies that interaction using the FedLearn platform's aggregation and coordination components in a reproducible single-machine simulator. The primary question is whether central differential privacy changes the attack-adjusted advantage of coordinate-wise trimmed mean over clipped uniform mean. Secondary comparisons measure head size, simulated cohort size and clipping. The intended contribution is measured, reproducible guidance for platform decisions, together with a usable dashboard workflow; it is not a new differential-privacy theorem or a clinical image-classification system.

Correct execution and measurement are part of that contribution. Preliminary work found that float32 probability saturation can distort AUROC, that submission counts can be mistaken for successful aggregation, and that an attack reading raw honest updates can invalidate a downstream single-upload sensitivity premise. These are separate failure mechanisms.

Correcting them before the confirmatory experiment makes its comparisons interpretable; passing software tests alone does not prove that the resulting model is useful.

2. Related work and comparison boundary

Guerraoui et al. study worker-side noisy gradients and Byzantine-resilience conditions with a curious server, motivating care when combining privacy and robustness. Their dimension-dependent analysis does not automatically characterize our aggregate-noise mechanism. Allouah et al. (2023) analyze item-level distributed privacy of worker-server transcripts and propose SAFE-DSHB. Its trust model, unit and algorithm differ from this study's conditional client-update mechanism.

DP-BREM combines record-level privacy with client momentum and noisy centered aggregation; its DP-BREM+ variant changes the server-trust architecture. The proceedings abstract for CafCor describes robust aggregation using pairwise secret randomness and correlated noise with an untrusted server. We have not checked CafCor's proof. Our specific shared-noise cancellation example therefore must not be generalized to every correlated-noise design.

These works establish relevant context, not interchangeable guarantees or measured baselines. This capstone evaluates existing FedLearn components under a declared workload and threat model; it does not claim a new joint algorithm, a reproduction of these methods, or state-of-the-art superiority. Its useful outcome is a supported platform decision with reproducible evidence and explicit applicability.

3. Data, representation and simulated clients

The workload is NIH ChestX-ray14 with a binary label: an image marked exactly No Finding is 0; any recognized listed finding or combination is 1. These labels are derived from radiology reports, not expert-certified image-level diagnoses. Wang et al. describe the source labelling. We verified the downloaded metadata and official split lists, rather than substituting counts from an earlier dataset-paper version. The 112,120 images contain 60,361 No Finding and 51,759 finding labels before development quarantine.

Patient separation was insufficient to establish independent image content. A full RGB audit found exact duplicate groups crossing splits and patient identifiers, including contradictory labels. The original preparation was retained as failed. A conservative development quarantine then excluded 111 images from nine non-test patients, preserving the complete official test set. The qualified cohort has 68,650 training images from 22,399 patients, 17,763 validation images from 5,600 patients, and 25,596 test images from 2,797 patients. No patient appears in two of those groups. This process addresses measured exact-content overlaps; it is not a near-duplicate or clinical-label correctness certificate.

Finding prevalence is about 41.54% in training, 42.05% in validation and 61.47% in test. That reversal makes accuracy alone an inadequate summary. We preserve prevalence, report AUROC and operating-point/calibration measures, and transfer a threshold selected on validation without retuning it on test. Test membership, labels, prevalence, duplicate groups and fixed-backbone features were inspected during preparation; official-test classifier performance remained unseen until the frozen confirmatory execution began. This disclosure distinguishes structural data checks from performance-driven recipe selection.

Images are represented by 512 features from a frozen pretrained ImageNet ResNet-18. The cache binds source and cohort hashes, transformation, pretrained model state, row identities and feature/label payload hashes. Direct reference forwards qualified it before use. No

backbone is trained or selected using test performance. The linear head has 1,026 parameters; MLP hidden widths 8, 128 and 512 give 4,122, 65,922 and 263,682 parameters. Changing width changes capacity and optimization, so the study compares each private model with its own matched no-DP control.

For each run, sorted whole-patient groups are shuffled and assigned to 10, 80 or 1,000 simulated clients. Patient counts are approximately equal while image counts and label distributions differ. Ownership is fixed throughout the run and recorded by an assignment digest and actual counts. These clients are synthetic patient groups, not observed hospitals, phones or verified institutions. Clients train on their own assigned data and the simulator aggregates their updates; frozen-feature simulation is not a benchmark of physical device/network performance.

4. Execution and privacy/threat model

The primary recipe uses 80 clients accepted in each of 20 rounds, seven local SGD epochs per round, learning rate 0.003, batch size 256 and joint L2 clipping C=0.05. Aggregation is uniform mean or coordinate-wise trimmed mean, removing the largest and smallest floor(0.2n) values in each coordinate. There is no proximal term, server optimizer, subsampling credit, dropout, deadline selection or early stopping.

Matched privacy modes are no DP and central DP with epsilon 1, 4 or 8, delta 1e-5 and replace-one simulated-client adjacency. For a fixed accepted cohort and all other final uploads fixed, the implementation uses sensitivity 2C/n for mean and 2C/(n-2k) for trimming, k=floor(0.2n). Thus, at 80 clients, trimming's denominator 48 requires 5/3 the coordinate noise SD of mean at the same multiplier. The full-cohort Gaussian accountant composes 20 rounds over its declared Rényi order grid and classic epsilon/delta conversion from Mironov. Numerical calibration and every prefix were reconciled separately in the independent study audit.

The privacy interpretation is conditional on an honest client's replacement, fixed assignment/accepted cardinality and the permitted prior transcript. The server is trusted with raw updates. The two attack conditions use sixteen fixed malicious slots: sign-flip multiplies each slot's own update by -4 before common clipping; label-flip reverses binary labels on that slot's own data. Neither reads another client's current raw update. Earlier IPM/ALIE oracle behavior is outside this study; a production-code counterexample showed why upstream dependence can defeat reuse of a single-final-upload sensitivity premise.

Observed full-cohort checks do not establish acceptance invariance for every possible neighboring dataset. Epsilon describes the stated ideal Gaussian mechanism under its execution premises; a seeded public diagnostic workflow is not itself a protected deployment release.

The engine's diagnostic record exposes seeds and pre-noise diagnostics and is not a protected deployment export. Common random numbers across matched private cells also mean that marginal run budgets cannot simply be added as a joint guarantee. For two first-round releases of a common query with shared noise at different amplitudes, a linear combination cancels the noise even if its seed is secret. This ideal upload-domain example concerns a joint first-round transcript, not a demonstrated reconstruction from the final-only NIH checkpoints. Per-run accounting does not cover publishing the entire matrix or tuning history, and patient-separated groups do not convert the unit into patient-level DP. A deployment would need a separately reviewed release boundary, secret randomness and accounting for every released mechanism. This capstone reports conditional research-mechanism comparisons, not those additional guarantees. The robust-gradient literature is background; its convergence/statistical results are

not transferred automatically to local-SGD deltas, unequal patient-group sizes, ReLU heads, clipping and Gaussian noise.

5. Prospective study and inference

Exploratory validation pilots preceded the study. They exposed scoring/calibration problems and different local minibatch trajectories as cohort size changed. A later bounded schedule probe qualified E7/R20 across three seeds. Matched E1/R140 gave similar exploratory validation utility with seven times the modeled payload, while changing shuffle/local trajectories. A short four-head cost probe and a twelve-cell single-seed privacy/attack qualification followed. Their results remain exploratory; they are not pooled with new confirmatory test effects.

Before official-test classifier scoring, protocol commit `aa7ae53` fixed all 360 cells: 240 primary, 72 head, 24 cohort and 24clipping cells. It specifies ten new primary base seeds 20261101-20261110, final-round endpoints, matching, failure/resource rules and one primary contrast. The first three seeds also supply bounded secondary families, reusing the primary controls rather than rerunning them. No model, round, seed, clipping norm or cell is selected from confirmatory outcomes.

Let A(r, p, a) be final official-test image AUROC for rule r, privacy p and attack a. For each seed the attack-adjusted trimming advantage is

B(p)=[A(trim, p, signflip)-A(mean, p, signflip)] -[A(trim, p, clean)-A(mean, p, clean)].

The primary effect is D=B(epsilon 4)-B(no DP), averaged over the ten matched seeds. The report retains all eight absolute components. Positive D means that DP changes the attack-adjusted advantage in favor of trimming; it does not establish that a private trimmed model has higher absolute utility. The prespecified approximate 95% paired t interval uses df 9 and is produced only if all 80 required component cells qualify. Otherwise complete-pair effects remain descriptive and the interval is suppressed. No replacement seeds, imputation or available-case formal interval. The nominal t interval treats the ten seed-level effects as independent replicates and relies on an approximately normal effect distribution; successful execution does not verify those assumptions. Within-seed coupling is intentional. It describes conditional seed variation on fixed cohorts, not clinical-population uncertainty. The small sample remains a limitation; all other comparisons are descriptive.

Final scores use float64 subtraction of the two stored float32 logits before AUROC. Default prediction is finding only for a positive margin, with ties assigned 0. For each model, a second operating threshold is the highest validation margin achieving at least 80% finding recall, including ties; it transfers unchanged to test. The report includes confusion counts, sensitivity, specificity, balanced accuracy, accuracy, logistic loss and ten-bin argmax-confidence ECE. Inverse images-per-patient weights diagnose uneven repeated images but do not create a patient classifier. A prespecified secondary mask excludes nine test images from seven patients in known contradictory-label content groups; primary membership remains unchanged.

6. Reproducibility and evidence qualification

The source-bound runner was committed at `3baea7d` after 68 focused and 2,076 full framework tests passed,14 tests were deselected and coverage was 81.66%. Two launch-blocking review findings were first reproduced: parent thread settings differed from saved prediction recipes, and malformed protocol/config files were not treated as global integrity failures. Regression-backed corrections preceded real execution.

All 360 configurations/hashes and pending outcomes are persisted before launch. Each cell runs in a fresh process with four CPU threads and at most 180 seconds; combined child execution is bounded by 10,800 seconds. Parent verification/control time is separate. An engine-completion process high-water RSS observation over 2 GiB rejects qualification; it is not an enforced process-tree or late-artifact memory cap. Ordinary failure retains evidence and later fixed cells continue. Source/cache/mask/ protocol/config integrity failure stops later launches. No concurrent test suite or tracked source edits run during capture.

Each successful cell binds the qualified record, actual final server parameters, checkpoint, validation/test scores and row identities. Start/end proofs identify loaded source bytes; a start proof survives abrupt interruption. Returned records survive later artifact errors, and failed/nonfinite/timeout/unrun outcomes remain visible. Reanalysis reopens raw artifacts and rejects missing hash entries or edited summaries rather than trusting the study index.


The separate checker passed all 360 final models, both split replays, 7,200 rounds, 148 committed source files and 16 patient allocations. It imports no project configuration, runner, model, codec, metric or accountant. It resolves source bytes from Git, reconstructs recipes/ownership, parses checkpoints, performs direct Torch forwards, recomputes rank AUROC and threshold/weight/mask/accounting/cost arithmetic, and rebuilds the primary contrast with a separate signed sum. Sharing underlying Torch kernels is disclosed: exact replay demonstrates consistency under the fixed runtime, not cross-hardware equality or independent clinical truth. Source and ignored evidence are separately backed up with per-file hash verification.

7. Results and practical platform decisions


All 360 fixed cells qualified once, with no failures/timeouts/unrun cells: 240 primary, 72 head, 24 cohort and 24 clipping cells. No outcome was replaced. Across ten matched seed effects, D=+0.002266150 AUROC, sample SD 0.002183178 and the prespecified paired 95% t interval is [+0.000704398,+0.003827901]. Mean B is +0.007443034 without DP and +0.009709183 at epsilon 4. The interval excludes zero under the declared method but the effect is small, conditional on fixed cohorts, and not a clinical population or practical-equivalence statement.

Condition	Mean, no DP	Trimmed, no DP	Mean, epsilon 4	Trimmed, epsilon 4
Clean	0.662202	0.662033	0.646336	0.627488
Own-update sign flip	0.648991	0.656265	0.627389	0.618250

These eight absolute components prevent an interaction-only recommendation. Without DP, trimming improves attacked AUROC; at epsilon 4, its attacked point mean is lower than mean by 0.009139 AUROC, and its clean baseline is lower too. The positive D measures a change in the attack-adjusted advantage, not superior private utility. The complete epsilon 1/4/8 and label-flip grid, all seed effects and descriptive ranges are retained in the study report and tables.



Points: individual seeds. Large points and bars: mean and observed range; these bars are not confidence intervals. Missing cells remain in the study ledger.



Interval describes conditional simulation-seed variation on fixed cohorts; no clinical-population coverage. A positive D does not imply higher absolute private utility.

The secondary families are descriptive, using three matched seeds. For clean clipped mean at epsilon 4, linear and MLP512 point means are 0.644213 and 0.643233, while modeled upload increases from 6.8 MB to 1,688.0688 MB across 80 clients/20 rounds. This supports requiring a measured learning benefit before accepting the extra payload; it does not establish equivalence, an optimum head or convergence after other tuning. Matched privacy penalties are not monotone in width.

Cohort size also requires a learning check. Clean private mean point means are 0.548356/0.644213/0.630644 for 10/80/1,000 clients. The thousand-client private/no-DP gap is smaller, yet its absolute private mean is lower than the eighty-client value. Local trajectories change along with aggregate sensitivity; these results do not measure physical-client scaling or isolate a pure noise effect.

Clipping changes the decision. At C0.4 under sign-flip, no-DP mean averages 0.495854 versus 0.658057 for trimming; private epsilon 4 means are 0.520096 and 0.546027. Changing C changes useful signal truncation, attacker influence and calibrated noise together. Validate clipping with the intended threat/privacy setting instead of transferring one rule ranking across configurations.

For primary clean epsilon 4 mean, the validation-selected 80% recall threshold yields test recall 0.915729 and specificity 0.241375 across ten models, against default recall 0.619790. The validation target does not guarantee a new-data operating point. Inverse-patient weighting raises that group's AUROC by 0.077657 on average; this is a weighting diagnostic, not a patient classifier or a replacement primary endpoint. The frozen nine-image exclusion changes any model's AUROC by at most 0.000165502. Its small measured effect does not validate all labels or near-duplicate independence.

The original study used 10446.316 child seconds and 2834.088 parent-control seconds, 13280.404 in total. Maximum recorded engine-completion high-water RSS was 1573.469 MiB. Modeled bytes/FLOPs, observed timing/memory scope, fixed order and power/background conditions must remain visible in the platform. The practical guidance maps these findings to comparison, admission, scoring and lifecycle actions.

8. Limitations and remaining delivery

Early capture was observed on battery, followed by restoration of external power. An in-flight backup copied closed outputs while the study continued. Report these background/power conditions with the fixed-order limitation; measured wall-time differences are descriptive, not isolated hardware/algorithm scaling effects.

The representation is frozen and not domain-trained by this project; labels come from reports, exact duplicate curation is conservative and incomplete for near-duplicates, and the official cohort shows measured prevalence differences. There is no external clinical validation or verified hospital/device distribution. Fixed seed pairing does not make stream components numerically independent. Head/cohort/ clipping manipulations change multiple learning mechanisms, so raw differences do not establish a noise-only causal explanation. Secondary comparisons are bounded and descriptive, and terminal resource failures must remain part of the report.

The dashboard now passed actual browser-to-API-to-worker checks: two three-round validation jobs completed, a separate job stopped with two of twenty rounds retained, and reload/export/comparison/ownership and disabled-workload behavior were checked. These short, differently seeded demonstration runs are not new matched research comparisons or a disease-specific baseline. A screenshot-exposed mobile clipping failure was corrected and verified with visible-control-width and keyboard checks. The verification receipt and live/replay guide preserve the evidence boundary.

Final submission review, final assessed layout, advisor-approved title/format, presentation and full rehearsal remain delivery gates. The stronger disease-specific follow-up also remains

separate and unqualified. A working simulator does not complete the assessed capstone without the remaining scientific and delivery evidence.

9. Conclusion

The measured privacy/robustness interaction is small and positive, while absolute private utility and its practical ordering depend on aggregation, clipping and learning configuration. This motivates a platform workflow that presents matched controls, actual accepted cohorts, rule-specific calibration, operating points and resource scopes together. Data/content qualification and versioned score arithmetic are prerequisites for trusting that comparison. The study supplies reproducible evidence for those decisions; it does not certify a clinical model or a protected end-to-end deployment. The integrated dashboard makes execution, partial outcomes, configuration differences and cost/privacy scopes inspectable. Its verified local workflow supports delivery; stronger prediction baselines and the final report, presentation and rehearsal still require completion.

References

[1] Wang et al. (2017). ChestX-ray8: Hospital-scale Chest X-ray Database and Benchmarks on Weakly-Supervised Classification and Localization of Common Thorax Diseases. Revised version with ChestX-ray14 appendix.

[2] Yin et al. (2018). Byzantine-Robust Distributed Learning: Towards Optimal Statistical Rates. ICML.

[3] Mironov (2017). Renyi Differential Privacy. IEEE Computer Security Foundations Symposium.

[4] Guerraoui et al. (2021). Differential Privacy and Byzantine Resilience in SGD: Do They Add Up? PODC.

[5] Allouah et al. (2023). On the Privacy-Robustness-Utility Trilemma in Distributed Learning. ICML.

[6] Gu, Li and Xiong (2025). DP-BREM: Differentially-Private and Byzantine-Robust Federated Learning with Client Momentum. USENIX Security.

[7] Allouah, Guerraoui and Stephan (2025). Towards Trustworthy Federated Learning with Untrusted Participants. ICML. Proceedings abstract used for positioning only.