Measuring Privacy and Robustness Trade-offs in Federated Learning

Anurag Lnu | MS Computer Science | Rochester Institute of Technology

Working report, 25 October 2026.

Abstract

This capstone builds a reproducible experimental path inside FedLearn and measures how representation, aggregation and privacy calibration interact under malicious updates. A browser dashboard, authenticated Spring API and supervised Python worker expose the same coordinator and strategy components used by the platform, while source-bound batch runners retain complete scientific outcomes. Experiments use patient-separated NIH ChestX-ray14 frozen features and simulated whole-patient clients. In a frozen twelve-seed Effusion comparison, projection from 512 to 128 features improved private-clean AUROC by **+0.019176**, with training-seed 95% interval **[+0.011011, +0.027340]**, at a clean no-noise cost of 0.014923. Trimming and released-history centered clipping changed their ranking across conditions. The contribution is an inspectable engineering implementation and conditional evidence for choosing its research baselines. The measured execution is single-host simulation; external-site prediction and a protected end-to-end release remain outside the evidence.

1. Problem and contributions

Robust aggregation and differential privacy interact through clipping, sensitivity, noise and optimizer state: a rule that resists an attack can lose clean utility after noise. Which composite mechanism preserves prediction under a declared workload, client unit and adversary?

This work contributes three concrete results. First, it connects controlled experimentation to an operational platform: canonical recipe resolution, persistent authenticated runs, process ownership, cancellation, provenance and explicit partial outcomes. Second, it adds and qualifies pinned ByzFL reducers, a coalition-owned-data attack, projection policies and independent metric/inference checks. Third, it completes a prespecified fresh-seed comparison that separates absolute utility from interaction effects and reports uncertainty for two different targets.

Projected128 is the strongest private research candidate among the four tested policies, conditional on this recipe and cohort. No new robust-private optimization theorem is proposed. Appendices A and B retain historical evidence and development diagnostics.

2. Implemented architecture and execution boundary

The React Simulation Lab resolves a recipe before launch, displays actual completed rounds, retains run history, compares compatible terminal runs and downloads projected research records. The Spring Boot API uses cookie authentication, platform roles and PostgreSQL ownership. Server configuration owns the interpreter, data pin and storage paths. Browser inputs cannot choose commands or filesystem locations.

The API persists the run before launch and admits one active worker per application instance. It launches python -m fedlearn.lab_worker with a minimal environment and a parent pipe. The worker resolves and revalidates canonical configuration, checks feature integrity and reports atomic progress/execution snapshots. The service supervises the process deadline, drains descendants on termination and reconciles unfinished runs on restart using process identity. Completion requires exit status, matching configuration, requested rounds and qualified

evidence; a progress counter alone cannot produce success. Cancellation retains partial evidence. Restart reconciliation is implemented; automatic numerical resume is not.

The simulation driver calls the production FLCoordinator and strategy interfaces directly. Clients train sequentially inside one process, with client/round-derived randomness. This exercises aggregation and round bookkeeping while eliding network transport. The ByzFL 0.0.11 adapter normalizes updates, applies server clipping, invokes the selected reducer and calibrates noise. Its private centered policy retains the **released** delta as history rather than an unnoised internal center. It refuses unsupported private combinations, including bucketing, median reduction and multi-iteration centered clipping.

A source-bound batch path supports the larger research matrix. Prospective manifests bind protocol, runtime, feature bundle and resolved configurations before fitting. Runners refuse existing outputs, retain failures and stop later fitting when native/ByzFL anchors fail. Saved-head analysis independently rescores five metrics and exports aggregate results. Patient mappings, features, heads and predictions remain private research artifacts. Path-free exports improve disclosure control; they do not make the complete research transcript differentially private.

Browser acceptance used the authenticated API, PostgreSQL and real Python training. Historical demonstrations completed two three-round runs and retained a stopped 2/20-round run. The Effusion follow-up completed a real three-round private run and reproduced the A7 recipe through the Lab with zero observed per-round AUROC difference and the same final digest. These demonstrate execution and persistence. Inspectable contracts and receipts: worker, API, browser evidence, and simulation driver.

All reported scientific clients are simulated patient groups on one host. The approved CPU-first extension across Mac, G14 and Orin, with 3/6/24/80-client configurations, is a proposed design whose implementation is ongoing. No completed physical multi-host experiment, measured network scaling result or institutional federation is claimed here.

3. Workload, methods and privacy model

NIH ChestX-ray14 labels were mined from radiology reports [1]. Effusion is positive when its exact label token occurs; all other labels are negative. Preparation found exact RGB duplicates crossing patients/splits, including conflicting labels. A conservative development quarantine removed 111 images from nine patients. The qualified groups contain 68,650 training images from 22,399 patients, 17,763 validation images from 5,600 patients, and 25,596 official-test images from 2,797 patients.

Effusion validation patients were assigned label-independently to development selection (9,075 images; 2,800 patients) and an internal holdout (8,688 images; 2,800 patients). Validation had already informed the historical task. Finalists reuse selection patients; remediation reopened neither holdout nor official-test inputs, labels, predictions or models.

R0 is frozen ImageNet ResNet-18 with 512 features and a two-output linear head: 1,026 trainable parameters. A fixed public orthonormal projection at seed 20261025 reduces the head to 128 features and 258 parameters. Training-only normalization and the prepared bundle are fixed inputs to the studied update mechanism. The backbone is not fine-tuned. This is binary logistic-head optimization, whose loss is convex in the head parameters; local minima do not explain the observed initialization or policy differences.

The final matrix crosses four policies, two noise settings, two attack settings and twelve seeds, 13001-13012: 192 main cells plus four native anchors. Each uses zero initialization, eighty whole-patient IID clients, full participation, twenty rounds, seven local epochs, batch 256,

learning rate 0.03 and outer clip C=0.05. Uniform client weighting differs from image-weighted centralized training. This common recipe compares composite mechanisms, not fully tuned optima.

The coordinator is trusted to see and clip individual updates and release a Gaussian-noised aggregate. Adjacency replaces one simulated client, conditional on fixed preprocessing and assignment. In attacked arms, the protected change is one honest client with coalition identities/data fixed, conditional on released history. Replacing a coalition member can alter several malicious uploads and lacks this single-upload bound. A change to one patient's data within one honest client is a subset of whole-client replacement under those fixed conditions, so the same abstract bound applies; there is no automatic amplification to a smaller ε. This does not qualify an end-to-end patient-private preprocessing, selection or export pipeline, or local privacy against the coordinator.

For N=80 and sixteen trimmed values per tail [2], the per-release sensitivities are:

Mean: Δ = 2C/80. Trim16: Δ = 2C/(80-32) = 2C/48. Centered: Δ = 2 min(C,τ)/80, conditional on released history.

Center_quarter uses τ=0.0125. Gaussian coordinate noise SD is σ = zΔ. With T full-participation releases, Gaussian differential privacy composes as **μ = √T/z** [3]. Calibration to ε=4 and δ=0.00001 at T=20 gives z≈4.8351; an independent normal-CDF calculation checks the trade-off. Mean noise SD is approximately 0.006044, trim noise is 5/3 times larger, and center_quarter noise SD is approximately 0.001511. Matching ε changes both noise amplitude and the update rule. No subsampling amplification is used.

The adversary owns sixteen persistent clients. Owned-data PGD uses their examples and updates plus previously released model/history; it cannot read selection labels or current raw honest updates. It performs twenty ascent steps and three restarts, totaling sixty gradient and sixty-three loss evaluations per round, with step ratio 0.25 and a full-norm negative coalition-mean initialization. In projected128 arms it receives the corresponding projected 128-feature data and matching head. Its loss uses a uniform-mean surrogate, so it is a permitted-information heuristic rather than a reducer-specific worst-case attack. Mandatory server clipping bounds actual reducer inputs despite small reconstruction rounding overshoots.

The primary outcome is projected128 minus mean512 private-clean AUROC. AUROC measures score ranking: higher is better, 0.5 is chance ranking, and it does not specify a clinical operating threshold. The prespecified technical margin is +0.01. A paired t95 interval across twelve seeds conditions on fixed patients; a separate 2,000-draw patient-cluster percentile bootstrap at seed 20261025 holds the twelve fitted head pairs fixed and preserves image weighting. Neither is joint training-and-population uncertainty. Thirty secondary contrasts are descriptive and unadjusted for multiplicity. Average precision, Brier score and sensitivity/specificity at probability 0.5 are also retained.

4. Final findings

All 196 planned cells completed: 3,920 full eighty-client rounds, including 1,920 PGD rounds and 98 private cells. The independent execution audit reconciled 150 source files and all 31 paired-seed contrasts, with maximum arithmetic difference 5.6e-17. Native/ByzFL final parameters had numerically zero maximum difference in all four anchor comparisons; this is not a bytewise equality assertion. Every saved head passed five-metric rescoring and independent weighted-AUROC checks.

Table 1 reports every final main-arm mean. Native anchors are excluded. Each entry averages twelve training seeds on the same selection patients; GDP4 denotes the ε=4, δ=0.00001 central mechanism defined above.

Policy	Clean, no noise	Owned PGD, no noise	Clean, GDP4	Owned PGD, GDP4
mean512	0.807298	0.528545	0.740361	0.551304
projected128	0.792375	0.761839	0.759536	0.683331
trim16	0.807002	0.599442	0.678365	0.605114
center_quarter	0.805107	0.722725	0.666497	0.508300




Figure 1. Final main-arm AUROC on the fixed Effusion selection cohort, twelve paired training seeds per condition. Higher is better; chance ranking is 0.5. Whiskers show one across-seed sample SD, not a 95% interval or patient uncertainty. GDP4 denotes ε=4, δ=0.00001.

The primary gain is **+0.019176**, with approximate paired training-seed t95 interval **[+0.011011, +0.027340]**, SD 0.012850, SE 0.003709 and eleven degrees of freedom. Its lower endpoint exceeds the technical margin by 0.001011. The separate fixed-head patient interval is **[+0.013136, +0.025893]**, with 2,000 valid and zero skipped draws. This meets the conditional technical criterion.

The gain is less than half the two-seed pilot estimate, +0.0406. One final seed favors full width (-0.005253); another gains only +0.000419. Selection optimism may contribute to the shrinkage; it is not an established sole explanation.




Figure 2. Projected128 minus mean512 private-clean AUROC: individual seed effects and separate conditional 95% intervals. Positive favors projection; the technical margin is +0.01. The paired-seed t interval holds patients fixed; the patient-cluster percentile interval holds fitted heads fixed. Neither combines both uncertainty sources.

Projection costs 0.014923 clean no-noise AUROC and improves attacked points under this PGD. It changes signal, head geometry, clipping and noise jointly. Reduced noise energy alone is not a demonstrated causal explanation. Likewise, center_quarter improves nonprivate attacked utility but has the lowest private attacked point. A noisy previous release may make its center stale or unstable; that is a hypothesis, not a causal finding. Trim16 improves private attacked utility over mean512 while losing private-clean utility. These reversals rule out choosing a default from robustness labels or sensitivity alone.

5. Related systems and comparison boundary

System or method	Relevant capability	Relationship to this study
ByzFL 0.0.11 [7]	Aggregators, preaggregators and attacks	Reducers executed through the qualified adapter; clipping, private history, accounting and evidence are integration responsibilities.
NVIDIA FLARE [8,9]	Orchestration; Opacus sample-DP training; update filters	Documentation/source inspected; no matched FLARE benchmark. Percentile sparsification alone does not supply this client-DP guarantee.
SAFE-DSHB [5]	Privacy/robustness/utility analysis and method	Relevant theory; protocol and assumptions were not reproduced as a matched baseline.
DP-BREM / DP-BREM+ [6]	Record-level cross-silo privacy; momentum, clipping and added integrity mechanisms	Different privacy unit and transcript; secure summation alone does not validate inputs or generate sufficient honest noise.
CafCor [12]	Correlated noise with pairwise secret randomness	A failure of this project's shared-noise design does not refute this separate protocol.
Byz-Clip21-SGD2M [10]	Client momentum, clipped error feedback and local noisy messages	Separate protocol-level reproduction needed; not equivalent to replacing a server reducer.
LA-LoRA [11]	Low-rank private fine-tuning	Changes the trainable model; not a matched frozen-head comparison.

Table 2 separates executed components from systems inspected through primary sources.

The one-step released-history center here is not a full reproduction of worker-momentum methods such as Learning from History [13]. Existing tools reduce implementation effort without settling sensitivity, attacker knowledge or matched evaluation. This comparison cannot establish state-of-the-art performance.

6. Consolidated validity and release scope

The scientific limit is repeated development-selection use. Fresh seeds assess training variability; they do not provide a fresh cohort or correct prior policy selection. The two reported interval targets also omit joint uncertainty. Weak report-mined labels, undetected near-duplicates, simulated IID clients and a frozen pretrained representation limit transfer to hospitals. Label-skew pilots do not reproduce scanner, institution or temporal shift.

The attack is damaging in its positive control but neither optimal nor exhaustive. Oracle attacks using current honest raw updates are separate nonprivate stress tests: their dependence can break the single-upload client-data argument. A good result against this PGD cannot certify Byzantine robustness in general.

The mathematical update bound does not cover preprocessing, all diagnostics, public experiment seeds, saved models and the cumulative research transcript. Public/shared randomness is not a protected deployment randomness design. Floating-point leakage, observable failures and malicious-input enforcement need separate qualification. Central privacy, local privacy and secure aggregation provide different trust guarantees.

Testing supports specified execution paths, not external validity or proof of complete security. The retained permitted full-framework run passed 2,378 tests, with fourteen deselected and 80.15% coverage; those are suite totals, not 2,378 newly added capstone tests. Local socket permission failures in the first sandbox run were resolved by the permitted rerun. The earlier

intermittent backend admin-login transport failure remains unexplained and is not described as fixed.

7. Conclusions and next work

Use projected128 as the next private research baseline for this workload, retain mean512 as the higher clean no-noise reference, and evaluate trimming against the required clean/attacked trade-off. Center_quarter is unsupported as a private default. The engineering result is a working, auditable experiment path that preserves configuration, completion and failure semantics alongside the measurements.

Prioritize a new, independently frozen cohort with a small matched protocol baseline. The ongoing physical-host extension should establish predictive parity before reporting transport, runtime or device scaling. Secure aggregation, private randomness and malicious-input checks require their own protocol scope. This report does not establish clinical readiness, institutional approval, submission completion or production security.

Appendix A. Historical findings and evidence chronology

The prospectively frozen any-finding study completed 360 cells and 7,200 rounds. Its ten-seed privacy-by-trimming interaction was +0.002266150 AUROC, t95 interval [0.000704398, 0.003827901]. Absolute private attacked utility was lower for trimming, so the positive interaction alone did not justify a private default.

Historical condition	Mean AUROC	Trimmed mean AUROC
Clean, no noise	0.662202	0.662033
Sign flip, no noise	0.648991	0.656265
Clean, private ε=4	0.646336	0.627488
Sign flip, private ε=4	0.627389	0.618250

Evidence stage	Retained role
Historical any-finding matrix	Original declared question and cohorts; descriptive wider comparisons.
Effusion A1-A23	Adaptive representation, privacy and attack development.
A10 internal holdout	One opening for previously frozen models; published aggregates reused here.
Retrospective reanalysis	173 contrasts from eight pinned summaries; separates patient and seed targets.
ByzFL qualification	Four cells and A17 reference reconciliation.
Diagnostic pilots	Eighty screen and forty-six nonprivate bucket cells; complete negative results retained.
Frozen finalists	192 main cells plus four anchors on fresh training seeds.

A10 published clean FedAvg/centralized-convex holdout AUROCs are approximately 0.836/0.835. The difference interval [-0.0021,+0.0044] establishes neither equivalence nor noninferiority. Private ε=8/4/1 recipes gave approximately 0.763/0.715/0.580. At their transferred frozen thresholds, sensitivity was approximately 0.908-0.923 while specificity fell

from approximately 0.545 to 0.386/0.296/0.141. Those operating points do not establish general specificity-only privacy costs or clinical triage value.

Subsequent evidence qualified zero initialization and full-participation calibration for the tested recipe, exposed weak original sign-flip controls, and found local-noise integrity and distributed clip-skipping failures. A23's μ/N noise allocation also lacks sufficient unknown honest noise after colluders reveal shares. Original measurements and artifact hashes remain preserved.

Appendix B. Complete diagnostic pilot AUROC results

The eighty-cell screen and forty-six-cell bucket stage completed all 126 cells and 2,280 iterative rounds. Each arm below has two seeds. The table retains every arm, including native anchors, scalar ERM and reused clean screen references; reused references are not additional fits. Min/max and sample SD describe seeds, not confidence intervals. The public pilot summary retains all five metrics and individual seed values.

Owned PGD's nonprivate mean damage was 0.2872, exceeding the declared 0.02 gate; original sign flip and full-norm owned sign flip caused only 0.0050/0.0075. Projection128 was selected by private-clean utility. Scalar private ERM uses a distinct one-release strongly convex scalar-head mechanism, finite-iteration sensitivity allowance and intercept regularization; its weak tested utility does not reject all private convex methods.




Figure 3. Projection pilot AUROC, two paired development seeds. Width 128 was selected before final fitting. Whiskers show one sample SD across seeds, not confidence intervals. Higher AUROC is better; the clean/private trade-off changes with width.

Bucket diagnostics use the separately selected LR0.1/C1 recipe without privacy. Larger buckets improve some clean skewed points and worsen several attacked points. Mixing heterogeneity and spreading contamination is consistent with the observations, not a uniquely proven explanation. Private bucketing was not qualified.




Figure 4. Nonprivate median/bucket AUROC under IID and simulated label skew, two paired seeds. Higher is better. Whiskers show one sample SD; attacked seed variability is substantial. Owned PGD and oracle Fang have distinct information boundaries.

Pilot arm	Mean AUROC	Minimum	Maximum	Seed SD
mean:native:nonprivate	0.8073	0.8065	0.8080	0.0011
mean:byzfl:nonprivate	0.8073	0.8065	0.8080	0.0011
mean:native:private	0.7295	0.7290	0.7300	0.0007
mean:byzfl:private	0.7295	0.7290	0.7300	0.0007
center_r0.25_clean:byzfl:nonprivate	0.8051	0.8043	0.8058	0.0011
center_r0.25_owned_pgd:byzfl:nonprivate	0.7028	0.7020	0.7036	0.0011
center_r1_clean:byzfl:nonprivate	0.8073	0.8065	0.8080	0.0011
center_r1_owned_pgd:byzfl:nonprivate	0.6033	0.6005	0.6061	0.0040
center_r4_clean:byzfl:nonprivate	0.8073	0.8065	0.8080	0.0011
center_r4_owned_pgd:byzfl:nonprivate	0.5201	0.5184	0.5217	0.0023
mean_sign_flip_scale_f16:byzfl:nonprivate	0.8022	0.7986	0.8058	0.0051
mean_owned_sign_flip_f16:byzfl:nonprivate	0.7998	0.7948	0.8048	0.0071
mean_owned_pgd_f16:byzfl:nonprivate	0.5201	0.5184	0.5217	0.0023
trim16_clean:byzfl:nonprivate	0.8070	0.8068	0.8072	0.0003
trim16_owned_pgd:byzfl:nonprivate	0.5864	0.5848	0.5880	0.0022
mean_k64:byzfl:nonprivate	0.7693	0.7691	0.7696	0.0003
mean_k128:byzfl:nonprivate	0.7926	0.7923	0.7929	0.0005
mean_k256:byzfl:nonprivate	0.7975	0.7968	0.7982	0.0010

Pilot arm	Mean AUROC	Minimum	Maximum	Seed SD
erm_l0.01:scalar:nonprivate	0.7843	0.7842	0.7843	0.0001
erm_l0.1:scalar:nonprivate	0.7691	0.7690	0.7691	0.0001
erm_l1:scalar:nonprivate	0.7557	0.7556	0.7559	0.0002
center_r0.25_clean:byzfl:private	0.6714	0.6669	0.6760	0.0065
center_r0.25_owned_pgd:byzfl:private	0.5423	0.5096	0.5751	0.0463
center_r1_clean:byzfl:private	0.5604	0.5586	0.5622	0.0026
center_r1_owned_pgd:byzfl:private	0.5302	0.5091	0.5514	0.0299
center_r4_clean:byzfl:private	0.7289	0.7280	0.7298	0.0013
center_r4_owned_pgd:byzfl:private	0.5967	0.5349	0.6585	0.0874
mean_sign_flip_scale_f16:byzfl:private	0.6691	0.6680	0.6701	0.0015
mean_owned_sign_flip_f16:byzfl:private	0.6563	0.6555	0.6572	0.0012
mean_owned_pgd_f16:byzfl:private	0.5963	0.5335	0.6591	0.0888
trim16_clean:byzfl:private	0.6586	0.6525	0.6647	0.0086
trim16_owned_pgd:byzfl:private	0.6136	0.5888	0.6383	0.0350
mean_k64:byzfl:private	0.7465	0.7461	0.7470	0.0006
mean_k128:byzfl:private	0.7702	0.7661	0.7742	0.0058
mean_k256:byzfl:private	0.7560	0.7500	0.7620	0.0085
erm_l0.01:scalar:private	0.5345	0.4295	0.6396	0.1485
erm_l0.1:scalar:private	0.5434	0.4405	0.6463	0.1455
erm_l1:scalar:private	0.5483	0.4470	0.6496	0.1433
median_recipe_tight:byzfl:nonprivate	0.8063	0.8061	0.8065	0.0003
median_recipe_loose:byzfl:nonprivate	0.8198	0.8186	0.8210	0.0017
median_b1_iid_pgd_f4:byzfl:nonprivate	0.8119	0.8102	0.8135	0.0023
median_b1_iid_pgd_f16:byzfl:nonprivate	0.6719	0.6658	0.6780	0.0087
median_b1_iid_oracle_fang16:byzfl:nonprivate	0.7668	0.7641	0.7695	0.0038
median_b2_iid_clean:byzfl:nonprivate	0.8198	0.8186	0.8210	0.0017
median_b2_iid_pgd_f4:byzfl:nonprivate	0.8101	0.8078	0.8125	0.0033
median_b2_iid_pgd_f16:byzfl:nonprivate	0.5819	0.5756	0.5882	0.0089
median_b2_iid_oracle_fang16:byzfl:nonprivate	0.6852	0.6645	0.7058	0.0292
median_b4_iid_clean:byzfl:nonprivate	0.8200	0.8192	0.8208	0.0011
median_b4_iid_pgd_f4:byzfl:nonprivate	0.8053	0.8019	0.8087	0.0048
median_b4_iid_pgd_f16:byzfl:nonprivate	0.5123	0.5077	0.5169	0.0065

Pilot arm	Mean AUROC	Minimum	Maximum	Seed SD
median_b4_iid_oracle_fang16:byzfl:nonprivate	0.6566	0.6532	0.6600	0.0048
median_b1_a0p1_clean:byzfl:nonprivate	0.7947	0.7931	0.7963	0.0022
median_b1_a0p1_pgd_f4:byzfl:nonprivate	0.7827	0.7800	0.7855	0.0039
median_b1_a0p1_pgd_f16:byzfl:nonprivate	0.6527	0.5518	0.7535	0.1426
median_b1_a0p1_oracle_fang16:byzfl:nonprivate	0.6313	0.6078	0.6548	0.0332
median_b2_a0p1_clean:byzfl:nonprivate	0.8089	0.8080	0.8097	0.0012
median_b2_a0p1_pgd_f4:byzfl:nonprivate	0.7964	0.7939	0.7990	0.0036
median_b2_a0p1_pgd_f16:byzfl:nonprivate	0.6189	0.4901	0.7477	0.1821
median_b2_a0p1_oracle_fang16:byzfl:nonprivate	0.4342	0.4277	0.4407	0.0092
median_b4_a0p1_clean:byzfl:nonprivate	0.8122	0.8121	0.8123	0.0001
median_b4_a0p1_pgd_f4:byzfl:nonprivate	0.7971	0.7964	0.7977	0.0010
median_b4_a0p1_pgd_f16:byzfl:nonprivate	0.5987	0.4614	0.7360	0.1942
median_b4_a0p1_oracle_fang16:byzfl:nonprivate	0.4115	0.3983	0.4247	0.0186
median_b1_iid_clean:byzfl:nonprivate	0.8198	0.8186	0.8210	0.0017

Appendix C. Reproduction and evidence checks

Reproduction requires the qualified NIH train/selection feature bundle and matching preparation hashes; public aggregates alone are insufficient to rerun training. Use Python 3.12, manifest-pinned runtime versions and isolated ByzFL 0.0.11. Preserve source snapshots: qualification 016677f, screen 8ea4b7d, buckets 5940d13 and finalists 1a9f0ef. Each stage has a zero-fitting preflight before checkpoint-bound execution into a fresh directory.

The reproduction guide documents exact entry points. repro/run_effusion_finalists.py validates the parent pilots and manifests; repro/analyze_effusion_finalists.py rescores retained heads without fitting; repro/plot_remediation_results.py consumes public summaries. Source, runtime, bundle and configuration mismatches are refusals to investigate, not checks to bypass. Holdout and official-test data are excluded.

Pilot audits reconciled 140 source hashes and independently checked AUROC/AP, with maximum metric difference below 2.3e-16. The phase receipts retain outcome accounting, source identities and scoped verification. Remediation totals 326 cells and 6,280 iterative rounds including qualification; older studies remain distinct.

References

- [1] Wang et al. ChestX-ray8 and ChestX-ray14 appendix. https://arxiv.org/html/1705.02315v5
- [2] Yin et al. Byzantine-Robust Distributed Learning: Towards Optimal Statistical Rates. https://proceedings.mlr.press/v80/yin18a.html
- [3] Dong, Roth and Su. Gaussian Differential Privacy. https://arxiv.org/abs/1905.02383
- [4] Guerraoui et al. Differential Privacy and Byzantine Resilience in SGD: Do They Add Up? https://arxiv.org/abs/2102.08166
- [5] Allouah et al. On the Privacy-Robustness-Utility Trilemma in Distributed Learning. https://proceedings.mlr.press/v202/allouah23a.html
- [6] Gu, Li and Xiong. DP-BREM. https://www.usenix.org/conference/usenixsecurity25/presentation/gu-xiaolan
- [7] ByzFL documentation. https://byzfl.epfl.ch/
- [8] NVIDIA FLARE differential privacy documentation. https://nvflare.readthedocs.io/en/2.9.0/user_guide/admin_guide/security/differential_privacy.html
- [9] NVIDIA FLARE PercentilePrivacy API. https://nvflare.readthedocs.io/en/main/apidocs/nvflare.app_common.filters.percentile_privacy.html
- [10] Islamov et al. Byzantine-Robust and Differentially Private Federated Optimization under Weaker Assumptions. https://arxiv.org/html/2603.23472v1
- [11] LA-LoRA, ICLR 2026. https://proceedings.iclr.cc/paper_files/paper/2026/hash/34b13425b5ba8ad05d97b0043df52ed3-Abstract-Conference.html
- [12] Allouah, Guerraoui and Stephan. Towards Trustworthy Federated Learning with Untrusted Participants. https://proceedings.mlr.press/v267/allouah25a.html
- [13] Karimireddy, He and Jaggi. Learning from History for Byzantine Robust Optimization. https://proceedings.mlr.press/v139/karimireddy21a.html