

Framework Architecture



DEVELOPMENTOR
DEVELOPING PEOPLE WHO DEVELOP SOFTWARE

Understanding the class hierarchy



DispatcherObject

thread and Win32 message processing

DependencyObject

dependency property support

Visual

hit-testing, transforms, basic rendering

UIElement

input , focus and events

FrameworkElement

layout, binding, animation and styling

Panel

Shape

Control


Decorator

**What you use to
create your UI**

Win32 history lesson



- WPF applications must run on top of Windows
 - must follow the rules of Win32 programming
- At the core of every Windows program is a **message pump**



What does this job in WPF?



- The Dispatcher pumps Win32 messages for the application
 - restricted to a single thread (it's creator)
 - UI elements belong to a single dispatcher
 - inbound events are queued for dispatch to appropriate element


```
public sealed class Dispatcher
{
    public static Dispatcher CurrentDispatcher { get; }
    public DispatcherHooks Hooks { get; }
    public Thread Thread { get; }

    public event ... ShutdownFinished;
    public event ... ShutdownStarted;
    public event ... UnhandledException;
    public event ... UnhandledExceptionFilter;
    ...
}
```

WPF threading architecture



- Message Dispatch is run on primary (creating) UI thread
 - created as part of **Window** initialization





- Base class for thread-affinitive objects is **DispatcherObject**
 - provides support for identifying and accessing proper thread
 - all **UIElements** derive from this class
 - interacts with **Dispatcher** to provide single-threaded behavior
 - all properties and methods must be called on UI thread^[1]

```
public abstract class DispatcherObject
{
    protected DispatcherObject();

    public Dispatcher Dispatcher { get; }

    public bool CheckAccess();
    public void VerifyAccess();
}
```

What if I need multiple threads?



- `DispatcherObject` prohibits changes on other threads
 - must marshal activity to proper UI thread through **Dispatcher**
- `Dispatcher` methods provide fine-grained control
 - **CheckAccess** to see if (current thread == UI thread)
 - **VerifyAccess** to enforce (current thread == UI thread)
 - **Invoke** to call UI thread synchronously
 - **BeginInvoke** to call UI thread asynchronously
- Can also use `SynchronizationContext` for agility
 - works in Windows Forms and WPF
- For timer-based callbacks, use `DispatcherTimer`
 - properly marshals to UI thread for callback



- Invoke performs synchronous call to UI thread
 - pauses calling thread until UI thread services request
 - returns result of delegate call (null if no return value)
 - must be cautious of possible deadlock scenarios
- BeginInvoke performs asynchronous call to UI thread
 - returns **DispatcherOperation** to monitor progress, get results
- All method versions take Delegate and optional parameter(s)
 - no specific signature required
- Can also pass optional priority to Invoke / BeginInvoke
 - defaults to "Normal"

Example: using the Dispatcher



```
void ProcessData(byte[] data, int count)
{
    Dispatcher dp = textBox1.Dispatcher;
    if (dp.CheckAccess())
    {
        textBox1.Text = ConvertData(data, count);
    }
    else
    {
        dp.Invoke((Action)((() => ProcessData(data, count))));
    }
}
```

If method is called by background thread it will recursively call ProcessData – the second time will be on the UI thread



- WPF utilizes a **Retained Mode** graphics model
 - entire scene and dirty regions are maintained by WPF
 - apps change properties and WPF determines what is redrawn
- Contrast that to GDI's Immediate Mode graphics model
 - application maintains UI state and dirty regions
 - application decides what to redraw, most punt and redraw screen



Visual change notifications



- WPF caches property values used to render visuals
 - application paint code is only called when something *changes*
 - properties changing size impact layout and positioning

```
class Window
{
    public Brush Foreground
    {
        get { ... }
        set { ... }
    }
}
```

← WPF needs to know when property value changes in order to invalidate cache




- Dependency Properties enhance traditional properties with
 - default values
 - calculated values
 - change notification support
 - property value inheritance
 - adding properties dynamically to classes at runtime
 - metadata
- Used to implement most core WPF features
 - themes and styles
 - data binding
 - animations
 - ...

Using Dependency Properties




- DPs look like a regular property to the consumer
 - because they have a normal .NET property "wrapper"
 - but the declaration is quite different



declared as static
fields on the class

... and then wrapped
with instance property
getter/setter



Creating dependency properties



- DependencyProperty class has static **Register** methods
 - name must be unique on owner type
 - storage type must have public default constructor
 - result generally stored in **public static readonly** field with **Property** suffix

```
public partial class Control
```

```
{
```

```
    public static readonly DependencyProperty
```

```
        BackgroundProperty = DependencyProperty.Register(  
            "Background",
```

```
            typeof(Brush),
```

```
            typeof(Control));
```

```
        ...
```

```
    }
```



name


storage type

owner type

Dependency Property Support



- Fundamental support provided in `DependencyObject`
 - maintains collection of properties that have *set* values^[1]
 - provides **GetValue** and **SetValue** method to alter collection



Providing traditional property wrapper



- Property wrapper gets/sets value in base class collection
 - property value is then managed by **DependencyObject**

```
public partial class Control
{
    public static readonly DependencyProperty BackgroundProperty;
    ...
    public Brush Background
    {
        get { return (Brush) base.GetValue(BackgroundProperty); }
        set { base.SetValue(BackgroundProperty, value); }
    }
}
```

static DependencyProperty used as key into collection

Getting the value of a dependency property



- Current value can be retrieved through property wrapper
 - or directly^[1] through **DependencyObject.GetValue**
- WPF determines value at runtime when GetValue is called
 - can be influenced by a variety of factors

```
Brush bkBrush = (Brush)  
button1.GetValue(Control.BackgroundProperty);
```

base value (default or inherited)


theme value

style value

trigger

local value

active animation



Current value

Motivation [dynamic properties]



- Some properties are only valid in certain context
 - adding all known combinations bloats object size
 - cannot foresee all possible combinations

inefficient
and inflexible
to store panel
properties directly



```
public class Control {  
    ...  
    public Dock DockPosition { get; set; }  
    public int CanvasLeft { get; set; }  
    public int GridColumn { get; set; }  
}
```

Attaching properties at runtime



- Properties can be **attached** to DependencyObjects at runtime
 - provides dynamic extensible property mechanism for WPF
 - used to store context-specific data and extend class behavior
- Values associated with specific object instances
 - ... but property definition is defined on separate class

DependencyProperty key

```
button.SetValue(DockPanel.DockProperty, Dock.Left);
```

value associated with key



Attached Property static helper functions



- Owner class defines **static helpers** to get/set the value
 - should be named **Get[Property]** and **Set[Property]**
 - provides compile-time type safety

```
Button button = new Button();  
DockPanel.SetDock(button, Dock.Left);  
Canvas.SetLeft(button, 100);  
Grid.SetColumn(button, 1);
```

```
public class DockPanel : Panel  
{  
    public static readonly DependencyProperty DockProperty;  
    public static Dock GetDock(UIElement element) {  
        (Dock) element.GetValue(DockPanel.DockProperty);  
    }  
    public static void SetDock(UIElement element, Dock dock) {  
        element.SetValue(DockPanel.DockProperty, dock);  
    }  
}
```

Attached Properties in XAML



- Attached properties accessed using **Type.PropertyName**
 - associates the value with the given **DependencyProperty** key

```
<TextBox Name="myTextBox"  
    SpellCheck.IsEnabled="True"  
    Text="This is misspelled" />
```



This is misspelled

```
TextBox myTextBox = new TextBox();  
myTextBox.Text = "This is misspelled";
```

```
SpellCheck.SetIsEnabled(myTextBox, true);
```

or

```
myTextBox.SetValue(SpellCheck.IsEnabledProperty, true);
```

Creating an attached property



- `DependencyProperty.RegisterAttached` creates property
 - associates property metadata with all **DependencyObjects**
 - step can be omitted if not storing any data on types


```
public partial class SpellCheck
{
    public static readonly DependencyProperty
        IsEnabledProperty =
        DependencyProperty.RegisterAttached(
            "IsEnabled",
            typeof(bool),
            typeof(SpellCheck));
    ...
}
```

Providing helper methods for attached properties



- Helper methods provide type safety for getter and setter
 - **DependencyObject** or derived type as first parameter
 - XAML bypasses methods by default^[1] but they must be defined

suffix should match property name^[1]




```
partial class SpellCheck
{
    public static bool GetIsEnabled(UIElement ui)
    {
        return (bool) ui.GetValue(IsEnabledProperty);
    }
    public static void SetIsEnabled(UIElement ui, bool b)
    {
        ui.SetValue(IsEnabledProperty, b);
    }
}
```

Back to visuals – how do these change the UI?



- Property change likely has a desired behavior
 - does changing the property affect the rendering?
 - does changing the property affect the layout?
 - does the property have a default value?
 - can the property be inherited by children?
- All this is specified using **metadata**
 - additional "bits" of information tied to the property description





- Metadata is defined in the form of **PropertyMetadata**

```
public partial class FrameworkPropertyMetadata : UIPropertyMetadata
{
    public object DefaultValue { get; set; }
    public bool AffectsArrange { get; set; }
    public bool AffectsMeasure { get; set; }
    public bool AffectsParentArrange { get; set; }
    public bool AffectsParentMeasure { get; set; }
    public bool AffectsRender { get; set; }
    public bool BindsTwoWayByDefault { get; set; }
    public UpdateSourceTrigger DefaultUpdateSourceTrigger { get; set; }
    public bool Inherits { get; set; }
    public bool IsDataBindingAllowed { get; }

    ...
    public CoerceValueCallback CoerceValueCallback { get; set; }
    public PropertyChangedCallback PropertyChangedCallback { get; set; }
}
```

Example: setting the metadata properties



- `DP.Register{Attached}` takes a `PropertyMetadata`
 - associates metadata to property definition

```
partial class FrameworkElement {  
  
    public static readonly DependencyProperty LayoutTransformProperty =  
        DependencyProperty.Register("LayoutTransform",  
                                     typeof(Transform),  
                                     typeof(FrameworkElement),  
                                     new FrameworkPropertyMetadata(  
                                         Transform.Identity, // Default value  
                                         FrameworkPropertyMetadataOptions.AffectsMeasure,  
                                         new PropertyChangedCallback(OnLayoutTransformChanged))  
                                     );  
}
```



- Rendering starts with **Visual**
 - abstract class which provides support for hit-testing and coordinate transforms
- **UIElement** adds "IFE", input, focus, event support
 - provides concrete rendering support through **OnRender**
- **FrameworkElement** adds layout and data binding support
 - this is what everything generally extends

```
public class Cross : FrameworkElement
{
    protected override void OnRender(DrawingContext dc)
    {
        double w = ActualWidth, h = ActualHeight;
        dc.DrawRectangle(Brushes.Black, null, new Rect(w/2-w/8,2,w/4,h-2));
        dc.DrawRectangle(Brushes.Black, null, new Rect(2, h/2-h/4, w-2, h/4));
    }
}
```




- Entire scene composed in memory and painted in one operation
 - creates layers (tree) of objects and draws bottom to top
 - overlapping objects can affect output on a pixel-by-pixel basis
- Drawing commands are buffered and repainted automatically
 - screen can be repainted without a full scene recomposition



Overlapping controls
with Windows Forms

VS.




Overlapping controls
with WPF

How can it do that on Windows?



- WPF creates a single **HWND** and uses it to interact with Win32
 - input, focus, controls, rendering are all managed by WPF
 - window adornments still drawn and managed by Win32


WM_CREATE
WM_PAINT
WM_SETFOCUS
WM_LBUTTONDOWN
...



Rendering architecture





- Everything in WPF is rendered through **DirectX**
 - takes full advantage of GPU hardware and memory
 - dedicated thread does composition and DirectX rendering



Logical Tree




- WPF builds **Logical Tree** to manage UI
 - identifies object relationships (parent to child)
 - follows the XAML structure







- WPF maintains **Visual Tree** to decide how to render items
 - builds on logical tree and adds visual information
 - enables complete replacement of visual representation ("lookless" controls)




Exploring the logical and visual tree



- Mole is a VS.NET debugging visualizer for WPF
 - <http://moleproject.com>



logical tree matches
the elements
created in XAML



visual tree is what is actually rendered



- WPF provides a new architecture built on top of Win32
 - hides most of the abstraction away with a few exceptions
- Remember only one thread touches UI elements
 - use the Dispatcher to work with other threads
- Dependency Properties are core to the framework
 - you will see them again (and again)
- Rendering is performed through DirectX
 - allows full hardware acceleration support
 - uses retained model for ease of use
- WPF manages elements in logical and visual trees
 - will become more important when we talk about controls