

Learning Registry Quick Reference Guide

Document Version: 1.0
Last Edited: 17 October, 2011

PENDING UPDATE, USE THIS INFORMATION WITH CARE

Prepared by:
John Brecht, SRI International (john.brecht@sri.com)



© 2011 - SRI International

This work is licensed under the [Creative Commons Attribution-NonCommercial-ShareAlike 3.0 Unported License](https://creativecommons.org/licenses/by-nc-sa/3.0/).

Learning Registry

Quick Reference Guide

Contents

[Introduction](#)

[Data Model](#)

[Conceptual Design](#)

[Document Updating and Lifetime](#)

[Resource Data Description Data Model](#)

[Extensibility](#)

[Generating Resource Data Descriptions](#)

[Services](#)

[Publishing Services](#)

[Basic Publish](#)

[SWORD Publish](#)

[Retrieval Services](#)

[Basic Obtain](#)

[Basic Harvest](#)

[getrecord](#)

[listrecords](#)

Introduction

Welcome to the Learning Registry! The purpose of this document is to provide a brief reference to the principal data structures and services that typical users of the Learning Registry will most frequently interact with. Administrative users (users standing up or maintaining Learning Registry nodes) and Learning Registry core developers should consult the Learning Registry Technical Specification for complete documentation of all Learning Registry features both internal and external. This document is intended to be consistent with the [Learning Registry Technical Specification](#).

The services are listed by purpose (publish, retrieve, etc.) Each has a description, samples and additional information. *Figure 1* is an example of a section describing a service. The start of each section contains the syntax for HTTP GET, and/or HTTP POST, as appropriate. Example code is illustrated with cURL command lines. Code examples have additional formatting for the purposes of readability.

Name of Service	
/verb	
GET <nodeURL>/verb ?arg=<value>	POST <nodeURL>/verb
This is a description of this service... Etc... Etc...	
Example	
Etc...	

Figure 1. Example description of a service topic.

Data Model

Conceptual Design

The Learning Registry data model describes resources, metadata, paradata, etc., that are distributed by the network. Data read from, or written to, the Learning Registry by users is referred to as a resource data description. The following definitions are necessary before proceeding:

Resource: Some document, media, web site, etc., that is designed for, or has been used, in an educational context. Within the Learning Registry it typically refers to digital resources. In principle, physical resources such as places, artifacts, meeting rooms, equipment and so forth may also be documented.

Resource Data: Data that describes a learning resource. Types of resource data include, but is not limited to, metadata and paradata.

Resource Data Description: A document submitted to, or retrieve from, the Learning Registry that serves as notification to the existence of a resource, metadata or paradata document within the network. It provides some insight as to the properties of the document it refers to and the resource that document describes. Data read from, or written to, the Learning Registry by users is a *resource data description*.

Its important to emphasize that the Learning Registry does not (typically) contain learning resources. Nor does it contain metadata or paradata about learning resources. Rather, it contains notifications indicating the *existence* of resources, metadata or paradata.

Most users will be familiar with metadata, in this context, as describing the *properties* of a learning resource. Examples

of such could be the author, subject, level, etc. Paradata, on the other hand, describe the contextualized *use* of a learning resource. Examples of paradata could be: the number of times used by some community, ratings, comments, etc.

The Learning Registry is agnostic as to the format of metadata or paradata referenced by a resource data description. The referenced document can be delivered inline, linked, or attached to a resource data description:

inline: Resource data is in an object that follows

linked: Resource data is at the link provided

attached: Resource data is in an attachment.

Clearly, many paradata documents may be associated with one learning resource. Multiple metadata descriptions of a learning resource may also be contributed. For example, using different metadata schemas, as authored by, or for, different communities, etc. What links these documents to a particular resource is the *resource locator* (typically a URI) in the resource data description. Thus, if one were interested in finding all the metadata and paradata associated with a particular learning resource, they would do so by finding resource data descriptions whose resource locator is that of the resource in question.

Document Updating and Lifetime

Generally, documents submitted to the Learning Registry may not be modified after submission. If an update is required, the publisher simply submits the new version of the document to the Learning Registry. When multiple versions are found (For instance, by identifying that documents have the same type, submitter, and resource locator) its up to the data consumer to identify the most recent.

Submitters of data may also specify a lifetime for the document. How lifetime is handled by the Learning Registry, if at all, is not yet specified as of the current version of the specification.

Resource Data Description Data Model

The resource data description is a JSON document. The elements of the document are described below in the following format:

Element	Description	Required	Immutable
element_name data_type (encoding)	About the element.	<input checked="" type="checkbox"/> True <input type="checkbox"/> False <input checked="" type="checkbox"/> Conditional	<input checked="" type="checkbox"/> True <input type="checkbox"/> False <input checked="" type="checkbox"/> Conditional

{			
doc_type resource_data	The literal "resource_data"	■	■
doc_version literal	The literal for the current LR Spec version. (e.g. "0.23.0")	■	■

◆ *General elements about the submission.*

doc_ID string	Unique document ID within scope of the LR.	■	<input type="checkbox"/>
resource_data_type string	Open (best practices) vocabulary ["paradata", "resource", "assertion", ...]	■	■
active Boolean	Is the resource data description document active?	■	■

◆ *Information about the submission, independent of the resource data.*

identity	Identity and curation	■	<input type="checkbox"/>
{			
submitter_type string	Fixed vocabulary ["anonymous", "user", "agent"]	■	■
submitter string	Identity of the submitter of the resource data.	■	■
curator string	Identity of the curator of resource data description.	<input type="checkbox"/>	
owner string	Identity of the owner of the resource.	<input type="checkbox"/>	
signer string	Identity of key owner used to sign the submission.	<input type="checkbox"/>	
}			

◆ *Submission and distribution workflow information.*

submitter_timestamp string (time/date)	Submitter-created timestamp.	<input type="checkbox"/>	<input type="checkbox"/>
submitter_TTL string (time/date)	Submitter statement of TTL of validity of submission.	<input type="checkbox"/>	<input type="checkbox"/>
publishing_node string	Node_id of node where injected into the network.	■	<input type="checkbox"/>
node_timestamp string (time/date)	Timestamp of when received by the current node.	■	■
create_timestamp string (time/date)	Timestamp of when first published to the network.	■	■

TOS		■	<input type="checkbox"/>
{	submission_TOS	Agreed terms of service by submitter	■ <input type="checkbox"/>

	string			
	submission_attribution	Attribution statement from submitter	<input type="checkbox"/>	<input type="checkbox"/>
	string			
}				

do_not_distribute	System provided key-value pair	<input type="checkbox"/>	<input type="checkbox"/>
string			
weight	Submitter assigned weight	<input type="checkbox"/>	<input type="checkbox"/>
integer	(strength)-100:100		

digital_signature		Digital signature of the submission	<input type="checkbox"/>	<input type="checkbox"/>
{	signature	Signature string	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	string			
	key_location	Array of public key locations	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	["string"]			
	signing_method	Fixed vocabulary ["LR-PGP.1.0"]	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	string			
}				

◆ *Information about the resource, independent of the resource data.*

resource_locator	Unique locator for the resource described. Shall resolve to a single unique resource.	<input checked="" type="checkbox"/>	<input type="checkbox"/>
string	<ul style="list-style-type: none"> • "http://www.url/data/1961.jpg" 		
keys	Array of hashtag, keyword value list used for filtering.	<input type="checkbox"/>	<input type="checkbox"/>
["string1","string2",...]	<ul style="list-style-type: none"> • ["energy", "gas", "collision", "LOM", "kinetics", etc...] 		
resource_TTL	TTL from resource owner for the resource itself, in days.	<input type="checkbox"/>	<input type="checkbox"/>
integer			

◆ *Applicable if the submission is a resource.*

payload_placement	<u>Required</u> : if the submission is a resource.	<input checked="" type="checkbox"/>	
string	Fixed vocabulary ["inline","linked","attached"] <ul style="list-style-type: none"> ◦ "inline": resource data is in an object that follows ◦ "linked": resource data is at the link provided ◦ "attached": resource data is in an attachment 		
payload_schema	<u>Required</u> : if the submission is a resource.	<input checked="" type="checkbox"/>	
["string"]	Array of schema description and keywords for the resource data. May use any metadata standard. <ul style="list-style-type: none"> ◦ ["LODE", "LOM", etc...] 		

payload_schema_locator string	<p><u>Optional</u>: if the submission is a resource. Otherwise ignored.</p> <p>Schema locator for the resource data.</p> <ul style="list-style-type: none"> o "http://www.openarchives.org/OAI/2.0/oai_dc/http://www.openarchives.org/OAI/2.0/oai_dc.xsd" 	<input type="checkbox"/>	
payload_schema_format string	<p><u>Optional</u>: if the submission is a resource. Otherwise ignored.</p> <p>schema MIME type</p>	<input type="checkbox"/>	
payload_locator string	<p><u>Required</u>: if the submission is a resource AND payload_placement value is "linked"</p> <p>Otherwise ignored.</p> <ul style="list-style-type: none"> o "http://www.url/files/filename.json" 	<input checked="" type="checkbox"/>	
resource_data <the resource data object>	<p><u>Required</u>: if the submission is a resource AND payload_placement value is "inline"</p> <p>Otherwise ignored.</p> <p>The actual inline resource data (resource, metadata, paradata). May be a JSON object, a string encoding XML or some other format, or a string encoding binary.</p> <ul style="list-style-type: none"> • "<expression xsi:schemaLocation=\"http://www.url/xsd/v1p0 http://www.url/lode/v1p0.xsd\" xmlns=\"http://www.url/v1p0\" xmlns:xsi=\"http://www.w3.org/2001/someschema1\"> <identifier><catalog>abc</catalog> <entry>123/135/entry> etc... <title> <string language=\"en\">Where is the dog?</string> <string language=\"de\">Wo ist der hund?</string> </title> etc... <entity>BEGIN:VCARD VERSION:3.0 FN:Iris Florian Children's Books N:Iris Florian ADR:1A Neuenstrasse, Nordsee, Germany END:VCARD</entity> etc..." 	<input checked="" type="checkbox"/>	

◆ *Extensibility.*

X_xxx string	Placeholder for extensibility	<input type="checkbox"/>	<input checked="" type="checkbox"/>
------------------------	-------------------------------	--------------------------	-------------------------------------

}

Extensibility

The data model may be extended with additional optional, mutable elements that describe a resource and have a character string value space. These extended elements must have names that begin with "X_". Such elements should provide additional hints about the resource content which, while also in the full metadata description, allow faster filtering based on the hints rather than information at the resource data description document level. Examples include: "X_subject", "X_title", "X_format", etc.

Generating Resource Data Descriptions

Many elements are either fixed with a constant value, automatically generated, or consistent for a given user. Some examples are some in Figure 2.

Fixed Elements	doc_type	doc_version	active		
Automatically Generated Elements	doc_ID	publishing_node	update_timestamp	node_timestamp	create_timestamp
Consistent Elements	submitter_type	submitter	submission_TOS		
Min Req'd Properties Differing Between Submissions	resource_data_type	resource_locator	payload_placement	payload_locator (if payload is linked)	resource_data (if payload is inline)

Figure 2. Example Element Value Types.

Thus, beyond the boilerplate, the minimum submission to the Learning Registry states what kind of resource data is being submitted (metadata, paradata, or the resource itself), what resource is being described (via its locator, typically a URI), and where the resource data can be found (either a locator or inlined.)

The following elements also vary from submission to submission, but are optional: `submitter_timestamp`, `submitter_TTL`, `keys`, `resource_TTL`, `payload_schema`, `payload_schema_locator`.

Below, *Figure 3* shows an example of a Resource Data Description Document.

```
{  "doc_type": "resource_data",
  "resource_data": "Put_anything_like_metadata, xml_or_whatever_here",
  "keys": [
    "science",
    "what_ever_you_want"
  ],
  "TOS": {
```



```

    "submission_TOS": "http://www.learningregistry.org/tos/cc0/v0-5/"
  },
  "payload_placement": "inline",
  "resource_data_type": "metadata",
  "payload_schema": [
    "hashtags", "describing",
    "resource", "format"
  ],
  "doc_version": "0.23.0",
  "active": true,
  "resource_locator": "URI_of_resource",
  "identity": {
    "curator": "",
    "owner": "",
    "submitter": "Your name or organization here",
    "signer": "Your name or organization if signing the document",
    "submitter_type": "agent"
  }
}

```

Figure 3: Example Resource Data Description Document

Although not yet implemented, filtering and querying the "keys" and optional "X_" elements, while possibly redundant with the payload, help lead data consumers to your data. Filtering or querying properties of inlined metadata may also be considered for implementation.

Services

Learning Registry services and their APIs provide the functionality to push, discover, or pull resource data from the network. They are RESTful and accessed via HTTP, accepting arguments and delivering results in JSON notation.

In the following Learning Registry service descriptions the address of the services have been shortened for clarity. For example, if a service has an address of "http://lr.someregistry.edu/servicename", it's shortened simply to "/servicename".

A decentralized Learning Registry network is comprised of multiple nodes. There is no requirement that a node implement a service. However, if implemented it will be consistent with the service API. Refer to the complete Learning Registry Specification for additional information.

Publishing Services

Current push/publish services include:

[Basic Publish](#)

[SWORD Publish](#)

Basic Publish

<nodeURL>/publish

GET (Not Applicable)**POST** <nodeURL>/publish

Basic Publish is the most basic, direct mechanism to publish resource data. The Basic Publish service pushes an instance of a the JSON resource data description document directly to a node in the network. It's performed via HTTP POST to <nodeURL>/publish.

GET

Arguments

POST**JSON Request Object**

Contains the resource data description documents to be published.

Object	Type	Note
{		
"documents": [array	Array of one or more resource data description documents.
{resource_data_description},		JSON Resource data description document(s).
{resource_data_description},		JSON Resource data description document(s).
etc...		etc...
]		
}		

Return Value

The future version is planned to include additional error codes with descriptive strings.

Code	String	Note
200	OK	The request has succeeded.
500	Internal Server Error	The server encountered an unexpected condition which prevented it from fulfilling the request.

JSON Result Object

Object	Type	Note
{		
"OK":	Boolean	"true" if successful.
"error":	string	Only present if "OK" is "false". Contains description of error or failure.
"document_results": [{		Array containing a result entry for each document in the request.
"doc ID":	string	ID of the document if successful.
"OK":	Boolean	"true" if document was published successfully.
"error":	string	Only present if "OK" is "false". Contains description of error or failure.
}		

]		
}		

Notes

1. The service may be configured to return only document IDs and not full documents.
2. If the request document ID is not provided, the service may be configured to return all resource data description documents subset of the as determined by the service.
3. Returned documents are ordered by data with the most recent being first.

Sample Code

Examples have additional formatting for the purposes of readability.

Publish the JSON formatted file named "fileName.json".

cURL	Format	<code>curl -X POST -H "Content-Type:application/json" "<<url>>" -d @fileName.json</code>
	Example	<code>curl -X POST -H "Content-Type:application/json" ␣ "http://testnode.org/publish ␣ -d @my_basicpublish_formatted.json"</code>
	Return	<code>{"document_results":[{"doc_ID": "klm174s08n05f031961td15sep011fad", "OK": "true"}], "OK": "true" }</code>

SWORD Publish

<nodeURL>/swordpub

GET (Not Applicable)

POST <nodeURL>/swordpub

SWORD (*Simple Web-service Offering Repository Deposit*) Publish achieves the same end as Basic Publish, but does so using the SWORD protocol. The SWORD 1.3 API provides the mechanism for publishing to a node. A node corresponds to a single, particular SWORD collection. The service currently supports only JSON resource data description documents.

GET

Arguments

POST JSON Request Object

Contains the resource data to be published.

Object	Note
{resource_data_description}	A single resource data description document.

Return Value

The future version is planned to include additional error codes with descriptive strings.

Code	String	Note
200	OK	The request has succeeded.

XML Result Object**Notes****Sample Code**

Examples have additional formatting for the purposes of readability.

Publish the JSON formatted file named "fileName.json".

cURL	Format	<code>curl -X POST -H "Content-Type:application/json" <<url>> -d @filename.json</code>
	Example	<code>curl -X POST -H "Content-Type:application/json" ↵ http://testnode.org/swordpub ↵ -d @swordpublish.json</code>
	Returns	<pre><?xml version="1.0"?> <entry xmlns="http://www.w3.org/2005/Atom" ↵ xmlns:sword="http://purl.org/net/sword/"> <title>klm174s08n05f031961td15sep011fad</title> <id>klm174s08n05f031961td15sep011fad</id> <updated>2011-10-17T17:58:59.061524Z</updated> <author><name>Learning Registry</name></author> <summary type="text">A summary</summary> <sword:userAgent>curl/7.21.7 (i386-pc-win32) libcurl/7.21.7 ↵ OpenSSL/0.9.8r zlib/1.2.5 libidn/1.18 libssh2/1.2.8 ↵ librtmp/2.3</sword:userAgent> <generator uri="http://testnode.org/sword" version="1.0"/> <content type="application/json" ↵ src="http://testnode.org/obtain/klm174s08n05f031961td15sep011fad"/> </entry></pre>

Retrieval Services

Services for pulling data from the Learning Registry include:

[Basic Obtain](#)

[Basic Harvest](#)

OAI-PMH Harvest

Basic Obtain is the simplest of the three retrieval services, providing the most direct way to retrieve documents from the Learning Registry. Basic Harvest provides more advanced services, and *Open Archives Initiative Protocol for Metadata Harvesting* (OAI-PMH) provides data access in a manner compliant with the OAI-PMH protocol.

Basic Obtain

<nodeURL>/obtain

GET <nodeURL>/obtain

?request_ID=<ID>
&by_doc_ID=<true|false>
&by_resource_ID=<true|false>
&ids_only=<true|false>
&resumption_token=<token>

POST <nodeURL>/obtain

The Basic Obtain service pulls an instance of a resource data description document (or a set of documents) directly from a node on a resource distribution network. It is the most basic, direct mechanism to access resource data.

Obtain has three modes:

by_doc_ID: If doc_IDs are included in a request, then the corresponding resource data description documents are returned.

by_resource_ID: If resource_locators are included in the request, then for each resource_locator an array of documents referring to that locator (whether they be metadata or paradata) are returned.

Not specified: If neither doc_IDs or resource_locators are supplied, the service may return all, or a service-determined subset, of the resource data description documents.

GET

Arguments

Object	Type	Note
"by_doc_ID"	Boolean	<u>Optional:</u> default "false". If "true" then request is for specific document for each ID in the list. request_ID value(s) are document IDs for a resource data description document(s).
"by_resource_ID"	Boolean	<u>Optional:</u> default "true". request_ID value(s) are unique resource identifier(s), e.g., the resource locator(s).
"resumption_token"	string	<u>Optional:</u> provided as a result of prior calls. Flow control resumption token.
"ids_only"	Boolean	<u>Optional:</u> default "false". If "true" the the request is just for IDs, not documents.
"request_ID"	string	Resource ID or resource data description document ID.

POST

JSON Request Object

Object	"true" type	Note
{		List of resource IDs or resource data description document IDs to obtain.
"by_doc_ID":	Boolean	<u>Optional</u> : default "false". If "true" then request is for specific document for each ID in the list. request_ID value(s) are document IDs for a resource data description document(s).
"by_resource_ID":	Boolean	<u>Optional</u> : default "true". request_ID value(s) are unique resource identifier(s), e.g., the resource locator(s).
"resumption_token":	string	<u>Optional</u> : provided as a result of prior calls. Flow control resumption token.
"ids only":	Boolean	<u>Optional</u> : default "false". If "true" the the request is just for IDs, not documents.
"request_IDs": ^[1] [array	<u>Optional</u> : ignored if ids_only is "true". Array of one or more resource IDs OR resource data description document IDs. If missing, documents are returned as determined by the service.
"request ID",	string	Resource IDs OR resource data description document IDs
"request_ID",		
etc...		
]		
}		

Return Value

The future version is planned to include additional error codes with descriptive strings.

Code	String	Note
200	OK	The request has succeeded.
500	Internal Server Error	The server encountered an unexpected condition which prevented it from fulfilling the request.

JSON Result Object

Object	Type	Note
{		
"documents": [array	Array of resource data description documents. ^[2]
{"document":	array	Array of JSON resource data description documents. Present only if:
[resource_data_description]		<ul style="list-style-type: none"> Document ID is valid Request was not for IDs only otherwise NULL.
		JSON Resource data description document(s).

,		
"doc_ID":	string	
},		
{"document":		etc...
[{resource_data_description}		etc...
]		
etc...		etc...
}		
]		
"resumption_token":	string	Flow control resumption token. ^{[3] [4]} Present only if: <ul style="list-style-type: none"> ○ flow control is supported ○ results require pagination. ○ NULL if this is the last set of paginated results
}		

Notes

1. If the request_ID is not provided, all resource data description documents, or a subset of documents may be returned as determined by the service.
2. The return value may be just document IDs and not full documents, as determined by the service.
3. Flow control implementation is determined by the service. If supported, the service determines how many documents to return per call. If the results returned is not the complete set the service returns one page of results and a resumption token. To retrieve the next page of results, the request would include the resumption token returned from the prior call.
4. The duration for which a resumption token is valid is determined by the service.

Sample Code

Examples have additional formatting for the purposes of readability.

Obtain a single document by its document ID. Specify that the request is for a document by setting by_doc_ID to "true".

cURL	Format	curl -X GET "<<url>>/obtain ↵ ?by_doc_ID=true ↵ &request_ID=some_Document_ID"
	Example	curl -X GET "http://testnode.org/obtain ↵ ?by_doc_ID=true ↵ &request_ID=klm174s08n05f031961td15sep011fad"
	Returns	{ "documents": [{ "document": [{ "update_timestamp": "2011-09-07T20:27:59.747579Z", etc., ... }], "doc_ID": "klm174s08n05f031961td15sep011fad", ... }] }
	Document Found	
	Returns	{"documents": [], "resumption_token": null}
	Document Not Found	

Obtain a list of all resources returning only their IDs. The default value of `by_resource_ID` is "true".

cURL	Format	<code>curl -X GET "<<url>>/obtain ↵ ?ids_only=true"</code>
	Example	<code>curl -X GET "http://testnode.org/obtain ↵ ?ids_only=true"</code>
	Returns	<pre>{ "documents": [{ "doc_ID": "http://192.191.190.89/node/31" }, { "doc_ID": "http://192.191.190.19/node/28" }, etc... etc...], "resumption_token": ↵ "eyJhbGciOiAiSFMyNTYiLCJkaWwIjogIkpXVCJ9.eyJzdGFydGtleSI6ICJodHRwOi8vMTk0LjklLjIwNy44OS9wcm9qZWt0ZS9wNzc5NjkuemlwIiwgImVuZGtleSI6IG51bGwsICJzdGFydGtleV9kb2NpZCI6ICJiOWM3N2ZkMDdmOTc0MzAxYWZkM2MxNzU0NmI1ODBlYyJ9.pBMEp5DvhYgfsrbiapGQIItevbPztWKiQBprwbzuE5Q"</pre>

The inclusion of "resumption_token" in the return value indicates that a single page of results was included and that another pager may be obtained by reissuing the request and including the "resumption_token" value.

Request another page of results.

cURL	Format	<code>curl X GET "<<url>>/obtain ↵ ?ids_only=true ↵ &resumption_token=unique_token_string"</code>
	Example	<code>curl -X GET "http://testnode.org/obtain ↵ ?ids_only=true ↵ &resumption_token= ↵ eyJhbGciOiAiSFMyNTYiLCJkaWwIjogIkpXVCJ9.eyJzdGFydGtleSI6ICJodHRwOi8vMTk0LjklLjIwNy44OS9wcm9qZWt0ZS9wNzc5NjkuemlwIiwgImVuZGtleSI6IG51bGwsICJzdGFydGtleV9kb2NpZCI6ICJiOWM3N2ZkMDdmOTc0MzAxYWZkM2MxNzU0NmI1ODBlYyJ9.pBMEp5DvhYgfsrbiapGQIItevbPztWKiQBprwbzuE5Q"</code>
	Returns	<pre>{ "documents": [{ "doc_ID": "http://192.191.190.18/node/10" }, { "doc_ID": "http://192.191.190.18/node/69" }, etc... etc...] }</pre>

Basic Harvest

The Basic Harvest service may be used to connect to a node to harvest (pull) resource data description documents. Harvesting is done by resource data description document ID or by resource ID. Both GET and POST encoding of requests are supported.

The service is patterned after the OAI-PMH specification and is extensible so that it may fully support OAI-PMH-compliant harvesting. For additional information about the mapping of Learning Registry Basic Harvest to OAI-PMH consult the [Learning Registry Technical Specification](#).

Basic Harvest includes six subservices:

[GetRecord](#)

Basic Harvest

<nodeURL>/harvest/getrecord

GET <nodeURL>/harvest/getrecord
?request_ID=<id>
&by_doc_ID=<true|false>
&by_resource_ID=<true|false>

POST <nodeURL>/harvest/getrecord

Getrecord returns the resource data description documents for a specified resource data document ID or resource ID. It operates similarly to Basic Obtain, with the principle exception that only a single doc_ID or resource_locator, rather than an array, may be specified in the request.^[1] If the request ID is a unique resource identifier, such as the resource locator, the service returns all resource data description documents for the resource.

GET

Arguments

Object	Type	Note
"request_ID":	string	Resource ID or resource data description document ID to harvest.
"by_doc_ID":	Boolean	<u>Optional</u> : default "false". If "true" then request is for specific document for each ID in the list. request_ID value(s) are document IDs for a resource data description document(s).
"by_resource_ID":	Boolean	<u>Optional</u> : default "true". request_ID value(s) are unique resource identifier(s), e.g., the resource locator(s).

POST

JSON Request Object

Contains the resource data to be published.

Object	Type	Note
{		
"request ID":	string	Resource ID or resource data description document ID to harvest.
"by_doc_ID":	Boolean	<u>Optional</u> : default "false". If "true" then request is for specific document for each ID in the list.

		request_ID value(s) are document IDs for a resource data description document(s).
"by_resource_ID":	Boolean	<u>Optional</u> : default "true". request_ID value(s) are unique resource identifier(s), e.g., the resource locator(s).
}		

Return Value

The future version is planned to include additional error codes with descriptive strings.

Code	String	Note
200	OK	The request has succeeded.
500	Internal Server Error	The server encountered an unexpected condition which prevented it from fulfilling the request.

JSON Result Object

Object	Type	Note
{		
"OK":	Boolean	"true" if successful
"error":	string	Description of error or failure. Present only if OK is "false".
"responseDate":	string	
"request":		The original API request.
{		
"verb":	string	The literal "getrecord".
"identifier":	string	Requested ID.
"by_doc_ID":	Boolean	
"by_resource_ID":	Boolean	
"HTTP request":	string	The HTTP request as a string.
}		
"getrecord": {		The requested resource data description document. Present only if request_ID is valid, otherwise NULL.
"record": [{		Record container
"header": {		Header info
"identifier":	string	Resource data description document ID.
"status":	string	<u>Optional</u> : "active" if not present. Fixed vocabulary ["active", "deleted"].
},		
"resource_data":		
{resource_data_description		JSON Resource data description document.
}		
}		
}		
}		

Notes

1. Flow control is not currently supported.

Sample Code

Examples have additional formatting for the purposes of readability.

Get a single document by its document ID.

cURL

Format	<pre>curl -X GET "<<url>>/harvest/getrecord ↓ ?request_ID=<<document ID>> ↓ &by_doc_ID=true"</pre>
Example	<pre>curl -X GET "http://testnode.org/harvest/getrecord ↓ ?request_ID=klm174s08n05f031961td15sep011fad ↓ &by_doc_ID=true"</pre>
Returns	<pre>{ "OK": "true", "responseDate": "2011-09-28T14:27:08.598835Z", "error": "" "request": { "by_doc_ID": "true", "HTTP_request": "", "verb": "getrecord", "by_resource_ID": "false", "identifier": "klm174s08n05f031961td15sep011fad" }, "getrecord": { "record": [{ "header": { "datestamp": "2011-09-28T14:27:08.607941Z", "status": "active", "identifier": "klm174s08n05f031961td15sep011fad" }, "resource_data": { etc... etc... } }] } }</pre>
Returns	<pre>{ "OK": "false", "responseDate": "2011-09-28T19:58:17.240463Z", "error": "idDoesNotExist", "request": { "by_doc_ID": "true", "HTTP_request": "", "verb": "getrecord", "by_resource_ID": "false", "identifier": "the_invalid_request_ID_you_submitted" }, "getrecord": { "record": []} }</pre>
Document Found	
Document Not Found	

Basic Harvest

<nodeURL>/harvest/listrecords

GET <nodeURL>/harvest/listrecords
?from=<date>
&until=<date>

POST <nodeURL>/harvest/listrecords

Listrecords is used to retrieve resource data description documents submitted within a specific time/date range. The headers of returned records contain a document ID in the identifier field. There is currently no support for resource locators as identifiers.

GET

Arguments

Object	Type	Note
"from"	string	<u>Optional.</u> time/date ^[1] Per ISO 8601 ^[2] Default is earliest timestamp Start of time/date range.
"until"	string	<u>Optional.</u> time/date ^[1] Per ISO 8601 ^[2] . Default is latest timestamp End of time/date range.

POST

JSON Request Object

Contains the resource data to be published.

Object	Type	Note
{		
"from":	string	<u>Optional.</u> time/date ^[1] Per ISO 8601 ^[2] Default is earliest timestamp Start of time/date range.
"until":	string	<u>Optional.</u> time/date ^[1] Per ISO 8601 ^[2] . Default is latest timestamp End of time/date range.
}		

Return Value

The future version is planned to include additional error codes with descriptive strings.

Code	String	Note
200	OK	The request has succeeded.

500	Internal Server Error	The server encountered an unexpected condition which prevented it from fulfilling the request.
-----	-----------------------	------------------------------------------------------------------------------------------------

JSON Result Object

Object	Type	Note
{		
"OK":	Boolean	
"error":	string	Descriptive string.
"responseDate":	string	Time/Date. Per ISO 8601 ^[2] of this report.
"request": {		The original request.
"verb":	string	The literal "listrecords".
"from":	string	Time/Date. Per ISO 8601 ^[2]
"until":	string	Time/Date. Per ISO 8601 ^[2]
"HTTP_request":	string	The HTTP request as a string.
},		
"listrecords": [{	Array	Array of records. ^[1]
"record": {		
"header": {	string	
"datestamp":	string	Time/Date. Per ISO 8601 ^[2] Resource data timestamp.
"status":	string	<u>Optional</u> : "active" if not present. Fixed vocabulary ["active", "deleted"].
"identifier":	string	Resource data description document ID.
}		
}		
}]		
}		

Notes

1. All matching results are returned in a single page as flow control is not currently supported.
2. Specified with one second accuracy per [ISO 8601](#) *Data elements and interchange formats — Information interchange — Representation of dates and times*.

Sample Code

Examples have additional formatting for the purposes of readability.

Find all documents which were submitted on, or after, 1:00 am on the 23rd of September, 2011.

cURL	Format	curl -o harvest_listrecords.json -X GET ↓ <<url>>/harvest/listrecords?from=<<date/time>>
	Example	curl -o harvest_listrecords.json -X GET ↓ "http://testnode.org/harvest/listrecords ↓ ?from=2011-09-23T01:00:00Z
	Returns	{ "OK": true, "responseDate": "2011-09-29T17:10:01.830800Z", "error": "", "request": { "HTTP_request": "", "verb": "listrecords",
	Document Found	

```

    "from": "2011-09-23T00:00:00Z"
  },
  "listrecords": [{
    "record": {
      "header": {
        "datestamp": "2011-09-29T17:10:02.074372Z",
        "status": "active",
        "identifier": "klm174s08n05f031961td15sep011fad"
      },
      "resource_data": {
        "doc_type": "resource_data",
        etc...
        etc...
      },
      {"record":...},
      etc...
    }
  ]}

```

Find all documents which were submitted on or between 01 Feb 2009, and 02 Feb 2009.

cURL

Format	<pre> curl -o harvest_listrecords.json -X GET ↓ <<url>>/harvest/listrecords?from=<<date/time>>&until=<<date/time>> </pre>
Example	<pre> curl -o harvest_listrecords.json -X GET ↓ "http://testnode.org/harvest/listrecords ↓ ?from=2009-01-01T12:00:00Z&until=2009-01-02T12:00:00Z" </pre>
Returns	<pre> { "request": { "HTTP_request": "", "verb": "listrecords", "from": "2009-02-01T12:00:00Z", "until": "2009-02-02T12:00:00Z" }, "OK": true, "responseDate": "2011-09-29T20:31:03.785982Z", "error": "" } </pre>
Document Not Found	